

INDEX

- altimeters (*Cont.*):
friction error, 33
hysteresis, 34
Kollsman Windows, setting the altimeter, 31
mechanical error, 34
misreading the altimeter, 31
preflight inspection, 38
scale error, 33
setting the altimeter, 31
stuck or corroded altimeters, 34
three-pointer altimeters, 31, **32**, 31
- aluminum corrosion, 6
ammeters, 173, **173**, 187–188
amp-hours, battery life, 154
amphibious landing gear system, **221**
amps, 154
angle of attack, propellers, 202
annual inspections, 62, 110
antennas
ADF frequencies, 25
dirt on antenna, 26
distance measuring equipment (DME), 25
emergency locator transmitter (ELT), 25
frequencies accessible to antenna, 24–25
global positioning system (GPS), 25
LORAN frequencies, 25
marker beacon frequencies, 25
orientation of antenna, 24–25
preflight inspection, 23–26
radio frequencies, 25
size of antenna, 24–25
transponders, 25
ultra high frequency (UHF), 25
very high frequency (VHF), 25
VOR/LOC frequencies, 25
- anticollision lights, 10–12, **11**
attitude indicators, 39–41, **40**
acceleration/deceleration errors, 40–41
bank-and-pitch errors, 40
cross-checking indicators for safety, 51
errors and problems, 40
errors, acceptable ranges, 51
gyroscopic within, 39–40
preflight inspection, 39–41, 45, 47
setting or caging the gyro, 40
- attrition, 2, 4
auto-ignition, 5
automatic direction finder (ADF), 25
- aviation gasoline (avgas), 129
avionics bus, electrical system, 177–178
- balanced propellers, 213
batteries, 153, 154–168, 181
adding water to battery, 163
ammeters, 173, **173**
charge state, 157
corrosion, 7
electrolytes, 157, 164
emergency locator transmitter (ELT), 22–23
explosion of batteries, 158
installation, 161, 163
lead-acid batteries, 154–164, 191–192, 196–198
load shedding, 173, 184–185, 188–191
nickel-cadmium (NiCd) batteries, 164–168, **165**, 192–194, 199
rating system, NiCd batteries, 165, 168
reversed polarity, explosion, 158
specific gravity (SPGR), 157–161, 162, 163
temperature vs. performance, 157–161, 162, 163
- Beech Baron B55 fuel system, **133**
Bendix drive for starter motor, 183–184
bird strikes, transparency (window)
strength, 16
- blade angle, propellers, 202, **209**
booststrapping, turbocharger systems, 146
boots, de-icing systems, 262–266
borescopes, 111
bottom dead center (BDC), 79, 87
Bourdon tube temperature measurement, 96
- brake fluid, 234–235, 238
brakes, 229–238, **231**, 275, **276**
build-and-fade signals, ELT, 23, **24**
bus, electrical, 176–178
- cabling, airframe inspection, 4
calibrated airspeed (CAS), 29–30
camber, propellers, 202
carbon monoxide, 5, 241
carburetor heat, 82, 108
carburetors, 79, 82, 97, 137, 138–139
cavitation, pumps, hydraulic systems, 278
- centrifugal force, propellers, 215
Cessna TU206G turbocharger, **145**
- charge state, batteries, 157