

- circuit breakers (CB), 152, **153**, 174, 179
 circuits, 152
 cleanliness of aircraft exterior, 3
 coils, 180–181
 combustion heaters, 239, 241–242, **242**
 compass (*see* magnetic compass)
 compression stroke, 79, 80, 87, 144
 compression test, 111
 conductors, 180–181
 connecting rods, 80
 constant-speed propellers, 204, 210
 cooling systems, 5, 82–87, 109–110, 112–113
 air cooling, 82–83
 airflow cooling engine, **85**
 corrosion, 7
 cowl flaps, 86–87
 cowling, 83, **84**
 cylinder head temperature (CHT)
 gauges, 84–85
 detonation problems, 85–87
 exhaust gas temperature (EGT) gauges, 84
 heat build up during operational
 phases, 86
 heat damage, 84
 oil as coolant, 116, 121
 preflight inspections, 106
 preignition problems, 85–87
 pressure (fluid) cooling, 83, **84**
 turbocharger systems, 147–148, 150
 velocity (air) cooling, 82–83
 corrosion
 airframe inspection, 6–8
 cleansing properties of oil, 116, 122
 propellers, 215
 cowl flap, **81**, 86–87
 cowling, 83, **84**
 cracks, airframe inspection, 4
 cracks, crankcase/cylinder, 64–65
 crankcase, 64–65
 (*See also* engines)
 crankshaft, **66**, 80
 crazing, transparencies (windows),
 15–16, 19–20
 current, 154, 180–181
 cycle of engine operation, 80
 cylinder head temperature (CHT)
 gauges, 5, 84–85, 96, 100, **100**,
 109–110, 147–148
 cylinders, 79, 80, 97, 111, 144–145
 damping, magnetic compass, 55–56
 dc-to-ac conversion, electrical systems, 179
 de-icing/anti-icing systems, 257–268
 boots, 262–266
 de-icing vs. anti-icing, 258
 electrothermal propeller de-icing,
 258–262, **259**, **260**
 HOTPROP system, 258–262
 pneumatic de-icing systems, 262–266,
 263, **264**
 preflight inspections, 261, 263–264
 preventive maintenance, 262, 265–266
 TKS Weeping Wing anti-icing system,
 266–268, **267**
 troubleshooting, 264–265
 deceleration errors
 attitude indicators, 40–41
 magnetic compass, 57–58
 deflection in aircraft tires, 222
 deformation of structure, airframe
 inspection, 4
 degree markings, magnetic compass, 54
 delamination of transparencies, 18–19
 delta p conditions, pressurization
 systems, 248
 density altitude, 34
 detonation problems, 85–87, 109, 130
 deviation, magnetic compass, 56
 dip angle, magnetic compass, 52, 55
 directional gyro (DG), 52, 57
 distance measuring equipment (DME), 25
 drift, heading indicators, 41, 50
 dry-pump pneumatic systems, 283
 dumping of fuel, 128
 dust, in interior of aircraft, 13
 dynamic errors, magnetic compass, 56
 Earth's magnetic fields, 52, **53**
 electrical systems, 151–200
 alternators, 168–172, **169**, **171**,
 175–176, 187–188, 194
 ammeters, 173, **173**, 187–188
 amp-hours, battery life, 154
 amps, 154
 avionics bus, 177–178
 batteries, 153, 154–168, 181
 adding water to battery, 163
 ammeters, 173, **173**
 charge state, 157
 electrolytes, 157, 164
 explosion of batteries, 158
 installation, 161, 163
 lead-acid batteries, 154–164,
 191–192, 196–198