

- lighting systems (*Cont.*):  
 preventive maintenance, 12–13  
 radio frequency interference (RFI), 12  
 strobe lights, 10–12, **11**  
 xenon flash tubes, strobe lights, 13
- load, airframe, overload, and G-force  
 load, 4–5
- load shedding, electrical systems, 173,  
 184–185, 188–191
- locks and latches, 14
- loose objects in interior, 13–14
- LORAN, 25
- lubber lines, magnetic compass, 54
- lubricating systems & lubricating  
 all mineral oils, 115, 116  
 analysis of oil for contaminants,  
 123–125  
 ashless dispersant oils, 115, 117  
 brakes, 237–238  
 changing the oil, 110, 111, 122–123,  
 125–126  
 cleansing properties of oil, 116, 122  
 cold weather oils, 121–122  
 contaminants and sludge, 118,  
 123–125  
 cooler for hot oil, 121  
 cooling properties of oil, 116, 121  
 engine-driven oil pump, **120**  
 filters, 118, **120**, 122–123  
 flash point, 116  
 friction, 116, 121  
 grades of oil, 115, 121  
 leaks and drips, 105, 122  
 metallic ash detergent oils, 116–117  
 mixing different types of oils, 117–118  
 oil consumption, 108, 112  
 oil pressure gauges, 102–103, 105, 118,  
 121  
 oil temperatures, 5, 96, 101  
 preventive maintenance, 121–123  
 propellers, 214  
 quantity of oil, 105, 121  
 sealing/cushioning properties of oil,  
 116  
 Society of Automotive Engineers (SAE)  
 ratings, 115  
 spark plug contamination with oil, 122  
 specifications, grades for oil, 115,  
 116–117, 121  
 synthetic oil, 117–118  
 turbocharger systems, 148, 150  
 viscosity, 110, 111, 115–116, 121–122, 124
- lubricating systems & lubricating (*Cont.*):  
 wet sump system, 118–121, **119**, **120**,  
 281–283
- Lycoming horizontally opposed engine,  
**79**
- machmeters, 29
- magnetic compass, 51–59  
 acceleration/deceleration errors, 57–58  
 agonic line of variation, 59  
 components of typical compass, 53–55, **54**  
 damping, 55–56  
 degree markings, 54  
 deviation, 56  
 dip angle, 52  
 dip error, 55  
 Earth's magnetic fields, 52, **53**  
 errors, static and dynamic, 56  
 fluid in compass, damping, 55–56  
 flux lines of Earth's magnetic field, 52  
 headings, cardinal, 54  
 lubber lines, 54  
 pelorus, 56  
 swinging the compass, 56  
 turning error, 57  
 variation, lines of, 58–59, **58**
- magnetic drift, heading indicators,  
 41, 50
- magnetic forces in a coil, 180–181, 180,  
**182**
- magnetic variation, lines of, 58–59, **58**
- magnetos, 80, 87, 88–89, **89**, 106–108,  
 112, 153
- maintenance (*see* preventive  
 maintenance)
- manifold pressure (m.p.) gauges,  
 101–102, 146
- marker beacons, 25
- master switch, 175
- mechanical error, in altimeters, 34
- mufflers, life expectancy, 61
- Naval N3N, Wright 760 radial engine, **78**
- navigational equipment, lighting  
 interference with navigation, 12
- needle/ball (*see* turn indicator)
- negative delta p conditions, pressurization  
 systems, 248
- nickel-cadmium (NiCd) batteries,  
 164–168, **165**, 192–194, 199
- noise abatement, transparencies  
 (windows) and noise reduction, 15