



## Standard Specification for Modular Gage Boards<sup>1</sup>

This standard is issued under the fixed designation F 707/F707M; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reappraisal. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reappraisal.

*This standard has been approved for use by agencies of the Department of Defense.*

### 1. Scope

1.1 This specification covers modular gage boards for mounting 89-mm (3½-in.), 114-mm (4½-in.), 152-mm (6-in.), and 216-mm (8½-in.) dial size pressure gages and dial thermometers for miscellaneous shipboard applications.

1.2 Gage boards ordered under this specification are suitable for pressure gages and dial thermometers with either turret or back flanged type cases and with either back or bottom connections (see Appendix X1).

1.3 Gage mounting dimensions shall be in accordance with ANSI B 40.1.

1.4 The values stated in metric units (SI) are to be regarded as the standard. The values given in parentheses (inch/pound) are provided for information purposes.

NOTE 1—Gage boards covered by this specification are those normally supplied by the shipyard as opposed to the shipyard's equipment subcontractor.

### 2. Referenced Documents

#### 2.1 ASTM Standards:

B 40.1 Gages, Pressure and Vacuum, Indicating Dial Type—Elastic Element<sup>2</sup>

#### 2.2 Other Standards:

Fed Spec. TT-P-645 Primer, Paint, Zinc-Chromate, Alkyd Type<sup>3</sup>

DoD-P-15328 Primer (Wash), Pretreatment (Formula No. 117 for Metals) (Metric)<sup>3</sup>

### 3. Classification

3.1 Gage boards are furnished in two types as follows:

3.1.1 *Type I*—Gage boards for mounting 89-mm (3½-in.) and 114-mm (4½-in.) dial size gages as specified in Section 5.

3.1.2 *Type II*—Gage boards for mounting 152-mm (6-in.) and 216-mm (8½-in.) dial size gages as specified in Section 5.

3.2 Gage boards are furnished in two grades as follows:

3.2.1 *Grade a*—Gage boards are to be manufactured from carbon steel as specified in Section 5.

3.2.2 *Grade b*—Gage boards are to be manufactured from aluminum alloy as specified in Section 5.

### 4. Ordering Information

4.1 Orders for gage boards under this specification shall include the following information:

4.1.1 Quantity (number of gage boards),

4.1.2 Name of item (gage board),

4.1.3 *Type* (Type I or Type II as specified by purchaser), see 3.1.1 and 3.1.2,

4.1.4 *Grade* (Grade a or Grade b as specified by purchaser), see 3.2.1 and 3.2.2,

4.1.5 *Paint* (as specified by purchaser), see 7.2,

4.1.6 *Drilling for gage mounting* (as specified by purchaser), see 5.1.1, and

4.1.7 ASTM designation and date of issue.

### 5. Materials and Manufacture

5.1 Unless otherwise specified the gage boards shall be manufactured from 11-gage (manufacturers standard gage) carbon steel for Grade a and 3 mm (⅛ in.) thick aluminum alloy for Grade b. Materials shall be capable of being bent at room temperature through 90° in any direction to an inside radius equal to its thickness without cracking on the outside of the bent portion.

5.1.1 Unless otherwise specified, Type I gage boards shall be drilled for mounting both 89-mm (3½-in.) and 114-mm (4½-in.) dial size gages and Type II gage boards shall be drilled for mounting both 152-mm (6-in.) and 216-mm (8½-in.) dial size gages. When specified by the purchaser, drilling shall be limited to one size gage for either Type I or Type II gage boards (see 4.1.6).

### 6. Dimensions and Permissible Variations

6.1 The dimensions of the gage board shall not vary by more than 0.4 mm ( $\pm 1/64$  in.) except as noted in Fig. 1 and Fig. 2.

### 7. Workmanship, Finish and Appearance

7.1 The gage boards shall have a workmanlike finish free of scale, burrs, cracks, and other defects affecting serviceability or appearance.


<sup>1</sup> This specification is under the jurisdiction of ASTM Committee F-25 on Shipbuilding and is the direct responsibility of Subcommittee F25.13 on Piping Systems.

Current edition approved Aug. 15, 1994. Published October 1994. Originally published F 707 – 81. Last previous edition F 707 – 82 (1988) $\epsilon^1$ .

<sup>2</sup> Available from American National Standards Institute, 11 W. 42nd St., 13th Floor, New York, NY 10036.

<sup>3</sup> Available from Standardization Documents Order Desk, Bldg. 4 Section D, 700 Robbins Ave., Philadelphia, PA 19111-5094, Attn: NPODS.

**ASTM F 707/F707M**



**FIG. 1 Gage Board Type I**

7.2 If paint is not specified by the purchaser, Grade a gage boards shall be supplied with a coat of zinc chromate primer in accordance with Federal Specification TT-P-645, Formula 84 or equal (yellow) 0.038-mm (1.5-mils) dry film thickness. Grade b gage boards shall be supplied with one pretreatment wash coat in accordance with Specification DOD-P-15328 Formula 117 or equal (dark green) 0.013-mm (0.5-mils) dry film thickness and one coat of zinc chromate primer in accordance with Federal Specification TT-P-645 Formula 84D or equal (dark green) 0.013 mm (1.5-mils) dry film thickness.


**8. Product Marking**

8.1 Each shipping unit shall bear a tag or be plainly marked with the following: ASTM designation number, name or trademark of manufacturer, number of pieces, and purchase order number.

**9. Keywords**

9.1 dial pressure gages; dial thermometers; modular gage boards; pressure gages

**F 707/F707M**



**FIG. 2 Gage Board Type II**

**APPENDIX**

(Nonmandatory Information)


**X1. RATIONALE USED FOR DEVELOPMENT OF SPECIFICATION FOR MODULAR GAGE BOARDS**

X1.1 This specification has been developed primarily to provide maximum versatility for the installation of 89-mm ( $3 \frac{1}{2}$ -in.), 114-mm ( $4 \frac{1}{2}$ -in.), 152-mm (6-in.), and 216-mm ( $8 \frac{1}{2}$ -in.) dial size simplex, duplex, and differential pressure gages and dial thermometers with either turret- or back-flanged cases. Fig. X1.1 Fig. X1.2 Fig. X1.3

X1.2 The gage board is suitable for single-gage installation,

but has the versatility of being bolted together horizontally, vertically, in pyramid fashion or a combination thereof to provide for multigage installations utilizing both Type I and Type II gage boards.

X1.3 When used in horizontally arranged installations, either bottom or back connected pressure gages and dial



**FIG. X1.1 Bottom- and Back-Connected Pressure Gages for Horizontal Installations of Type I or Type II Gage Boards**




FIG. X1.2 Back-Connected Pressure Gages for Vertical or Combined Vertical, Horizontal, and Pyramid Arrangements of Type I or Type II Gage Boards





FIG. X1.3 Back Connected Type I and Type II Gage Boards Combined For Vertical, Horizontal, and Pyramid Arrangements

thermometers may be used. When used vertically or in combination with vertical, horizontal, or pyramid arrangements, back connected pressure gages and dial thermometers must be used.

X1.4 This specification does not cover flush-mounted gages.

 **F 707/F707M**

*The American Society for Testing and Materials takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.*

*This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.*

*This standard is copyrighted by ASTM, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or [service@astm.org](mailto:service@astm.org) (e-mail); or through the ASTM website ([www.astm.org](http://www.astm.org)).*