



Designation: **B 505/B 505M – 9602**

Standard Specification for Copper-Base Copper Alloy Continuous Castings¹

This standard is issued under the fixed designation B 505/B 505M; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

This standard has been approved for use by agencies of the Department of Defense.

¹ This specification is under the jurisdiction of ASTM Committee B-5 B05 on Copper and Copper Alloys and is the direct responsibility of Subcommittee B05.05 on Castings and Ingots for Remelting.

Current edition approved ~~Sept. Oct. 10, 1996~~ 2002. Published November ~~1996~~ 2002. Originally published as B 505 – 70. Last previous edition B 505 – 956.

1. Scope *

1.1 This specification establishes requirements for continuously cast rod, bar, tube, and shapes produced from ~~copperbase~~ copper alloys with nominal compositions as listed in Table 1.²

1.2 Castings produced to this specification may be manufactured for and supplied from stock. In such cases the manufacturer shall maintain heat traceability to specific manufacturing date and chemical analysis.

1.3 The values stated in inch/pound or SI units are ~~to be regarded separately as standard.~~ ~~SI~~ The values ~~given~~ stated in ~~each~~ system may not be exact equivalents; therefore, each system ~~shall~~ be used independently of the other. ~~Combining values from the two systems may result in nonconformance with the specification.~~

1.4 This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.

2. Referenced Documents

2.1 The following documents in the current issue of the Book of Standards form a part of this specification to the extent referenced herein:

2.2 ASTM Standards:

B 208 Practice for Preparing Tension Test Specimens for ~~Copper-Base~~ Copper Alloys for Sand, Permanent Mold, Centrifugal and Continuous Castings³

B 824 Specification for General Requirements for Copper Alloy Castings³

B 846 Terminology for Copper and Copper Alloys³

E 8 Test Methods for Tension Testing of Metallic Materials⁴

E 8M Test Methods for Tension Testing of Metallic Materials (Metric)⁴

E 10 Test Method for Brinell Hardness of Metallic Materials⁴

E 18 Test Methods for Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials⁴

E 255 Practice for Sampling of Copper and Copper Alloys for the Determination of Chemical Composition⁵

E 527 Practice for Numbering Metals and Alloys (UNS)⁶

3. Terminology

3.1 For definitions of terms related to copper and copper alloys, refer to Terminology B 846.

4. General Requirements

4.1 The following sections of Specification B 824 form a part of this specification. The definition of a casting lot as defined in Section 12, Sampling, takes precedence over Specification B 824.

² The UNS system for copper and copper alloys (see Practice E 527) is a simple expansion of the former standard designation system accomplished by the addition of a prefix "C" and a suffix "00". The suffix can be used to accommodate composition variations of the base alloy.

³ Annual Book of ASTM Standards, Vol 02.01.

⁴ Annual Book of ASTM Standards, Vol 03.01.

⁵ Annual Book of ASTM Standards, Vol 01.01, 03.05.

⁶ Available from the American Society

⁶ Annual Book of Mechanical Engineers, United Engineering Center, 345 East 47th St., New York, NY 10017; ASTM Standards, Vol 01.01.

*A Summary of Changes section appears at the end of this standard.

TABLE 1 Nominal Composition

Copper Alloy UNS No.	Designation	Composition, %							
		Copper	Tin	Lead	Zinc	Nickel	Aluminum	Iron	Manganese
C83600	leaded red brass	85	5	5	5
C83800	leaded red brass	83	4	6	7
C83800	leaded red brass	82.9	3.8	6	6.5
C84200	leaded semi-red brass	80	5	2	13
C84200	leaded semi-red brass	80	5	2.5	13
C84400	leaded semi-red brass	84	3	7	9
C84400	leaded semi-red brass	80	2.9	7	8.5
C84800	leaded semi-red brass	76	3	6	15
C84800	leaded semi-red brass	76	2.5	6.2	15
C85700	leaded naval brass	64	4	4	37
C85700	leaded naval brass	61	1	1.2	36
C86200	high-strength yellow brass	66	23	...	5	3	3
C86200	high-strength yellow brass	63	25	...	4	3	3.8
C86300	high-strength yellow brass	62	26	...	6	3	3
C86300	high-strength yellow brass	63	25	...	6.2	3	3.8
C86500	high-strength yellow brass	58	39	...	4	4	4
C86500	high-strength yellow brass	57.5	39	...	1	1.2	0.8
C89320 ^A	bismuth tin bronze	89	6
C90300	tin bronze	88	8	...	4
C90300	tin bronze	87.5	8.2	...	4
C90500	tin bronze	88	40	...	2
C90500	tin bronze	87.5	10	...	2
C90700	tin bronze	89	11
C91000	tin bronze	85	15
C91300	tin bronze	84	49
C91300	tin bronze	80.5	19
C92200	leaded tin bronze	88	6	2	4
C92200	leaded tin bronze	88	6	1.5	4
C92300	leaded tin bronze	87	8	4	4
C92300	leaded tin bronze	87	8.2	0.6	3.8
C92500	nickel-phosphor bronze	86.5	44	4	...	4.5
C92500	nickel-phosphor bronze	86.5	11	1.2	...	1.2
C92700	leaded tin bronze	88	40	2
C92700	leaded tin bronze	87.5	10	1.8
C92800	leaded tin bronze	79	46	5
C92800	leaded tin bronze	80	16	5
C92900	leaded nickel-tin bronze	84	40	2.5	...	3.5
C92900	leaded nickel-tin bronze	84	10	2.6	...	3.4
C93200	high-leaded tin bronze	83	7	3
C93200	high-leaded tin bronze	83	6.9	7	3
C93400	high-leaded tin bronze	84	8	8
C93400	high-leaded tin bronze	83.5	8	8
C93500	high-leaded tin bronze	85	5	9	4
C93500	high-leaded tin bronze	84.5	5.2	9	1
C93600	high-leaded tin bronze	81	7	12
C93700	high-leaded tin bronze	80	40	40
C93700	high-leaded tin bronze	80	10	9.5
C93800	high-leaded tin bronze	78	7	15
C93800	high-leaded tin bronze	77	6.9	14.5
C93900	high-leaded tin bronze	78	6	16
C94000	high-leaded tin bronze	72	43	15
C94000	high-leaded tin bronze	70.5	13	15
C94100	high-leaded tin bronze	75	5	20
C94100	high-leaded tin bronze	75.5	5.5	20
C94300	high-leaded tin bronze	70	5	25
C94300	high-leaded tin bronze	69.5	5.2	25
C94700	nickel-tin bronze	88	5	0	2	5
C94700	nickel-tin bronze	87.5	5.2	0	1.8	5.2
C94800	leaded nickel-tin bronze	87	5	4	2	5
C94800	leaded nickel-tin bronze	86.5	5.2	0.6	1.8	5.2
C95200	aluminum bronze	88	9	3	...
C95200	aluminum bronze	87.8	9	3.2	...
C95300	aluminum bronze	89	40	4	...
C95300	aluminum bronze	88.8	10	1.2	...
C95400	aluminum bronze	86	44	4	...
C95400	aluminum bronze	85.2	10.8	4	...
C95410	aluminum bronze	84	2	40	4	...
C95410	aluminum bronze	83.2	2	10.8	4	...
C95500	nickel-aluminum bronze	84	4	44	4	...
C95500	nickel-aluminum bronze	81	4.2	10.8	4	...
C95520	nickel-aluminum bronze	78.5	6.5	44	5.0	...
C95520	nickel-aluminum bronze	79.1	5.1	11	4.8	...
C95700	manganese nickel aluminum	76	2	8	3	42
C95700	manganese nickel aluminum	74.8	2.2	7.5	3	12.5
C95800	nickel-aluminum bronze	81.3	4.5	9	4	1.2
C95900	aluminum bronze	82.5	2	13	4.5	...
C95900	aluminum bronze	83.2	12.8	4.0	...
C96400	copper-nickel	70	30
C96400	copper-nickel	67	30	...	0.90	...

- 4.1.1 Terminology (Section 3),
- 4.1.2 Other Requirements (Section 7),
- 4.1.3 Workmanship, Finish, and Appearance (Section 9),
- 4.1.4 Number of Tests and Retests (Section 11),
- 4.1.5 Specimen Preparation (Section 12),
- 4.1.6 Test Methods (Section 13),
- 4.1.7 Significance of Numerical Limits (Section 14),
- 4.1.8 Inspection (Section 15),
- 4.1.9 Rejection and Rehearing (Section 16),
- 4.1.10 Certification (Section 17),
- 4.1.11 Test Report (Section 18),
- 4.1.12 Product Marking (Section 19),
- 4.1.13 Packaging and Package Marking (Section 20),
- 4.1.14 Keywords (Section 21), and
- 4.1.15 Supplementary Requirements.

5. Ordering Information

3.1 Orders for continuous castings under this specification should include

5.1 Include the following information:

3.1.1 Specification title, number, information in orders for product:

5.1.1 ASTM designation and year of issue,

3.1.2 Quantity, dimensions, and temper,

3.1.3 Copper issue (for example, B 505/B 505M-96),

5.1.2 Copper Alloy UNS Number,

3.1.4 Tolerances, No. (for example, C93200), including HT if different from Section 8 and Tables 2- heat treatment is required.

5.1.3 Condition (Table 9) and (as cast, heat treated, and so forth),

5.1.4 Dimensions: inside diameter, outside diameter, thickness and width,

5.1.5 Form: cross-section, such as tube, round, hexagon, octagon, square, or rectangle,

5.1.6 Tolerances, if different from Section 10 and Tables 2-8,

5.1.7 Length (including length tolerance if other than mill lengths),

35.1.8 Number of castings or total weight, for each size and form,

5.1.9 ASME Boiler and Pressure Vessel Code⁷ requirements (if required see Section 7 9),

35.1.610 When castings are purchased for agencies of the U.S.—G government, the Supplementary Requirements of Specification B 824 may be specified.

35.2 The following requirements are optional and should be specified in the purchase order when required:

35.2.1 Chemical analysis of residual elements (Section 5 7 and Specification B 824),

35.2.2 Mechanical requirements, (Section 6 8 Test Methods E 8),

35.2.3 Witness inspection (Specification B 824),

35.2.4 Certification (Specification B 824),

35.2.5 Foundry test report (Specification B 824),

35.2.6 Product marking (Specification B 824),

35.2.7 Castings for seawater service (Section 4 6), and

35.2.8 Approval of weld repair and records of repair (Section 9):

~~4- 11).~~

6. Materials and Manufacture

46.1 For better corrosion resistance in seawater applications, castings in Copper Alloy UNS No. C95800 shall be given a temperature anneal heat treatment at $1250 \pm 50^\circ\text{F}$ ($675 \pm 10^\circ\text{C}$) for 6 h minimum. Cooling shall be by the fastest means possible that will not cause excessive distortion or cracking. Propeller castings shall be exempt from this requirement.

46.2 Copper Alloy UNS Nos. C95300, C95400, C95410, and C95500 may be supplied in the heat-treated condition to obtain the higher mechanical properties shown in Table 9. 9. Suggested heat treatments for these alloys and Copper Alloy UNS No. C95520 are given in Table 2. Actual practice may vary by manufacturer.

46.3 Copper Alloy UNS No. C95520 is used only in the quench-hardened and tempered (TQ30) condition, see Table 2.

46.4 Copper Alloy UNS No. C96900 is normally supplied heat treated at 1520°F (825°C) for 1 h followed by a water quench, then aged at 800°F (425°C) for 4 h followed by a water quench.

⁷ Available from American Society of Mechanical Engineers (ASME), ASME International Headquarters, Three Park Ave., New York, NY 10016-5990.

**TABLE 11.3 Sum of Finishing Allowances for Tubing
(Rounds Analyzed)**

Copper Alloy UNS No. (mm)	Finish Allowance Plus Added to Name Finished or Print Dimensions of the Part, % in. (mm)	
	Copper Alloy UNS No.	Copper Alloy UNS No.
C83600	99.3	99.3
C83800	99.3	99.3
Up to 4 (102), excl	-0.031 (-0.79)	+ 0.031 (0.79)
C84200	99.3	99.3
4 (102)-5 (127), incl	-0.063 (-1.6)	+ 0.063 (1.6)
C84400	99.3	94 (2.4)
Over 5 (127)	-0.094 (-2.4)	+ 0.09
98.7		
C84800, C94100, C98.7		
Copper Alloy UNS Nos. C86200, C86300, C86500, C95200, C95300, C95400, C95500, C95800, C95900, and C96400		
C94300	99.0	99.0
Up to 3 (76.2), incl	-0.125 (-3.2)	+ 0.063 (1.6)
C94700	99.3	99.3
Over 3 (76.2)-4 (102), incl	-0.125 (-3.2)	+ 0.094 (2.4)
C94800	99.0	99.3
Over 4 (102)-5 1/2 (140), incl	-0.188 (-4.8)	+ 0.09
C95200	99.0	99.0
Over 5 1/2 (140)	-0.250 (-6.4)	+ 0.09
C95300	99.4	99.0
C95400	99.7	99.5
C95410	99.4	99.5
C95500	99.4	99.5
C95520	99.4	99.5
C95700	99.3	99.5
C95800	99.3	99.5
C95900	99.3	99.5
C96400	99.3	99.5
C96900	99.3	99.5
C97300	99.3	99.0
C97600	99.2	99.7
C97800	99.2	99.6
C97800	99.2	99.6
C99500	99.4	99.7
C99500	99.4	99.7

46.5 If test bar coupons representing castings made in Copper Alloy UNS Nos. C94700HT, C95300HT, C95400HT, C95410HT, C95500HT, C95520HT, C95800 temper annealed, C95900 annealed, and C96900 are removed from the continuous castings before heat treatment, the coupons shall be heat treated with the continuous castings.

57. Chemical Composition

- 57.1 The continuous castings shall conform to the requirements for major elements shown in Table 10.
- 57.2 These specification limits do not preclude the presence of other elements. Limits may be established and analysis required for unnamed elements agreed upon between the manufacturer or supplier and the purchaser. Copper or zinc may be given as remainder and may be taken as the difference between the sum of all elements analyzed and 100 %. When all named elements in Table 10 are analyzed, their sum shall be as specified in Table 11.
- 57.3 It is recognized that residual elements may be present in cast copper-base alloys. Analysis shall be made for residual elements only when specified in the purchase order.

68. Mechanical Property Requirements

- 68.1 Reference should be made to Table 9 for minimum mechanical requirements.
- 68.2 Mechanical tests are required only when specified by the purchaser in the purchase order.
- 68.3 Exceptions to mechanical property requirements may be taken in the case of small diameter solids or castings having section thicknesses less than the 1/2-in. (12.7-mm) diameter nominal size of the standard tension test specimen. In these cases, mechanical property requirements shall be subject to agreement between the purchaser and the manufacturer. For suggested dimensions of subsize substandard test bars, see Test Methods E 8.

 **B 505/B 505M – 9602**

**TABLE 9 4 MecFinishing Allowanical Requis foreme Rod antsd
Bar**

CoppFinished Outside Diameter-All or UNS No.	TensDile-Streangth, min ^A	Yield Str Bngth, at 0.5 %-Extensioen UndParallel Sur-Lofadces, m inA	El (. mm)	Roundsf
C83600	36	248	19	134
C83600	36	248	19	134
C83800	30	207	15	16
Up to 4 (102), excl	30	207	15	16
C84200	32	224	16	13
4 (102)-5 (127), incl	32	224	16	13
C84400	30	207	15	
Over 5 (127)	30	207	15	
103			16	
C84800 30207	4510316			
Copper Alloy UNS Nos. C86200, C863007	4, C86500, C95200, C95300, C95400, C95500, C95800, C95900, C96400			
C85700	40	276	14	15
Up to 3 (76.2), incl	40	276	14	15
C86200	90	624	45	18
Over 3 (76.2)-4 (102), incl	90	624	45	18
C86300	110	758	62	14
Over 4 (102)-5 1/2 (140), incl	110	758	62	14
C86500	70	483	25	25
C89320	35	244	18	15
Over 5 1/2 (140)	35	244	18	15
C90300	44	303	22	18
C90500	44	303	25	10
C90700	40	276	25	10
C91000	30	207	...	160 (3000-kg)
C91300
C92200	38	262	19	18
C92300	40	276	19	16
C92500	40	276	24	10
C92700	38	252	20	8
C92800
C92900	45	310	25	8
C93200	35	244	20	10
C93400	34	234	20	8
C93500	30	207	16	12
C93600	33	227	20	10
C93700	35	244	20	6
C93800	25	172	16	5
C93900	25	172	16	5
C94000	80 (500-kg)
C94100	25	172	17	7
C94300	21	145	15	7
C94700	45	310	20	25
C94700HT	75	517	50	5
C94800	40	276	20	20
C95200	68	469	26	20
C95300	70	483	26	25
C95300HT	80	552	40	12
C95400	85	586	32	12
C95400HT	95	655	45	10
C95410	85	586	32	12
C95410HT	95	655	45	10
C95500	95	655	42	10
C95500HT	110	758	62	8
C95520HT	125	862	95 ^D	262 (3000-kg)
C95700	90	620	40	15
C95800 ^E	85	586	35	18
C95900	241 (3000-kg)
C96400	65	448	35	25
C96900HT	110	758	105 ^D	4
C97300	30	207	15	8
C97600	40	276	20	10
C97800	45	310	22	8
C99500	70	483	40	12

^A Minimum tensile strength and yield strength shall be reduced 10 % for cast bars having a cross section, thickness, diameter, or wall of 4 in. (102 mm) or more. The cross sections are the diameter of a round solid, the distance across the flats of a solid hexagon, the thickness of a rectangle, and the wall thickness of a tube.

^B ksi = 1000 psi.

^C See Appendix.

^D Yield strength at 0.2 % offset, min^A, ksi^B, MPa^C.



TABLE 2 5 SuggDiamested Heat Tr Toleratmnces for Rod and Bar

Table with columns for Diameter-All oyr Distance, UNS No., and Tolerances. Includes rows for UNS C95300, C95300, C95410, C95500, C95800, C95900, and C96400.

^ When tolerances are specified as all plus or all minus, double the values given.

79. ASME Requirements

79.1 When specified in the purchase order to meet ASME Boiler and Pressure Vessel Code requirements, continuous castings shall comply with the following:

79.1.1 Certification requirements of Specification B 824.

79.1.2 Foundry test report requirements of Specification B 824.

79.1.3 Continuous castings shall be marked with the manufacturer’s name, the Copper Alloy UNS No., and the casting quality factor. In addition, heat numbers, or serial numbers that are traceable to heat numbers, shall be marked on all pressure-containing castings individually weighing 50-lb (22.7 kg) or more.

79.1.4 When Copper Alloy UNS No. C95200 is specified to meet ASME Boiler and Pressure Vessel Code requirements, a sample from each 2000-lb interval or continuous casting shall be tested. Each continuous casting from which the test bar was taken shall be identified should retesting be required.

810. Dimensions and Permissible Variations

810.1 Allowance for finishing over maximum outside dimension and under inside dimension of round tubes to be machined shall be as shown in Table 3. Allowances for finishing the outside diameter of rounds and distance between parallel surfaces of bars to be machined shall be as shown in Table 4.

810.2 Concentricity:

810.2.1 All Alloys Except as Noted in-8 10.2.2—The outside periphery of continuously cast tubing shall be concentric with the bore within a permissible variation of 2 % of the nominal wall thickness over 1/4 in. (6.35 mm).

810.2.2 Copper Alloy UNS Nos. C86200, C86300, C86400, C95200, C95300, C95400, C95410, C95500, C95520, C95800, C95900, and C96400—The outside periphery of continuously cast tubing shall be concentric with the bore within a permissible variation of 4 % of the nominal wall thickness.

810.3 Diameter Tolerances for Continuously Cast Rod and Bar—See Table 5.

8.4 Tolerances of Average Diameter

10.4 Diameter Tolerances for Continuously Cast Tube (Round only)—See Table 6.

TABLE 5 6 Diameter Tolerances for Tube (Rod and Bar Only)

Average Outside or Distance Between Two Parallel Surfaces (mm)	Tolerances, in. (mm)		
	Outside Diameter	Inside Diameter	
	Plus ^A and or Minus ^A in. (mm)	Plus ^B	Minus ^B
	Rounds	Squares, Rectangles, Hexagons, Octagons	
		Plus ^B	Minus ^B Rectangles, Hexagons, Octagons
^B			
All Alloys Except as Noted Below			
Up to 4 (102), excl	0.005 (0.13)	0.016 (0.30)	-0.033 (0.841)
Up to 4 (102), incl	0.005 (0.13)	0.012 (0.30)	0.033 (0.84)
4 (102)–5 (127), incl	0.008 (0.20)	0.016 (0.41)	
4 (102)–5 (127), incl	0.008 (0.20)	0.016 (0.41)	0.046 (1.2)
Over 5 (127)	0.016 (0.41)	0.016 (0.41)	
Over 5 (127)	0.016 (0.41)	0.032 (0.81)	0.064 (1.6)
Copper Alloy UNS Nos. C86200, C86300, C86500, C95200, C95300, C95400, C95500, C95800, C95900, and C96400			
Up to 3 (76.2), incl	0.010 (0.25)	0.020 (0.32)	-0.033 (0.51)
Up to 3 (76), incl	0.010 (0.25)	0.012 (0.32)	0.033 (0.84)
Over 3 (76.2)–4 (102), incl	0.015 (0.38)	0.020 (0.38)	0.054
Over 3 (76)–4 (102), incl	0.015 (0.38)	0.015 (0.38)	0.050 (1.3)
Over 4 (102)–5½ (140), incl	0.020 (0.51)	0.020 (0.564)	0.070 (1)
Over 4 (102)–5½ (140), incl	0.020 (0.51)	0.025 (0.64)	0.070 (1.8)
Over 5½ (140)	0.025 (0.64)	0.025 (0.64)	0.090 (2.3)
Over 5½ (140)	0.025 (0.64)	0.035 (0.86)	0.090 (2.3)

^A When tolerances are specified as all plus or all minus, double the values given.

^B When tolerances are specified as all plus or all minus, total the values given.

810.5 Roundness—For continuously cast tubing in straight lengths, the roundness tolerances shall be as shown in Table 7.

810.6 Dimensional Tolerances for All Other Shapes (not Covered by 7-10.1 or 8-210.2)—See Table 8.

8.7 Straightness Tolerances for Continuously Cast Rod, Tube, Bars, and Shapes—See Table 12.

9. Casting Repair

9.1 Continuous castings shall not be mechanically repaired, plugged, or burned in.

9.2 Weld repair is permitted for Copper Alloy UNS Nos. C95200, C95300, C95400, C95410, C95500, C95800, and C95900.

9.3 Weld repairs may be made at the manufacturer's discretion provided each excavation does not exceed 20 % of the casting section or wall thickness or 4 % of the casting surface area.

9.4 Excavations that exceed those described in 8.2 may be made at the manufacturer's discretion except that when specified in the purchase order (4.1.12) the weld procedure shall be approved by the purchaser and the following records shall be maintained:

9.4.1 A sketch or drawing showing the dimensions, depth, and location of excavations;

9.4.2 Post-weld heat treatment, when applicable;

9.4.3 Weld repair inspection results;

9.4.4 Casting identification number;

9.4.5 Weld procedure identification number;

9.4.6 Welder identification, and

9.4.7 Name of inspector.

9.5 The castings shall not be impregnated without approval of the purchaser.

9.6 Weld repair of other alloys in this specification is not permitted without approval by the purchaser.

10. General Requirements

10.1 The following sections of Specification B 824 form a part of this specification.

10.1.1 Terminology (Section 3);

10.1.2 Other Requirements (Section 6);

10.1.3 Workmanship, Finish, and Appearance (Section 8);

10.1.4 Number of Tests and Retests (Section 10);

10.1.5 Specimen Preparation (Section 11);

10.1.6 Test Methods (Section 12);

10.1.7 Significance of Numerical Limits (Section 13);

10.1.8 Inspection (Section 14);



B 505/B 505M – 9602

TABLE 6 7 DiamRoundneterss Tolernances for Tube (Round Only)

Average Outside Diameter, in. (mm)	Tolerances, in. (mm)	
Outside Diameter	Inside Diameter	
Outside Diameter	Outside Diameter	
Plus ^A	or	
Minus ^A		
(mm)		
Plus ^A		
in.		
(mm)	Plus ^B	Minus ^B
	All Alloys Except as Noted Below	
Up to 0.005 (0.13)		
4		
(102),		
excl		
Up to 0.020 (0.51)		
4		
(102),		
excl		
0.012 (0.30)		0.033 (0.84)
4 (102)–5 (127), incl		0.032 (0.81)
4		0.016 (0.41)
(102)–5		0.046 (1.2)
(127),		
incl		
0.008 (0.20)		0.016 (0.41)
		0.046 (1.2)
Over 0.016 (0.41)		
5		
(127)		
Over 0.064 (1.6)		
5		
(127)		
	0.032 (0.81)	0.064 (1.6)
	Copper Alloy UNS Nos. C86200, C86300, C86500, C95200, C95300, C95400, C95500, C95800, C95900, and C96400	
Up to 0.010 (0.25)		0.012 (0.32)
3		–0.033 (0.84)
(76),		
incl		
Up to 3 (76.2), incl		0.025 (0.32)
Over 0.015 (0.38)		0.015 (0.38)
3		
(76)–4		
(102),		
incl		
Over 3 (76.2)–4 (102), incl		0.040 (1.0)
0.050 (1.3)		
Over 0.020 (0.51)		
4		
(102)–5½		
(140),		
incl		
Over 0.060 (1.5)		
4		
(102)–5½		
(140),		
incl		
0.025 (0.64)		0.070 (1.8)
Over 0.025 (0.64)		0.035 (0.86)
5½		0.090 (2.3)
(140)		
Over 0.075 (1.64)		0.035 (0.86)
5½		0.090
(140)		

^AWhen deviation from roundness is specified, the values are plus or minus double the values given.

^BWhere difference between major and minor diameters are specified, the values are plus or minus cross section of the tubes given.

TABLE 7.8 Roundness Tolerances for Shapes

Outside Diameter, in. (mm)	Maximum Out-of-Roundness, ^A in. (mm)	Up to Inside Diameter, in. (mm), except	Over 4 in. (102 mm), except
0.020 (0.51) All Alloys Except as Noted Below			
4 (102)–5 (127), in. Plus	0.032 (0.81)		
Over 5 (127)	0.064 (1.6)		
Minus	Plus	0.064 (1.6)	
Copper Alloy UNS Nos. C86200, C86300, C86500, C95200, C95300, C95400, C95500, C95800, C95900, and C96400			
Copper Alloy UNS Nos. C86200, C86300, C86500, C95200, C95300, C95400, C95500, C95800, C95900, and C96400			
Up to 3 (76.2), incl	0.025 (0.64)	Over 3 (76.2)–4 (102), incl	0.040 (1.0)
0.016 (0.41)	0.016 (0.41)	0.032 (0.81)	0.064 (1.6)
Over 4 (102)–5 (140), incl			d C96400
Copper Alloy UNS Nos. C86200, C86300, C86500, C95200, C95300, C95400, C95500, C95800, C95900, and C96400			d C96400
0.060 (1.5)			
Over 5½ (140)	0.075 (1.9)		
Over Dimensional Tolerances shall be subject to agreement between purchaser and manufacturer.			

^A When deviation from roundness are specified as all plus or all minus, double the values given.
^B When between major and minor diameters are specified at any plus or all minus see, the values given.

- 10.1.10 Certification (Section 16);
- 10.1.11 Test Report (Section 17);
- 10.1.12 Product Marking (Section 18);
- 10.1.13 Packaging and Package Marking (Section 19);
- 10.1.14 Supplementary Requirements.

11. Sampling

11.1 Unless otherwise specified, a lot shall consist of Casting Repair

11.1 Continuous castings of the same composition and same cross-sectional dimensions, produced during the continuous operation of one casting machine, and submitted for inspection at one time.

11.2 A sample for chemical analysis shall not be taken from each lot mechanically repaired, plugged, or burned in.

11.2 Weld repair is permitted for Copper Alloy UNS Nos. C95200, C95300, C95400, C95410, C95500, C95800, and C95900.

11.3 Weld repairs may be made at the manufacturer’s discretion, provided each interval excavation does not exceed 20 % of 2000 lb (910 kg) of continuous production of the lot. When castings are produced from alloy ingots casting section or wall thickness or 4 % of known composition, the sampling interval casting surface area.

11.4 Excavations that exceed those described in 11.3 may be raised to one sample for each 4000 lb (1810 kg) of continuous production of made at the lot.

11.3 When mechanical testing is manufacturer’s discretion, except that when specified by the purchaser in the purchase order one sample for tension testing shall be taken from each lot. This sample may be taken before mechanical straightening. Test coupons shall be positively identified with (5.2), the castings they represent. Where castings are heat treated, test coupons weld procedure shall be heat treated with approved by the castings they represent.

11.4 When Copper Alloy UNS No. C95200 is specified for ASME boiler purchaser and pressure vessel requirement, a sample from each 2000-lb interval or continuous casting the following records shall be tested. Each continuous cast bar from which maintained:

- 11.4.1 A sketch or drawing showing the dimensions, depth, and location of excavations,
- 11.4.2 Post-b-weld heat treatment, when applicable,
- 11.4.3 Weld repair inspection results,
- 11.4.4 Casting identification number,
- 11.4.5 Weld procedure identification number,
- 11.4.6 Welder identification, and



B 505/B 505M - 9602

TABLE 8.9 Typical Mechanical Requirements for Shapes

Outside Diameter Alloy UNS No.	Tensile Strength, min ^A in. (mm)		Yield Strength, at 0.5 % Extension Under Load, min ^A		Elongation in 2 in. or 50 mm, min, %	Brinell Hardness, min	Remarks
	ksi ^B	MPa ^C	ksi (mm)				
			ksi	MPa ^C			
All Alloys Except as Noted Below	36	248	19	131	15		
C83600	36	248	19	131	15		
Plus	Minus	Plus	Minus	97	46		
C83800	30	207	15	97	16		
0.016 (0.41)	0.016 (0.41)	0.032 (0.81)	0.064 (1.6)				
C84200	32	221	16				
				110	13		
Copper Alloy UNS Nos. C86200, C86300, C86500, C95200, C95300, C95400, C95500, C95800, C95900, and C96400	Dimension	30	207	15	403	46	
C84400	30	207	15	103	16		
C84800	30	207	15	103	16		
C85700	40	276	14	97	15		
C86200	90	621	45	310	18		
C86300	110	758	62	427	14		
C86500	70	483	25	172	25		
C89320	35	241	18	124	15		
C90300	44	303	22	152	18		
C90500	44	303	25	172	10		
C90700	40	276	25	172	10		
C91000	30	207	160 (3000 kg)	
C91300		
C92200	38	262	19	131	18		
C92300	40	276	19	131	16		
C92500	40	276	24	165	10		
C92700	38	252	20	138	8		Round tolerances for all of Rockwell B 72-82
C92700	38	252	20	138	8		
C92800		
C92900	45	310	25	172	8		
C93200	35	241	20	138	10		
C93400	34	234	20	138	8		
C93500	30	207	16	110	12		
C93600	33	227	20	138	10		
C93700	35	241	20	138	6		
C93800	25	172	16	110	5		
C93900	25	172	16	110	5		
C94000	80 (500 kg)	
C94100	25	172	17	117	7		
C94300	21	145	15	103	7		
C94700	45	310	20	138	25		
C94700HT	75	517	50	345	5		her shapes (not covered by heat treated
C94700HT 4-800	40	276	20	138	20		
C94800	40	276	20	138	20		
C95200	68	469	26	179	20		
C95200	68	469	26	179	20		
C95300	70	483	26	179	25		
C95300HT	80	552	40	276	12		shall be subject to agreement heat treated
C95300HT	80	552	40	276	12		
C95400	85	586	32	221	12		
C95400HT	95	655	45	310	10		heat treated
C95400HT	95	655	45	310	10		heat treated
C95410	85	586	32	221	12		
C95410HT	95	655	45	310	10		heat treated
C95410HT	95	655	45	310	10		heat treated
C95500	95	655	42	290	10		
C95500HT	110	758	62	427	8		heat treated
C95500HT	110	758	62	427	8		heat treated
C95520HT	125	862	95 ^D	655 ^D	2	262 (3000 kg)	heat treated ^E
C95520HT	125	862	95 ^D	655 ^D	2	262 (3000 kg)	heat treated ^E
C95700	90	620	40	275	15		
C95800 ^F	85	586	35	241	18		
C95900	241 (3000 kg)	
C96400	65	448	35	241	25		
C96900HT	110	758	105 ^D	724 ^D	4		Rockwell C32
C97300	30	207	15	103	8		
C97600	40	276	20	138	10		
C97800	45	310	22	152	8		
C99500	70	483	40	276	12		

^AThe minimum tensile strength and yield strength shall be reduced 10% for cast shapes having a cross section thickness, diameter, or wall of 4 in. (102 mm)

**TABLE 3 11 Finishing Sum of Allowances for Tubed Elements
(Recommended Analyzed)**

Finish Copper Outside Diameter; Alloy in UNS No. (mm)	Finish All Coppers Added to Finished or Printed Dimensions of the Parts, %min. (mm)		
	Inside Diameter	Outside Diameter Copper Plus Named Element	
S, %min			
All Alloys Except as Noted	99.3	C93600	99.3
Below C83600			
C83600	99.3	C93600	99.3
Up to 4 (102), excl	-0.031 (-0.79)	+ 0.031 (0.700)	.9)
C83800	99.3	C93700	99.0
4 (102) - 5 (127), incl	-0.063 (-1.6)	+ 0.063 (1	.6)
C84200	99.3	C93800	99.0
Over 5 (127)	-0.094 (-2.4)	+ 0.094 (-2.4)	
C84400	99.3	C93900	99.0
			98.9
Copper Alloy UNS Nos. C86200; C86300, C86500; C	95200, C95300;	C95400; C95500, C	95800, C95900, and C96400
C84800	99.3	C94000	98.7
Up to 3 (76.2), incl	-0.125 (-3.2)	+ 0.063 (1	.6)
C85700	98.7	C94100	98.7
Over 3 (76.2) - 4 (102), incl	-0.125 (-3.2)	+ 0.0	94 (2.4)
C86200	99.0	C94300	99.0
Over 4 (102) - 5 1/2 (140), incl	-0.188 (-4.8)	+ 0.0	98.125 (3.2)
C86300	99.0	C94700	98.7
Over 5 (140)	-0.250 (-6.4)	+ 0.0	98.7
C86500	99.0	C94800	98.7
C89320	99.5	C95200	99.0
C90300	99.4	C95300	99.0
C90500	99.7	C95400	99.5
C90700	99.4	C95410	99.5
C91000	99.4	C95500	99.5
C91300	99.4	C95520	99.5
C92200	99.3	C95700	99.5
C92300	99.3	C95800	99.5
C92500	99.3	C95900	99.5
C92700	99.3	C96400	99.5
C92800	99.3	C96900	99.5
C92800	99.3	C96900	99.5
C92900	99.3	C97300	99.0
C93200	99.0	C97600	99.7
C93400	99.0	C97800	99.6
C93400	99.0	C97800	99.6
C93500	99.0	C99500	99.7

11.4.7 Name of inspector.

11.5 The castings shall not be identified should retesting be required. If all impregnated without approval of the test bars from the initial sampling meet the requirements, the lot shall be acceptable.

11.4.1 The fractured bars shall be retained for chemical verification.

11.5 Tension test bar specimens shall be taken from continuous castings in accordance with Fig. 6 purchaser.

11.6 Weld repair of Practice B-208 other alloys in this specification is not permitted without approval by the purchaser.

12. Test Methods

12.1 Analytical Sampling

TABLE 4 12 ~~F~~Strainig~~hting~~ Allowances ~~fs~~ Toler Rod and Barces

Finished Outside Diameter or Distance Between Parallel Surfaces; in. (mm) [†]	Length, ^A ft (m)	Maximum Curvatures ^B (Depth of Arc); Rectangles; Hexagons; Octagons
All Alloys Except as Noted Below		
All Alloys Except as Noted Below. (mm)		
Up to 4 (102), excl	+ 0.031 (0.79)	+ 0.031 (0.79)
Round rod or tube up to 10 (3.05)		1/4 (6.4) in any 5-ft (1.52-m) portion
4 (102)–5 (127), incl	+ 0.063 (1.6)	+ 0.063 1/2 (1.6)
	10 (3.05) and over	1/2 (13) in any 10-ft (3.05-m) portion ^A
Over 5 (127)	+ 0.094 (2.4)	+ 0.094 1/2 (2.4) Copper Alloy UNS Nos. C86200, C86300, C86500, C95200, C95300, C95400, C95500, C95800, C95900, C96400
Bar and shape	any length	1/2 (13) in any 6-ft (1.83-m) C95400, C95500, C95800, C95900, C96400
Up to 3 (76.2), incl	+ 0.0625 (1.6)	+ 0.0625 (1.6)
Up to 3 (76.2), incl	+ 0.0625 (1.6)	+ 0.0625 (1.6)
Over 3 (76.2)–4 (102), incl	+ 0.093 (2.4)	+ 0.0625 (1.6)
Over 3 (76.2)–4 (102) ^A , incl	+ 0.093 (2.4)	+ 0.0625 (1.6)
Over 4 (102)–5 1/2 (140), incl	+ 0.125 (3.2)	+ 0.0625 (1.6)
Over 5 1/2 (140) ^A	+ 0.188 (4.8)	+ 0.0625 (1.6)
Over 5 1/2 ^B (140)	+ 0.188 (4.8)	+ 0.0625 (1.6)

^A Of total length.

^B Applicable to any longitudinal surface or edge.

12.1 Sampling shall be accordance with the requirements of Practice E 255.

12.2 Unless otherwise specified, a lot shall consist of castings of the same composition and same cross-sectional dimensions, produced during the continuous operation of one casting machine, and submitted for inspection at one time.

12.3 A sample for chemical methods are given in Specification B 824 (Section 12).

12.2 Brinell Hardness Reading analysis shall be taken from each lot at each interval of 2000 lb (910 kg) of continuous production of the grip end lot. When castings are produced from alloy ingots of known composition, the sampling interval may be raised to one sample for each 4000 lb (1810 kg) of continuous production of the lot.

12.4 When mechanical testing is specified by the purchaser in the purchase order one sample for tension testing shall be taken from each lot. This sample may be taken before mechanical straightening. Test bar specimens shall be positively identified with the castings they represent. Where castings are heat treated, test bar and specimens shall be made in accordance heat treated with Test Method E 10 with the exception that castings they represent.

12.5 When Copper Alloy UNS No. C95200 is specified for ASME boiler and pressure vessel application, a 3000-kg load sample from each 2000-lb interval or continuous casting shall be used.

12.3 Rockwell Hardness Reading tested. Each continuous cast bar from which the test bar was taken shall be taken on the grip end identified should retesting be required. If all of the tension test bars from the initial sampling meet the requirements, the lot shall be acceptable.

12.5.1 The fractured bars shall be retained for chemical verification.

12.6 Tension test bar and specimens shall be made taken from continuous castings in accordance with Test Methods E 18. Fig. 6 of Practice B 208.

13. Test Methods

13.1 Analytical chemical methods are given in Specification B 824 (Section 12).

13.2 Brinell Hardness Reading shall be taken on the grip end of the tension test bar and shall be made in accordance with Test Method E 10. If a Brinell hardness is required and a tension test is not required, testing shall be in accordance with Test Method E 10.

13.3 Rockwell Hardness Reading shall be taken on the grip end of the tension test bar and shall be made in accordance with Test Methods E 18. If a Rockwell hardness is required and a tension test is not required, testing shall be in accordance with Test Method E 18.

14. Product Marking

134.1 At the request of the purchaser castings shall be marked with the alloy number.

145. Keywords

145.1 continuous castings; copper alloy castings; ~~copper-base alloy castings~~

APPENDIX

(Nonmandatory Information)

X1. METRIC EQUIVALENTS

X1.1 The SI unit for strength properties now shown is in accordance with the International System of Units (SI). The derived SI unit for force is the newton (N), which is defined as that force which when applied to a body having a mass of one kilogram gives it an acceleration of one metre per second squared ($N = \text{kg}\cdot\text{m}/\text{s}^2$). The derived SI unit for pressure or stress is the newton per square metre (N/m^2), which has been named the pascal (Pa) by the General Conference on Weights and Measures. Since $1 \text{ ksi} = 6\,894\,757 \text{ Pa}$ the metric equivalents are expressed as megapascal (MPa), which is the same as MN/m^2 and N/mm^2 .

SUMMARY OF CHANGES

~~This section identifies principle~~

Committee B05 has identified the location of selected changes to this specification standard since the last issue.

~~1. Section 10 was rewritten to list issue (B 505 – 96) that may impact the sections use of Specification B 824 which apply to this specification.~~

~~2. Section 3 was rewritten.~~

~~3. The second sentence of paragraph 5.2 was revised standard.~~

(1) Comprehensive 5-year review completed. Some sections were renumbered, and, in some cases reworded to provide conform to the new Committee B05 Outline of Form for “analysis required.”

~~4. Paragraphs 6.2 Specifications (OFS) and 11.3 were revised to eliminate an existing conflict.~~

~~5. New Section 7 was added combining paragraph 9.4 Form and Section 12 and adding other ASME requirements.~~

~~6. Paragraph 12.1 Style for ASTM Standards (Blue Book).~~

(2) The safety caveat was added.

(3) The Terminology section was added.

(4) Table 1, Nominal Composition was revised.

(5) Table 10, Chemical Requirements has been changed to reflect the current CDA Standard Designations. Some required chemical compositions have been changed.

(6) Added UNS Nos. ~~C69600~~ C89320 and C93600 to Table 11, Sum of All Named Elements Analyzed. These additions reflect the current CDA Standard Designations.

(7) UNS No. C953800 ~~w~~ has been changed to reflect the current CDA Standard Designations.

(8) Practice E 255 has been added to Section 2, Referenced Documents and Section 12, Sampling.

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org).