



Standard Test Method for Laboratory Measurement of Noise Reduction of Sound- Isolating Enclosures¹

This standard is issued under the fixed designation E 596; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

This standard has been approved for use by agencies of the Department of Defense.

1. Scope

1.1 This test method covers the reverberation room measurement of the noise reduction of sound-isolating enclosures.

1.2 The noise isolation class may be determined from the noise reduction measured in accordance with this test method.

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 ASTM Standards:

C 423 Test Method for Sound Absorption and Sound Absorption Coefficients by the Reverberation Room Method²

C 634 Terminology Relating to Environmental Acoustics²

E 413 Classification for Rating Sound Insulation²

2.2 ANSI Standards:

S1.4 Specification for Sound Level Meters³

S1.11 Specification for Octave-Band and Fractional-Octave-Band Analog and Digital Filters³

3. Terminology

3.1 *Definitions and Symbols*—Except as noted in 3.2, the terms and symbols used in this test method are defined in Terminology C 634.

3.2 Definitions of Terms Specific to This Standard:

3.2.1 *sound-isolating enclosure*—any enclosure that completely encloses a space, is intended to provide sound isolation for the enclosed space, and can be tested in a reverberation room.

3.2.2 *useful volume of a sound isolating enclosure*—the part of the space inside the enclosure in which the noise reduction is of interest. For example, in an audiometric booth, the useful volume is the part of the space inside the booth where a test

subject's head is likely to be during audiometric tests.

4. Summary of Test Method

4.1 The enclosure to be tested is placed in a reverberation room and prepared for testing. The background noise levels inside the enclosure and in the reverberation room are measured in one-third octave bands. After bands of random noise are produced in the reverberation room, one-third octave band sound pressure levels are measured at several points in the reverberation room and at appropriate points inside the enclosure. The noise reduction in each one-third octave band is the difference between the space-averaged sound pressure level in the reverberation room and the space-averaged sound pressure level inside the enclosure. The noise isolation class (NIC) may be determined from the noise reduction data.

5. Significance and Use

5.1 The noise reduction of an enclosure is a property of the enclosure, the location of the sound source used to measure noise reduction, and the space in which the enclosure is placed. It is not a property of the enclosure alone, and its measurement under different conditions can be expected to give different results. When the noise reduction is measured in accordance with this test method, the sound source is outside the enclosure and the sound field outside the enclosure approximates a diffuse sound field. Measurements made in accordance with this test method can be expected to be reproducible from one laboratory to another.

5.2 The noise reduction measured in accordance with this test method may be used for the following purposes:

5.2.1 To rank the order of sound-isolating enclosures according to noise isolation class, NIC.

5.2.2 To estimate the highest one-third octave band sound pressure levels that can occur outside the enclosure without exceeding specified sound pressure levels inside the enclosure.

5.2.3 To estimate the one-third octave band sound pressure levels that will occur inside the enclosure with specified sound pressure levels outside.

5.3 The noise reduction measured in accordance with this test method may not estimate accurately the isolation that the enclosure will provide when it is used to isolate a noise source inside it from the space outside. The user should be cautious when using noise reductions measured by this test method to

¹ This test method is under the jurisdiction of ASTM Committee E-33 on Environmental Acoustics and is the direct responsibility of Subcommittee E33.03 on Sound Transmission.

Current edition approved Jan. 10, 1996. Published April 1996. Originally published as E 596 – 77. Last previous edition E 596 – 94a.

² *Annual Book of ASTM Standards*, Vol 04.06.

³ Available from American National Standards Institute, 11 W. 42nd St., 13th Floor, New York, NY 10036.

evaluate enclosures used to enclose noise sources.

5.4 Sound-isolating enclosures are frequently made from prefabricated modular panels. The noise reduction measured by this test method applies to the complete enclosure and not to individual panels from which it is made and cannot be used to infer the sound transmission loss of the individual panels.

5.5 Specifications for sound-isolating enclosures may include reference to noise reduction and noise isolation class measured in accordance with this test method.

6. Reverberation Room

6.1 *Sound Diffusion*—The sound field in the reverberation room shall closely approximate a diffuse field when the enclosure to be tested is in place for testing. In general, the requirements for the reverberation room are those listed in the section dealing with *Reverberation Room* of Test Method C 423. These requirements include:

6.1.1 The effective room volume (actual room volume minus the volume occupied by the enclosure) should not be less than 200 m³.

NOTE 1—Experience and experimental data have shown that as long as the requirements of 9.1.2 and 9.5 are satisfied, the room volume is not critical.

6.1.2 The sound absorption in the reverberation room shall be made as low as possible in order to achieve the best possible simulation to an ideal diffuse field and in order to keep the region dominated by the direct field of the source as small as possible. Within the frequency range described below the sound absorption of the reverberation room should be no greater than the following:

$$A = V^{2/3}/3 \quad (1)$$

where:

V = room volume, m³, and

A = room sound absorption in metric sabins.

For frequencies below $f = 2000/V^{1/3}$ (where the number 2000 is an empirical constant with the units seconds per metre), somewhat higher absorption may be desirable to accommodate other test requirements (for example, ANSI S1.32, ISO 3741); in any case, the absorption should be no greater than three times the value given by Eq 1. For frequencies above 2000 Hz, atmospheric absorption may make it impossible to avoid a slightly higher value of sound absorption.

6.1.3 Diffusing devices such as rotating and stationary diffusing surfaces are useful for creating an adequate approximation to a diffuse sound field.

6.2 Background Noise:

6.2.1 The sound pressure level of the background noise inside the enclosure should be at least 10 dB below the level of the test signal. If the difference between the level of the test signal and the background noise level is less than 10 dB and greater than 5 dB, the adjusted value of the signal level is calculated by:

$$L_a = 10 \log (10^{L_c} - 10^{L_b}) \quad (2)$$

where:

L_a = adjusted signal level, dB,

L_c = level of combined signal and background noise, dB, and

L_b = level of background noise, dB.

If the difference between the level of the test signal and the background noise level is not at least 5 dB, then subtract 2 dB from the level of the combined signal and background noise and use this adjusted level. When the difference between the signal level and the background noise level is less than 5 dB, the measurements provide only an estimate of the lower limit of the noise reduction of the enclosure. Identify such limited measurements in the test report.

6.2.2 Structureborne noise within the reverberation room structure can excite the enclosure to be tested and cause the sound pressure level within the enclosure to be higher than would be measured due to the test signal alone. Therefore, the reverberation room floor should be adequately isolated against structureborne vibrations which are propagated into the reverberation room from the outside.

NOTE 2—When the background noise inside the enclosure is the same as the background noise in the reverberation room, it is likely that either the vibration isolation (if any) between the enclosure and the reverberation room floor is ineffective or the measured background noise is the internal noise of the measuring instruments.

6.3 *Construction*—In accordance with 6.1.2, the reverberation room should be constructed of materials that have low sound absorption coefficients. Normally, when a reverberation room is to be used to measure sound absorption, sound power level, or sound transmission loss, it must be constructed using materials and design details that will provide needed sound insulation against outside noise sources. If a reverberation room is to be constructed solely for testing sound-isolating enclosures in accordance with this test method, the sound isolation requirements are not so critical, and lighter materials may be used as long as the requirements of 6.1 and 6.2 are met.

7. Measuring Instrumentation

7.1 The minimum instrumentation required for this test method is:

7.1.1 A microphone and amplifier that satisfy the requirements of ANSI S1.4 for Type 1 or better sound level meters with the exception that A and B-weighting networks are not required.

NOTE 3—A flat characteristic is desirable and, when available, should be used in place of the C-weighting network.

7.1.2 A one-third octave filter set satisfying the requirements of ANSI S1.11 for a one-third octave band filter set, Order 3 or higher, Type 1 or better. The nominal center frequencies of the filters shall be those frequencies that are within the frequency range where the noise reduction is to be measured. This frequency range shall include all of the preferred one-third octave bands from 125 to 4000 Hz and may be extended, if desired.

7.1.3 A level meter, graphic level recorder, or other device from which the sound pressure level can be read. The averaging time of the instrumentation shall be sufficient to permit reading the average sound pressure level with adequate precision (see Section 11).

7.2 Additional microphone systems may be used. If additional microphones are used, differences in their responses should be accounted for either by careful calibration or by an appropriate measurement procedure (see 9.6).

8. Test Signal

8.1 The test signals shall be bands of random noise at least one-third octave wide and including every one-third octave band within the test range. The test range shall include all of the preferred one-third octave bands from 125 to 4000 Hz and may be extended, if desired.

8.2 The signal source shall be placed so that the enclosure to be tested is not in its direct field; the minimum distance from the source to any part of the enclosure shall be:

$$r \geq 0.63 A^{1/2} \quad (3)$$

where A is the sound absorption in the reverberation chamber with the enclosure present. Normally, the best practice is to direct the source into a trihedral corner of the reverberation room. If more than one loudspeaker is used, it is advisable that each loudspeaker be driven by an independent noise source.

8.3 The signal level shall be at least 10 dB above the measured background noise inside the enclosure at each test frequency.

9. Procedure

9.1 *Enclosure Placement*—Place the enclosure in the reverberation room so that:

9.1.1 No enclosure wall is parallel to a reverberation room wall.

9.1.2 The enclosure is at least one-half wavelength away from the reverberation room walls and ceiling and any diffusing surfaces at the center frequency of the lowest one-third octave band in which the noise reduction is to be measured.

9.1.3 The enclosure is mounted on the floor in the same way as when it is in normal use. Do not mount the enclosure on beams, rails, or vibration isolators unless they are normally used with the enclosure.

9.2 *Enclosure Preparation*:

9.2.1 If the enclosure is equipped with a self-contained air conditioning or ventilating system, operate the system for at least 10 min, turn the system off, and test without further adjustment.

9.2.2 After the procedure of 9.2.1 has been completed, open and close each enclosure door and access opening at least ten times and test without further adjustment.

9.2.3 If the enclosure is equipped with a connector for external air conditioning and ventilation, connect the enclosure to an external duct system that satisfies the manufacturer's specifications or recommendations for the enclosure.

9.3 *Inside Measuring Positions*—Select at least four microphone positions inside the enclosure as follows:

9.3.1 Determine the useful volume of the enclosure.

9.3.2 Distribute microphone positions evenly throughout the useful volume.

9.3.2.1 Microphone positions or traverses should not be located or pass within 0.30 m of the enclosure interior walls unless the useful volume necessarily includes these regions.

9.3.2.2 Microphone positions should not approach one an-

other to within a distance of one-half-wavelength at the lowest frequency of interest.

9.3.2.3 For low frequencies it is almost never possible to select four microphone positions that satisfy the requirement of 9.3.2.2. Whenever this is the case, microphone positions inside the enclosure should be selected to get the best estimate of the space-time average sound pressure level within the useful volume, disregarding spatial correlation among positions.

9.3.3 The potential number of statistically independent microphone positions N within a space is calculated as

$$N = UV \left(\frac{\lambda}{2} \right)^3 \quad (4)$$

where UV is the useful volume.

9.3.3.1 The effective number of independent measurement locations n shall be calculated as follows:

$n = N$ if N independent stationary microphone locations are used,

$= 2\pi r/(\lambda/2)$ if rotating microphone traverse of radius r is used,

$= L/(\lambda/2)$ if linear microphone traverse of length L is used. (5)

NOTE 4—A half-wavelength correlation distance is assumed, and the number of independent data samples is calculated on this basis. A minimum of four independent data points is required for calculation of the 95 % confidence limits from the table. This is not often possible in small enclosures at low frequencies. When this is the case, the data should be so identified in the report.

9.4 *Background Noise*—With the sound sources not operating, measure the background noise levels in the receiving room at each microphone position or traverse. Corrections shall be made unless the background level is more than 10 dB below the combination of signal and background. (The signal is the sound pressure level due to transmission through the test enclosure.) If the background level is between 5 and 10 dB below the combined level, correct the signal level using:

$$L_s = 10 \log_{10} \left(\frac{L_{sb}}{10^{10}} - \frac{L_b}{10^{10}} \right) \quad (6)$$

where:

L_b = the background noise level, dB,

L_{sb} = the level of signal and background combined, dB,
and

L_s = the adjusted signal level, dB.

9.5 *Outside Measuring Positions*—Select at least six independent microphone positions in the reverberation room. Microphone positions shall be no less than one-half wavelength or 1 m, whichever is less, away from any solid surface at the lowest test frequency. In addition, outside measuring positions should not lie within the direct field of the signal source as defined in 8.2.

9.6 *Measurements*—The purpose of these measurements is to obtain the difference between the space-averaged, one-third octave band sound pressure level outside the enclosure and the space-averaged, one-third octave band sound pressure level inside the enclosure. This may be done by one of the following three methods:

9.6.1 Use one microphone to measure sound pressure level both inside and outside the enclosure. If this test method is used, the sound power level of the test signal shall be constant

throughout the measurement.

9.6.2 Use two microphones to measure the required sound pressure levels, one inside the enclosure and one outside. Interchange the microphones and make the same measurement again. Average the two sets of measurements. The averaging eliminates errors caused by the difference between the sensitivities of the two microphones.

9.6.3 Use two or more calibrated microphones and adjust the measured sound pressure levels for microphone sensitivity.

9.7 *Noise Reduction*—Calculate the noise reduction in each one-third octave band as follows:

$$NR = \bar{L}_1 - \bar{L}_2 \quad (7)$$

where:

NR = noise reduction,

\bar{L}_1 = space averaged sound pressure level measured outside the enclosure (in the reverberation room), and

\bar{L}_2 = space averaged sound pressure level measured inside the enclosure.

9.7.1 *Determination of Space-Average Levels*—The space-average level corresponding to each set of sound pressure level data is given by:

$$\bar{L} = 10 \log \left(\frac{1}{n} \sum_{i=1}^n 10^{\frac{L_i}{10}} \right) \quad (8)$$

9.7.2 *Octave Band Noise Reduction*—Calculate 1/3-octave band noise reduction data as follows:

$$NR_{octi} = -10 \log_{10} \sum_{j=i-1}^{i+1} \frac{10^{\frac{NR_j}{10}}}{3} \quad (9)$$

It is not permissible to calculate the noise reduction using octave band sound pressure levels.

9.7.3 *Measurement Uncertainty*:

9.7.3.1 It is strongly recommended that the uncertainty of the noise reduction measurement (NR) be monitored to determine if more microphone positions would be beneficial. The overall uncertainty is derived from the uncertainty of the outside and inside sound pressure level measurements. The procedure is to calculate the 95 % confidence interval for both sound fields and then combine them to calculate the uncertainty for NR. The method, described in ASTM STP 15D,⁴ is summarized in 9.7.3.2 and following.

9.7.3.2 The standard deviation of the sound field is calculated as:

$$s = \left(\frac{\sum_{i=1}^n (L_i - \bar{L})^2}{n - 1} \right)^{1/2} \quad (10)$$

where:

s = standard deviation,

L_i = an individual sound pressure level reading, and

\bar{L} = the average sound pressure level.

9.7.3.3 The 95 % confidence interval in each sound field is:

$$\Delta_L = a s \quad (11)$$

where the factor a is determined by the number of independent microphone positions n and is drawn from Table 1.

9.7.3.4 The uncertainty of the noise reduction is the combined uncertainty of the sound pressure levels inside and outside the enclosure:

$$\Delta_{NR} = (\Delta_{L1}^2 + \Delta_{L2}^2)^{1/2} \quad (12)$$

9.7.3.5 *Precision Requirements*—It is recommended that the noise reduction uncertainty be no greater than 3 dB for the one-third octave bands centered on 125 and 160 Hz, 2 dB for bands on 200 and 250 Hz, and 1 dB for the bands centered in the range 315 to 4000 Hz. In certain small, highly reverberant rooms it may not be possible to achieve these figures.

9.8 *Noise Isolation Class*—Determine the noise isolation class, NIC, by using Classification E 413, except that the measured noise reduction values are used instead of the transmission loss values.

10. Report

10.1 Report the following information:

10.1.1 A statement, if true in every respect, that the test was conducted in accordance with this test method.

10.1.2 Description of the enclosure tested. The description should be sufficient to identify whether another enclosure is the same as the enclosure tested. It should include dimensions, weight, construction details, and materials used in construction.

10.1.3 Complete description of the microphone positions used to measure the sound pressure levels inside the enclosure.

10.1.4 Listing of the measured noise reduction for each one-third octave band within the test range, rounded to the nearest 1 dB. In addition, a graph showing the variation of the noise reduction with frequency may be included.

10.1.5 Statement of the estimated uncertainty of the noise reduction in each one-third octave band.

10.1.6 If a single number rating is given, it shall be the noise isolation class determined in accordance with 9.8. No other single number rating shall be reported.

TABLE 1 Factors for 95 % Confidence Limits for Averages

Number of Measurements	Confidence Limits ^A , $\bar{X} \pm as$
n	a
4	1.591
5	1.241
6	1.050
7	0.925
8	0.836
9	0.769
10	0.715
11	0.672
12	0.635
13	0.604
14	0.577
15	0.554
16	0.533
17	0.514
18	0.497
19	0.482
20	0.468
21	0.455
22	0.443
23	0.432
24	0.422
25	0.413

⁴ Manual on Presentation of Data and Control Chart Analysis, ASTM STP 15D, ASTM, 1976.

^A Limits that may be expected to include the "true" average, \bar{X} , 95 times in 100 in a series of problems, each involving a single sample of observations.

 **E 596**

10.1.7 Statement that the information listed in 10.2 is available on request, if it is not included in the test report.

10.2 The following information shall be made available by the testing laboratory to any one requesting it:

- 10.2.1 Detailed description of the test procedure,
- 10.2.2 Description of the reverberation room, and
- 10.2.3 List of the measuring instruments used and when they were last calibrated.

11. Precision and Bias⁵

11.1 *Precision and Bias*—Due to the difficulty of performing round robin tests, the precision and bias of this test method have not been measured. However, there is no known bias inherent in this test method. Furthermore, repeatability and reproducibility standard deviations are thought to be on the order of the figures given in 9.7.3.5.

12. Keywords

12.1 enclosures; noise isolation; noise isolation class; noise reduction; sound-isolating

⁵ Supporting data are available from ASTM Headquarters. Request RR: E33 – 1004.

ANNEX

(Mandatory Information)

A1. LABORATORY ACCREDITATION

A1.1 Scope

A1.1.1 This annex describes the critical testing procedures, instrumentation, and facilities required in order for a laboratory to demonstrate its competence to perform tests according to this test method.

A1.2 Facilities and Instrumentation

A1.2.1 The reverberation room shall satisfy the requirements of Section 6.

A1.2.2 Measuring instrumentation shall satisfy the requirements of Section 7. Included in the instrumentation shall be a noise source or noise sources that satisfy the requirements of Section 8.

A1.3 Procedures

A1.3.1 Test procedures shall satisfy the requirements of Section 9.

A1.3.2 The information required by 10.2 shall be available if not normally included in test reports.

A1.4 Quality Assurance

A1.4.1 *Calibration*—Calibration procedures shall provide confidence that sound pressure levels can be measured accurately enough to satisfy the precision requirements of Section 11.

A1.4.2 *Proficiency Testing*—Proficiency testing specimens are not practical for this test method.

The American Society for Testing and Materials takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, 100 Barr Harbor Drive, West Conshohocken, PA 19428.

This standard is copyrighted by ASTM, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (<http://www.astm.org>).