



Designation: E 2061 – 02

Guide for Fire Hazard Assessment of Rail Transportation Vehicles¹

This standard is issued under the fixed designation E 2061; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

INTRODUCTION

The traditional approach to codes and standards is the specification of individual fire-test-response requirements for each material, component, or product that is found in a given environment and is deemed important to maintain satisfactory levels of fire safety. This practice has been in place for so long that it gives a significant level of comfort; manufacturers know what is required to comply with the specifications and specifiers simply apply the requirements. The implicit assumptions are not stated, but they are that the use of the prescribed requirements ensures an adequate level of safety. There is no need to impose any change on those manufacturers who supply safe systems meeting existing prescriptive requirements; however, as new materials, components, and products are developed, manufacturers, designers, and specifiers often desire the flexibility to choose how overall safety requirements are to be met. It is the responsibility of developers of alternative approaches to state explicitly the assumptions being made which result in a design having an equivalent level of safety. One way to generate explicit and valid assumptions is to use a performance-based approach, based on test methods that provide data in engineering units, suitable for use in fire safety engineering calculations, as this guide provides.

This fire hazard assessment guide focuses on rail transportation vehicles. Such a fire hazard assessment requires developing all crucial fire scenarios that must be considered and consideration of the effect of all contents and designs within the rail transportation vehicle, which will potentially affect the resulting fire hazard. The intention of this guide is that rail transportation vehicles be designed either by meeting all the requirements of the traditional prescriptive approach or by conducting a fire hazard assessment, that needs to provide adequate margins of error, in which a level of safety is obtained that is equal to or greater than the level of safety resulting from the traditional approach.

1. Scope

1.1 This is a guide to developing fire hazard assessments for rail transportation vehicles. It has been written to assist professionals, including fire safety engineers, who wish to assess the fire safety of rail transportation vehicles, during or after their design (see also 1.6). This guide is not in itself a fire hazard assessment nor does it provide acceptance criteria; thus, it cannot be used for regulation.

1.2 Hazard assessment is a process that results in an estimate of the potential severity of the fires that can develop under defined scenarios, once defined incidents have occurred. Hazard assessment does not address the likelihood of a fire occurring. Hazard assessment is based on the premise that an ignition has occurred, consistent with a specified scenario, and that potential outcomes of the scenario can be reliably estimated.

1.3 Consistent with 1.2, this guide provides methods to estimate whether particular rail passenger designs provide an equal or greater level of fire safety when compared to designs developed based on the traditional applicable fire-test-response characteristic approaches currently widely used in this industry. Such approaches have typically been based on prescriptive test methodologies, as exemplified by guidelines of the Federal Railroad Administration (FRA) and recommended practices of the Federal Transit Administration (FTA) (Table X1.1). Selective use of parts of the methodology in this guide and of individual fire-test-response characteristics from Table X1.1 does not satisfy the fire safety objectives of this guide or of the table. This guide shall be used in its entirety to develop a fire hazard assessment for rail transportation vehicles or to aid in the design of such vehicles.

1.4 This guide includes and applies accepted and clearly defined fire safety engineering techniques and methods consistent with both existing, traditional prescriptive codes and standards and performance based fire codes and standards under development throughout the world.

1.5 This guide provides recommended methods to mitigate

¹ This guide is under the jurisdiction of ASTM Committee E05 on Fire Standards and is the direct responsibility of Subcommittee E05.17 on Transportation.

Current edition approved August 10, 2002. Published September 2002. Originally published as E 2061 – 00. Last previous edition E 2061 – 01a.

potential damage from fires in rail transportation vehicles, by assessing the comparative fire hazard of particular products, assemblies, systems or overall designs intended for use in rail transportation vehicles. Such methods could include changes to the materials, components, products, assemblies, or systems involved in the construction of the rail transportation vehicle or changes in the design features of the vehicle, including the number and location of automatically activated fire safety devices present (see 4.4.4 for further details).

1.6 This guide is intended, among other things, to be of assistance to personnel addressing issues associated with the following areas.

1.6.1 Design and specification of rail transportation vehicles.

1.6.2 Fabrication of rail transportation vehicles.

1.6.3 Supply of assemblies, subassemblies, and component materials, for use in rail transportation vehicles.

1.6.4 Operation of rail transportation vehicles.

1.6.5 Provision of a safe environment for all occupants of a rail transportation vehicle.

1.7 The techniques provided in this guide are based on specific assumptions in terms of rail transportation vehicle designs, construction and fire scenarios. These techniques can be used to provide a quantitative measure of the fire hazards from a specified set of fire conditions, involving specific materials, products, or assemblies. Such an assessment cannot be relied upon to predict the hazard of actual fires, which involve conditions, or vehicle designs, other than those assumed in the analysis. In particular, the fire hazard may be affected by the anticipated use pattern of the vehicle.

1.8 This guide can be used to analyze the estimated fire performance of the vehicle specified under defined specific fire scenarios. Under such scenarios, incidents will begin either inside or outside a vehicle, and ignition sources can involve vehicle equipment as well as other sources. The fire scenarios to be used are described in detail in Section 5.3.

1.8.1 Fires with more severe initiating conditions than those assumed in an analysis may pose more severe fire hazard than that calculated using the techniques provided in this guide. For this reason severe fire conditions must be considered as part of an array of fire scenarios.

1.9 This fire standard cannot be used to provide quantitative measures.

2. Referenced Documents

2.1 *ASTM Standards:*

C 542 Specification for Lock-Strip Gaskets²

C 1166 Test Method for Flame Propagation of Dense and Cellular Elastomeric Gaskets and Accessories²

D 123 Terminology Relating to Textiles³

D 2724 Test Methods for Bonded, Fused, and Laminated Apparel Fabrics⁴

D 3574 Test Methods for Flexible Cellular Materials—Slab,

Bonded, and Molded Urethane Foams⁵

D 3675 Test Method for Surface Flammability of Flexible Cellular Materials Using a Radiant Heat Energy Source⁵

D 5424 Test Method for Smoke Obscuration of Insulating Materials Contained in Electrical or Optical Fiber Cables When Burning in a Vertical Cable Tray Configuration⁶

D 5537 Test Method for Heat Release, Flame Spread and Mass Loss Testing of Insulating Materials Contained in Electrical or Optical Fiber Cables When Burning in a Vertical Cable Tray Configuration⁶

D 6113 Test Method for Using a Cone Calorimeter to Determine Fire-Test-Response Characteristics of Insulating Materials Contained in Electrical or Optical Fiber Cables⁵

E 119 Test Methods for Fire Tests of Building Construction and Materials²

E 162 Test Method for Surface Flammability of Materials Using a Radiant Heat Energy Source²

E 176 Terminology of Fire Standards²

E 603 Guide for Room Fire Experiments²

E 648 Test Method for Critical Radiant Flux of Floor-Covering Systems Using a Radiant Heat Energy Source²

E 662 Test Method for Specific Optical Density of Smoke Generated by Solid Materials²

E 906 Test Method for Heat and Visible Smoke Release Rates for Materials and Products²

E 1321 Test Method for Determining Material Ignition and Flame Spread Properties²

E 1354 Test Method for Heat and Visible Smoke Release Rates for Materials and Products Using an Oxygen Consumption Calorimeter²

E 1355 Guide for Evaluating the Predictive Capability of Fire Models²

E 1472 Guide for Documenting Computer Software for Fire Models²

E 1474 Test Method for Determining the Heat Release Rate of Upholstered Furniture and Mattress Components or Composites Using a Bench Scale Oxygen Consumption Calorimeter²

E 1537 Test Method for Fire Testing of Upholstered Furniture²

E 1546 Guide for the Development of Fire-Hazard-Assessment Standards²

E 1590 Test Method for Fire Testing of Mattresses²

E 1591 Guide for Obtaining Data for Deterministic Fire Models²

E 1623 Test Method for Determination of Fire and Thermal Parameters of Materials, Products, and Systems Using an Intermediate Scale Calorimeter (ICAL)²

E 1740 Test Method for Determining the Heat Release Rate and Other Fire-Test-Resistance Characteristics of Wallcovering Composites Using a Cone Calorimeter²

2.2 *NFPA Standards:*⁷

NFPA 70 National Electrical Code

² Annual Book of ASTM Standards, Vol 04.07.

³ Annual Book of ASTM Standards, Vol 07.01.

⁴ Annual Book of ASTM Standards, Vol 07.02.

⁵ Annual Book of ASTM Standards, Vol 08.02.

⁶ Annual Book of ASTM Standards, Vol 10.02.

⁷ Available from the National Fire Protection Association (NFPA), 1 Batterymarch Park, Quincy, MA, 02269-9101.

NFPA 130 Standard for Fixed Guideway Transit Systems
NFPA 262 Standard Method of Test for Flame Travel and Smoke of Wires and Cables for Use in Air-Handling Spaces
NFPA 265 Standard Methods of Fire Tests for Evaluating Room Fire Growth Contribution of Textile Wall Coverings
NFPA 901 Uniform Coding for Fire Protection
2.3 *ISO Standards*.⁸
ISO 13943: Fire Safety: Vocabulary
ISO 4880: Burning Behaviour of Textiles and Textile Products
ISO 9705: Full Scale Room Fire Test for Surface Products
2.4 *Federal Aviation Administration Standards*.⁹
FAR 25.1359: Federal Aviation Administration 60° Bunsen Burner Test for Electric Wire
FAR 25.853 (a): Federal Aviation Administration Vertical Bunsen Burner Test
FAR 25.853 (c): Federal Aviation Administration Oil Burner Test for Seat Cushions
2.5 *Other Federal Standards*.¹⁰
Americans with Disabilities Act
FED STD 191A Textile Test Method 5830
2.6 *Underwriters Laboratories Standards*.¹¹
UL 44: Standard for Safety for Thermoset-Insulated Wires and Cables
UL 83: Standard for Safety for Thermoplastic-Insulated Wires and Cables
UL 1581: Reference Standard for Electrical Wires, Cables, and Flexible Cords, 1080 (VW-1 (Vertical Wire) Flame Test)
UL 1581: Reference Standard for Electrical Wires, Cables, and Flexible Cords, 1160 Vertical Tray Flame Test
UL 1685: Standard Vertical Tray Fire Propagation and Smoke Release Test for Electrical and Optical Fiber Cables
UL 1975: Standard Fire Tests for Foamed Plastics Used for Decorative Purposes
2.7 *Canadian Standards Association Standards*.¹²
CSA Standard C22.2 No. 3, Test Methods for Electrical Wires and Cables, Vertical Flame Test—Cables in Cable Trays/FT4
2.8 *Institute of Electrical and Electronic Engineers Standards*.¹³
IEEE Standard 383, Standard for Type Tests of Class 1E

Electric Cables, Field Splices, and Connections for Nuclear Power Generating Stations
2.9 *National Electrical Manufacturing Association Standards*.¹⁴
NEMA WC 3/ICEA S-19, Rubber-Insulated Wire and Cable for the Transmission and Distribution of Electrical Energy
2.10 *CA Standards*.¹⁵
CA Technical Bulletin 129, Flammability Test Procedure for Mattresses for Use in Public Buildings
CA Technical Bulletin 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies

3. Terminology

3.1 *Definitions*—For terms related to fire used in this guide, refer to Terminology E 176 and ISO 13943. In case of conflict, the terminology in Terminology E 176 shall prevail. For terms relating to textiles used in this guide, refer to Terminology D 123 or to ISO 4880. In case of conflict, the terminology in Terminology D 123 shall prevail.

3.1.1 *fire-characteristic profile, n*—array of fire-test-response characteristics, all measured using tests relevant to the same fire scenario, for a material, product, or assembly to address, collectively, the corresponding fire hazard.

3.1.1.1 *Discussion*—This array of fire-test response characteristics is a set of data relevant to the assessment of fire hazard in a particular fire scenario. In other words, all the fire tests used would have a demonstrated validity for the fire scenario in question, for example, by having comparable fire intensities. The fire-characteristic profile is intended as a collective guide to the potential fire hazard from a material, product, or assembly involved in a fire that could be represented by the laboratory test conditions.

3.1.2 *fire hazard, n*—the potential for harm associated with fire.

3.1.2.1 *Discussion*—A fire may pose one or more types of hazard to people, animals, or property. These hazards are associated with the environment and with a number of fire-test-response characteristics of materials, products, or assemblies including but not limited to ease of ignition, flame spread, rate of heat release, smoke generation and obscuration, toxicity of combustion products, and ease of extinguishment (see Terminology E 176).

3.1.3 *fire performance, n*—response of a material, product, or assembly in a particular fire, other than in a fire test involving controlled conditions (different from fire-test-response characteristics, q.v.).

3.1.3.1 *Discussion*—The ASTM policy on fire standards distinguishes between the response of materials, products, or assemblies to heat and flame “under controlled conditions,” which is fire-test-response characteristic, and “under actual fire conditions,” which is fire performance. Fire performance depends on the occasion or environment and may not be measurable. In view of the limited availability of fire-performance data, the response to one or more fire tests,

⁸ Available from International Organization for Standardization (ISO), 1 rue de Varembe, Case postale 56, CH-1211, Geneva 20, Switzerland or American National Standards Institute (ANSI), 25 W. 43rd St., 4th Floor, New York, NY 10036.

⁹ Available from the Federal Aviation Administration, Technical Center, Atlantic City International Airport, Atlantic City, NJ 08405.

¹⁰ Available from General Services Administration, Specifications Activity, Printed Materials Supply Division, Building 197, Naval Weapons Plant, Washington, DC 20407.

¹¹ Available from Underwriters Laboratories, Inc., 333 Pfingsten Rd., Northbrook, IL 60062.

¹² Available from the Canadian Standards Associations, 178 Rexdale Blvd., Rexdale, Ontario, Canada M9W 1R3.

¹³ Available from the Institute of Electrical and Electronic Engineers, Inc., 345 East 47th Street, New York, NY 10017.

¹⁴ Available from National Electrical Manufacturers Association, 1300 North 17th St., Ste 1847, Rosslyn, VA 22209.

¹⁵ Available from California Bureau of Home Furnishings and Thermal Insulation, State of California, Department of Consumer Affairs, 3485 Orange Grove Avenue, North Highlands, CA 95660-5595.

approximately recognized as representing end-use conditions, is generally used as a predictor of the fire performance of a material, product, or assembly (see Terminology E 176).

3.1.4 *fire scenario, n*—a detailed description of conditions, including environmental, of one or more of the stages from before ignition to the completion of combustion in an actual fire, or in a full-scale simulation.

3.1.4.1 *Discussion*—The conditions describing a fire scenario, or a group of fire scenarios, are those required for the testing, analysis, or assessment that is of interest. Typically, they are those conditions that can create significant variation in the results. The degree of detail necessary will depend upon the intended use of the fire scenario. Environmental conditions may be included in a scenario definition but are not required in all cases. Fire scenarios often define conditions in the early stages of a fire while allowing analysis to calculate conditions in later stages (see Terminology E 176).

3.1.5 *flashover, n*—the rapid transition to a state of total surface involvement in a fire of combustible materials within an enclosure.

3.1.5.1 *Discussion*—Flashover occurs when the surface temperatures of an enclosure and its contents rise, producing combustible gases and vapors, and the enclosure heat flux becomes sufficient to heat these gases and vapors to their ignition temperatures. This commonly occurs when the upper layer temperature reaches 600°C or when the radiant heat flux at the floor reaches 20 kW/m² (see Terminology E 176).

3.1.6 *heat release rate, n*—the heat evolved from the specimen, per unit of time.

3.1.7 *smoke, n*—the airborne solid and liquid particulates and gases evolved when a material undergoes pyrolysis or combustion (see Terminology E 176).

3.2 Definitions of Terms Specific to This Standard:

3.2.1 *product, n*—material, component, or complete end-use product, in use in rail transportation vehicles.

4. Significance and Use

4.1 This guide is intended for use by those undertaking the development of fire hazard assessments for rail transportation vehicles and products contained within rail transportation vehicles.

4.2 This guide provides information on an approach to develop a fire hazard assessment, but fixed procedures are not established. Any limitations in the availability of data, of appropriate test procedures, of adequate fire models, or in the advancement of scientific knowledge, will place significant constraints upon the procedure for the assessment of fire hazard.

4.3 A fire hazard assessment developed following this guide must specify all steps required to determine fire hazard measures for which safety thresholds or pass/fail criteria can be meaningfully set by responsible authorities. It is preferred that such exercises have input from various sources.

4.4 *Outcomes: Use and Application.* A fire hazard assessment developed as a result of using this guide should be able to assess a new product being considered for use in a certain rail transportation vehicle and reach one of the conclusions listed in 4.4.1-4.4.4.

4.4.1 *New Product Safer than Product Currently in Use.*

The new product is safer, in terms of predicted fire performance, than the one in established use. In this case, the new product is desirable, from the point of view of fire safety.

4.4.2 *New Product Equivalent in Safety to Product Currently in Use.* There is no difference between the predicted fire safety of the new product and of the one in established use. In this case, use of the new product provides neither advantage nor disadvantage, from the point of view of fire safety.

4.4.3 *New Product Less Safe than Product Currently in Use.* The new product is less safe, in terms of predicted fire performance, than the one in established use. In this case, a direct substitution of products would provide a lower level of safety and the new product would be undesirable, and should not be used, from the point of view of fire safety, without other compensatory changes being made.

4.4.3.1 *New Product Different in Safety to Product Currently in Use.* A new product that is less safe, in terms of predicted fire performance, can nevertheless be made acceptable if, and only if, it is part of a complete, comprehensive, fire safety design for the rail transportation vehicle. Such redesign of the vehicle should include other features such as use of an alternative layout or increased use of automatic fire protection systems, that demonstrably produce the same or better safety for the complete design. In such cases, a more in-depth fire hazard assessment would have to be conducted to ensure that the entire design achieves the safety goals, and the new product would be acceptable only as part of the larger, approved design.

4.4.4 The new product could offer some safety advantages and some safety disadvantages over the item in established use. An example of such an outcome could be increased smoke obscuration with decreased heat release. In such cases, a more in-depth fire hazard assessment would have to be conducted to ensure that the advantages outweigh the disadvantages, and the resulting overall level of safety is no less than that provided by the traditional approach (see Table X1 and Appendix X1).

4.5 Following the analysis described in 4.4, a fire hazard assessment developed following this guide would reach a conclusion regarding the desirability of the new product studied. It is essential for the results of the assessment to lead to a design that is at least as safe as the one being replaced.

5. Procedure

5.1 Fire Safety Objectives

5.1.1 The primary fire safety objective is to ensure the safe (unharmful) evacuation of all occupants of a rail transportation vehicle in the event of a fire.

5.1.1.1 This is achieved if the time required, in the event of a fire, to evacuate the vehicle is less than the time for the fire to create untenable conditions, preferably for the fire not to create conditions that cause harm to people, whenever possible, in the passenger compartment. The evacuation time includes the time required for the occupants to reach, or be transported, to a safe location and notification time.

5.1.1.2 The time to untenability shall be the shortest time until untenable conditions are created for any occupant starting at any location within the vehicle or along the evacuation path.

5.1.1.3 If the fire scenario involves a vehicular accident, then the assessment shall assume evacuation is achieved through rescue by emergency personnel. The fire hazard

assessment needs to recognize that the accident may take place in an area (or at a time) when such rescue is difficult. Examples of conditions of difficult access are tunnels, bridges, remote locations, and unfavorable weather.

5.1.1.4 Tenability is assessed on the basis of fire effects on the occupants, including both direct effects, such as heat, toxic gases, or oxygen deprivation, and indirect effects, such as reduced visibility due to smoke obscuration. A tenable environment, therefore, will prevent loss of life and reduce the likelihood of harm, including nonfatal injury to individuals.

(1) Levels of tenability should be set by the developer of the fire hazard assessment generated from using this guide or by the specific.

NOTE 1—Investigations of the tenability in a fire scenario have shown the maximum temperatures which human beings can withstand (1-3),¹⁶ the maximum convected heat humans can tolerate (4), the heat flux required to blister or burn skin (5-8), the restrictions to escape imposed by smoke obscuration (9, 10), the effects of the primary toxic gases (11-16), the overall effects of smoke toxicity (17-20) and various ways to combine one or more of these effects (4, 21 and 22).

(2) If no levels of tenability are chosen, the default tenability criteria should be the values specified in the documentation for HAZARD (21, 22)

5.1.2 A secondary fire safety objective is to prevent flash-over inside the rail transportation vehicle.

5.1.3 The user shall consider inclusion of a third fire safety objective, which is to maintain a safe working environment for safety personnel, including fire fighters.

5.2 Considerations of Design Factors in Calculations for Estimates of Fire Hazard

5.2.1 The issue of design of products or entire rail transportation vehicles can have significant impact on fire safety. Design specifications can be used as input into the calculation methods of a fire hazard assessment; however, for design specifications to be useful, they cannot be expressed in vague terms but must be expressed as either numerical values or as other instructions, for example, equations compatible with the fire hazard assessment calculation method used.

5.2.1.1 Once expressed as numerical or other specific values, design specifications are a source for input variables for fire hazard assessment. For example, design specifications will include specification of the materials or components to be used in the vehicle compartment linings, including ceilings, walls, and floors. The calculations required to assess whether flash-over will be prevented in the vehicle (an objective specified in 5.1.2) will require heat absorption parameters for the compartment linings. These heat absorption parameters will not be identical to the design specifications for the compartment lining materials but will be derivable from these specifications by reference to data from established test methods. Because this guide does not specify the models as calculation methods to be used, it follows that it cannot list the input variables that will be required or the appropriate procedures to use in deriving those input variables from design specifications.

5.2.1.2 A fire hazard assessment is an evaluation of a complete design that addresses certain fire safety objectives;

therefore, the design specifications used must address and include all relevant products and design features used, including those specified by conventional prescriptive practices. A fire hazard assessment of a retrofit, rebuild, or repair cannot be limited to the parts of the design being changed. Rather, a fire hazard assessment of a retrofit carried out according to the practices presented in this guide must address the resulting car, including contents, in its entirety.

5.2.1.3 This guide does not address minor changes to vehicles designed using components or materials that are defined originally by property lists, such as those described in 5.7.8. In such cases, the techniques presented in this guide will have less applicability and may present fewer, if any, economic benefits than continuing the use of the lists described in 5.7.8.

5.2.2 In connection with this guide, the term “design” refers both to the general arrangement of the vehicle (for example, size, location of doors and windows, the nature of emergency exits, the number and configuration of levels and compartments) and to the materials, components, and products used to fabricate the vehicle. The development of such designs often involves decisions that include tradeoffs and ad-hoc benefit analyses and is a traditional approach.

5.2.2.1 An example of such a decision are trade-offs considered between using traditional glazing materials, which are not combustible but have high mass and low impact resistance. The use of these materials may compromise passenger and staff security, due to the hazard of projectiles. An alternative, to address hazards posed by projectiles to noncombustible, but friable, glazing is the use of more impact resistant materials, which are combustible.

NOTE 2—The use of plastic glazing materials with high impact resistance is a common practice in the transportation industry and has been since the 1970s.

5.2.3 Design specifications for materials, components, and products will include fire-test-performance characteristics. Appendix X1 and Appendix X4 provide a list of test methods from which the test methods to be used should be chosen. Alternative test methods are contained in Table X1 (23) and Appendix X1, and they generate fire-test-response characteristics, albeit ones that cannot be used for fire safety engineering calculations.

5.2.3.1 The test methods referenced include, but are not limited to, those required to measure the fire-test-response characteristics included in recommendations or requirements of NFPA 130, the Federal Railroad Administration (FRA) (24) AMTRAK (25), and the Federal Transit Administration (FTA) (26). A new FRA rule was issued in 1999, which incorporated the majority of the earlier FRA guidelines (27).

(1) The choice of any test method is nonmandatory, and the developer of a fire hazard assessment will need to provide evidence of its validity for use in testing of rail transportation system components or composites (see also 5.7.7.1). Design and quality control of component materials critically affects the precision of composite fire test results; therefore, manufacturers should ensure consistency in the fire performance of components which are assessed as part of a composite system, preferably by testing the components.

5.2.3.2 The test methods referenced in Appendix X4 have

¹⁶ The boldface numbers in parentheses refer to the list of references at the end of this standard.

been designed to yield results in fire safety engineering units, which are appropriate for fire hazard assessment, and measure heat release rate, which has been demonstrated to be an essential component of fire hazard assessment (28, 29).

5.2.3.3 It is likely that design specifications of any finished product with different component materials will not be available normally (from the suppliers of the individual materials or components that go into them) in a form suitable for application of fire hazard assessment. Manufacturers of such products normally cannot be expected to have developed data on characteristics that are not part of existing sets of requirements or recommendations for their products. Similarly, suppliers of individual materials cannot be expected to identify or provide materials, components, or products, based exclusively on the kinds of design specifications required for fire hazard assessment; therefore, suppliers of such products may require the translation of the performance specifications into conventional specifications for the individual materials. A prescriptive approach to achieve fire safety objectives should always exist as an alternative. In the case of rail transportation vehicles, such an approach would be through use of the traditional methods as exemplified by the recommendations in Table X1 and Appendix X1. The hazard assessment approach becomes an option available to those manufacturers who prefer to seek alternative means of achieving acceptable levels of fire safety inside rail transportation vehicles.

5.3 Fire Scenarios

5.3.1 Fire Scenario 1 is a fire that originates within the rail transportation vehicle.

5.3.1.1 Fire Scenario 1a, specified as the highest-challenge likely scenario of this type (see also 5.3.1.7), begins as an incendiary ignition involving the use of accelerants and prior damage exposing the fillings of the two upholstered seats nearest the point of ignition. Fire begins while the vehicle is in motion between stations, at the maximum distance from any station (see also Appendix X3).

5.3.1.2 Fire Scenario 1b, specified as one of the most common scenarios, is a trash fire that begins under a seat assembly and spreads to that seat assembly, in a passenger compartment.

5.3.1.3 If cooking is permitted on any passenger vehicle, an additional fire scenario, to be called Scenario 1c, also must be assessed. Fire Scenario 1c is a cooking fire originating at the cooking equipment and involving initial ignition of cooking fuel, if equipment is gas-fueled, or cooking oil, if equipment is not gas-fueled. Fire begins while the vehicle is in motion between stations, at the maximum distance from any station.

5.3.1.4 If there are one or more vehicles provided for overnight sleeping, fire scenario 1d also must be assessed, where Fire Scenario 1d is a small open-flame ignition of bedding in an unoccupied bed in a vehicle, with other beds occupied by sleeping people. Fire begins while the vehicle is in motion between stations, at the maximum distance between stations.

5.3.1.5 If there are one or more vehicles provided for cargo (or cargo storage space is provided within a passenger vehicle), Fire Scenario 1e also must be assessed, where Fire Scenario 1e consists of small open-flame ignition of a combustible, for

example trash, in a fully-filled cargo vehicle. The assumed fuel load shall be the maximum allowed, including the highest quality of hazardous materials possible under the planned operating procedures. Openings connecting the cargo vehicle to an assumed adjacent passenger vehicle shall be assumed to be open to the maximum degree permitted by the design.

5.3.1.6 If the rail transportation vehicle overturns and then catches on fire, it is possible that different considerations apply as a function of the way the vehicle ends up. If it remains in its normal orientation, the earlier scenarios apply, but if it falls on its side or if it turns around completely, to end up upside down, they represent different scenarios. In both cases, fire begins while the vehicle is stationary between stations, at the maximum distance between stations.

5.3.1.7 Any one of the Type 1 fire scenarios (where the fire starts inside the rail transportation vehicle) becomes more severe if the fire occurs when the rail transportation vehicle is in a location where escape and rescue is particularly difficult, for example, in a tunnel.

5.3.2 Fire Scenario 2 is a fire that originates outside the rail transportation vehicle, penetrates the rail transportation vehicle, and endangers the evacuation route from the vehicle through the spread of flames or smoke into the evacuation route.

5.3.2.1 Fire Scenario 2a, specified as the highest-challenge likely scenario of this type, begins with ignition of a fuel spill following a collision in which there are survivors. Fire begins in a tunnel, where the vehicle has stopped due to the collision, at a point maximally distant from any egress to the outside. Evacuation is to a place of safe refuge.

5.3.2.2 If the vehicles are individually electrically powered, Fire Scenario 2b must be assessed, where Fire Scenario 2b is an electrical fire that causes the vehicle to stop in a tunnel, at a point maximally distant from any egress to the outside. The interruption of electrical power also affects operation of the vehicle doors, in accordance with the vehicle's design. The point of origin is assumed to be whatever point in the electrical system will lead to the fastest spread of smoke and toxic gases to the vehicle interior.

5.3.3 The specification of fire scenarios included in this section assumes that other fire scenarios either are less severe, and therefore, will lead to achievement of fire safety objectives if the design achieves the objectives for the specified fire scenarios, or are sufficiently unlikely that they need not be considered as part of the overall fire hazard assessment, although they may be considered individually.

5.3.3.1 The fire scenarios that are appropriate for a certain rail system may not be adequate for a different rail system. Additional or different fire scenarios may be needed in certain cases.

5.4 Additional Model Assumptions

5.4.1 Occupancy of the rail transportation vehicle and any other relevant occupiable spaces, such as the platform to which occupants may move to evacuate, shall be set for analysis purposes so as to pose the greatest challenge to the fire safety objectives. A logical assumption would be occupancy to capacity and a mix of occupants of different abilities, where some will have various physical or mental disabilities, and

capabilities, for example, some will be assumed to be impaired by alcohol, or drugs, or by age-related limitations.

5.4.1.1 Assumptions regarding numbers and abilities of disabled persons shall incorporate relevant provisions of the Americans with Disabilities Act.¹⁰

5.4.1.2 Assumptions regarding age distributions of the occupants shall reflect data on age patterns among users of the rail system. Assumptions regarding the capabilities of older or younger occupants shall reflect patterns in the general population, or known applications to the specific rail transportation scenario chosen, if they differ, and shall be documented as to sources of data.

5.4.1.3 Assumptions regarding alcohol or drug impairment among occupants shall be documented as to source data and shall be based on patterns in the general population, weighted to reflect the age and economic distribution of users of the rail system. If such data are not available, conservatively assume that 10 % of adult occupants are impaired by alcohol.

5.4.1.4 If the rail vehicles provide sleeping accommodations, assume that fire occurs when the maximum number of occupants will be sleeping. If there are no data available to determine the maximum fraction of people sleeping, assume all passengers are sleeping.

5.5 Required Calculations

5.5.1 The fire hazard assessment involves using one or more calculation procedures to determine whether the fire safety objectives in Section 5.1 will be met if the design specified in Section 5.2 experiences each of the fires of the scenarios specified in Section 5.3, and given the additional assumptions specified in Section 5.4.

5.5.1.1 This guide does not assign a specific choice of calculation procedure just as it does not assign a specific test method. It simply gives guidance on the types of procedures available and on the required output to generate a valid fire hazard assessment.

5.5.1.2 Use Guide E 1546 when developing the procedure.

5.5.1.3 Use NFPA 901 if needed for overall coding of materials or products.

5.5.2 Because the fire safety objectives are all stated in terms of specified fire effects by location and time, the fire hazard assessment calculation procedures must support the calculations in 5.5.2.1-5.5.2.5.

5.5.2.1 Translate the fire scenario specifications into a description of the fire in its initial stages, as a function of time in the initially involved space. The fire-test-response characteristics of the materials, components, or products initially involved that should be considered for such a description are rate of heat release, rate of mass loss, total heat release (if burned to completion, or cumulative heat release to end of burning otherwise), flame spread, cumulative full-scale smoke obscuration and toxic potency of the products of combustion released. A thorough analysis of the actual rail transportation vehicle fire scenario should result in a final decision on the properties required for the fire hazard assessment. If the product under consideration is a structural component, assess also its fire endurance.

5.5.2.2 Assess and evaluate the vehicle design specifications to develop and describe foreseeable characteristics of the fuel

load environment near the initial fire. Use these and the time-based description of the initial fire as a function of time to calculate the spread of fire to secondary items and the ignition of those secondary items.

5.5.2.3 For each space, or potential fire compartment, calculate the timing of major fire events, including the onset of flashover, as well as, fire spread from one space to an adjacent space, whether through barriers or not, particularly from outside a rail vehicle to inside the vehicle. The calculation of fire spread from one space to another will require measurement of barrier fire resistance characteristics.

5.5.2.4 For each potentially exposed occupant, calculate the time to reach safe refuge and compare it to the calculated time until exposure to an unacceptable potential for harm (hazard). The former requires calculation of occupant alerting response, travel speed, and other behavior. For occupants requiring rescue, calculations will need to estimate the size, capabilities, and arrival time of fire department or other rescue personnel. The latter can be calculated as time to exposure to an untenable cumulative dose of fire effects or conservatively calculated as time to first exposure to unacceptably hazardous fire conditions. Calculations will be required for the area of fire origin, any occupied spaces, and any spaces that are part of escape or rescue routes.

5.5.2.5 When making the calculations described in 5.5.2.3 and 5.5.2.4, incorporate the activation and effects of any fire protection systems, including automatic or manual fire suppression, detection, and smoke control systems. Consider that, once a collision has occurred, electrically-controlled detection and protection systems may be damaged.

5.5.3 For the fire safety objective of preventing flashover, flashover shall be calculated as occurring when the radiative heat flux at the center of the floor reaches 20 kW/m². Other fire characteristics that are sometimes used as indicators of flashover, such as an upper layer temperature of 600°C, can be used in the calculations but are not to be used to assess achievement of the objective.

5.6 Procedural Steps in Conducting a Fire Hazard Assessment

5.6.1 The detailed procedural steps for conducting a fire hazard assessment on a product in a rail transportation vehicle are given in Section 5.7, for the fire safety objectives, see Section 5.1. Conducting these procedures requires applying the design considerations in Section 5.2; for the scenarios considered, see Section 5.3; and, under the additional assumptions presented, see Section 5.4. Appendix X1 and Appendix X4 provide a list of test methods from which the test methods to be used should be chosen (see also X3.3). Some appropriate calculation methods are listed in Appendix X5 and Appendix X6.

5.6.2 Following the steps in Section 5.7, the final step in a fire hazard assessment procedure should be the development of a detailed procedure to ensure consistent quality control over time.¹⁷ In the absence of prescriptive small-scale tests that dictate the minimum fire-test response characteristics required

¹⁷ One way to ensure consistent quality control is by listing materials, components, products, or assemblies.

for each material, component, or product, alternative means should be described so that the fire safety of the rail transportation vehicle can be ensured without having to conduct full rail transportation vehicle burn tests.

5.7 Steps in Conducting a Fire Hazard Assessment

5.7.1 Fire hazard assessment begins by choosing fire safety objective(s) to be achieved. This step is described in Section 5.1.

5.7.2 Fire hazard assessment requires specification of the design to be assessed, in a form that permits the fire safety performance of the design to be tested and modeled. This step is described in Section 5.2.

5.7.3 Fire hazard assessment requires specification of the fire scenarios for which a design must meet the fire safety objectives. This step is described in Section 5.3.

5.7.4 Fire hazard assessment requires specification of any additional assumptions, such as conditions of the environment, in the assessment. This step is described in Section 5.3.

5.7.5 Fire hazard assessment finds a specified design to be acceptable if, under the specified assumptions, a vehicle built to the design will meet each of the objectives for each of the specified fire scenarios.

5.7.6 It is the intention of this standard to maintain or exceed the levels of fire safety in rail transportation vehicles associated with the traditional applicable fire-test-response characteristic requirements for rail transportation systems, including the recommendations from the Federal Transit Administration and the guidelines from the Federal Railroad Administration, while providing an alternative method of assessing designs to achieve equivalent safety. Appendix X7 (**30, 31**) illustrates the level of safety achieved in 1990–1991.

5.7.6.1 Fire hazard assessment requires the use of testing and calculation methods to determine whether the objectives will be met by a specified design for a specified fire scenario, under the specified assumptions. The calculations to be performed are described in Section 5.3, and the selection and qualifying of calculation methods for the assessment are described in Section 5.3.

5.7.7 For the fire hazard assessment procedure to be valid, it is necessary that the calculation methods and the fire-test-response characteristics used produce valid estimates of success or failure in achievement of the fire safety objectives, given the specified fire scenario(s).

5.7.7.1 It is advisable for the validity of the fire hazard assessment procedure to be confirmed by peer review.

5.7.8 One way in which acceptable levels of safety would be achieved is through a design that complies with the applicable fire-test-response characteristic requirements for rail transportation systems, including the traditional recommendations from the Federal Railroad Administration in 1989 (**24**), or those in NFPA 130. If a rail transportation vehicle is designed fully with materials, components, and products meeting those require-

ments or recommendations, that vehicle would not traditionally need to be subjected to the fire hazard assessment procedure described here.

5.7.8.1 A complete listing of the fire-test-response characteristics of a design, together with the corresponding Federal Railroad Administration recommendations for those characteristics (see Table X1 and Appendix X1), would constitute an acceptable design.

5.7.9 The recommendations cited in 5.7.8 should be used to set specific values in the fire safety objectives and in other qualified elements of the fire hazard assessment in any instance where those values are not specified by this guide. This should be done so as not to compromise the fire safety levels reflected in the statistics of fire incidents shown in Appendix X7. Any values or other assumptions specified by the user must be set explicitly and conservatively, that is, providing greater safety, with an explicitly stated rationale for the specific values or assumptions.

6. Selection and Qualification of Fire Hazard Calculation Methods

6.1 Because no applicable calculation methods have been adopted as ASTM standards, the choice of calculation methods is nonmandatory and must include written evidence of the validity of the method for this purpose. Use Guide E 1355 in order to evaluate the predictive capability of the fire model used. Guide E 1591 provides guidelines on how to obtain the appropriate input data, in particular material properties, that are needed for fire modeling. Guide E 1472 illustrates the type of documentation required for fire models to be satisfactory.

6.2 The user must provide guidance on safety factors needed to offset the uncertainties and biases associated with the method or with the data used by the method. Any valid calculation method is valid only for certain applications and within the limits of its own uncertainties and biases and the uncertainties of its source data; therefore, the evidence of validity required in 5.4.1 will provide the basis for specifying safety factors.

6.3 See Appendix X5 and Appendix X6 for candidate calculation methods.

6.4 Under the provisions in 5.7.8, a design fully complying with the existing requirements or recommendations based on fire-test-response characteristics is deemed to satisfy the fire hazard assessment. This is equivalent to stating that a fire-characteristic profile for the design is deemed to satisfy the fire hazard assessment if it satisfies the fire-test-response characteristic limits in Table X1 and Appendix X1. This does not constitute acceptance of the fire-characteristic profile in general as a simplification of the fire hazard assessment procedure. Any use of the fire-characteristic profile other than this specific application must be shown to be valid.

APPENDIXES

(Nonmandatory Information)

X1. EXAMPLE OF FIRE-TEST-RESPONSE CHARACTERISTICS RECOMMENDATIONS

X1.1 *Notes to Table X1.1 as set out by the Federal Railroad Administration (25):*

X1.1.1 *Test Methods D 3675 and E 162*—Materials tested for surface flammability should not exhibit any flaming running or flaming dripping; window and light diffuser panels need not meet the running or dripping requirement.

X1.1.2 *Cushions, Mattresses, Seat Upholstery, Mattress Ticking, Covers, and Curtains*—The surface flammability and smoke emission characteristics of a material should be demonstrated to be permanent by washing, if appropriate, according to FED STD 191-A Textile Test Method 5830.¹⁸

X1.1.3 *Seat Upholstery, Mattress Ticking, Covers, and Curtains*—The surface flammability and smoke emission characteristics of a material should be demonstrated to be permanent by dry-cleaning, if appropriate, according to Test Methods D 2774. Materials that cannot be washed or dry-cleaned should

be so labeled and should meet the applicable performance criteria after being cleaned as recommended by the manufacturer.

X1.1.4 *Window Panels*—For double window glazing, only the interior glazing should meet the material recommendations specified herein; the exterior need not meet those recommendations.

X1.1.5 *Test Method E 662*—Test Method E 662 maximum test limits for smoke emission (specific optical density) should be measured in either the flaming mode or the nonflaming mode, depending on which mode generates the most smoke.

X1.1.6 *Test Methods E 119*—Structural flooring assemblies should meet the performance criteria during a nominal test period determined by the transit property. The nominal test period should be twice the maximum expected period of time, under normal circumstances, for a vehicle to come to a complete, safe stop from maximum speed, plus the time necessary to evacuate all passengers from a vehicle to a safe area. The nominal time period should not be less than 15 min. Only one specimen need be tested. A proportional reduction may be made in dimensions of the specimen provided that it represents a true test of its ability to perform as a barrier against undercar fires. Penetrations (ducts, etc.) should be designed against acting as passageways for fire and smoke.

¹⁸ The American Association of Textile Chemists and Colorists (AATCC, P.O. Box 12215, Research Triangle Park, NC, 27709) has issued the Standard Laboratory Practice for Home Laundering Fabrics prior to Flammability Testing, to Differentiate Between Durable and Nondurable Finishes (May 1, 1991). Although no AATCC formal equivalent standard exists, the practice mentioned is likely to be useful as a replacement to the Federal Test Method, since the Federal standards are in the process of being withdrawn.

TABLE X1.1 U.S. Flammability and Smoke Emission Recommendations for Passenger Rail Vehicles (22)

Category	Function of Material	Flammability		Smoke Emission	
		Test Procedure	Performance Criteria	Test Procedure	Performance Criteria
Passenger seats, sleeping, and dining car components	Cushions, mattresses	ASTM D 3675	$I_s \leq 25$	ASTM E 662	$D_s(1.5) \leq 100$: $D_s(4.0) \leq 175^A$
	Seat Frames, mattress frames	ASTM E 162	$I_s \leq 35$	ASTM E 662	$D_s(1.5) \leq 100$; $D_s(4.0) \leq 200$
	Seat and toilet shroud, food trays	ASTM E 162	$I_s \leq 35$	ASTM E 662	$D_s(1.5) \leq 100$; $D_s(4.0) \leq 200$
	Seat upholstery, mattress ticking and covers, curtains	FAR 25.853 (a) (Vertical burner)	Flame time ≤ 10 s Burn length ≤ 6 in	ASTM E 662	$D_s(4.0) \leq 250$ coated $D_s(4.0) \leq 200$ uncoated
Panels	Wall, ceiling, partition, tables and shelves, windscreen, HVAC ducting	ASTM E 162 ASTM E 119	$1_s \leq 35$ as appropriate ^B	ASTM E 662 ASTM E 662	$D_s(1.5) \leq 100$; $D_s(4.0) \leq 200$
	Window, light diffuser	ASTM E 162	$I_s \leq 100$	ASTM E 662	
	Structural	ASTM E 119	nominal evacuation time, at least 15 min	ASTM E 662	
Flooring	Covering	ASTM E 648 ASTM E 162 ^C	C.R.F. ≥ 5 kW/ $m^{2D,E}$ $I_s \leq 25$	ASTM E 662 ASTM E 662	$D_s(1.5) \leq 100$; $D_s(4.0) \leq 200$
Insulation	Thermal, acoustic	ASTM E 162	$I_s \leq 25$	ASTM E 662	$D_s(4.0) \leq 100$
Elastomers	Window gaskets, door nosing, diaphragms, roof mat	ASTM C 542	Pass	ASTM E 662	$D_s(1.5) \leq 100$; $D_s(4.0) \leq 200$
Exterior plastic components	End cap roof housings	ASTM E 162	$I_s \leq 35$	ASTM E 662	$D_s(1.5) \leq 100$; $D_s(4.0) \leq 200$
Component box covers	Interior, exterior boxes	ASTM E 162	$I_s \leq 35$	ASTM E 662	$D_s(1.5) \leq 100$; $D_s(4.0) \leq 200$

^ANFPA 130 and FTA requirement is $D_s(1.5) \leq 100$; $D_s(4.0) \leq 200$

^BTest criteria for floors or criteria appropriate to the physical locations and magnitude of the major ignition, energy, or fuel loading sources, may be used.

^CNFPA 130 only.

^DAmtrak requirement is C.R.F. ≥ 6 kW/m²

^EAmtrak requirement is $I_s \leq 35$.

X1.1.7 *Floor Coverings*—Floor coverings should be tested in accordance with Test Method E 648 with its padding, if the padding is used in actual installation.

X1.1.8 *Seat or Mattress Frames*—Arm rests, if foamed plastic, are tested as cushions, and, if hard material, are tested as a seat back shroud.

X1.1.9 *Cushions and Mattresses*—Testing is performed without upholstery.

X1.1.10 *Wall and Ceiling Panels, Floor Coverings*—Carpeting on walls and ceilings are to be considered wall and ceiling panel materials, respectively.

X1.1.11 *Elastomers*—The fire test method in Specification C 542 is Test Method C 1166.

X1.2 Table X1.1 shows all of the materials and products addressed by the Federal Railroad Administration, and indicates the traditional approach to fire-test-response characteristic requirements for rail transportation systems.

X1.3 NFPA 130 requires that wiring materials and installations in fixed guideway transit systems, other than for

traction power, conform to the requirements of NFPA 70, the National Electrical Code. It also requires that wire and cable constructions intended for use in operating vital train circuits and power circuits to emergency fans and lights pass the flame propagating criteria of IEEE 383. AMTRAK also has issued separate specifications for wire and cable (32).

X1.3.1 IEEE 383 is substantially similar to the flame spread portion of Protocol A of Test Method D 5537. It is a vertical cable tray flame propagation test, with a 2.4-m (8-ft) long test sample.

X1.3.2 The National Electrical Code states that cables that meet a more severe fire test can be appropriately used in applications where a less severe test is required (see X4.12.7 for the applicable test methods).

X1.3.3 In comparison, the Federal Aviation Administration requires electric wire insulation to meet requirements based on a 60° angle test method [FAR 25.1359]. Average extinguishing time not to exceed 30 s; average drip extinguishing time not to exceed 3 s; average burn length not to exceed 76-mm (3-in.), and the wire shall not break during the test.

X2. Federal Railroad Administration Rule

X2.1 Table X2.1 shows the fire-test-response characteristic requirements for materials and products set out by the Federal Railroad Administration (29), provided as reference material. Explanatory notes to the table, taken directly from the Federal Railroad Administration rulemaking, are shown in the following sections.

X2.1.1 Materials tested for surface flammability should not exhibit any flaming running or flaming dripping.

X2.1.2 The Test Method E 662 maximum test limits for smoke emission (specific optical density) should be measured in either the flaming mode or the nonflaming mode, utilizing the mode which generates the most smoke.

X2.1.3 Testing of a complete seat assembly (including cushions, fabric layers, upholstery) according to Test Method E 1537 with application of pass/fail criteria of Cal TB 133 and of a complete mattress assembly (including cushions, fabric layers, upholstery) according to Test Method E 1590 with application of pass/fail criteria of Cal TB 129, shall be permitted in lieu of the test methods prescribed herein, provided the assembly component units remain unchanged or new (replacement) assembly components possess equivalent fire performance properties to the original components tested. A fire hazard analysis must also be conducted that considers the operating environment within which the seat or mattress

TABLE X2.1 FRA Requirements for Commuter and Intercity Rail Vehicle Materials (29)

Category	Function of Material	Flammability		Smoke Emission	
		Test Procedure	Performance Criteria	Test Procedure	Performance Criteria
Cushions, mattresses	All (1, 2, 3, 4, 5, 6, 7, 8) ^A	ASTM D 3675	$I_s \leq 25$	ASTM E 662	$D_s (1.5) \leq 100$; $D_s (4.0) \leq 175$
Fabrics	All (1, 2, 3, 6, 7, 8)	FAR 25.853 (a) (vertical)	Flame time ≤ 10 s Burn length ≤ 6 in.	ASTM E 662	$D_s (4.0) \leq 200$
	All except flexible cellular foams, floor coverings, light transmitting plastics, and items addressed under other specific categories (1, 2)	ASTM E 162	$I_s \leq 35$	ASTM E 662	$D_s (1.5) \leq 100$
Vehicle components (9, 10, 11, 12)	Flexible cellular foams (1, 2)	ASTM D 3675	$I_s \leq 25$	ASTM E 662	$D_s (1.5) \leq 100$ $D_s (4.0) \leq 175$
	Floor covering (13, 14)	ASTM E 648	$CRF \leq 5$ kW/m ²	ASTM E 662	$D_s (1.5) \leq 100$ $D_s (4.0) \leq 200$
	Light transmitting plastics (2, 15)	ASTM E 162	$I_s \leq 100$	ASTM E 662	$D_s (1.5) \leq 100$ $D_s (4.0) \leq 200$
	Elastomers (16)	ASTM C 1166	Pass	ASTM E 662	$D_s (1.5) \leq 100$ $D_s (4.0) \leq 200$
Wire and cable	Low voltage wire and cable	ICEA S-19/NEMA WC3 or UL 44 and UL 83 (17)	Pass	ASTM E 662	$D_s (4.0) \leq 200$ (flaming) $D_s (4.0) \leq 75$ (nonflaming)
	Power cable	IEEE Std 383 (18)	Pass	ASTM E 662	$D_s (4.0) \leq 200$ (flaming) $D_s (4.0) \leq 75$ (nonflaming)
Structural components (19)	Flooring (20), other (21)	ASTM E 119	Pass		

^AThe numbers in brackets refer to the corresponding subsections within X2.1.

assemblies will be used in relation to the risk of vandalism, puncture, cutting, or other acts which may expose the individual components of the assemblies.

NOTE X2.1—The wording in X2.1.3 is different from that in the rulemaking, because Test Method E 1590, with the pass/fail criteria of Cal TB 129 is appropriate for mattresses.

X2.1.4 Testing is performed without upholstery.

X2.1.5 The surface flammability and smoke emission characteristics shall be demonstrated to be permanent after dynamic testing according to Test Method D 3574, Test I-2 (dynamic fatigue test by the roller shear at constant force) or Test I-3 (dynamic fatigue test by constant force pounding), both using Procedure B.

NOTE X2.2—The sample sizes required for Test Method D 3574 I-2 and I-3 (300 mm × 380 mm × 50 mm and 380 mm × 380 mm × 50 mm, respectively) are different than that required for Test Method D 3675 (150 mm × 460 mm × 25 mm), so that a sample that has been used for Test Method D 3574 would then have to be used for Test Method D 3675 by placing specimens in series. Sampling for Test Method D 3675, following testing by Test Method D 3574, should be conducted such that the samples are taken from the interior of the foam bun, to prevent contamination from affecting the flame spread test results.

X2.1.6 The surface flammability and smoke emission characteristics shall be demonstrated to be permanent by washing, if appropriate, according to FED STD 191A Textile Test Method 5830.¹⁷

X2.1.7 The surface flammability and smoke emission characteristics shall be demonstrated to be permanent by dry-cleaning, if appropriate, according to Test Method D 2724.

X2.1.8 Materials that cannot be washed or dry-cleaned shall be so labeled and shall meet the applicable performance criteria after being cleaned as recommended by the manufacturer.

X2.1.9 As a minimum, combustible component materials required to be tested include seat and mattress frames, wall and ceiling panels, seat and toilet shrouds, tray and other tables, partitions, shelves, windscreens, HVAC ducting, thermal and acoustic insulation, exterior plastic components, and interior and exterior box covers.

X2.1.10 Materials used to fabricate miscellaneous, discontinuous small parts, such as knobs, rollers, fasteners, clips, grommets, and small electrical parts) that will not contribute materially to fire growth in end use configuration may be exempted from fire and smoke emission performance requirements, provided that the surface area of any individual small part does not exceed 100 cm² (16 in.²) in end use configuration and an appropriate fire hazard analysis is conducted which addresses the location and quantity of the materials used, and the vulnerability of the materials to ignition and contribution of flame spread.

X2.1.11 If the surface area of any individual small part is less than 100 cm² (16 in.²) in end use configuration, materials used to fabricate such small part shall be tested in accordance with Test Method E 1354, unless such small part has been shown not to contribute materially to fire growth following an appropriate fire hazard analysis as specified in X2.1.10. Materials tested in accordance with Test Method E 1354 shall meet the performance criteria that the ratio of the time to ignition to the peak rate of heat release shall exceed 1.5 s m²/kW. Testing shall be at 50 kW/m² applied heat flux.

NOTE X2.3—The wording in X2.1.11 is different from that in the rulemaking, because the criterion that the ratio of the time to ignition to the peak rate of heat release shall exceed 1.5 s m²/kW is appropriate for these materials.

X2.1.12 Assessment of smoke generation by small miscellaneous, discontinuous parts may be made by utilizing the results from the Test Method E 1354 test procedure conducted in accordance with X2.1.11, rather than the Test Method E 662 test procedure, if an appropriate fire hazard analysis is provided, which addresses the location and quantity of the materials used, and the vulnerability of the materials to ignition and contribution of smoke spread.

X2.1.13 Carpeting used as a wall or ceiling covering shall be tested as a vehicle component.

X2.1.14 Floor covering shall be tested in accordance with Test Method E 648, if the padding is used in the actual installation.

X2.1.15 For double window glazing, only the interior glazing is required to meet the materials requirements specified herein (the exterior glazing need not meet these requirements).

X2.1.16 Elastomeric materials used for parts having a surface area not exceeding 100 cm² (16 in.²) shall be tested in accordance with Test Method C 1166. As a minimum, parts required to be tested include window gaskets, door nosing, diaphragms, and roof mats.

X2.1.17 Testing of low voltage wire and cable shall be conducted in accordance with ICEA S-19/NEMA WC3, paragraph 6.19.6; or UL 44 for thermosetting wire insulation and UL 83 for thermoplastic wire insulation.

NOTE X2.4—See also X1.3.1 and X1.3.2.

X2.1.18 Testing of power cable shall be conducted in accordance with IEEE Standard 383, Section 2.5, with the additional requirement that circuit integrity shall continue for 5 min after the start of the test.

NOTE X2.5—The circuit integrity test requirement is not defined in the IEEE 383 standard.

X2.1.19 Penetrations (ducts, etc.) shall be designed to prevent fire and smoke from entering a vehicle, and representative penetrations shall be included as part of test assemblies.

X2.1.20 Structural flooring assemblies shall meet the performance criteria during a nominal test period as determined by the railroad. The nominal test period shall be twice the maximum expected period of time, under normal circumstances, for a vehicle to stop completely and safely from its maximum operating speed, plus the time necessary to evacuate all the vehicle's occupants to a safe area. The nominal test period must not be less than 15 min. Only one specimen need be tested. A proportional reduction may be made in dimensions of the specimen, provided the specimen represents a true test of the ability of the structural flooring assembly to perform as a barrier against under-vehicle fires. The fire resistance period shall be consistent with the safe evacuation of a full load of passengers from the vehicle under worst-case conditions.

X2.1.21 Portions of the vehicle body (including equipment carrying portions of a vehicle's roof but not including floors) which separate major ignition sources, energy sources, or sources of fuel-load from vehicle interiors, shall have sufficient

fire endurance as determined by a fire hazard analysis acceptable to the railroad which addresses the location and quantity

of the materials used, as well as vulnerability of the materials to ignition, flame spread, and smoke generation.

X3. PHYSICAL CHANGES OCCURRING IN MATERIALS, COMPONENTS AND PRODUCTS AFTER MANUFACTURE

X3.1 Some materials, components, and products may be exposed to the effects of accidental or intentional disfiguration, so that the exposed surface is different from the one intended to be exposed when it is offered for sale.

X3.2 The exposure to a flame source of inner layers of various products has been shown, in some cases, to result in different fire performance.

X3.3 The standard test methods referenced in this guide do not address changes to protective layers due to wear, tear, or abuse, which potentially affect the fire-test-response characteristics of the item. Such changes would have to be addressed by tests specifically intended for such purposes.

X3.4 If the user of a particular test method chooses to

expose one or more of the inner layers during testing, the mode in which the inner layer was exposed should be described in detail.

X3.5 The user of this guide should consider anticipated conditions of use of any material, component, or product to ensure that the performance characteristics do not deteriorate beyond acceptable levels.¹⁹

¹⁹ It should be noted that changes caused by aging, wear and tear, willful or accidental damage, and inconsistency in the manufacturing process, for example practices which do not ensure retention of assembly fire properties, are examples of ways in which the fire performance characteristics of a material, component, product, or assembly can vary in service.

X4. RECOMMENDED METHODS FOR GENERATING APPROPRIATE DATA FOR USE IN CALCULATIONS

X4.1 Use Test Method E 1474 to expose composites of seat materials to radiant heat, at an incident heat flux of 35 kW/m². Test Method E 1474 is an applications method of the cone calorimeter, while Test Method E 1354 addresses the mounting for upholstered furniture and mattress composites.

X4.2 Use Test Method E 1354 to expose individual materials in component products to radiant heat, at an incident heat flux of 35 kW/m².

X4.3 Use Test Method E 1354 to expose all panel materials, in a construction representative of that in which they are installed in the rail transportation vehicle, to radiant heat, at an incident heat flux of 35 kW/m².

X4.4 Use Test Method E 1740 to expose all wallcovering systems, in a construction representative of that in which they are installed in the rail transportation vehicle, to radiant heat, at an incident heat flux of 35 kW/m². Test Method E 1740 is an applications method of the cone calorimeter, while Test Method E 1354, addresses the mounting method for wallcovering systems.

X4.5 Use Test Method E 1354 to expose the floor covering materials, in a manner representative of the way they are installed in the rail transportation vehicle, to radiant heat, at an incident heat flux of 25 kW/m². The rationale for testing floor coverings at a lower incident flux level than other fuel sources is that it has been shown that floor covering systems are not exposed to very high heat fluxes until after the compartment has reached flashover (heat flux to the floor of 20 kW/m²), by which time they have no further contribution to the probability of reaching flashover.

X4.6 Use Test Method D 6113 to expose all wire and cable products used in the rail transportation vehicle, to radiant heat,

at an incident heat flux of 40 kW/m². Test Method D 6113 is an applications method of the cone calorimeter, Test Method E 1354 addresses the mounting method for electrical and optical fiber cables. The incident heat flux was chosen because of the extensive amount of information available on testing cables and cable materials at that incident heat flux (33, 34). If a specific incident heat flux is found to be suitable for a particular application, it shall be used instead of using an incident heat flux of 40 kW/m².

X4.7 In X4.1-X4.6, exposure to radiant heat using Test Method E 906 is an acceptable alternative, provided a valid correspondence of heat release results between the test methods has been demonstrated in advance. Other test methods also are acceptable, provided it has been demonstrated validly that the fire-test-response characteristics resulting from them are equivalent to cone calorimeter heat release rate data for the specific purpose of performing a fire hazard assessment.

X4.8 Use Test Method E 1623 for assessment of materials, components, products, or assemblies which require a somewhat larger scale of testing, primarily because of the effects of joints or other edge effects. Use an incident heat flux relevant to the product under consideration, in its location within the rail transportation vehicle.

X4.9 Calculate the heat released by each material and by each composite of materials.

X4.10 Compare the results obtained with the estimations of the minimum heat release for flashover, to ensure that no material, and no composite of materials, is used in quantities large enough that its potential for heat release is such that it is capable of yielding flashover conditions, or creating an untenable environment, on its own.

X4.11 Compare too the results obtained with estimation for tenability values for smoke obscuration or smoke toxicity (see 5.1.1.4).

X4.12 *Full-Scale Test Methods:*

X4.12.1 Properly conducted fire tests involving a complete rail transportation vehicle, and which determine all relevant fire properties, containing all the composites and components present in an actual vehicle will be sufficient to carry out this fire hazard assessment; however, such testing is not practical as a normal procedure. It may be desirable, therefore, to carry out properly validated full-scale tests on individual products, or on specially designed portions of rail transportation compartments, as a more general practice.

X4.12.2 There are few standardized examples of full-scale fire tests of individual products. The test method or methods to be used should address expected fire performance to all surfaces potentially affected by the fire scenario being considered (for example, in the case of a seat, to include at least the seat area, back area and top area).

X4.12.3 Test Method E 1537 (upholstered furniture, 19 kW exposure) and Test Method E 1590 (mattresses, 18 kW exposure) are deemed to be adequate procedures for testing individual items of upholstered furniture or mattresses for purposes of fire hazard assessment in some public occupancies; however, such individual stand-alone (not fixed in place) items are not those normally present in rail transportation vehicles. The applicability of the test methods to rail transportation vehicles has not been validated, and they are probably not sufficiently representative of the situation, and may require some modifications for better applicability (see also X4.12.4).

X4.12.4 The use of alternative ignition sources (by varying the location, the gas flow intensity or the exposure time) for Test Method E 1537 or Test Method E 1590 may be a means of addressing some very high challenge fire scenarios, potentially present in rail transportation vehicles. Examples of more powerful ignition sources that could be used include a 50 kW gas burner (35) or the oil burner used for aircraft seat cushions [FAR 25.853 (c)], but the measurements should involve the same fire properties as in Test Method E 1537 or Test Method E 1590.

X4.12.4.1 The FAA oil burner test [FAR 25.853 (c)] is used for aircraft seat cushions, but in its current form, it is a pass-fail test and cannot be used for fire safety engineering calculations; however, the exposure conditions of the oil burner test itself can be used as an alternative ignition source for evaluating rail transportation vehicle seats, and that would better address a higher challenge fire scenario than the exposure conditions of the burner from Test Method E 1537.

X4.12.5 In fire scenarios intended to reflect willful (vandalism) or accidental damage of the initially fabricated seat (or mattress) assembly, before fire ignition, one example of such damage may be a knife cut 6 in. long and 1 in. deep in the middle of an actual seat (or mattress) assembly. Other examples also may be used. Bench-scale representations of the proposed damage should take into account test method sample size.

X4.12.6 NFPA 265 or ISO 9705 are means of testing wall or ceiling linings in a standardized room for their contribution to

compartment fire development. This can be used to test room surface finishes. ISO 9705 lists several ways in which the test method is conducted. NFPA 265 differs from the usual way of conducting ISO 9705 lists several ways in which the test method is conducted. NFPA 265 differs from the usual way of conducting ISO 9705 in the following three ways: the ignition source is 40 kW (for 5 minutes), and then 150 kW (for 10 minutes), while in ISO 9705 it is 100 kW (for 10 minutes) and 300 kW (for 10 minutes); the ceiling is covered in ISO 9705, but not in NFPA 265; and, that the positioning of the ignition burner is somewhat different.

X4.12.6.1 Most combustible wall linings are likely to reach flashover when tested according to ISO 9705; however, the test results are likely still to produce useful information. This can be used to test products that occupy large interior areas of the rail transportation vehicle.

X4.12.7 Use Test Methods D 5424 and D 5537 (20 kW exposure) for testing wire and cable products used in the rail transportation vehicle for heat release, smoke release, mass loss, and flame spread. Examples of acceptance criteria for flame travel distance (or flame spread) and smoke obscuration are given in UL 1685 and in the National Electrical Code.

X4.12.7.1 The National Electrical Code uses several cable fire test methods for approval purposes.

X4.12.7.2 The single vertical wire test, UL 1581-1080, is used where minimal fire retardance of individual conductors is required.

X4.12.7.3 The bunched cables vertical tray tests, UL 1581-1160 and CSA FT4, are used for tray cable and general purpose cables where flame spread (and heat release) needs to be controlled. Test Methods D 5424 and D 5537 assess vertical flame spread of cables in the same way as UL 1581-1160 (when using Protocol A) or as CSA FT4 (when using Protocol B). They also assess heat release and smoke release for the same cable.

X4.12.7.4 The vertical cable tray tests listed are not of identical severity. Protocol B of Test Method D 5537 or D 5424 (CSFA FT4) is somewhat more severe than Protocol A (UL 1581-1160), but cables meeting either requirement are accepted for the same application in the National Electrical Code.

X4.12.7.5 The plenum cable test, NFPA 262, is required for assessing flame travel distance and smoke obscuration of wires and cables installed in ducts, plenums, and other spaces used for environmental air, which are to be listed as suitable for use as plenum cables and as having adequate fire resistant and low smoke producing characteristics.

X4.12.7.6 Limited smoke is defined in the National Electrical Code on the basis of the UL 1685 vertical cable tray test.

X4.12.8 UL 1975 is an example of a full-scale furniture calorimeter test of an individual product, in this case foam displays. The exact same technology (testing of the individual finished product in a furniture calorimeter) could be used for full-scale tests of several other individual products.

X4.12.9 If nonstandardized full-scale tests are being designed, use Guide E 603 to develop a realistic representation of the rail transportation vehicle under consideration and for guidance on full-scale testing.

X4.12.10 Use an ignition source realistic for the fire scenario investigated, and applicable to as large as possible a variety of potential fire scenarios, to ignite one of the potential products. The applicability of the ignition source must be explicitly addressed. When designing the ignition source to be used, the fuel load and items carried by passengers also must be considered.

X4.13 When using full-scale test methods carry out measurements of heat release rates, smoke obscuration, mass loss rates, and carbon monoxide and carbon dioxide emissions, during the test. If the fire hazard estimation procedure requires measurements of other gaseous combustion products, such as hydrogen chloride or hydrogen cyanide, measure those products as well. If no combustion products other than carbon

oxides are measured, explain the rationale for not conducting such measurements for major combustion gases.

X4.14 When using full-scale test methods, also compare the results obtained with the estimations of the minimum heat release for flashover, to ensure that no product, or combination of products, is used in such a way that its potential for heat release is such that it is capable of yielding flashover conditions, or creating an untenable environment, on its own.

X4.15 Measurements of physical dimensions of rail transportation vehicles (with particular emphasis on their interior) have been made in NFPA 130, as well as in work by Braun (36) and by Peacock and Braun (37), all of which also contain a number of measurements of fire properties.

X5. CALCULATION METHODS FOR ESTIMATING TIME TO UNTENABILITY

X5.1 Use a room fire growth model to estimate the development of potentially incapacitating conditions in a rail transportation vehicle, as a function of time, for Fire Scenario 1, in which the fire begins in the vehicle.

X5.1.1 In a recent survey (38), 36 actively supported fire models were identified. Of these, 20 predict the fire generated environment (mainly temperature) and 19 predict smoke movement in some way. Six calculate fire growth rate, nine predict fire endurance, four address detector or sprinkler response, and two calculate evacuation times. The computer models now available vary considerably in scope, complexity, and purpose.

X5.1.2 The simplest ones are “room filling” models, such as the Available Safe Egress Time (ASET) model (39), which run quickly on almost any computer, and provide adequate estimates of a few parameters of interest for a fire in a single compartment.

X5.1.3 Special purpose models can provide a single function. For example, COMPF2 (40) calculates post-flashover room temperature and LAVENT (41) includes the interaction of ceiling jets with fusible links in a room containing ceiling vents and draft curtains. Very detailed models like the HARVARD 5 code (42) or FIRST (43) predict the burning behavior of multiple items in a room, along with the time-dependent conditions therein.

X5.1.4 In addition to the single-room models mentioned above, there are a smaller number of multiroom models, which have been developed. These include the BRI transport model (44), the HARVARD 6 code (45), (which is a multiroom version of HARVARD 5) (42), FAST (46–47), CCFM (48) and

the CFAST model (49).

X5.1.5 None of the cited models has been adopted as an ASTM standard or demonstrated as valid for application to rail transportation systems. As part of the preparation of written evidence of validity required for any calculation methods selected for use, the user may find some existing detailed reviews useful. It is essential to consider the shortcomings of these models.

X5.1.5.1 Reports by Mitler (50), Jones (51), and Janssens (52) have reviewed the underlying physical concepts in several of the fire models in detail.

X5.1.5.2 The fire models fall into two categories: those that start with the principles of conservation of mass, momentum, and energy; and, the curve fits to particular experiments or series of experiments, used in order to develop the relationship among some parameters. In both cases, errors arise in those instances where a mathematical short cut is taken, a simplifying assumption is made, or something important is not well enough understood to include.

X5.2 To operate any room fire growth model, it will be necessary to estimate the time to secondary ignition of each of the major combustible items in the vehicle (53).

X5.3 In calculating times, as required to assess the primary or secondary fire safety objective, absolute time values are not required and are less useful than accurate estimations of the relative size of the time for hazard development and the time for evacuation.

X6. CALCULATION METHODS FOR ESTIMATING FLASHOVER POTENTIAL

X6.1 A secondary objective is to prevent flashover. This objective can be achieved by the use of a room fire model, such as the ones described in Appendix X5. Alternatively, it is possible to estimate whether flashover will occur by means of a calculation approach. The shortcomings of these calculation methods should be considered.

X6.2 A variety of calculation approaches have been developed to predict the minimum rate of heat release required to achieve flashover in a certain compartment. Some of these models or calculation methods may apply to specific scenarios that do not involve contents, and then they would be inappropriate for use. Estimations of flashover in compartment fires via a model involve the use of certain input fire curves, and the output from the rail transportation vehicle furnishings or contents then would become a part of that input fire curve.

X6.2.1 Direct estimations, by simple calculations, have been proposed by Babrauskas and Krasny (54), Thomas (55) and Quintiere (56), based simply on geometrical characteristics of the compartment. These expressions are a first approximation, but they will vary depending on the materials used for construction and for lining the various surfaces.

X6.3 The first two of those approaches permit the calculation of a range of values of heat release rate sufficient to cause flashover in a compartment with a floor area not to exceed 500 m². The equations are optimized for surfaces made from gypsum wallboard, concrete or thermally similar materials, on walls, floors and ceilings (preferably with the same type of material on all surfaces). These equations have been validated for heat release rates in the range of 0.5 to 1.0 MW. The most commonly used one is that by Thomas, Eq X6.1:

$$Q = 7.8 * 10^{-3} * A_T + 0.758 * m \quad (\text{X6.1})$$

where:

Q = the rate of heat release (MW),

E = the energy released per kg of air consumed ($E=3.00$ MJ/kg),

A_T = the total compartment area: walls, floor and ceiling (in m²), and the maximum air flow (kg/s) into the compartment following flashover.

X6.4 The air flow rate in equation (1) can be estimated by Eq X6.2:

$$m = 0.5 A \sqrt{h} \quad (\text{X6.2})$$

where:

A = the area of the ventilation opening (in m²), and

h = the height of the ventilation opening (in m).

X6.5 The approach by Quintiere (56) is less limited in the choice of interior surface materials, but is more complex, because it includes thermal properties of the compartment surfaces.

X6.6 Two empirical relative approaches also have been proposed by Ostman and Nussbaum (57) and Hirschler (58, 59).

X6.7 The Ostman-Nussbaum (57) relationship was designed to predict time to flashover from room wall lining materials in the ISO 9705 test, at 100 and 300 kW input, and materials lining three walls and the ceiling. It uses input data from Test Method E 1354, at incident heat fluxes of 25 and 50 kW/m², and has been validated with test data on wall lining materials (60).

X6.8 The Hirschler empirical approach (58, 59) is a first order approximation for relative time to flashover in a room-corner fire scenario and uses input data from Test Method E 1354, at an incident flux, which is relevant to the fire scenario in question. Recent work has shown the simultaneous application of this method to room-corner and an aircraft interior (61).

X6.9 The other three approaches to be mentioned are fire models where heat release rates in the compartment are estimated from wall lining test result data in a small scale test (52).

X6.10 The OSU model by Smith and Satija (62) uses as its input data obtained from the OSU small scale heat release calorimeter (Test Method E 906), in a model has been validated properly with wood materials, but not with some other wall linings. No work on its development has been conducted since 1990.

X6.11 The EUREFIC method, by Wickström and Göransson, (60, 63) predicts time to flashover of wall linings in the ISO 9705 test method (with lining material covering three walls and the ceiling and using successive ignition sources of 100 and 300 kW), as a function of time using results obtained with the cone calorimeter (Test Method E 1354) at an incident heat flux of 50 kW/m². The model is a reasonably simple empirical approach, based on three major assumptions: there is no direct relationship between the burning area growth rate and the heat release rate; the burning area growth rate is directly proportional to the ease of ignition, in other words it is inversely proportional to the time to ignition in the cone calorimeter, and the history of the heat release rate per unit area at each location is the same in full-scale (cone calorimeter).

X6.12 The Lund model, by Karlsson and Magnusson (64-66) represents a fire scenario similar to that in the EUREFIC model, except that the walls only are lined with the material being investigated in ISO 9705, instead of walls and ceiling. Furthermore, it requires input from the lateral ignition and spread of flame test (LIFT) apparatus (Test Method E 1321), as well as from the cone calorimeter (Test Method E 1354). Third, it predicts a large number of room fire test variables, rather than simply heat release rate and time to flashover. The model assumes that the total heat release rate comes from five sources: the gas burner, the vertical wall area behind the burner flame, a horizontal strip of material at the ceiling/wall intersection corresponding to the vertical height of the ceiling jet, the wall material in the upper layer, after flame

spread has started and the wall linings burning below the hot gas layer.

X6.13 Any one of the eight approaches can be used to estimate, at least on a relative basis, the energy required for flashover of a rail transportation vehicle. This total should be compared with the sum of the heat release rates measured or estimated for all items proposed as rail transportation vehicle

contents. If the former exceeds the latter, the analysis indicates that flashover is not likely to occur. Report the method used.

X6.14 The combination of fire models and equations contained in FPETool (67) can be employed to calculate upper layer compartment temperatures, by using fire growth curves with quadratic growth, as well as flashover heat release rate requirements, using the approach by Thomas (55).

X7. STATISTICS ON FIRES IN MASS TRANSPORTATION

X7.1 Table X7.1 contains some statistics of fire incidents, injuries and fatalities, according to statistics by U.S. Department of Transportation (Federal Transit Administration) for 1990 and 1991 (excluding intercity trains) (23, 24). Table X7.2 contains FTA fire statistics for the years 1992 through 1997 and data on fire fatalities and fire injuries for 1997 (72). Table X7.3 contains NFPA average annual statistics for the years 1991 to 1995 for all rail transportation (73). Table X7.4 contains NFPA average annual statistics for fires in rail passenger and diner cars for the years 1988 through 1997 (74). The statistics should

not be averaged to obtain overall yearly average representative data, but should be analyzed as representing an adequately low number of fire fatalities for some recent years.

X7.2 Accidental fatalities in railroad accidents have been steady for a few years: 1165 in 1987, 1279 in 1993, and 1114 in 1995 (69). The fraction of fire fatalities is unknown, but the fraction of fires compared to other accidents was close to 3 % during the mid 1970's (37).

TABLE X7.1 FTA Statistics of Fire Incidents in Rail Transportation (1990–1991) (23, 24)

	1990	1991
Commuter Rail Fires	1226	695
Light Rail Fires	72	96
Rapid Rail Fires	4217	5124
Total Rail Fires	5515	5915
Commuter Rail Fire Fatalities	0	0
Light Rail Fire Fatalities	0	0
Rapid Rail Fire Fatalities	2	0
Total Rail Fire Fatalities	2	0
Commuter Rail Fire Injuries	583	12
Light Rail Fire Injuries	0	1
Rapid Rail Fire Injuries	438	160
Total Rail Fire Injuries	1021	173
Commuter Rail Fire Miles (millions)	204.2	205.3
Light Rail Miles (millions)	24.1	27.3
Rapid Rail Miles (millions)	528.6	521.8
Total Rail Miles (millions)	756.9	754.4
Commuter Rail Passengers (millions)	319.4	307.3
Light Rail Passengers (millions)	174.0	183.6
Rapid Rail Passengers (millions)	2252.5	2123.2
Total Rail Passengers (millions)	2745.9	2614.1



TABLE X7.2 FTA Statistics of Fire Incidents in Rail Transportation (1992–1997)^A (72)

	1992	1993	1994	1995	1996	1997
Commuter Rail Fires	527	540	715	544	503	602
Light Rail Fires	101	75	67	50	106	83
Rapid Rail Fires	5068	4452	4117	3201	3154	3253
Total Rail Fires	5696	5067	4899	3795	3763	3938
Total Fire Fatalities	0	0	0	2	0	0
Commuter Rail Fire Injuries	13	25	49	28	36	31
Light Rail Fire Injuries	0	0	3	238	3	3
Rapid Rail Fire Injuries	365	172	310	0	78	99
Total Rail Fire Injuries	378	197	362	266	117	133

^A Note that Table X7.3 indicates that there were multiple rail fire fatalities and multiple rail fire injuries in the years 1992 to 1996. Note also that data reported by FTA does not include Amtrak fire-related accident/incident information; including the 8 fire fatalities from the 1996 MARC/Amtrak collision and fire.

TABLE X7.3 NFPA Statistics of Fires in Overall Rail Transportation (1991–95, and 1992–96) (73, 74)

Annual Average Fires in Transportation 1991–95; 1992–96				
	Fires 91–95	% 91–95	Fires 92–96	% 92–96
Passenger Road	308,760	85.9	298,570	72.9
Freight road transport	39,990	11.1	38,050	9.3
Heavy equipment	6,070	1.7	5,870	1.4
Special	2,040	0.6	2,000	0.5
Water transport	1,820	0.5	1,670	0.4
Rail Transport	700	0.2	630	0.2
Air Transport	240	0.1	230	0.1
Total Transport Vehicles	359,620		409,750	

Annual Average Fires in Rail Transportation 1991–95; 1992–96				
	% 91–95	Fires 92–96	% 92–96	
Freight cars	36	230	36	
Locomotive	25	160	26	
Equipment	9	50	8	
Passenger	8	50	8	
Other	22	130	22	

Causes of Fires in Rail Transportation 1991–95; 1992–96				
	%	Fires 92–96	% 92–96	
Incendiary	20	130	21	
Non-incendiary	80	500	79	

Material First Ignited in Fires in Rail Transportation 1991–95; 1992–96				
	% 91–95	Fires 92–96	% 92–96	
Fuel	17	110	17	
Electrical Wire	11	70	11	
Trash	8	60	9	
Upholstery	3		2	
Unclassified	16		15	
Other	45		46	

Average Annual Fire Fatalities and Fire Injuries in Rail Transportation 1991–95; 1992–96				
	Fatalities 91–95	Injuries 91–95	Fatalities 92–96	Injuries 92–96
Overall	1	12	4	11

TABLE X7.4 NFPA Statistics of Fires in Rail Transportation Passenger and Diner Cars (1988–97) (75)

Annual Average Rail Passenger & Diner Car Data 1988–97		
Fires		Number
Fire Fatalities		71
Fire Injuries		2
		4
Annual Average Causes of Rail Passenger & Diner Car Fires 1988–97		
	Fires	%
Incendiary	12	12
Non-incendiary	59	88
Annual Average Material First Ignited in Rail Passenger & Diner Car Fires 1988–97		
	Fires	%
Fuel	12	16
Electrical Wire	13	18
Trash	1	1
Upholstery	7	11
Unclassified	5	7
Other	33	47

X8. EXAMPLE CALCULATION

X8.1 Table X8.1 and Table X8.2 contain cone calorimeter data for rail transportation vehicle materials (33, 37, 68-71).

X8.2 One of the methods that can be employed to calculate upper layer room temperatures is the fire model contained in the FPETOOL software (67). In that fire model, a moderate fire is defined as one where the growth is governed by a constant $\alpha = 11.72 \times 10^{-3} \text{ kJ/s}^3$ and a fast fire is defined as one where the growth is governed by a constant $\alpha = 46.88 \times 10^{-3} \text{ kJ/s}^3$. Using a fast fire curve, and a BART-type rail transportation vehicle (36), flashover is reached after 9 minutes, while the moderate fire does not reach flashover in 15 minutes. The analyses were conducted using resilient flooring. In order to

see the sensitivity of the analysis, alternate ones were conducted using wood flooring and concrete flooring of similar thickness. Slightly different upper layer temperatures were obtained for the various flooring types, representing the thermal response characteristics of the flooring material.

X8.3 The FP-PVC2 and PO1-PO3 cables from Table X8.1 were used to investigate their relative effectiveness, which respectively have, excellent and borderline-failing fire performance in the vertical cable tray test). Application of a different fire model within the same FPETOOL software can be made using specially-constructed fire curves. In the first curve it is assumed that only a few lengths of cable were present (some 40

TABLE X8.1 Cone Calorimeter Test Data for Some Materials Used in Rail Transportation Vehicle^A(33, 37, 69-71)

Material	Flux [kW/m ²]	Pk RHR [kW/m ²]	T _m Pk [s]	Av RHR 3 [kW/m ²]	THR [MJ/m ²]	EHC [MJ/kg]	T _{ig} [s]	Av SEA [m ² /kg]	Pk SEA [m ² /kg]	Thickness [mm]
Low smoke polychloroprene foam (37)	25	27	634		12	NA	NA	NA		25 ^B
Vinyl chloride acrylic copolymers window mask (37)	25	200	99		2	NA	90	NA		25 ^B
Acrylic wall covering	25	410								25 ^B
Nylon floor covering with underlayment (37)	25	350	228		21	NA	117	NA		25 ^B
CMHR Upholst. Foam A (69)	35	26	5	12	3	5	5	12		27
CMHR Upholst. Foam 2 (69)	35	20	25	11	3	3	4	139		27
CMHR Upholst. Foam B (70)	35			31						50 ^B
CMHR Upholst. Foam C (70)	35			34						50 ^B
Neoprene Uph. Foam (71)	35			32						50 ^B
Wire and Cable										
PVC1-PVC2 Cable (33)	40	189		56	54	11	113	387		10
PVC1-PO1 Cable (33)	40	163		77	88	19	59	261		10
FP-PVC2 Cable (33)	40	132		46	46	12	72	654		10
PO2-PO1 (33)	40	282		52	77	24	62	272		10
PO1-PO3 (33)	40	398		52	124	26	114	303		

^AThe materials chosen from reference (71) are high performance foams potentially used in rail. The designation CMHR in this table is not restricted to polyurethane foam but reflects an advanced degree of improved fire performance. Foams were tested at 50-mm thickness (except the graphite foam tested at 25-mm); other materials were tested at use thickness. The cable material data from (33) were obtained from testing communications cables of various chemical compositions (insulation and jacket), of which the first four meet the flame spread, heat and smoke requirements from UL 1685 in Test Method D 5424, a test method which is somewhat similar to the AMTRAK Specifications for High Performance Wire and Cable Spec 323-1990 (31) and the last one does not meet them (PO1-PO3). Abbreviations: PO: polyolefin, halogen-free; PVC: poly(vinyl chloride-based); FP: fluoropolymer. Property abbreviations: Flux: incident heat flux; Pk RHR: maximum rate of heat release; T_m Pk: time to Pk RHR; Av RHR 3: 3 min average rate of heat release; THR: total heat released; EHC: effective heat of combustion; T_{ig}: time to ignition; Av SEA: average specific extinction area; Pk SEA: peak specific extinction area.

^B?: Symbol indicates that the thickness used for testing is likely to be that indicated.



TABLE X8.2 Cone Calorimeter NIST Test Data for Some Additional Materials Used in Rail Transportation Vehicles at 50 kW/m² (68)

Material ^A	Pk RHR ^B [kW/m ²]	Tm Pk ^B [s]	THR ^B [MJ/m ²]	Av RHR 3 ^B [kW/m ²]	Av MLR ^B [g/s m ²]	EHC ^B [MJ/kg]	T _{ig} ^B [s]	Av SEA ^B [m ² /kg]	Pk SEA ^B [m ² /kg]	Thickness [mm]
Individual Seat/Mattress Materials										
CMHR upholstery foam	77	25	15.7	32	3.17	9.7	14	18	211	50
Graphite upholstery foam ^C	99	8	8.5	43	2.42	17.5	5	48	457	26
Upholstery interliner	25	13	0.9	5	0.94	18.5	5	421	2388	1
Wood/nylon upholstery fabric	423	20	6.2	31	9.42	16.7	11	225	418	1
PVC upholstery cover fabric	359	13	6.0	29	16.51	11.9	7	782	1040	1
Mattress ticking	14	10	0.2	1	0.51	12.5	5	38		1
Polychloroprene elastomer seat support diaphragm	295	53	24.2	114	9.83	12.5	32	1219	1779	1
FR cotton muslin seat support diaphragm	193	12	2.5	12	4.89	9.7	7	494	1346	1
PVC/acrylic seat shroud	107	353	43.5	484	9.20	11.9	29	552	1427	2
Armrest pad foam, coach seat	659	168	121.5	431	12.23	20.1	17	643	1128	7
Polychloroprene elastomer seat footrest cover	190	98	34.8	125	10.32	11.4	26	689	1401	4
Polychloroprene seat track cover	267	40	62.5	207	15.95	12.8	18	1011	1246	15
Individual Interior Finish Materials										
Wall finish wool carpet	655	95	76.7	394	15.67	29.6	30	509	857	1
Wall finish wool fabric	745	35	18.8	91	2.68	19.2	21	209	464	2
Polycarbonate space divider	272	153	246.9	208	7.66	21.1	108	787	1958	13
Wall material FRP/PVC	122	40	21.9	101	10.94	11.4	22	627	1328	2
Wall panel FRP	612	57	62.9	140	8.33	13.5	54	578	925	4
Individual Glazing Materials										
Polycarbonate window glazing	329	208	137.2	263	13.13	21.7	91	857	1141	6
FRP window mask	398	68	22.4	111	15.07	10.0	45	586	718	2
Individual Fabrics										
Door privacy curtain window drapery fabric	308	22	5.3	27	12.25	14.5	13	381	475	1
Polyester drapery fabric	175	30	5.4	28	4.35	12.7	21	757	1091	1
Blanket, wool fabric	168	15	1.9	8	2.16	7.2	11	561	2443	3
Blanket, modacrylic fabric	18	25	0.4	2	1.35	10.7	17	3
Floor carpet, nylon	245	72	17.8	97	9.01	17.0	10	245	771	4
Other Individual Materials										
Rubber mat, styrene butadiene	281	95	83.1	173	3.09	29.3	32	943	1610	20
Table, phenolic-wood laminate	249	55	188.9	132	9.00	11.0	45	48	222	29
Air duct, polychloroprene	143	53	13.5	71	2.71	32.4	30	736	1077	1
Pipe wrap, insulation foam	93	10	7.0	38	4.22	14.3	7	689	1190	13
Window gasketing, polychloroprene elastomer	208	305	196.6	165	2.60	37.4	33	714	1409	15
Door gasketing, polychloroprene elastomer	207	275	263.5	175	2.70	49.6	38	731	1474	15
Composite Systems										
Seat cover with CMHR foam, interliner and wool/nylon cover	268	15	8.9	46	4.92	11.3	12	318	847	51
Seat cover with CMHR foam, interliner and PVC cover	269	30	10.7	51	8.64	10.3	7	319	596	51
Mattress: CMHR foam interliner, and ticking	174	10	11.7	53	5.07	10.1	7	30	144	51
Bed pad: CMHR foam and ticking	143	10	7.8	42	5.47	10.2	7	31	130	39
Pillow: cotton fabric and polyester filler	341	58	19.6	108	14.74	19.3	24	563	656	51

^AThe materials were all tested at use thickness.

^BProperty abbreviations: Flux: incident heat flux; Pk RHR: maximum rate of heat release; Tm Pk: time to Pk RHR; Av RHR 3: 3 min average rate of heat release; THR: total heat released; EHC: effective heat of combustion; T_{ig}: time to ignition; Av SEA: average specific extinction area; Pk SEA: peak specific extinction area.

^CThis material does not comply fully with all the recommendations in Table X1.1.

kg). In that case, the better performing cable causes virtually no problem (peak heat release rate: < 30 kW). On the other hand the poorer cable (peak heat release rate > 200 kW) causes a row of seats to ignite and release enough heat to ignite the next row, and so on; however, the overall fire is still much slower than a moderate fire curve. In reality, however, there are approxi-

mately 500–1000 kg of cable in a rail transportation vehicle, so that changing to the poorer fire performing cable would decrease safety considerably and should not be done unless it is accompanied by a number of other compensatory fire safety measures.

REFERENCES

- (1) Blockley, W.V. and Taylor, C.L. "Human Tolerance Limits for Extreme Heat," *Heating, Piping & Air Conditioning*, 21, 111–116 (May 1949).
- (2) Crane, C.R., "Human Tolerance Limit to Elevated Temperature: An Empirical Approach to the Dynamics of Acute Thermal Collapse," Federal Aviation Administration, Aviation Toxicology Lab., Oklahoma City, OH, Memorandum Report AAC-114-78-2 (1978).
- (3) Kosunen, K.J., et al, "Plasma Renin Activity, Angiotension II, Alldosterone During Intense Heat Stress," *Journal of Applied Physiology*, 41, 323–327 (1976).
- (4) Purser, D.A. "Toxicity Assessment of Combustion Products," *SFPE Handbook of Fire Protection Engineering, 2nd Ed.*, Eds P.J. DiNenno, C.L. Beyler, R.L.P. Custer, W.D. Walton, J.M. Watts, D. Drysdale & J.R. Hall, Natl Fire Prot. Assoc. Quincy, MA, pp. 2–85 to 2-146 (1995).
- (5) Henriques, F.C., Jr., "Studies of Thermal Injuries V, the Predicability and the Significance of Thermally Induced Rate Processes Leading to Irreversible Epidermal Injuries," *Archives of Pathology* 43, 489–502 (1947).
- (6) Stoll, A.M. and Greene, L.C., "Relationship Between Pain and Tissue Damage Due to Thermal Radiation," *Journal of Applied Physiology*, 14, 373–382 (1959).
- (7) Derksen, W.L., Monahan, T.I. and deLhery, G.P., "The Temperature Associated with Radiant Skin Energy Burns," in *Temperature—Its Measurement and Control in Science and Industry*, 3(3), 171–175 (1963).
- (8) Stoll, A.M. and Chianta, M.A., "Method and Rating System for Evaluation of Thermal Protection", *Aerospace Medicine*, 40, 1232–1238 (1969).
- (9) Jin, T., "Visibility Through Fire Smoke," *Report of the Fire Research Institute of Japan*, 2(33), 12–18 (1971).
- (10) Malhotra, H.L., "Movement of Smoke on Escape Routes, Part 1—Instrumentation and Effect of Smoke on Visibility," Joint Fire Research Organization, Fire Research Station, Note 651, pp. 21, January, Borehamwood, Herts, UK, 1967.
- (11) Levin, B.D., Paabo, M., Gurman, J.L., Harris, S.E. and Braun, E., "Toxicological Interactions Between Carbon Monoxide and Carbon Dioxide," *Toxicology* 47, 135–164 (1987).
- (12) Hartzell, G.E., Priest, D.N. and Switzer, W.G., Modeling of Toxicological Effects of Fire Gases, II. Mathematical Modeling of Intoxication of Rats by Carbon Monoxide and Hydrogen Cyanide, *J. Fire Sciences*, 3, pp. 115–128, (1985).
- (13) Kaplan, H.L., Grand, A.F., and Hartzell, G.E., "Combustion Toxicology: Principles and Test Methods", *Technomic*, Lancaster, PA (1983).
- (14) Hinderer, R.K. and Hirschler, M.M. "The Toxicity of Hydrogen Chloride and of the Smoke Generated by Poly(Vinyl Chloride), Including Effects on Various Animal Species, and the Implications for Fire Safety," in *ASTM E-5 Symposium on Smoke, Dec. 3, 1988, Phoenix (AZ), "Characterization and Toxicity of Smoke," ASTM STP 1082*, ASTM, Philadelphia, PA, Ed. H.I. Hasegawa, pp. 1–22, (1990).
- (15) Babrauskas, V., Harris, R.H., Jr., Braun, E., Levin, B.C., Paabo, M., and Gann, R.G., Large-Scale Validation of Bench-Scale Fire Toxicity Tests, *J. Fire Sciences* 9, 125–149 (1991).
- (16) Sakurai, T., Toxic Gas Tests With Several Pure and Mixed Gases Using Mice, *J. Fire Sciences*, 7 22–77, (1989).
- (17) Babrauskas, V., Harris, R.H., Jr., Braun, E., Levin, B.C., Paabo, M., and Gann, R.G., Large-Scale Validation of Bench-Scale Fire Toxicity Tests, pp. 3–12 in *INTERFLAM '90: Fifth Intl. Fire, Conf. Proc.*, London (1990).
- (18) Babrauskas, V., Levin, B.C., and Gann, R.G., "New Approach to Fire Toxicity Data for Hazard Evaluation," *Fire J.*, 81, pp. 22–23, (March/April 1987).
- (19) Babrauskas, V., Harris, R.H., Braun, E., Levin, B., Paabo, M., and Gann, R.G., The Role of Bench-Scale Test Data in Assessing Real-Scale Fire Toxicity (Tech. Note 1284), Natl. Inst. Stand. Technol., Gaithersburg, MD (1991).
- (20) Hirschler, M.M., "Fire Retardance, Smoke Toxicity and Fire Hazard," in *Proc. Flame Retardants '94*, British Plastics Federation Editor, Interscience Communications, London, UK, January 26–27, 1994, pp. 225–37 (1994).
- (21) Peacock, R.D., Jones, W.W., Bukowski, R.W. and Forney, C.L. "Technical Reference Guide for the HAZARD I Fire Hazard Assessment Method, Version 1.1," "NIST Handbook 146, Vol II, Natl. Inst. Stand. Technol., Gaithersburg, MD (1991).
- (22) Peacock, R.D., Jones, W.W., Forney, G.P., Portier, R.W., Reneke, P.A., Bukowski, R.W. and Klote, J.H., "An Update Guide for HAZARD I, Version 1.2," NISTR 5410, Natl. Inst. Stand. Technol., Gaithersburg, MD (1994).
- (23) U.S. Dept. Transportation, Federal Transit Administration, "Safety Management Information Statistics (SAMIS)," *1990 Annual Report, FTA-MA-06-0194-92, DOT-UNTSC-FTA-92-2*, John A. Volpe National Transportation Systems Center, Cambridge, MA, April 1992.
- (24) U.S. Dept. Transportation, Federal Transit Administration, "Safety Management Information Statistics (SAMIS)," *1991 Annual Report, FTA-MA-26-0009-93-1, DOT-UNTSC-FTA-93-1*, John A. Volpe National Transportation Systems Center, Cambridge, MA, February 1993.
- (25) Federal Railroad Administration, "Rail Passenger Equipment: Reissuance of Guidelines for Selecting Materials to Improve Their Fire Safety Characteristics," *Federal Register* 54 (10) 1837–40 (January 17, 1989).
- (26) Peacock, R.D., Bukowski, R.W., Jones, W.L., Reneke, P.A. Babrauskas, V. and Brown, J.E., "Fire Safety or Passenger Trains: A Review of U.S. and Foreign Approaches," *National Institute of Standards and Technology (under contract to U.S. Dept. of Transportation, John A. Volpe National Transportation Systems Center, Cambridge, MA)*, Gaithersburg, MD 20899 (NIST Technical Note 1406) 1994.
- (27) Amtrak Specification for Flammability, Smoke Emissions and Toxicity, No. 352, January 29, 1990.
- (28) Federal Transit Administration, "Recommended Fire Safety Practices for Transit Bus and Van Materials Selection; Notice," *Federal Register* 57 (8) 1360–63 (January 13, 1992).
- (29) Federal Register, Wednesday May 12, 1999, Dept. of Transportation, Federal Railroad Administration, 49 CFR Part 216 et al., Fed. Reg. Vol. 64, No. 91, pp. 25539–25705, "Passenger Equipment Safety Standards: Final Rule".
- (30) Thomas, P.H., "How Heat Release Influences Fire Hazard" in *International Conference Fire: Control the Heat ... Reduce the Hazard*, London, UK, 24–25, Oct. 1988, paper 1.
- (31) Babrauskas, V. and Peacock, R.D., "Heat Release Rate: The Single Most Important Variable in Fire Hazard," *Fire Safety J.*, 18, 255-72 (1992).
- (32) Amtrak Specification for High Performance Wire and Cable Used in Amtrak Passenger Vehicles, No. 323, March 23, 1990.
- (33) Barnes, M.A., Briggs, P.I., Hirschler, M.M., Matheson, A.E., and O'Neill, T.J. "A Comparative Study of the Fire Performance of Halogenated and Non-Halogenated Materials for Cable Applications, Part II, Tests on Cables," *Fire and Materials* 20, 17–37 (1996).
- (34) Hirschler, M.M., "Analysis of and Potential Correlations Between Fire Tests for Electrical Cables, and How to Use This Information for Fire Hazard Assessment," *Fire Technology*, 33, 291–315, (1997).
- (35) Hirschler, M.M., "A New Mattress Fire Test for Use in Detention Environments," Business Communications Company Eighth Ann. Conference on Recent Advances in Flame Retardancy of Polymeric Materials, June 2–4, 1997, Stamford, CT, Ed. M. Lewin, pp., Norwalk, CT, 1997.
- (36) Braun, E., "Fire Hazard Evaluation of BART Vehicles," NBSIR 78–1421, Natl. Bur. Stds, Gaithersburg, MD, 1978.
- (37) Peacock, R.D. and Braun, E., "Fire Tests of Amtrak Passenger Rail Vehicle Interiors," NBS Technical Note 1193, Natl. Bur. Stds, Gaithersburg, MD, 1984.

- (38) Friedman, R., "An International Survey of Computer Models for Fire and Smoke," *J. Fire Protection Engng* 4(3) 81–92 (1992).
- (39) Cooper, L.Y., "A Mathematical Model for Estimating Available Safe Egress Time in Fires," *Fire and Materials*, 6, No. 4, 135–144 (1982).
- (40) Babrauskas, V., "COMPF2—A Program for Calculating Post-Flashover Fire Temperatures," National Bureau of Standards (U.S.) Technical Note 991 (1979).
- (41) Davis, W.D. and Cooper, L.Y., "Computer Model for Estimating the Response of Sprinkler Links to Compartment Fires With Draft Curtains and Fusible Link-Actuated Ceiling Vents," *Fire Technology*, 27, No. 2, 113–127 (1991).
- (42) Mitler, H.E. and Emmons, H.W., "Documentation for CFCV, the Fifth Harvard Computer Fire Code," *National Bureau of Standards (U.S.)*, NBSGCR 81–344, Gaithersburg, MD (1981).
- (43) Mitler, H.E. and Rockett, J., "A User's Guide for FIRST, a Comprehensive Single-Room Fire Model," National Bureau of Standards (U.S.), NBSIR 87–3595, Gaithersburg, MD (1987).
- (44) Tanaka, T., "A Model of Multiroom Fire Spread," National Bureau of Standards (U.S.), NBSIR 83–2718, Gaithersburg, MD (1983).
- (45) Gahm, J.B., "Computer Fire Code VI, Volume I," National Bureau of Standards (U.S.), NBS GCR 83–451, Gaithersburg, MD (1983).
- (46) Jones, W.W., "A Multicompartment Model for the Spread of Fire, Smoke and Toxic Gases," *Fire Safety Journal*, 9, 55–79 (1985).
- (47) Jones, W.W. and Peacock, R.D., "Refinement and Experimental Verification of a Model for Fire Growth and Smoke Transport," in *Fire Safety Science, Proc. 2nd International Symposium on Fire Safety Science*, Tokyo, Japan, 13–17 June, 1988, Eds. T. Wakamatsu, Y. Hasemi, A. Sekizawa, P.G. Seeger, P.J. Pagni and C.E. Grant, Hemisphere, Washington, DC, pp. 897–906 (1989).
- (48) Forney, G.P. and Cooper, L.Y., *The Consolidated Compartment Fire Model (CCFM) Computer Application CCFM. VENTS—Part II: Software Reference Guide*, National Institute of Standards and Technology, NISTIR 90–4343 (1990).
- (49) Jones, W.W. and Forney, G.P., *A Programmer's Reference Manual for CFAST, the United Model of Fire Growth and Smoke Transport*, National Institute of Standards and Technology, Technical Note 1283 (1990).
- (50) Mitler, H.E., "Comparison of Several Compartment Fire Models: An Interim Report," National Bureau of Standards (U.S.), NBSIR 85–3233 (1985).
- (51) Jones, W.W., "A Review of Compartment Fire Models," National Bureau of Standards (U.S.), NBSIR 83–2684 (1983).
- (52) Janssens, M., "Room Fire Models," General, Chapter 6a, in *Heat Release in Fires*, Elsevier, London, UK, Eds. V. Babrauskas and S.J. Grayson, 1992, pp. 113–158.
- (53) Babrauskas, V., "Will the Second Item Ignite?" *Fire Safety J.* 4, 281–292 (1981/82).
- (54) Babrauskas, V. and Krasny, J., "Fire Behavior of Upholstered Furniture," NBS Monograph 173, *Natl. Bur. Stds. (U.S.)*, Gaithersburg, MD, 1985.
- (55) Thomas, P.H., "Testing Products and Materials for Their Contribution to Flashover in Rooms," *Fire and Materials*, 5 103–11 (1981).
- (56) Quintiere, J.G., "Smoke Measurements: An Assessment of Correlations Between Laboratory and Full-Scale Experiments," *Fire and Materials*, 6, 145–160 (1982).
- (57) Ostman, B.A.-L. and Nussbaum, R.M., "Correlation Between Small Scale Rate of Heat Release and Full Scale Room Flashover for Surface Linings," in *Fire Safety Science, Proc. 2nd Int. Symp.*, Tokyo, Japan, 13–17 June, 1988, Eds. T. Wakamatsu, Y. Hasemi, A. Sekizawa, P.G. Seeger, P.J. Pagni and C.E. Grant, Hemisphere, Washington, DC, 1989, pp. 823–32.
- (58) Hirschler, M.M., "Smoke and Heat Release and Ignitability as Measures of Fire Hazard from Burning of Carpet Tiles," *Fire Safety J.* 18, 305–24 (1992).
- (59) Hirschler, M.M., "Heat Release from Plastic Materials," Chapter 12 a, in *Heat Release in Fires*, Elsevier, London, UK, Eds. V. Babrauskas and S.J. Grayson, 1992, pp. 375–422.
- (60) Wickstrom, U. and Göransson, U., "Full-Scale/Bench-Scale Correlations of Wall and Ceiling Linings," in *Heat Release in Fires*, Eds. V. Babrauskas and S.J. Grayson, Chapter 13, Elsevier, London, 1992, p. 461–77.
- (61) Hirschler, M.M., "Tools Available to Predict Full Scale Fire Performance of Furniture," in *Fire and Polymers, New Materials and Tests for Hazard Prevention*, Ed. G.L. Nelson, American Chemical Society, Washington, D.C. (1995).
- (62) Smith, E.E. and Satija, S., "Release Rate Model for Developing Fires," *J. Heat Transfer*, 105, 282–87 (1983).
- (63) Wickström, U., and Göransson, U., "Prediction of Heat Release Rates of Large Scale Room Fire Tests Based on Cone Calorimeter Results," *J. Testing and Evaluation*, 15, pp. 364–370 (1987).
- (64) Karlsson, B. and Magnusson, S.E., "Combustible Wall Lining Materials: Numerical Simulation of Room Fire Growth and the Outline of a Reliability Based Classification Procedure," in *Fire Safety Science, Proc. Third Int. Symp.*, G. Cox and B. Langford, Eds., Elsevier, London, UK, 1991, pp. 667–76.
- (65) Karlsson, B. and Magnusson, S.E., "An Example Room Fire Model," Chapter be in *Heat Release in Fires*, Elsevier, London, UK, Eds., V. Babrauskas and S.J. Grayson, 1992, pp. 159–172.
- (66) Karlsson, B., "Models for Calculating Flame Spread on Wall Lining Materials and the Resulting Heat Release Rate in a Room," *Fire Safety J.* 23, pp. 365–86 (1994).
- (67) Nelson, H.E., "FPETOOL: Fire Protection Engineering Tools for Hazard Estimation," National Institute of Standards and Technology, NISTIR 90–4380 (1990).
- (68) Peacock, R.D. and Braun, E., "Fire Safety of Passenger Trains: Phase I: Material Evaluation (Cone Calorimeter)," *National Institute of Standards and Technology (under contract to U.S. Dept. of Transportation, John A. Volpe National Transportation Systems Center, Cambridge, MA)*, Gaithersburg, MD, 20899 (NIST IR 6132: U.S. Dept. of Transport, DOT-VNTSC-FRA-98-26: DOT/FRA/ORD-99/01) March 1999.
- (69) Federal Railroad Administration, "Enhancing Rail Safety Now and Into the 21st Century: The Federal Railroad Administration's Safety Programs and Initiatives," Report to Congress, FRA, Washington, DC, October 1996.
- (70) Hirschler, M.M., Data from Testing of Present Day Rail Upholstery Materials, unpublished.
- (71) Babrauskas, V., "Bench-Scale Predictions of Mattress and Upholstered Chair Fires—Similarities and Differences," NISTIR 5152, Natl Inst. Stands Technol., Gaithersburg, MD, 1993.
- (72) US Dept. Transportation, Federal Transit Administration, "Safety Management Information Statistics (SAMIS)", *1997 Annual Report, FTA-MA-26-5002-99-01, DOT-VNTSC-FTA-99-3, John A. Volpe National Transportation Systems Center*, Cambridge, MA, March 1999.
- (73) Ahrens, M., "U.S. Vehicle Fire Trends and Patterns," Natl. Fire Protection Assoc., Quincy, MA, January 1998.
- (74) Ahrens, M., "U.S. Vehicle Fire Trends and Patterns," Natl. Fire Protection Assoc., Quincy, MA, February 1999.
- (75) Ahrens, M., "Statistics of US Fires in Rail Transportation Passenger and Diner Vehicles Between 1988 and 1997", Report developed for Stephanie Markos, US Dept. Transportation, *John A. Volpe National Transportation Systems Center*, Cambridge, MA, by Natl Fire Protection Assoc., Quincy, MA, October 26, 1999.

**NOTICE: This standard has either been superseded and replaced by a new version or discontinued.
Contact ASTM International (www.astm.org) for the latest information.**



E 2061 – 02

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org).