



Designation: E 2187 – 02

Standard Test Method for Measuring the Ignition Strength of Cigarettes¹

This standard is issued under the fixed designation E 2187; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

INTRODUCTION

The most common initiating event in a fatal fire in the United States is the dropping of a lit cigarette onto a bed or piece of upholstered furniture. The cigarette coal heats the furnishing materials to the point where smoldering combustion begins, perhaps followed by a transition to flaming combustion. Since limiting the frequency of ignitions is a principal approach to reducing fire loss, it is desirable to establish a test method for the propensity of a cigarette to ignite soft furnishings. This test method uses standard substrates to determine the extent to which, as the substrate draws heat from the cigarette, the cigarette combustion remains strong enough to be capable of initiating a fire.

1. Scope

1.1 This fire-test-response standard provides a standard measure of the capability of a cigarette, positioned on one of three standard substrates, to generate sufficient heat to continue burning and thus potentially cause ignition of bedding or upholstered furniture.

1.2 This method has value as a predictor of the relative propensity of a cigarette to ignite upholstered furnishings.

1.3 This method is applicable to cigarettes that burn along the length of a tobacco column.

1.4 The values stated in SI units are to be regarded as the standard. The values given in parentheses are for information only.

1.5 This standard measures and describes the response of materials, products, or assemblies to heat under controlled conditions, but does not by itself incorporate all factors required for fire hazard or fire risk assessment of the materials, products, or assemblies under actual fire conditions.

1.6 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.* For specific hazard statements, see Section 6.

2. Referenced Documents

2.1 ASTM Standards:

E 176 Terminology of Fire Standards²

E 691 Practice for Conducting an Interlaboratory Study to

Determine the Precision of a Test Method³

E 1352 Test Method for Cigarette Ignition Resistance of Mock-up Upholstered Furniture Assemblies²

E 1353 Test Method for Cigarette Ignition Resistance of Components of Upholstered Furniture²

2.2 Other Standard:

Standard for the Flammability of Mattresses and Mattress Pads, 16 Code of Federal Regulations, Part 1632

3. Terminology

3.1 *Definitions*—For definitions of terms used in this test method refer to Terminology E 176.

3.2 Definitions of Terms Specific to This Standard:

3.2.1 *full-length burn, n*—the outcome of a determination in which the cigarette burns at least to the beginning of the tipping paper, which covers the filter and perhaps a short section of the tobacco column in a filter tip cigarette, or to within 5 mm of the end of the tobacco column if the cigarette has no filter.

4. Summary of Test Method

4.1 This test method measures the probability that a cigarette, placed on a substrate, will generate sufficient heat to maintain burning of the tobacco column. Each determination consists of placing a lit cigarette on the horizontal surface consisting of a set number of layers of filter paper. Observation is made of whether or not the cigarette continues to burn to the beginning of the tipping paper. Forty determinations (comprising a test) are performed to obtain the relative probability that the cigarette will continue burning despite heat abstraction by the substrate.

5. Significance and Use

5.1 The most common initiating event in a fatal fire is the

¹ This test method is under the jurisdiction of ASTM Committee E05 on Fire Standards and is the direct responsibility of Subcommittee E05.15 on Furnishings and Contents.

Current edition approved Feb. 10, 2002. Published April 2002.

² *Annual Book of ASTM Standards*, Vol 04.07.

³ *Annual Book of ASTM Standards*, Vol 14.02.

dropping of a cigarette onto a bed or piece of upholstered furniture, causing 20 % of the estimated U.S. fire deaths from 1992–1996 in residential structures, according to statistics provided by the U.S. Consumer Product Safety Commission. Test Methods E 1352 and E 1353 have been developed to evaluate the susceptibility of upholstered furniture mock-ups and components to ignition by cigarettes. Federal Standard 16 CFR Part 1632, Standard for the Flammability of Mattresses and Mattress Pads, was promulgated to reduce the likelihood that mattresses and mattress pads would ignite from a lighted cigarette.

5.2 This test method enables comparison of the relative ignition strength of different cigarette designs.

5.3 In this procedure, the specimens are subjected to a set of laboratory conditions. If different conditions are substituted or the end use conditions are changed, it may not be possible, using this test, to predict quantitative changes in the fire test response characteristics measured. Therefore, the quantitative results are valid only for the fire test exposure conditions described in this procedure.

6. Hazards

6.1 This test method involves the use of combustible materials that are exposed to ignition sources. Consequently, the user shall take proper precautions to avoid thermal injuries.

6.1.1 Personnel shall be instructed on general procedures to handle an unwanted fire. Appropriate fire extinguishing equipment shall be provided to suppress any fires that exceed normal controlled limits.

6.2 Personnel shall take proper precautions to avoid inhaling combustion products.

6.2.1 Exhaust systems shall be checked regularly to ensure that they are removing all products of combustion from the workspace.

6.2.2 Respiratory equipment shall be made available for personnel.

6.3 The user shall ensure that all burning has ceased before discarding used test materials. An appropriate closed metal waste container shall be used in each fire test laboratory for safe disposal of specimens and test assemblies after being exposed to heat and fire.

7. Apparatus and Equipment

7.1 *Test and Conditioning Environment*—An environmental conditioning room shall be maintained which provides an area adequate for conditioning both cigarettes and filter paper specimens. This room shall be capable of maintaining a relative humidity of 55 % \pm 5 % and a temperature of 23°C \pm 3°C (73°F \pm 5°F) and shall be continuously monitored. The room in which the tests are conducted, which may also be the conditioning room, shall be maintained within the same temperature and relative humidity ranges.

7.2 *Constant Humidity Box*—Alternatively, cigarettes and filter paper shall be stored in a box of sufficient size to hold the needed quantities of filter paper and cigarettes. The interior of the box shall be maintained at a relative humidity of 55 % \pm 5 % and a temperature of 23°C \pm 3°C (73°F \pm 5°F) and shall be continuously monitored. A tray containing a saturated solution of sodium bromide (NaBr) in water will provide the

appropriate relative humidity when the box temperature is as prescribed. The box shall be located convenient to the test chamber such that test materials shall not be exposed to a non-conditioned environment for more than 5 min between their removal from the box and the beginning of a test.

7.3 *Test Chamber*—A test chamber of the design photographed in Fig. 1 shall be constructed of clear plastic such as PMMA, nominally 6 mm (0.25 in.) in thickness. The inside dimensions shall be: height: 340 mm \pm 2 mm (15.5 in. \pm 0.1 in.), width: 292 mm \pm 2 mm (11.5 in. \pm 0.1 in.), depth: 395 mm \pm 2 mm (15.5 in. \pm 0.1 in.). The full front panel of the chamber shall be hinged, with a latch to effect positive closure. The top of the chamber shall have a flattop cylindrical chimney of height 178 mm \pm 2 mm (6.00 in. \pm 0.1 in.) and inside diameter 150 mm \pm 2 mm (6.00 in. \pm 0.1 in.). The chimney shall be centered on the chamber top and sealed to the chamber top panel.

7.4 *Filter Paper Holder*—A cylindrical support for the layers of filter paper, shown in Fig. 2, shall be made of PMMA or similarly rigid material, dimensioned as follows. The outer diameter shall be 165 mm \pm 1 mm (6.50 in. \pm 0.04 in.), the inner diameter shall be 127 mm \pm 1 mm (5.00 in. \pm 0.04 in.), and the height shall be 50 mm \pm 1 mm (1.97 in. \pm 0.04 in.). A recess in the top, 8 mm \pm 1 mm (0.31 in. \pm 0.04 in.) deep, shall expand the inner diameter to 152 mm \pm 1 mm (6.00 in. \pm 0.04 in.). Three or four legs shall raise the bottom of the holder approximately 20 mm (0.8 in) above the chamber floor.

7.5 *Metal Rim*—A circular brass or other dense metal rim, shown in Fig. 2, shall be used to hold the sheets of filter paper flat against each other. The outside diameter of the rim shall be 150 mm \pm 2 mm (5.90 in \pm 0.08 in). The inner diameter shall be 130 mm \pm 2 mm (5.1 in. \pm 0.08 in.). The thickness shall be 3 mm \pm 1 mm (0.12 in. \pm 0.04 in.). The rim surface shall be flat and smooth. A pair of parallel metal pins, each approximately 1 mm in diameter and 8.1 mm \pm 0.05 mm (0.32 in. \pm 0.02 in.) apart, shall protrude 20 mm \pm 2 mm (0.8 in. \pm 0.1 in.) toward the center of the rim. The pins are to be spaced to keep the non-ignited end of a conventional 25 mm circumference cigarette from rolling, but without pressuring the cigarette. If cigarettes of significantly different diameter are to be tested, other pairs of pins, appropriately spaced, shall be inserted into the rim.

7.6 *Cigarette Holder*—A holder shall be used to support the lit cigarette in a horizontal position in the test chamber prior to placement of the cigarette onto the filter paper substrate. The holder shall not clamp the cigarette nor stress it in any other manner, nor shall it contact the cigarette within 30 mm of its lit end.

7.7 *Cigarette Ignition System*—A system consisting of an air draw component and an ignition source shall be used to ignite the test cigarettes. The cigarette shall be supported in a horizontal position. A butane gas lighter capable of producing a stable luminous flame for 15 mm \pm 3 mm (0.6 in. \pm 0.1 in.) in length or a hot coil igniter shall be used for lighting the cigarette. The airflow and the draw time through the lit cigarette shall be sufficient to establish a coal to within \pm 1 mm of the pencil mark 5 mm (0.2 in.) from the tip of the cigarette. Appropriate filtering media shall be used downstream of the



FIG. 1 Photograph of Test Chamber and Filter Paper Holder

cigarette to remove smoke and condensable combustion gases in order to prevent contamination of the downstream components.

7.8 Exhaust Hood—A chemical or canopy hood shall be used for removing combustion products from the test room. Air flow through the hood shall be sufficient to remove cigarette and substrate combustion products while not being high enough to influence the combustion processes in the test chamber(s). (See 8.1.2.)

7.9 Extinguishment—Following a determination, the cigarette and sheets of filter paper shall be completely extinguished, for example, by smothering or by application of water.

8. Calibration and Standardization

8.1 Calibrations of equipment shall be carried out as noted below and at any time when equipment or test conditions indicate that evaluation and re-calibration are necessary. The

time intervals for calibrations stated in this method shall be considered to be the minimum.

8.1.1 The test chambers shall be checked before use to minimize air leakage so that the smoke plume from a cigarette rises undisturbed during testing. Door seals shall be checked visually to ensure that they are closed flush against the chamber's side wall and the latching device secures the door tightly. All construction seams shall be inspected to ensure they are airtight and no cracks shall be visible on any surface of the test chamber. If leaks are detected, measures shall be taken to ensure that these areas are again made sufficiently air tight.

8.1.2 Stability of air inside the test chamber shall be determined daily by placing a lit cigarette in the test position on three or more layers of filter paper, then closing the chamber door. Air movement in the chamber shall be observed to ensure that smoke being emitted by the cigarette is rising vertically and is not showing turbulence within 150 mm (6 in.) above the



FIG. 2 Close-up of Test Cigarette, Filter Paper Holder, Metal Pins and Metal Rim

lit end of the cigarette. If turbulence is noted, then (a) the test chamber shall be checked for leaks, (b) the test chamber locations shall be evaluated for excess air flow in the laboratory, and (c) the air flow of the exhaust system shall be evaluated as the source of the disturbance.

8.1.3 The humidity and temperature sensors used to record environmental conditions in the conditioning room or the chamber and test room shall be checked for accuracy each week.

8.1.4 The air draw apparatus used for igniting cigarettes shall be calibrated at least each week using a rotameter, wet test meter or equivalent device.

9. Test Specimens and Standard Substrate Assemblies

9.1 Cigarette test specimens and filter paper substrates are sensitive to contamination. Clean plastic or rubber gloves shall be worn at all times when these materials are handled.

9.2 Cigarettes:

9.2.1 Cigarette test specimens shall be protected from physical or environmental damage while in handling and storage. It is important that the specimens not be crushed or deformed in any manner. Measures shall be taken to ensure that the specimens are not contaminated while in storage and they shall be protected from degradation by insects. If the specimens are to be stored for more than one week, they shall be placed in a freezer at approximately 0°C (32°F) reserved for the sole protection of cigarette specimens to minimize the risk of contamination.

9.2.2 Prior to testing, cigarette test specimens shall be marked, using a #2 or softer graphite pencil, on their paper seam 5 mm ± 1 mm and 15 mm ± 1 mm (0.2 in. and 0.6 in., each ± 0.04 in.) from the end of the cigarette that will be lit. These marks are used to establish the start (11.4) and completion (11.5.4) of a uniform pre-burn period, respectively.

9.3 *Filter Paper*—The substrates consist of 150 mm (6 in.) diameter circles of Whatman #2 ash-free cellulosic filter paper. Substrates are formed by placing multiple layers of filter paper into the holder assembly, then placing the metal rim on top to ensure good contact between the layers.

10. Conditioning

10.1 Cigarettes shall be conditioned at a relative humidity of 55 % ± 5 % and a temperature of 23°C ± 3°C (73°F ± 5°F) for at least 24 h prior to testing. The cigarettes shall be oriented vertically in a small clean container, with the number of cigarettes being sufficiently small as to enable free air access to the specimens, for example, a maximum of 20 cigarettes in a 250 mL polyethylene or glass beaker.

10.1.1 Boxes of filter paper shall be conditioned at a relative humidity of 55 % ± 5 % and a temperature of 23°C ± 3°C (73°F ± 5°F) for at least one week prior to testing. The top of each 100 sheet box of filter paper shall be removed prior to being placed in the conditioning room or box. The top opening of the box shall not be obstructed. The paper sheets need not be removed from the box.

11. Procedure

11.1 Turn on the exhaust system designated for removal of test combustion products 30 min prior to beginning testing.

11.2 Ensure that the filter paper holder is in the test chamber at the geometric center of its bottom. Cover the chimney on the test chamber.

11.3 Conduct the test beginning with 15 layers of filter paper except as indicated in Annex A1. Select the number of layers of filter paper for the scheduled determinations using the procedure in Annex A1.

11.3.1 If the relative humidity and temperature in the test room cannot be maintained within the specified ranges, the filter papers and cigarettes shall be sealed in plastic bags in the conditioning room and transported. Care shall be taken to ensure that test materials are protected from physical damage during transport and prior to use.

11.3.2 Immediately before testing, place the proper number of filter papers on the filter paper holder and place the metal test rim on top. Discard filter papers that will not lay flat.

11.3.3 Place the cigarette holder on the floor of the chamber.

11.4 Without delay, remove a cigarette from the conditioned space. Insert the unmarked end of the cigarette into the cigarette ignition system and hold it in a horizontal position.

Turn on the air draw. Hold the ignition flame or hot wire coil to the marked end of the cigarette for as long as is necessary to achieve uniform ignition without passing the 5 mm mark.

11.5 Holding the cigarette vertically, coal end up and under a 600 ml beaker, transport the cigarette to the test chamber.

11.5.1 Place the lit cigarette, in a horizontal position with the cigarette paper seam up, in the cigarette holder.

11.5.2 Simultaneously close the door and remove the chimney cover.

11.5.3 If the cigarette self-extinguishes while in the cigarette holder, terminate the determination and record the results as a self-extinguishment, noting that this occurred in the holder. This attempt shall count as a valid determination.

11.5.4 When the cigarette has burned to the 15 mm mark, open the chamber door, gently remove the cigarette from the holder, and move the holder to the front corner of the test chamber.

11.5.5 Gently lay the cigarette with the ash still attached onto the top of the filter papers so that the non-ignited end is placed between the appropriately sized cigarette anti-roll parallel metal pins. (Fig. 2). The cigarette paper seam shall be turned up. Do not drop the cigarette onto the filter papers and do not press the coal into the papers. If the ash falls off during any part of the transport or positioning process, terminate the determination and begin again; do not count the attempt.

11.5.6 Without delay, simultaneously remove the chimney cover and gently close the door.

11.6 Observe the burning cigarette. The smoke plume near the cigarette must remain undisturbed. If it does not, the chamber and exhaust system shall be re-checked as in 8.1.2. If the chamber and exhaust system are behaving properly, but the particular test cigarettes continue to produce disturbed smoke plumes, this observation shall be noted on the test sheet.

11.7 Record the following results:

(1) The cigarette burns at least to the beginning of the tipping paper (filter tip cigarettes) or to within 5 mm of the end of the tobacco column for non-filter tip cigarettes; or

(2) The burning ceases before reaching the tipping paper or at least 5 mm (filter tip cigarettes) from the end of the tobacco column for non-filter tip cigarettes.

(3) The observations stated in 11.5.3 and 11.6.

11.8 Ensure that neither the cigarette nor the filter papers are burning.

11.9 Open the test chamber door to allow air to circulate throughout its volume. After the chamber has cleared, prepare for the next determination.

11.10 Repeat the determination with each cigarette 40 times per test. Calculate the fraction of determinations in which the cigarettes burned their full length. This fraction is the test result.

12. Test Report

12.1 Results shall be reported for one test on each of the three substrates, except as described in Annex A1.

12.2 Report the following information for each test:

12.2.1 Laboratory name and name of person performing the determinations,

12.2.2 The temperature and relative humidity in the laboratory and (if used) the conditioning box,

12.2.3 Date and start time of each determination,

12.2.4 Cigarette identification,

12.2.5 Number of layers of filter paper per determination,

12.2.6 The fraction of determinations in which the cigarettes burned at least to the beginning of the tipping paper (filter tip cigarettes) or to within 5 mm of the end of the tobacco column for non-filter tip cigarettes, and

12.2.7 The observations noted in 11.5.3 and 11.6.

13. Precision and Bias

13.1 *Precision*—The precision of a test method nearly identical to this was established during an interlaboratory evaluation conducted according to Practice E 691. The only difference was that the cigarettes were supported in a vertical rather than a horizontal position during the pre-burn period (11.5). The evaluation involved 9 laboratories, 5 cigarette types, and 3 substrates, each with a different number of filter papers. See Ref (1).

13.2 The calculated repeatability, r , and reproducibility, R , limits have been determined for 40 determinations in a test and the fractions of cigarettes that produced full-length burns (P):

TABLE 1 Repeatability and Reproducibility Limits for a Test Involving 40 Replicate Determinations

P	r	R
0.05 or 0.95	0.10	0.11
0.10 or 0.90	0.13	0.16
0.20 or 0.80	0.18	0.21
0.30 or 0.70	0.20	0.24
0.40 or 0.60	0.22	0.26
0.50	0.22	0.26

r : band within which differences among repeat test results (same laboratory) will fall about 95 % of the time.

R : band within which differences among test results from different laboratories will fall about 95 % of the time.

If either interval contains negative values they are to be omitted.

13.3 *Bias*—This test method has no bias because the value for the ignition strength is determined solely in terms of this test method itself.

14. Keywords

14.1 bed flammability; cigarette; fire; furniture flammability; ignition; ignition propensity



ANNEX

(Mandatory Information)

A1. PROCEDURE FOR SELECTION OF SUBSTRATE ASSEMBLIES FOR TESTING

A1.1 The performance of a cigarette design on all three substrate assemblies shall be evaluated.

A1.2 In the absence of any information about the likely performance of the cigarette design, testing shall begin with 15 layers of filter paper.

A1.2.1 If full length burning of the cigarette is observed in over 90 % of the determinations with 15 layers, then it shall be presumed that testing on 3 or 10 layers would also produce virtually all full length burns and no testing on those substrate assemblies shall be performed. (See Appendix X1)

A1.2.2 If full length burning is observed in under 90 % of the determinations with 15 layers, then testing shall proceed using 10 layers. If full length burning is observed in over 90 % of the tests with 10 layers, then it shall be presumed that testing on 3 layers would also produce virtually all full length burns and no testing on those shall be performed. If full length burning is observed in under 90 % of the tests with 10 layers, then testing shall proceed using 3 layers.

A1.3 If there is information about the likely performance of a cigarette design that suggests a low tendency to ignite furnishings, the test operator shall have the option to begin testing with 10 or 3 layers of filter paper.

A1.3.1 Starting with 10 layers. If full length burning is observed in over 10 % of the tests with 10 layers, testing shall proceed using 15 layers. It shall be presumed that testing on the assemblies using 3 layers would also produce virtually all full length burns and no testing on that substrate assembly shall be performed. If full length burning is observed in under 10 % of the tests with 10 layers, then testing using 15 layers shall not be performed and testing shall proceed using 3 layers.

A1.3.2 Starting with 3 layers. If full length burning is observed in under 10 % of the tests with 3 layers, then testing using 10 and 15 layers shall not be performed. If full length burning is observed in over 10 % of the tests with 3 layers, testing shall proceed using 10 layers. If full length burning is observed in over 10 % of the tests with 10 layers, testing shall proceed using 15 layers.

A1.4 The test report shall address the performance of a cigarette on all 3 types of substrate assemblies. For those assemblies on which no testing was performed, as prescribed in A1.2 and A1.3, the outcome of the trial shall be described as “Substrate not required to be tested.”

APPENDIX

(Nonmandatory Information)

X1. IGNITION SUSCEPTIBILITY OF SUBSTRATE ASSEMBLIES

X1.1 During the development of this test method, it was established (1) that the filter paper substrates showed a systematic progression in measuring ignition strength, i.e., the capability of potentially initiating a fire while heat is being drawn from the cigarette. Additional data have recently been developed for two commercial cigarettes (2). In Table X1.1, the cigarettes are listed in decreasing order of ignition strength. The cigarettes with high percentages of full-length burns on the filter paper substrates generate enough heat to keep burning and thus are more likely to ignite soft furnishings than the cigarettes with lower such percentages. This means that, relative to a substrate assembly using 3 or 10 layers of filter paper, the 15 layer assembly requires a stronger heat source (cigarette) for full length burning.

X1.2 Table X1.1 also shows that the substrates used in this test method produce results consistent with those from a similar method that measures the propensity of cigarettes to ignite substrates made of standard cotton fabrics and a flexible polyurethane foam.

TABLE X1.1 Percent Ignitions or Full Length Burns on Test Method Substrates
[data from Ref (1) except as noted]

Substrate → Cigarette ↓	3 layers	Duck #10	10 layers	Duck #6	15 layers	Duck #4
B	100	100	100	92	94	73
503	100	100	100	100	100	53
Conventional (2)	100	100	100	100	100	19
501	100	100	100	100	100	11
D	100	100	94	73	88	46
E	100	100	100	96	94	0
531	99	98	94	95	88	0
A	100	100	94	92	38	4
F	100	100	100	79	19	0
529	57	30	6	8	2	0
Banded (2)	39	37	8	50	12	3
530	6	3	0	0	0	0

X1.3 Analysis of the data from the cigarette industry studies of 500 and 300 upholstery fabrics (3, 4, 5) has shown that most fabrics (80 % and 70 %, respectively) that discriminated among four test cigarettes ranked these cigarettes in the same order as did the cotton duck test fabrics (6, 7, 8). In both



studies, the remainder of the test fabrics produced some reversal of cigarette rankings.

X1.4 There is a good correlation between actual pieces of furniture and mock-ups made of the same materials (9).

X1.5 It is thus expected that significantly improved performance on this test method will lead to reduced ignitions of soft furnishings.

REFERENCES

- (1) Ohlemiller, T.J., Villa, K.M., Braun, E., Eberhardt, K.R., Harris, Jr., R.H., Lawson, J.R., and Gann, R.G., *Test Methods for Quantifying the Propensity of Cigarettes to Ignite Soft Furnishings*, NIST Special Publication 851, National Institute of Standards and Technology, Gaithersburg, MD, 1993.
- (2) Gann, R.G., Steckler, K.D., Ruitberg, S., Guthrie, W.F., and Levenson, M.S., "Relative Ignition Propensity of Test Market Cigarettes," NIST Technical Note 1436, National Institute of Standards and Technology, Gaithersburg, MD, 2001.
- (3) Spears, A.W., Rhyne, A.L., and Norman, V., "Factors for Consideration in a Test for Cigarette Ignition Propensity on Soft Furnishings," *J. Fire Sci.* 13, 59-83 (1995).
- (4) Dwyer, R.W., Fournier, L.G., Lewis, L.S., Furin, D., Ihrig, A.M., Smith, S., Hudson, W.Z., Honeycutt, R.H., and Bunch, J., "The Effects of Upholstery Fabric Properties on Fabric Ignitabilities by Smoldering Cigarettes," *J. Fire Sci.* 12, 268-283 (1994).
- (5) Lewis, L.S., Morton, M.J., Norman, V., Ihrig, A.M., and Rhyne, A.L., "The Effects of Upholstery Fabric Properties on Fabric Ignitabilities by Smoldering Cigarettes. II," *J. Fire Sci.* 13, 445-471 (1995).
- (6) Hirschler, M.M., "Comparison of the Propensity of Cigarettes to Ignite Upholstered Furniture Fabrics and Cotton Ducks (500-Fabric Study)," *Fire and Materials* 21, 123-141 (1997).
- (7) Eberhardt, K.R., Levenson, M.S., and Gann, R.G., "Fabrics for Testing the Ignition Propensity of Cigarettes," *Fire and Materials* 21, 259-264 (1997).
- (8) Gann, R.G., Levenson, M.S., and Eberhardt, K.R., "Fabrics for Testing the Ignition Propensity of Cigarettes; II-300-Fabric Study," in preparation, 2000.
- (9) Gann, R.G., Harris, Jr., R.H., Krasny, J.F., Levine, R.S., Mitler, H.E., and Ohlemiller, T.J., "The Effect of Cigarette Characteristics on the Ignition of Soft Furnishings," NBS Technical Note 1241, U.S. National Bureau of Standards, Gaithersburg, MD, 1987.

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org).