



Standard Test Method for Volume of Processed Peat Materials¹

This standard is issued under the fixed designation D 2978; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope*

1.1 This test method covers the measurement of the volume of loose and baled processed peat expressed as cubic feet.²

1.2 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 ASTM Standards:

D 653 Terminology Relating to Soil, Rock, and Contained Fluids³

D 3740 Practice for Minimum Requirements for Agencies Engaged in the Testing and/or Inspection of Soil and Rock as Used in Engineering Design and Construction³

E 11 Specification for Wire-Cloth Sieves for Testing Purposes³

3. Summary of Test Method

3.1 The test method consists of dividing the particles of peat by passing them through a 12.5-mm ($\frac{1}{2}$ -in.) sieve and allowing them to fall into a volume-measuring container.

4. Significance and Use

4.1 This test method may be used to quantify the volume of peats under consideration in commercial transactions.

4.2 The quality of the result produced by this standard is dependent on the competence of the personnel performing it, and the suitability of the equipment and facilities used. Agencies that meet the criteria of Practice D 3740 are generally considered capable of competent and objective testing/sampling/inspection/ and the like. Users of this standard are cautioned that compliance with Practice D 3740 does not in

itself assure reliable results. Reliable results depend on many factors; Practice D 3740 provides a means of evaluating some of those factors.

5. Apparatus

5.1 *U. S. Standard Sieve*, 12.5-mm ($\frac{1}{2}$ -in.), conforming to Specification E 11.

5.2 *Container* of steel or wood bound with metal, having one of the following sets of inside dimensions:

5.2.1 $\frac{1}{2}$ ft³ = 12 by 12 by 12-in. container with line scribed 6 in. from the bottom.

5.2.2 $\frac{3}{4}$ ft³ = 12 by 12 by 12-in. container with line scribed 9 in. from the bottom.

5.2.3 1-ft³ = 12 by 12 by 12-in. container.

5.2.4 2-ft³ = 16 by 16-in. base by 13 $\frac{1}{2}$ -in. height.

5.2.5 5-ft³ = 16 by 16-in. base by 33 $\frac{3}{4}$ -in. height.

6. Procedure

6.1 *Loose Peat*—Remove the material from the bag or container, pass it through the 12.5-mm ($\frac{1}{2}$ -in.) sieve and place directly into the measuring box. Pour the contents from approximately 2 ft into the measuring box. Determine the contents of the bag or container only once. The corners of the measuring box shall be well filled by shaking with a rotary motion, one rotation per second for 5 s without lifting the box from the floor or other surface. When filled, level it off by a straightedge to determine the volume.

6.2 *Baled Peat*—The volume of baled material shall be the product of the height by the area of the base. Measurements must be corrected for outside wrappers. Determine the amount of loose peat in a bale by passing through the 12.5-mm ($\frac{1}{2}$ -in.) sieve and measuring the amount of loose peat using the 12 by 12 by 12-in. box and the procedure described in 5.1.

7. Report

7.1 Report the volume of peat in cubic feet.

8. Precision and Bias

8.1 *Precision*—Due to the nature of the soil or rock materials tested by this method it is either not feasible or too costly at this time to produce multiple specimens which have uniform physical properties. Any variation observed in the data is just

¹ This test method is under the jurisdiction of ASTM Committee D18 on Soil and Rock and is the direct responsibility of Subcommittee D18.18 on Peats and Related Materials.

Current edition approved July 10, 2003. Published July 2003. Originally approved in 1971. Last previous edition approved in 1998 as D 2978–71(1998).

² Standards for determining the volume and bulk density of undisturbed, in situ peats are presently being prepared by Committee D – 18.

³ *Annual Book of ASTM Standards*, Vol 14.02.

*A Summary of Changes section appears at the end of this standard.

as likely to be due to specimen variation as to operator or laboratory testing variation. Subcommittee D18.18 welcomes proposals that would allow for development of a valid precision statement.

8.2 *Bias*—There is no accepted reference value for this test method, therefore, bias cannot be determined.

9. Keywords

9.1 peat; volume; volume measure

SUMMARY OF CHANGES

In accordance with Committee D18 policy, this section identifies the location of changes to this standard since the last edition (71–(1998)) that may impact the use of this standard.

- (1) Terminology D 653 and Practice D 3740 were added to the Referenced Documents Section. (2) 4.2 was added to the Significance and Use Section.
(3) Typographical errors in 5.2.4 and 5.2.5 were corrected.

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org).