



Designation: D 5730 – 024

## Standard Guide for Site Characterization for Environmental Purposes With Emphasis on Soil, Rock, the Vadose Zone and Ground Water<sup>1</sup>

This standard is issued under the fixed designation D 5730; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

### INTRODUCTION

This guide covers the selection of the various ASTM Standards that are available for the investigation of soil, rock, the vadose zone, ground water, and other media where the investigations have an environmental purpose.<sup>2</sup> It is intended to improve consistency of practice and to encourage rational planning of a site characterization program by providing a checklist to assist in the design of an environmental reconnaissance/investigation plan. The subsurface conditions at a particular site are usually the result of a combination of natural geologic, topographic, hydrologic, and climatic factors, and of historical modifications both natural and manmade. An adequate and internally consistent site characterization program will allow evaluation of the results of these influences. Site characterization for engineering, design, and construction purposes are addressed in a separate guide, Guide D 420.

The understanding of environmental processes occurring in soil and rock systems depends on adequate characterization of physical, chemical, and biological properties of soil and rock. Processes of interest may include, but are not limited to, surface and subsurface hydrology, contaminant mobilization, distribution, fate and transport; chemical and biological degradation of wastes; and geomorphological/ecological processes. Although this guide focusses primarily on characterization of soil and rock, it is understood that climatic and biotic factors may also be important in understanding environmental processes in soil and rock systems.

### 1. Scope

1.1 This guide covers a general approach to planning field investigations that is useful for any type of environmental investigation with a primary focus on the subsurface and major factors affecting the surface and subsurface environment. Generally, such investigations should identify and locate, both horizontally and vertically, significant soil and rock masses and ground water conditions present within a given site area and establish the characteristics of the subsurface materials by sampling or in situ testing, or both. The extent of characterization and specific methods used will be determined by the environmental objectives and data quality requirements of the investigation. This guide focuses on field methods for determining site characteristics and collection of samples for further physical and chemical characterization. This guide does not address special considerations required for characterization of karst and fractured rock terrane. In such hydrogeologic settings refer to Quinlan and Guide D 5717, (1).

1.2 This guide refers to ASTM standard methods by which soil, rock, vadose zone, and ground water conditions may be determined. Laboratory testing of soil, rock, and ground-water samples is specified by other ASTM standards which are not specifically discussed in this guide. Laboratory methods for measurement of physical properties relevant to environmental investigations are included in Appendix X1.

1.3 The values stated in SI units are to be regarded as the standard.

1.4 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility*

<sup>1</sup> This guide is under the jurisdiction of ASTM Committee D18 on Soil and Rock and is the direct responsibility of Subcommittee D18.01 on Surface and Subsurface Characterization.

Current edition approved July 10, 2002; Jan. 1, 2004. Published October 2002; March 2004. Originally published as D 5730–95; approved in 1995. Last previous edition approved in 2002 as D 5730 – 9802.

<sup>2</sup> This guide is under the jurisdiction of Subcommittee D18.01 (Surface and Subsurface Characterization) of the Committee on Soil and Rock, and as such has a primary focus on subsurface characterization, including soil, rock, and fluids contained therein (including liquid and gaseous components), and subsurface biota. Surface hydrology, meteorology, air quality, geomorphic processes, biota, and waste materials (when present at a site) are to a greater or lesser extent linked to environmental processes in soil and rock systems. Consequently other ASTM methods of particular relevance to environmental site investigations are identified in this guide, but are addressed in less detail.

of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.

1.5 This guide offers an organized collection of information or a series of options and does not recommend a specific course of action. This document cannot replace education or experience and should be used in conjunction with professional judgment. Not all aspects of this guide may be applicable in all circumstances. This ASTM standard is not intended to represent or replace the standard of care by which the adequacy of a given professional service must be judged, nor should this document be applied without consideration of a project's many unique aspects. The word "Standard" in the title of this document means only that the document has been approved through the ASTM consensus process.

## 2. Referenced Documents

2.1 The pertinent ASTM guides for selection of field investigation methods are listed at appropriate points in the sections that follow, and a comprehensive list of guides, standards, methods, practices, and terminology is contained in Appendix X1. Table X1.1 and Table X1.2 provide an index of field and laboratory standards listed in Appendix X1.

### 2.2 ASTM Standards:<sup>3</sup>

- C 998 Practice for Sampling Surface Soil for Radionuclides
- D 420 Guide to Site Characterization for Engineering, Design, and Construction Purposes
- D 422 Test Method for Particle-Size Analysis of Soils
- D 653 Terminology Relating to Soil, Rock, and Contained Fluids
- D 1140 Test Method for Amount of Material in Soils Finer than the No. 200 (75- $\mu$ m) Sieve
- D 1452 Practice for Soil Investigation and Sampling by Auger Borings
- D 1586 Test Method for Penetration Test and Split-Barrel Sampling of Soils
- D 1587 Practice for Thin-Walled Tube Geotechnical Sampling of Soils
- D 2113 Practice for Diamond Core Drilling for Site Investigation
- D 2434 Test Method for Permeability of Granular Soils (Constant Head)
- D 2487 Classification of Soils for Engineering Purposes (Unified Soil Classification System)
- D 2488 Practice for Description and Identification of Soils (Visual-Manual Procedure)
- D 2922 Test Methods for Density of Soil and Soil-Aggregate In Place by Nuclear Methods (Shallow Depth)
- D 3404 Guide for Measuring Matric Potential in the Vadose Zone Using Tensiometers
- D 3441 Test Method for Deep, Quasi-Static, Cone and Friction-Cone Penetration Tests of Soil
- D 3550 Practice for Ring-Lined Barrel Sampling of Soils
- D 3584 Practice for Indexing Papers and Reports on Soil and Rock for Engineering Purposes
- D 4043 Guide for Selection of Aquifer-Test Method in Determining of Hydraulic Properties by Well Techniques
- D 4044 Test Method (Field Procedure) for Instantaneous Change in Head (Slug Tests) for Determining Hydraulic Properties of Aquifers
- D 4050 Test Method (Field Procedure) for Withdrawal and Injection Well Tests for Determining Hydraulic Properties of Aquifer Systems
- D 4104 Test Method (Analytical Procedure) for Determining Transmissivity of Nonleaky Confined Aquifers by Overdamped Well Response to Instantaneous Change in Head (Slug Test)
- D 4105 Test Method (Analytical Procedure) for Determining Transmissivity and Storage Coefficient of Nonleaky Confined Aquifers by the Modified Theis Nonequilibrium Method
- D 4106 Test Method (Analytical Procedure) for Determining Transmissivity and Storage Coefficient of Nonleaky Confined Aquifers by the Theis Nonequilibrium Method
- D 4127 Terminology Used with Ion-Selective Electrodes
- D 4210 Practice for Interlaboratory Quality Control Procedures and a Discussion on Reporting Low Level Data
- D 4220 Practice for Preserving and Transporting Soil Samples
- D 4448 Guide for Sampling Groundwater Monitoring Wells
- D 4547 Practice for Sampling Waste and Soils for Volatile Organics
- D 4630 Test Method for Determining Transmissivity and Storativity of Low Permeability Rocks by In Situ Measurements Using the Constant Head Injection Test
- D 4631 Test Method for Determining Transmissivity and Storativity of Low Permeability Rocks by In Situ Measurements Using the Pressure Pulse Technique
- D 4687 Guide for General Planning of Waste Sampling
- D 4696 Guide for Pore-Liquid Sampling from the Vadose Zone
- D 4700 Guide for Soil Sampling from the Vadose Zone
- D 4750 Test Method for Determining Subsurface Liquid Levels in a Borehole or Monitoring Well (Observation Well)

<sup>3</sup> For referenced ASTM standards, visit the ASTM website, [www.astm.org](http://www.astm.org), or contact ASTM Customer Service at [service@astm.org](mailto:service@astm.org). For *Annual Book of ASTM Standards*, Vol 12.04, volume information, refer to the standard's Document Summary page on the ASTM website.

- D 5079 Practices for Preserving and Transporting Rock Core Samples
- D 5084 Test Method of Hydraulic Conductivity of Saturated Porous Materials Using a Flexible Wall Permeameter
- D 5092 Practice for Design and Installation of Ground Water Monitoring Wells in Aquifers
- D 5093 Test Method for Field Measurement of Infiltration Rate Using a Double-Ring Infiltrometer With a Sealed-Inner Ring
- D 5195 Test Method for Density of Soil and Rock In-Place at Depths Below the Surface by Nuclear Methods
- D 5254 Practice for Minimum Set of Data Elements to Identify a Ground-Water Site
- D 5269 Test Method for Determining Transmissivity of Nonleaky Confined Aquifers by the Theis Recovery Method
- D 5270 Test Method for Determining Transmissivity and Storage Coefficient of Bounded, Nonleaky, Confined Aquifers
- D 5314 Guide for Soil Gas Monitoring in the Vadose Zone
- D 5408 Guide for Set of Data Elements to Describe a Ground-Water Site; Part 1—Additional Identification Descriptors
- D 5409 Guide for Set of Data Elements to Describe a Ground-Water Site; Part 2—Physical Descriptors
- D 5410 Guide for Set of Data Elements to Describe a Ground-Water Site; Part 3—Usage Descriptors
- D 5447 Guide for Application of a Ground-Water Flow Model to a Site-Specific Problem
- D 5451 Practice for Sampling Using a Trier Sampler
- D 5717 Guide for the Design of Ground-Water Monitoring Systems In Karst and Fractured-Rock Aquifers
- E 177 Practice for Use of the Terms Precision and Bias in ASTM Test Methods
- E 380 Practice for Use of the International System of Units (SI) (The Modernized Metric System)
- E 1527 Practice for Environmental Site Assessments: Phase I Environmental Site Assessment Process
- G 57 Test Method for Field Measurement of Soil Resistivity Using the Wenner Four-Electrode Method

NOTE 1—*Non-ASTM*

*References: Appendix*

2.3 Non-ASTM References—Appendix X2 identifies major non-ASTM references that focus on field methods for environmental site characterization. Other guidance documents covering procedures for environmental investigations with specific objectives or in particular geographic settings may be available from federal, state, and other agencies or organizations. The appropriate agency or organization should be contacted to determine the availability and most current edition of such documents.

### 3. Terminology

#### 3.1 Definitions: <sup>4</sup>

- 3.1.1 *site, n*—a place or location designated for a specific use, function, or study.
- 3.1.2 *site, v*—to determine a place or location for a specific use, function, or study.
- 3.1.3 *characterization, n*—the delineation or representation of the essential features or qualities existing at a site.
- 3.1.4 *characterize, v*—the process of delineation or representation of the essential features or qualities existing at a site.
- 3.1.5 *conceptual site model, n*—for the purposes of this guide, a testable interpretation or working description of the relevant physical, chemical, and biological characteristics of a site.<sup>5</sup>
- 3.1.6 *environment, n*—the aggregate of conditions, influences, and circumstances that affect the existence or development of properties intrinsic to a site.
- 3.1.7 *environmental, adj*—having to do with the environment.
- 3.1.8 *environmental site characterization, n*—the delineation or representation of the essential features or qualities, including the conditions, influences, and circumstances, existing at a place or location designated for a specific use, function, or study.<sup>6</sup>
- 3.1.9 *environmental audit, n*—the investigation process to determine if the operations of an existing facility are in compliance with applicable environmental laws and regulations.
- 3.1.10 *environmental site assessment (ESA), n*—the process by which a person or entity seeks to determine if a particular parcel of real property (including improvements) is subject to recognized environmental conditions.<sup>7</sup>

3.2 In addition to Terminology D 653, Appendix X3 identifies major references from a range of disciplines that can be used as sources for definitions of terms that are related to environmental site characterization.

### 4. Significance and Use

4.1 This guide provides a general approach to environmental site characterization. Environmental site characterization provides

#### *Annual Book*

<sup>4</sup> The first seven definitions are ordered logically to illustrate construction of ASTM Standards, Vol 04.08, the definition for *environmental site characterization* rather than in alphabetical order.

*Annual Book*

<sup>5</sup> The meaning of ASTM Standards, Vol 11.01, conceptual site model may have more restricted or specific meanings depending on the objective or use of the model. For example, ground water flow modeling focuses on the physical characteristics as they relate to subsurface flow (see Guide D 5447), and a conceptual site model for the purpose of risk assessment will focus on contaminant sources, pathways, and receptors to exposure.

*Annual Book*

<sup>6</sup> Environmental audits and environmental site assessments as defined below are examples of ASTM Standards, Vol 11.04, environmental site characterization with specific objectives.

*Annual Book*

information for a wide variety of uses including:

4.1.1 Determination of ambient background or baseline conditions, including, but not limited to, geochemistry, hydrogeology, microbiology, mineralogy, and water quality.

4.1.2 Assessment of site suitability for a future use or a use which may be compromised by site characteristics, such as flooding, seismic activity, and landslides (mass wasting).

4.1.3 Protection of site quality from the detrimental effects of human activities and natural processes, or minimization of adverse environmental impacts. Specific examples of uses of environmental site characterization for these purposes include: (1) delineation of ground-water or wellhead protection areas, (2) assessing the suitability of sites for disposal of industrial and residential liquid and solid wastes, (3) assessing soil suitability for land treatment of wastes, and (4) evaluating soil suitability for agricultural practices in order to minimize soil erosion and contamination from agricultural chemicals.

4.1.4 Assessment of the type, distribution, and extent of surface and subsurface contamination to determine compliance; risk to human health and the environment; and responsibility for remediation. Such assessments include: (1) sites involved in real estate transactions, (2) controlled and uncontrolled hazardous waste sites, (3) controlled and uncontrolled municipal solid waste, wastewater, and other nonhazardous waste disposal sites.

4.1.5 Assessment of surface and subsurface environmental processes that affect the fate, mobilization, and rate of transport of natural and anthropogenic chemicals in the subsurface.

4.1.6 Assessment of the type, distribution, and extent of natural and anthropogenic radioactive elements in the subsurface.

4.1.7 Assessment of the degree of risk that adverse subsurface site conditions not related to 4.1.4 and 4.1.5 pose to human health and safety or the natural ecosystem.

4.1.8 Selection and design of remediation systems for cleanup of subsurface contamination and of other reclamation or rehabilitation practices on disturbed land.

4.2 This guide is meant to be a flexible description of investigation requirements; methods defined by other ASTM Standards (Appendix X1) or non-ASTM techniques (Appendix X2) may be appropriate in some circumstances. The methods and amount of effort required for environmental site characterization will vary with site conditions and objectives of the investigation. This standard does not set mandatory guidelines and does not constitute a list of necessary steps or procedures for all investigations. In karst and fractured rock hydrogeologic settings, this guide should be used in conjunction with Guide D 5717.

## 5. Steps in Planning and Conducting Environmental Site Characterization

5.1 The following minimum elements, not necessarily in sequential order, are required for most environmental site investigations to determine project and site strategy:

5.1.1 Definition of objectives, site boundaries,<sup>8</sup> and other information necessary for efficient project planning.<sup>9</sup>

5.1.2 Collection of available existing data and information about the site, pertinent to the objectives of the investigation.<sup>10</sup>

5.1.3 Development of one or more conceptual site models of the site from existing information. The objectives of the investigation will affect the type and complexity of site conceptualization.

5.1.4 Performance of a reconnaissance site investigation, that may include nondestructive geophysical methods, and relatively simple field sampling and characterization methods,<sup>11</sup> to refine the conceptual model of the site.

5.1.5 Development of a detailed site investigation and sampling plan, that identifies methods to be used to collect and analyze required additional data, protocols for sampling and field measurements, and procedures to ensure quality assurance and quality

<sup>7</sup> This definition is taken from Practice E 1527. Other definitions of ASTM Standards, Vol 04.09, environmental site assessment may apply in other contexts. For example, EPA's Site Assessment Branch, Hazardous Site Evaluation Division in the Office of Emergency and Remedial Response defines site assessment as the decision process for identifying the most seriously contaminated uncontrolled hazardous waste sites that will receive funding for long-term remediation. Practice E 1527 defines *recognized environmental conditions* as "the presence or likely presence of any hazardous substances or petroleum products on a property under conditions that indicate an existing release, a past release, or a material threat of a release of any hazardous substances or petroleum products into structures on the property or into the ground, ground water, or surface water of the property." In other environmental site investigations, nonhazardous substances (because of their physical condition, smell, or other aesthetic properties) or substances that have hazardous characteristics but do not meet a regulatory definition of hazardous may be the focus of concern.

*Annual Book*

<sup>8</sup> The boundaries of ASTM Standards, Vol 14.02, a site are defined using one or more of the following considerations: (1) land ownership, (2) current and past land use, (3) natural site characteristics (topography, soils, geology, hydrology, biota). Where site boundaries are initially defined by ownership, natural site characteristics should be evaluated to determine whether the scope of at least parts of the investigation should include areas that are offsite. For example, investigations of ground water contamination should include identification of any potential sources of contamination that are upgradient from a site.

*Annual Book*

<sup>9</sup> This should include, but not necessarily be limited to: (1) definition of the technical and scientific approach to be used, (2) organization of a data management system, including both paper and electronic records, (3) identification of types of personnel and technical expertise, appropriate ASTM and other methods and field equipment required to meet the defined objective, (4) defining how spatial data will be recorded (see Section 7.1.3), (5) identification of applicable primary and secondary regulatory programs, and any required coordination with government agencies and other organizations, (6) development of health and safety plans, where appropriate, (7) identification of scheduling and budgetary constraints, (8) definition of data quality requirements for each stage of the investigation, (9) identification of deliverables at intermediate stages of the investigation and upon completion, (10) selection of performance measures to determine whether the objective has been achieved, and (11) definition of project decision statements.

<sup>10</sup> The first seven definitions are ordered logically

<sup>10</sup> A site visit prior to illustrate construction extensive collection of existing data should be made unless the limited scope of a project does not allow multiple visits. The advantage of such a visit is that it may prevent preconceived ideas derived from inaccurate existing information from influencing initial conceptual site characterization rather than in alphabetical order. model development.

<sup>11</sup> The meaning of conceptual site model may have



control of site characterization data. Criteria defining the quality of data that are collected is a requirement for most environmental site investigations.<sup>12</sup>

5.1.6 Collection of field samples and measurements in accordance with the site investigation and sampling plan.<sup>13</sup>

5.1.7 Analysis of field and laboratory data to further refine the conceptual model of the site and preparation of a report that fulfills the objectives of the investigation.

5.2 Environmental site characterization is an iterative process of continually refining a conceptual site model of a site as new information becomes available. The objective of the investigation and availability of funds to carry out the investigation will affect the final number of iterations that are possible. For example, a Phase I Environmental Site Assessment (Guide E 1527) for a real estate property transaction may require only a single site visit to evaluate whether any activities may have resulted in contamination of the site. Complex sites, however, may require multiple site visits to collect data in order to develop a satisfactory conceptual model of the site, especially if a human health and environmental risk assessment is required. The number of site visits may be reduced by on-site analysis of results and real-time adjustments to the site investigation plan (see Section 7).

5.2.1 Planning for environmental site investigations should recognize that regional and local differences in climate, biota, soils, geology, and hydrology will influence the selection of appropriate methods and procedures.

5.2.2 Urban settings create special challenges for planning environmental site investigations. Difficulties include busy streets, access to public and private property, especially occupied buildings and fenced areas, and determining predisturbance background environmental conditions. Consult with local agencies and private property owners for relevant information. Select methods and schedule activities accordingly.

## 6. Collection of Existing Data and Site Reconnaissance

6.1 Collect and review available technical data from the literature and historical records, and conduct interviews before any field program is started. These include, but are not limited to, topographic maps, aerial photography, satellite imagery, geologic maps, statewide or county soil surveys, and mineral resource surveys covering the proposed project area. Reports of subsurface investigations of nearby or adjacent projects should be studied. If feasible, all existing data should be critically evaluated and independently confirmed.

6.1.1 The Natural Resource Conservation Service (formerly U.S. Soil Conservation Service) and the Agricultural Stabilization and Conservation Service (ASCS) are the primary sources of aerial photographs at the county level. The U.S. Geological Survey is the primary source for satellite imagery, and agencies other than SCS (USGS EROS Data Center).<sup>14</sup> Aerial photographs also may be available from the following federal agencies where lands under their jurisdiction are involved: Bureau of Land Management, Bureau of Reclamation, U.S. Army Corps of Engineers, U.S. Environmental Protection Agency Photo-Interpretation Center (EPIC), U.S. Forest Service, and U.S. Fish and Wildlife Service. State natural resource agencies and local/regional planning

<sup>11</sup> When contaminated sites are being investigated, field chemical analytical methods can be valuable for identifying areas where more restricted or specific meanings depending on the objective or use detailed investigations may be required, and for designing cost-effective detailed sampling and monitoring plans. Surface geophysical methods may be especially valuable for guiding placement of the model. For example, exploratory drillholes and placement of vadose zone and ground water flow modeling focuses on the physical characteristics as they relate to subsurface flow (see Guide D 5447), and a conceptual site model monitoring installations. Any such field methods should be documented for the purpose of risk assessment will focus on contaminant sources, pathways, quality assurance and receptors to exposure, quality control.

<sup>12</sup> Environmental audits

<sup>12</sup> The level of data accuracy and precision needed to meet the intended use for the data must be determined and this constitutes the "data quality requirements" referred to in this guide. The term data quality requirements is similar to the term data quality objectives (DQOs) used to describe the quality determination process in the U.S. EPA RCRA/Superfund program, but does not necessarily include statistically based confidence levels for assessing false negative or false positive designations. For chemical characterization, data quality requirements may vary depending on the phase of the investigation. For example, relatively inexpensive field instrumentation such as defined below are examples colorimetric test kits, or portable gas chromatographs can be used to analyze a relatively large number of environmental site characterization samples initially to identify areas with different levels of contamination. Data requirements at this level would specify that instrumentation used be capable only of detecting the presence of a contaminant at or above the regulatory level of concern. These results in turn would guide sampling of a moderate number of samples for more accurate field analytical methods or a mobile laboratory. Finally, a relatively small number of samples might be selected for analysis that would meet the rigorous data quality requirements of EPA's contract laboratory program (CLP). This phased approach has the potential for significant cost and time savings as compared to the use of CLP laboratories for the analysis of all samples.

<sup>13</sup> This definition is taken from Practice E 1527. Other definitions

<sup>13</sup> Prior to commencement of environmental site assessment may apply in other contexts. For example, EPA's Site Assessment Branch, Hazardous Site Evaluation Division in any intrusive exploration the Office of Emergency and Remedial Response defines site assessment as the decision process should be checked for identifying the most seriously contaminated uncontrolled hazardous waste sites that will receive funding for long-term remediation. Practice E 1527 defines *recognized environmental conditions* as "the presence underground utilities or likely presence other buried materials. Should evidence of any potentially hazardous substances or petroleum products on a property under conditions that indicate an existing release, a past release, otherwise contaminated materials or a material threat of a release of any hazardous substances or petroleum products into structures on conditions be encountered in the property or into the ground, ground water, or surface water course of the property." In other environmental site investigations, nonhazardous substances (because of their physical condition, smell, or other aesthetic properties) or substances that have hazardous characteristics but do not meet a regulatory definition of hazardous may investigation, work should be interrupted until the focus of concern circumstances have been evaluated and revised instructions issued before resumption.

<sup>14</sup> The boundaries of a site are defined using one or more of the following considerations: (1) land ownership, (2) current and past land use, (3) natural site characteristics (topography, soils, geology, hydrology, biota). Where site boundaries are initially defined by ownership, natural site characteristics should be evaluated to determine whether the scope of at least parts of the investigation should include areas that are offsite. For example, investigations of ground water contamination should include identification of any potential sources of contamination that are upgradient from a site.

<sup>14</sup> USGS EROS Data Center, Sioux Falls, SD 57198.

agencies also may be good sources of aerial photographs.<sup>15</sup> <sup>16</sup> Guide D 5518 provides additional information of how to obtain air photos.

6.1.2 The United States Geological Survey and the geological surveys of the various states are the principal sources of geologic maps, reports on mineral resources, ground water, and surface water.<sup>17</sup> Guidebooks prepared by professional associations, technical journals, and published conference and symposium proceedings may also be important sources of information.

6.1.3 United States Department of Agriculture Soil Conservation Service soil surveys, where available and of recent date, should enable the investigator to estimate the range in soil profile characteristics to depths of 1.5 or 2 m (5 or 6 ft) for each soil mapped.<sup>18</sup>

6.1.4 Preliminary information on sites where commercial and industrial activity has occurred should include site history, such as type of activity, location of existing surface and subsurface building, and chemicals, manufactured, used, or stored at the site.<sup>19</sup>

6.2 Study the soil and rock in the vicinity of the proposed project in areas where descriptive data are limited by insufficient or inadequate geologic or soil maps. Take advantage of all exposures of the rock and soil to obtain the best understanding of them. Obtain information on both vertical and horizontal properties of the materials and their distribution. Make appropriate notes and, where appropriate, illustrate by sketches. The notes should include data outlined in 9.3.<sup>20</sup>

6.3 Prepare and compile preliminary maps of the project area using aerial photography and topographic maps that show ground conditions. The scale of the map should be appropriate for the area being investigated. Aerial photographs and topographic maps at scales of 1:15 000 to 1:24 000 are available for most parts of the United States and are usually adequate as a basis for a preliminary map of sites covering tens to hundreds of acres. The distribution of the predominant soil and rock deposits likely to be observed during the investigation may be shown using data obtained from geologic maps, landform analysis, and limited ground reconnaissance. Experienced photointerpreters can deduce much subsurface data from a study of black-and-white, color, and color-infrared photographs because similar soil or rock conditions, tend to have similar patterns of appearance in regions of similar climate or vegetation.<sup>21</sup>

<sup>15</sup> This should include, but not necessarily

<sup>15</sup> The following references on air-photo interpretation may be limited to: (1) definition of the technical value: Avery (2),<sup>22</sup> Ciciarelli (3), Denny et al (4), Drury (5), Dury (6), Johnson and scientific approach to be used, (2) organization of a data management system, including both paper Gnaedinger (7), Lattman and electronic records, (3) identification of types of personnel Ray (8), Lueder (9), Miller and technical expertise, appropriate ASTM and other methods and field equipment required to meet the defined objective, (4) defining how spatial data will be recorded (see Section 7.1.3), (5) identification of applicable primary and secondary regulatory programs, and any required coordination with government agencies and other organizations, (6) development of health and safety plans, where appropriate, (7) identification of Miller (10), Ray (11) and budgetary constraints, (8) definition of data quality requirements for each stage of the investigation, (9) identification of deliverables at intermediate stages of the investigation and upon completion, (10) selection of performance measures to determine whether the objective has been achieved, and (11) definition of project decision statements, SCS (12), Strandberg (13), Wright (14).

<sup>16</sup> A site visit prior

<sup>16</sup> The boldface numbers in parentheses refer to extensive collection a list of existing data should be made unless references at the limited scope end of a project does not allow multiple visits. The advantage of such a visit is that it may prevent preconceived ideas derived from inaccurate existing information from influencing initial conceptual site model development. the text.

<sup>17</sup> Sun and Wheneks (15) provide a comprehensive bibliography of the U.S. Geological Survey's regional aquifer systems analysis program. Data from the RASA program are being investigated, field chemical analytical methods can be valuable for identifying areas where more detailed investigations may be required, synthesized and for designing cost-effective detailed sampling and monitoring plans. Surface geophysical methods may be especially valuable for guiding placement published in the Ground Water Atlas of exploratory drillholes and placement of vadose zone and ground water monitoring installations. Any such field methods should be documented for quality assurance and quality control: the United States (16).

<sup>18</sup> The level of data accuracy and precision needed

<sup>18</sup> Each soil type has a distinctive soil profile due to meet the intended use for the data must be determined age, parent material, relief, climatic condition, and this constitutes the "data quality requirements" referred to biological activity. Consideration of these factors can assist in this guide. The term data quality requirements is similar to evaluating the term data quality objectives (DQOs) used to describe the quality determination process potential for movement of contaminants in the U.S. EPA RCRA/Superfund program, but does not necessarily include statistically vadose zone and ground water based confidence levels for assessing false negative or false positive designations. For chemical characterization, data quality requirements may vary depending on the phase differing soil characteristics. Boulding (17) and Cameron (18) provide guidance on interpretation of the investigation. For example, relatively inexpensive field instrumentation such as colorimetric test kits, or portable gas chromatographs can be used soil properties in relation to analyze a relatively large number of samples initially to identify areas with different levels of contamination. Data requirements at this level would specify that instrumentation used be capable only of detecting the presence of a potential for contaminant at or above the regulatory level of concern. These results transport. Changes in turn would guide sampling of a moderate number of samples for more accurate field analytical methods soil properties in adjacent areas often indicate changes in parent material or a mobile laboratory. Finally, a relatively small number of samples might be selected for analysis that would meet the rigorous data quality requirements of EPA's contract laboratory program (CLP). This phased approach has the potential for significant cost and time savings as compared to the use of CLP laboratories for the analysis of all samples: relief.

<sup>19</sup> Prior to commencement of any intrusive exploration

<sup>19</sup> Practice E 1527 and Practice E 1528 provide guidance on the site should be checked for underground utilities or other buried materials. Should evidence types of potentially hazardous or otherwise contaminated materials or conditions be encountered in the course of the investigation, work information that should be interrupted until the circumstances have been evaluated collected and revised instructions issued before resumption; sources from which such information can be obtained.

<sup>20</sup> USGS EROS Data Center, Sioux Falls, SD 57198.

<sup>20</sup> The following major references may be useful for field geologic and hydrogeologic investigations: Bishop (19), Brassington (20), Bureau of Reclamation (21, 22), Compton (23, 24), Dutton, et al (25), Erdélyi and Gálfi (26), Fetter (27), Lahee (28), LeRoy, et al (29), Low (30), Rahn (31), Tearpocke and Bischke (32). Guides for field description of rocks include: Fry (33), Thorpe and Brown (34), and Tucker (35).

<sup>21</sup> The following references on air-photo interpretation

<sup>21</sup> This preliminary map may be of value: Avery (2),<sup>22</sup> Ciciarelli (3), Denny et al (4), Drury (5), Dury (6), Johnson expanded into a detailed site map by locating all test holes, pits, and Gnaedinger (7), Lattman sampling stations and Ray (8), Lueder (9), Miller by revising boundaries as determined from the detailed subsurface survey. Geographic information systems (GIS) should be considered for visualization, map preparation, data manipulation, and Miller (10), Ray (11), SCS (12), Strandberg (13), Wright (14): analysis.

6.4 Perform site reconnaissance. This provides an opportunity to check the accuracy of information compiled from existing sources, and to make site observations to assist in refining the conceptual model of the site. Site reconnaissance should be planned to identify the site characteristics needing further investigation.<sup>22</sup>

## 7. Detailed Site Investigation

7.1 Review objectives of the investigation and develop a detailed site investigation plan. The detailed site investigation plan should clearly identify the types of data that are required to meet the objectives of the investigation.<sup>23</sup> A complete environmental site investigation will usually encompass the following activities:<sup>24</sup>

7.1.1 Review available information, both regional and local, on the geologic history (including seismic activity and other potential geologic hazards), rock, soil, ground water, surface water, and other significant environmental and anthropogenic features (for example, buried utilities) occurring at the proposed location and in the immediate vicinity of the site.

7.1.2 Interpret aerial photography and other remote sensing data.

7.1.3 Select appropriate methods for locational data collection coincident with field observations and sampling.<sup>25</sup> Failure to accurately locate elevation and *x-y* coordinates of observation points and samples can severely compromise the accuracy of interpretations developed from the data. Where geographic information systems (GIS) are to be used for data management, analysis and visualization, locational accuracy should at a minimum satisfy the resolution of the system to be used.

7.1.4 Perform field reconnaissance for identification of surficial geologic and hydrologic conditions, mapping of stratigraphic or lithologic exposures and outcrops, mapping of vegetation and other significant ecological conditions, and examination of anthropogenic features at the site.

7.1.5 Perform on-site investigation of the surface and subsurface materials by geophysical surveys, borings, or test pits.

7.1.6 Obtain representative samples for chemical, biological, and physical analysis of soil, rock, and ground water. When required for the objectives of the investigation, these should be supplemented by samples suitable for the determination of in situ physical and chemical properties, such as hydraulic conductivity and flow-through sorption tests (see 11.2). Measurement of in situ properties requires collection of undisturbed samples (see definitions in Terminology D 653). Where present, wastes and sediments from surface water bodies should also be sampled.

7.1.7 Perform field identification of soil, sediments, and rock with particular references to physical and chemical properties, such as, but not limited to, color, odor, texture (grain-size distribution), mineralogy, zone of increased or reduced porosity and permeability, depth of occurrence, and the types and locations of structural discontinuities.

7.1.8 Identify and measure the potentiometric surface(s) of the aquifer or aquifers. Methods for determining ground-water levels are covered in Test Method D 4750. The variability of these positions in both short (minutes to days) and long (months to years) time frames should be considered.<sup>26</sup>

7.1.9 Assess vertical and horizontal variations in the pedologic, geologic, and hydrologic characteristics of the subsurface, including the vadose zone, aquifers, and confining units. When the flow direction and velocity of ground water are concerns, special emphasis should be placed on evaluating the degree of aquifer anisotropy, presence of highly permeable unconsolidated materials such as sands and gravels, extent and orientation of soil joint and rock fracture development, and extent of conduit development in karst limestone. Where unconsolidated materials consist of thick loess, alluvial, lacustrine materials, or glacial till,

<sup>22</sup> The boldface numbers

<sup>22</sup> Exploratory sampling of soil solids, soil gas, or ground water using temporary in parentheses refer to a list situ samplers may provide useful information for design of references at the sampling plan in the detailed site investigation plan. Surface geophysical methods may also be useful at this stage of the text investigation.

<sup>23</sup> Considerations for identifying data requirements include: (1) data required to comply with applicable federal, state, or local regulatory programs, (2) data required as inputs to computer models expected to be used, (3) data required for selection and Weeks (15) provide a comprehensive bibliography design of the U.S. Geological Survey's regional aquifer systems analysis program. Data from the RASA program are being synthesized and published in the Ground Water Atlas of the United States (16). Implementation measures (that is, protective measures at controlled waste disposal sites, remediation options at contaminated sites).

<sup>24</sup> Each soil type has a distinctive soil profile due to age, parent material, relief, climatic condition, and biological activity. Consideration

<sup>24</sup> Examples of these factors can assist in evaluating the potential for movement investigations that may not require all of contaminants in the vadose zone and ground water based on differing soil characteristics. Boulding (17) and Cameron (18) provide guidance on interpretation of soil properties activities in relation to potential this section include environmental site assessments for contaminant transport. Changes in soil properties in adjacent areas often indicate changes in parent material real estate property transactions that do not identify recognized environmental conditions using Practice E 1527 Phase I Assessment Process or Practice E 1528 Transaction Screen Process, and Environmental Audits to assess presence or degree of lead or asbestos contamination in a building.

<sup>25</sup> Practice E 1527

<sup>25</sup> The U.S. EPA (36) requires latitude/longitude determination for all agency-sponsored data collection and Practice E 1528 provide activities that define or describe environmental characteristics about a site. The U.S. EPA (37) provides guidance to selecting latitude/longitude determination methods. Global positioning systems (GPS) are used for locating field observation points when accuracy on the types order of information that should be collected and sources from tens of meters is sufficient, which is sufficient for many GIS applications (U.S. EPA, (38)). Other coordinate systems (such as *x-y* coordinates referenced to a known datum, State Plane, UTM) can also be used if more convenient in the field, and converted to latitude and longitude, if required.

<sup>26</sup> The following major references

<sup>26</sup> Other methods in addition to direct water level measurements may be useful for field geologic characterizing depth to water table. For example, description of the color, depth, and hydrogeologic investigations: Bishop (19), Brassington (20), Bureau patterns of R mottling of soil horizons may be indicative of long-term seasonal high ground water positions. Boulding (21, 22), Compton (23, 24), Dutro, et al (25), Erdelyi (39) and Gálfi Vepraskas (26), Fetter (40) (27), Lahee describe methods recently adopted by the Soil Survey Staff (28), LeRoy, et al (29), Low (30), Rahn (31), Tearpocke and Bischke (32). Guides (41) for field description of rocks include: Fry (33), Thorpe and Brown (34), and Tucker (35). Interpretation of morphologic features indicative of soil wetness. At contaminated sites, color variations can also be chemically induced or the result of staining.

the spacing and depth of vertical soil jointing should be evaluated as potential zones of preferential contaminant movement (42). Guide D 5717 identifies methods for characterization of karst and fractured rock aquifers.

7.1.10 Assess temporal changes in subsurface hydrologic conditions, including changes in ground-water levels using piezometers or monitoring wells, changes in soil moisture conditions using tensiometers (see Guide D 3404), neutron soil moisture probes (see Test Method D 5093) or other methods, and measurement or estimation of soil moisture flux. Changes in soil solute quality using suction lysimeters and other methods (see Guide D 4687).

7.1.11 Identify type and extent of contaminants, if present, and identify and assess the geochemical characteristics of subsurface solids and ground water that may affect the fate and transport of contaminants. Temporal changes in soil pore liquids and ground-water quality should be characterized by periodic sampling from monitoring wells installed in accordance with standard procedures (see Guide D 4696—pore liquids, and Practice D 5092—ground-water monitoring wells). Important geochemical characteristics include organic matter content, clay mineralogy, pH, Eh, specific conductance, and temperature.<sup>27</sup>

## 8. Use of Field Methods in Environmental Site Characterization

NOTE 21—All field procedures should be documented by identifying time, date, location, and personnel involved. Practice D 5254 identifies additional basic information required for documentation. Guide D 5408, Guide D 5409, and Guide D 5410 can serve as checklists to ensure that important additional information is not omitted. Paragraph 7.1.3 contains additional discussion of locational data considerations.

8.1 Equipment and procedures used in site characterization for environmental purposes can be classified in the following general categories:

8.1.1 Indirect observation of surface and subsurface conditions using remote sensing techniques and geophysical surveys (see Section 9),

8.1.2 Direct observation of subsurface conditions and field description using visual-manual procedures (see Section 10),

8.1.3 Sampling for further physical, chemical, and biological testing and analysis (see Section 11), and

8.1.4 In situ testing of soil, rock, vadose zone, and aquifer characteristics (see Section 12).

8.2 Many test methods and procedures are potentially applicable to environmental site investigations.<sup>28</sup> Factors to consider when selecting equipment and procedures for a site investigation include:

8.2.1 *Objectives and Data Quality Requirements of the Investigation*—For example, a Phase I Environmental Site Assessment may require only simple, hand-held equipment. On the other hand, site investigations for suitability for long-term storage of high-level radioactive wastes involve complex and sophisticated instrumentation and testing.

8.2.2 *Characteristics of the Site*—Soils and geology of the site and properties of known or suspected contaminants will influence the type of drilling methods used and selection of sampling equipment. Different aquifer test procedures and analytical methods are required based on aquifer characteristics such as degree of confinement, presence of nearby hydrologic boundaries, and how much of an aquifer is intersected by the central test well.

8.2.3 *Characteristics of the Equipment or Method*—When several alternatives are available to achieve a given objective a number of factors should be considered in selecting equipment and methods. Equipment available from commercial sources is generally preferable to homemade equipment because specifications can be readily documented and replacement parts can usually be obtained quickly and be used without affecting the comparability of results with the broken equipment. Equipment with the greatest durability and reliability is preferable. Standard ASTM test methods or standard operating procedures and protocols established by government agencies should be used whenever applicable. The timeliness of results is another important consideration when selecting equipment or methods. Methods that provide real-time data that fulfill data quality requirements are preferable to methods that require use of offsite laboratories. Special circumstances may require use of uncommon or nonstandard equipment, methods, or procedures. The use of such equipment and procedures should be justified in the detailed site investigation plan.

8.2.4 *Cost of the Equipment or Method*—All factors affecting cost should be considered before selecting equipment or methods. For example, the higher initial cost of using dedicated samplers for ground-water monitoring wells may be more cost-effective in the long run as a result of reduced sample collection costs.

8.3 Equipment and standard operating procedures (SOPs) should be identified in the detailed site investigation plan. Equipment design and specifications should be documented and standard operating procedures defined. Any departures from equipment and procedures defined in the site investigation plan should be documented and justified.

## 9. Field Methods: Remote Sensing and Geophysical Surveys

9.1 Remote sensing techniques may assist in mapping the geological formations and for evaluating variations in soil and rock

<sup>27</sup> This preliminary map

<sup>27</sup> Microorganisms in soil and ground water may be expanded into play a detailed site map by locating all test holes, pits, significant role in the transport and sampling stations fate of inorganic constituents (such as nitrate, sulfate, and by revising boundaries redox sensitive species, such as determined from the detailed subsurface survey. Geographic information systems (GIS) should be considered iron, manganese, arsenic, chromium, and selenium) and organic chemicals. Table X1.2 identifies ASTM methods for visualization, map preparation, data manipulation, characterization of microorganisms and analysis; biodegradation potential.

<sup>28</sup> Exploratory sampling of soil solids, soil gas, or ground water using temporary in situ samplers may provide useful

<sup>28</sup> A recent EPA report, (43) provides information for design of the sampling plan in the detailed site investigation plan. Surface geophysical methods may also be useful at this stage of the investigation. on more than 280 methods.



properties. Satellite and airborne mapping methods, such as multispectral imagery obtained from the LANDSAT platform and SLAR (side-looking airborne radar imagery), may be used to find and map the areal extent of subsurface materials and geologic structure. Interpretation of aircraft photographs and satellite imagery may locate and identify significant geologic features that may be indicative of faults and fractures. Interpretation of aerial photography taken at different times can identify changes in land use and identify areas that have been disturbed by human activity. Some ground control is generally required to verify information derived from remote sensing data.

9.2 Surface geophysical investigations can be a useful guide in the placement of boring, test hole, vadose zone, and monitoring well locations. Surface geophysical methods are essential at most contaminated sites to avoid hazardous drilling locations. Surface geophysical methods, together with push technologies (see 10.1.5), are especially valuable for ensuring that permanent monitoring well locations intercept contaminant plumes and that background reference wells reflect uncontaminated conditions. Interpretation of surface geophysical surveys should be verified by borings or test excavations, or confirmed by different types of geophysical measurements. Surface and borehole geophysical measurements provide a useful supplement to borehole and outcrop data and assist in interpolation between holes. Seismic, ground penetrating radar, electrical resistivity and electromagnetic methods can be particularly valuable when distinct differences in the physical or electrochemical properties of contiguous subsurface materials are indicated.<sup>29</sup>

9.3 Major applications of surface geophysical methods for environmental site characterization include:<sup>30</sup>

9.3.1 Ground penetrating radar may be useful in defining soil and rock layers, water table, and man-made structures in the depth range from 1/3 to 10 m (1 to 30 ft).

9.3.2 Electromagnetic induction, electrical resistivity, and induced polarization (or complex resistivity) techniques can be used to map variations in water content, clay horizons, stratification, depth to aquifer/bedrock, and conductive contaminant plumes.<sup>31</sup>

9.3.3 The shallow seismic refraction method can be used to map soil horizons, stratigraphic depth profiles, and water tables. It can be especially useful in determining depth of unconsolidated material where bedrock is at a depth of 30 m or less.

9.3.4 The seismic reflection method may be useful in delineating geological units at depths below 15 to 30 m (50 to 100 ft). It is not constrained by layers of low seismic velocity and is especially useful in areas of rapid stratigraphic change.

9.3.5 Magnetic surveys may be useful for detecting the presence of subsurface ferrous materials within 1 to 3 m of the ground surface.

9.4 Borehole geophysical methods can be used to obtain information on lithology, stratigraphy and formation properties, aquifer properties, ground-water flow and direction, borehole fluid characteristics, contaminant characterization, and borehole/casing characterization. Major categories of borehole logging methods include: (1) electrical and electromagnetic, (2) nuclear, (3) acoustic and sonic, and (4) miscellaneous methods, such as caliper, temperature, and borehole flowmeters. Considerations in the selection of borehole logging methods include, but are not limited to, (1) diameter of the borehole, (2) presence or absence and type of casing, (3) presence or absence and type of borehole fluid; and (4) characteristics of the subsurface formations.<sup>32</sup>

9.5 All geophysical methods require site conditions that provide contrasts in the subsurface property being measured by the method, and, depending on the method, may be subject to interferences at a site, such as metal fences, powerlines, FM radio transmission, or ground vibrations. The depth of penetration and interference effects are highly site specific. Depth penetration and resolution vary with local conditions. Data collection and interpretation for geophysical surveys require skilled personnel familiar with the principles and limitations of the method being used.

<sup>29</sup> Considerations

<sup>29</sup> Major references that address use of surface geophysical methods for identifying data requirements environmental site characterization include: (1) data required to comply with applicable federal, state, or local regulatory programs, (2) data required as inputs to computer models expected to be used, (3) data required for selection Benson et al (44), Boulding (45), Haeni (46), Ward (47,48), and design of implementation measures (that is, protective measures at controlled waste disposal sites, remediation options at contaminated sites); Zohdy et al (49).

<sup>30</sup> Examples of investigations that may not require all of

<sup>30</sup> Depth ranges indicated here and for other geophysical methods are typical ranges for instruments available at the activities in time this guide was written and intended to give a general idea of the capabilities of different methods. Actual depth penetration at a particular site is dependent on site conditions, instrumentation used for real estate property transactions that do not identify recognized environmental conditions using Practice E 1527 Phase I Assessment Process or Practice E 1528 Transaction Screen Process; field measurements, and Environmental Audits methods used to assess presence or degree analyze the signal data. Depth of lead or asbestos contamination in a building; penetration can also increase with improved instrumentation and signal analysis methods.

<sup>31</sup> The U.S. EPA (36) requires latitude/longitude determination

<sup>31</sup> Test Method G 57 is intended for all agency-sponsored data collection and activities that define or describe environmental characteristics about a site. The U.S. EPA (37) provides guidance to selecting latitude/longitude determination methods. Global positioning systems (GPS) are used for locating field observation points when accuracy on use in the order control of tens of meters is sufficient, which is sufficient for many GIS applications (U.S. EPA, (38)). Other coordinate systems (such as x-y coordinates referenced to a known datum, State Plane, UTM) can also be used if more convenient corrosion in buried structures. Use of the electrical resistivity method in environmental investigations involves field; procedures and converted to latitude and longitude, if required; data interpretation that differ substantially from the procedures outlined in this guide.

<sup>32</sup> Major references that address use of borehole geophysical methods in addition to direct water level measurements may be useful for characterizing depth to water table. For example, description of the color, depth, and patterns of mottling of soil horizons may be indicative of long-term seasonal high ground water positions; environmental site characterization include: Boulding (39) and Vepraskas (45), Keys (450) describe methods recently adopted by the Soil Survey Staff, Keys and MacCary (41) for description (51), and interpretation of morphologic features indicative of soil wetness. At contaminated sites, color variations can also be chemically induced or the result of staining; Respod (52).

## 10. Field Methods: Direct Observation of Subsurface Conditions<sup>33</sup>

10.1 The type of equipment required for an intrusive subsurface investigation depends upon various factors including, but not limited to, the type of subsurface material, the depth of exploration, the nature of the terrain, the intended use of the data, and prevention of cross-contamination of aquifers.<sup>34</sup> Identify the location of buried utility lines, pipes, and any other subsurface anthropogenic features using maps or geophysical methods (9.2) prior to drilling.

10.1.1 Hand augers, hole diggers, shovels, and push tube samplers are suitable for exploration of surficial soils to depths of 1 to 5 m (3 to 15 ft).

10.1.2 Earth excavation equipment, such as backhoes, draglines, and drilled pier augers (screw or bucket) can allow in situ examination of soil deposits and sampling of materials containing cobbles and boulders.

10.1.3 In soil and unconsolidated material hollow-stem augers are commonly used for collection of geoenvironmental samples and installation of monitoring wells. Hollow-stem augers commonly reach depths of up to 45 m (about 150 ft) and large auger rigs can reach depths of up to 100 m (about 330 ft) under favorable conditions.<sup>35</sup> Greater depths are possible in unconsolidated material if casing advancement methods are used. Sections 11.2.2 and 11.2.3 identify ASTM methods for collection of unconsolidated material samples.

10.1.4 For bedrock and for deep unconsolidated material, well drilling equipment such as rotary and cable tool systems is usually required. Normally samples are collected in the form of sand sized cuttings captured from the return flow, which generally are not adequate for environmental site characterization but other methods of determining stratigraphy, such as borehole geophysical logging methods are available (see Section 9.4). Diamond rotary coring (see Practice D 2113) is the preferred method of obtaining samples for physical property testing and geologic characterization of rocks. Diamond drills are effective to depths of up to 600 m or more, even in extremely strong igneous and metamorphic rocks. As depths in unconsolidated material increase, sampling devices attached to drill rods become increasingly cumbersome due to the time required to lower and retrieve the sampler. Wireline soil sampling, in which the sampler is lowered, driven, and retrieved on a wireline through the drill pipe, allows retrieval of samples at frequent intervals and provides for prompt visual identification of soil texture and subsurface features (Section 10.3). More commonly wireline systems are used for rock coring. Various factors affect the depth at which wireline sample becomes more cost effective than drill-rod attached sampling devices, including the length of the core barrel, the height of the mast on the rig being used, the number of hoist lines available for handling sampling tools and the hardness of the rock. The breakeven point for the two methods typically ranges between 15 m (50 ft) and 45 m (150 ft). As hole depths increase, cost savings using wireline sampling methods increase. Reduced physical labor for drill crews using wireline methods help to reduce worker fatigue, improving efficiency and safety.

10.1.5 Cone penetration technologies (CPT) and other drive/push technologies (DPT) are being used increasingly for environmental field investigations to depths of 100 to 300 ft (30.5 to 100 m) depending on geology and push capacity of the system. The CPT methods can be used for lithologic characterization, measurement of hydraulic conductivity of soils, sampling of solids, soil gases and ground water, and in situ chemical detection (see 11.3). Accurate lithologic characterization using CPT requires correlation of measured resistance with one or more direct subsurface observations for each site. Advantages of CPT and DPT at contaminated sites include: no cuttings, increased worker safety, and improved siting of permanent monitoring wells.

10.2 A stratigraphic profile in complex geology is often developed by correlation of lithologic character established by a significant number of borings, by continuous geophysical profiling techniques, and surface mapping. This phase of the investigation may be implemented by plotting logs of soil and rock exposures in walls of excavations or cut areas and by plotting logs of the test borings. Then one may interpolate between, and extrapolate a reasonable distance beyond, these logs. The spacing of these investigations depends on the geologic complexity of the project area and on the importance of soil and rock continuity to the project design. Exploration should be deep enough to identify all strata that might be significant in assessing environmental conditions at the site.

10.3 Field description of test pits and excavations and boring logs are an essential element of environmental site investigations. Test pits allow observation of pedogenic soil features that are larger than the diameter of borings and allow the most accurate description of subsurface features in the soil zone that may influence movement of contaminants in the vadose zone. Paragraph 6.4.3 in Guide D 5409 identifies key features that should be included in field description of samples and unconsolidated material. Additional description of samples of soil and rock may be added after samples have been transported from the field. Subsurface observation records should be kept in a systematic manner for each project. Such records should include, when applicable:

<sup>33</sup> Microorganisms in soil and ground water may play a significant role in

<sup>33</sup> Major references on borehole drilling methods for direct observation of the transport subsurface and for installation of inorganic constituents (such as nitrate, sulfate, ground-water monitoring wells include: Aller et al (53), Eggington et al (54), Clark (55), Driscoll (56), Harlan et al (57), Lehr et al (58), Roscoe Moss Company (59), Ruda and redox-sensitive species, such as iron, manganese, arsenic, chromium, Bosscher (60), and selenium) Shuter and organic chemicals. Table X1.2 identifies ASTM methods for characterization of microorganisms and biodegradation potential. Teasdale (61).

<sup>34</sup> A recent EPA report, (43) provides information on more than 280 methods.

<sup>34</sup> Plans for a program of intrusive subsurface investigation should check whether there are requirements for licensing of installers and permits for installation and proper closure of bore holes and wells at the completion of the investigation.

<sup>35</sup> Major references that address use of surface geophysical methods

<sup>35</sup> Fluid rotary drilling can extend to greater depths in unconsolidated materials, but is generally not recommended for environmental site characterization include: Benson et al (44), Boulding (45), Haeni (46), Ward (47,48), and Zohdy et al (49); investigations because drilling fluids can alter subsurface chemistry.

10.3.1 *Description of Each Site or Area Investigated* —Each test hole, boring, test pit, or geophysical test site should be referenced to an established coordinate system, datum, or permanent monument (see 7.1.3):

10.3.2 Subsurface investigation logs of each test hole, boring, test pit, or cut surface exposure should show the field description and location of each material, and any water encountered, either by symbol or verbal description. Guide D 5434 provides guidance for field logging of subsurface explorations for soil and rock. Reference to a Munsell Soil or Rock Color Chart designation is a substantial aid to the description of soil and rock materials.<sup>35</sup> Various soil classification systems are available for description of soil and other unconsolidated materials in the field. The selection of the classification system depends on the purpose and data needs of the investigation and the end users of the information. The ASTM (Classification D 2487 and Practice D 2488) version of the Unified Soil Classification System (USCS) is used by most governmental agencies and geotechnical engineering firms for the description of soil for engineering purposes both in the United States and in many other countries. The USDA textural system (41,63,64),<sup>36</sup> developed by the Soil Conservation Service for agricultural aspects of near surface soils, is especially useful for environmental investigations because it can provide hydrologic information for soils. Using the modified Wentworth grain size scale (AGI Date Sheet 29.1; (65), which is widely used by geologists, in combination with the USDA textural system will provide useful additional data on soil particle-size distribution because the Wentworth system has more subdivisions in the silt and gravel particle-size classes. Field classification of samples and exposures should be confirmed with laboratory tests (Classification D 2487, Test Method D 422, and Test Method D 1140) if the information is critical to the investigation program.<sup>37</sup> Laboratory test results should clearly identify the textural system being used, because different systems may have slightly different grain-size cutoffs. Use of sieves that include all divisions of the USCS, USDA and modified Wentworth scales will provide the greatest amount of useful information for the coarse fraction, and measurement of all relevant cutoffs for the fine fraction in the three systems will ensure that environmental and engineering interpretations using all three systems will be possible.

10.3.3 Location and description of seepage and water-bearing zones, zones of low permeability, and records of potentiometric elevations found in each test hole, boring, piezometer, or test pit,

10.3.4 Grain size distribution of unconsolidated materials in the interval to be screened when installation of a ground-water monitoring well is planned,

10.3.5 The results and locations of in situ test results (see Section 12),

10.3.6 Percentage of core recovery and rock quality designation (RQD) in core drilling. Deere and Deere (69) provides guidance on RQD, and

10.3.7 Graphical presentation of field and laboratory data, such as graphic borehole logs, cross sections, potentiometric maps, and contaminant concentration isopleths, facilitates interpretation and understanding of subsurface conditions.

## 11. Field Methods: Sampling

11.1 The location, type of samples collected, and sampling equipment should be in accordance with the sampling plan developed in the detailed site investigation plan. A statistically valid method should be used to select sampling locations if required by the data-collection objectives. Sample equipment and procedures should be appropriate for the medium being sampled (soil, rock, soil gas, soil-pore liquids, ground water, solid/liquid waste) and be designed to minimize the introduction of error into physical and chemical test results. Barth et al (70) and Mason (71) provide guidance on development of soil sampling plans. Gilbert (72) provides a good general reference on statistical aspects of sampling and monitoring for environmental purposes. Geostatistical methods are especially useful for developing a sampling strategy and analysis of results when parameters are spatially correlated.<sup>38</sup>

<sup>36</sup> Depth ranges indicated here

<sup>36</sup> Color photographs of rock cores, soil samples, and for other geophysical methods are typical ranges for instruments available at the time this guide was written and intended to give a general idea exposed strata may be of the capabilities of different methods. Actual depth penetration at considerable value. Each photograph should include an identifying number or symbol, a particular site is dependent on site conditions, instrumentation used for field measurements, date, and methods used to analyze the signal data. Depth a reference scale. Soil Conservation Service (62) provides standardized procedures for photographic documentation of penetration can also increase with improved instrumentation and signal analysis methods; rock cores.

<sup>37</sup> Test Method G 57

<sup>37</sup> Both USCS and USDA classification systems can be used to estimate some hydrologic properties of soils impacting the fate and transport of contaminants. The plasticity index of the USCS is intended for use directly related to colloidal content in the soil and resulting sorptive capacity. The USCS system is more applicable to very coarse-grained alluvial deposits containing appreciable gravels. Saturated hydraulic conductivity can often be estimated within two or three orders of magnitude based on both USCS and USDA classification, and estimates can sometimes be narrowed within one order of magnitude for clean sands or in buried structures. Use fine-grained soils where descriptions of morphology (structure, macroporosity, fissures, laminations, etc.) of undisturbed cores or exposures are possible. Numerous additional hydrologic parameters have been correlated to the electrical resistivity method in environmental investigations involves USDA classification system for near-surface soils and could be useful for fine-grained unconsolidated material at greater depths. These parameters include: capillary fringe (39), specific yield (66), field procedures moisture capacity (67), and data interpretation that differ substantially from available water capacity (68). Estimation of hydrologic parameters may be useful during the initial site characterization phases, but should not replace necessary definitive field and laboratory measurements which may be required for final site evaluations.

<sup>38</sup> Major references that address use

<sup>38</sup> Most soil physical and chemical properties are spatially correlated, and the location of borehole geophysical methods for environmental site characterization include: Boulding contaminants in soil and ground water are also usually spatially correlated. Clark (45), Keys (73) is a good introductory text on geostatistics and Isaaks and Srivastava (50)(74) provide advanced treatment of this subject. The ASCE Task Committee on Geostatistical Techniques in Geohydrology, Keys (75) contains a good review of basic concepts and MacCary applications. Several public domain geostatistical software packages are available from U.S. EPA (51)(76,77,78). Geostatistical methods may not be appropriate where soil contamination exists as localized hotspots. Zirschky and Respoold Gilbert (52)(79) provide guidance on statistical sampling designs for detecting hot spots at hazardous-waste sites.

11.2 *Solids Sampling*<sup>39</sup>—The type of solids sample will depend on the purpose of the sample.

11.2.1 Disturbed or grab samples using augers (see Practice D 1452) and trier samplers (see Practice D 5451) are used primarily for chemical analyses, but are also suitable for texture analysis.

11.2.2 Split barrel samplers (see Test Method D 1586) provide samples that allow description of lithology and other subsurface features, and laboratory measurements of soil parameters unaffected by sample disturbance (for example, water content, gradation or particle size, organic content, and nonsensitive and chemical constituents) but are not suitable for laboratory measurement of soil properties.

11.2.3 Thin-wall tube (see Practice D 1587) and ring-lined barrel samplers (see Practice D 3550) collect undisturbed samples of unconsolidated material that are suitable for laboratory testing of hydrologic properties, and diamond core drilling (see Practice D 2113) provides similar samples for consolidated rock. Undisturbed core samples can provide important information on structure, sedimentary features, secondary porosity, and color patterns that cannot be obtained from disturbed samples.

11.2.4 Guide D 4700 provides guidance on soil sampling in the vadose zone. Special considerations in sampling of soil for radionuclides and volatile organics are addressed in Practice C 998 and Practice D 4547, respectively. Practice D 4220 covers procedures for preservation and transportation of soil samples and Practices D 5079 does the same for rock core samples.

11.3 *Other Sampling*:

11.3.1 Characterization of the vadose zone may require sampling of soil gases and soil pore liquids. Guide D 5314 provides guidance on soil gas sampling for detection of volatile contaminants. Guide D 4696 addresses various methods for sampling soil pore liquids in the vadose zone.

11.3.2 *Ground Water Sampling*—Guide D 4448 covers ground-water sampling methods from permanent monitoring wells. Springs can also be used for sampling and monitoring ground water quality as covered by Guide D 5717. The CPT and other push technologies (see 10.1.5) allow collection of one-time or multiple samples for preliminary delineation of ground-water quality and installation of driven monitoring wells. Manually driven well points are generally restricted to shallow depths (<10 m) that can be sampled using suction-lift ground-water sampling devices. The CPT rigs can install small-diameter monitoring wells to depths exceeding 30 m which can be sampled with small diameter ( $\frac{5}{8}$ -in. (15.8-mm) outside diameter typical) bailers and pumps.<sup>40</sup>

11.3.3 Submerged sediments can be sampled with coring devices (see Guide D 4823) or with dredges, such as the Eckman, Peterson, and Ponar dredges. Guide D 4411 provides guidance on sampling of fluvial sediments in motion.<sup>41</sup>

11.3.4 Waste materials often require special sampling equipment and procedures. Devices for sampling single-phase and multiphase liquids include: coliwasa, dipper, drum thief, glass tube, and peristaltic pump. Mixed liquid/solid phases are usually sampled using a coliwasa, dipper, or long-handled sludge sampler. Consolidated waste solids are usually sampled using an auger, chipper, hammer and chisel, or a rotating coring device. Unconsolidated waste solids can be sampled using a trier (see Practice D 5451), grain sampler, or conventional soil sampling equipment (see 10.1.1). Lagoons may require sludge sampling tools.

11.3.5 *Biological Sampling*—Investigation of soil and ground-water geochemistry may involve sampling for aerobic and anaerobic microorganisms and other subsurface biota.<sup>42</sup> Special care is required when sampling for anaerobic microorganisms to ensure that the sample is not exposed to the air (90). Table X1.1 identifies ASTM methods for microbiological analysis of water samples. Ecosystem characterization may require sampling of plants and animals at a site. Table X1.2 provides an index to ASTM methods for field sampling of phytoplankton, zooplankton, benthic macroinvertebrates, and fishes.

11.3.6 *Atmospheric Sampling*—Measurement of atmospheric parameters such as precipitation, humidity, temperature, and wind may be required for ground-water budget studies. Humidity, temperature, and wind should be routinely monitored during field investigations to document site conditions. Such monitoring is especially important for worker health and safety when it is very cold, or impermeable protective clothing is required when ambient temperatures are high. Air quality sampling may be required during environmental site investigations for: (I) identifying unsafe working conditions and monitoring worker exposure to

<sup>39</sup> Major references on borehole drilling methods for direct observation of

<sup>39</sup> The investigation may require the subsurface collection of sufficiently large soil, rock, waste, and for installation ground water samples of ground-water monitoring wells include: Aller et al (53), Eggington et al (54), Clark (55), Driscoll (56), Harlan et al (57), Lehr et al (58), Roseoe Moss Company (59), Ruda such quality as to allow adequate testing to determine the soil or rock classification or mineralogic type, or both, and Boscher (60), and Shuter and Teasdale (61); chemical constituents of potential interest or concern.

<sup>40</sup> Plans for a program of intrusive subsurface investigation should check whether there

<sup>40</sup> Driven wells are requirements for licensing of installers relatively easy and inexpensive to install in most unconsolidated materials where ground water is shallow. Deeper sampling and well installation methods using CPT and other push methods may be an alternative to conventional monitoring well installations. The decision to use these techniques for permanent monitoring well installations should be based on information indicating that sample representativeness and installation integrity (that is, avoidance of cross-contamination of aquifers) are comparable to conventional monitoring well installations with screens, filter pack, and grouting. To ensure comparability of ground-water quality results, all monitoring well installations for a particular phase of investigations at the completion a site should be of the same type (that is, either all conventional or all drive/push installations).

<sup>41</sup> Fluid rotary drilling can extend to greater depths in unconsolidated materials, but is generally not recommended

<sup>41</sup> Good references for environmental investigations because drilling fluids can alter subsurface chemistry: additional information on sampling of submerged bottom sediments include: Barth and Starks (80) and Palmer (80). Guy and Norman (80) provide additional information on sampling of fluvial sediment.

<sup>42</sup> Color photographs of rock cores, soil samples, and exposed strata may be of considerable value. Each photograph should include an identifying number or symbol, a date, and a reference scale. Soil Conservation Service

<sup>42</sup> Chappelle (62)(83) provides standardized procedures a useful reference for photographic documentation microbial sampling of ground water. Some major references on soil microbiology and ecology, geomicrobiology and microbial biogeochemistry include: Alexander (84), Ehrlich (85), Killham (86), Kuznetsov et al (87), Paul and Clark (88), and Zajic (89).



hazardous chemicals, (2) evaluating air exposure pathways for environmental risk assessment, and (3) assessing ambient concentrations of regulated air pollutants. Table X1.1 provides an index to ASTM methods for monitoring ambient atmospheric parameters, and field sampling.

#### 11.4 *Other Sampling Considerations* :

11.4.1 All sampling procedures for chemical analysis require cleaning and decontamination of sampling equipment to prevent cross contamination of samples. Practice D 5088 addresses decontamination of field equipment at nonradioactive waste sites.

11.4.2 Special care is required when locating permanent vadose-zone and ground-water monitoring installations for time-series sampling. Failure to site such permanent installations in locations downgradient from potential contaminant sources or to intersect zones of preferential movement of contaminants can result in wasteful expenditure of funds for chemical analysis, or even failure to detect contaminant movement. The location of permanent monitoring installations should be thoroughly justified based on the conceptual model of the site. Surface geophysical methods, multiple piezometers for measurement of ground-water flow direction, and analysis of samples taken using in situ soil gas and ground-water samplers can provide information required for rational siting of permanent monitoring installations.

## 12. Field Methods: In Situ Testing and Analytical Methods

12.1 In situ testing (for example, tests that measure the in-place characteristics of subsurface materials) is useful for: measuring the hydrologic properties of a larger volume of the subsurface than is possible in laboratory tests on soil and rock cores; for rapid or closely spaced measurements, or both, of earth properties without the necessity of sampling; measuring subsurface chemical parameters to minimize chemical alterations by bringing samples to the surface for analysis; and measurement of engineering properties of soil or rock in an undisturbed condition including consideration of lateral and vertical loads associated with the surrounding mass.

12.2 Field analytical methods use conventional or adapted laboratory methods for analysis of samples that have been removed from their in-place position. Mechanical sieve analysis of soil samples is commonly used to assist in field classification of soil texture. Field analytical methods such as portable gas chromatographs, X-ray fluorescence, and enzyme immunoassay kits are being increasingly used for environmental site characterization. Field instrumentation and procedures for chemical characterization are changing rapidly and the appropriate regulatory authority should be consulted for accepted methods and procedures when investigations are performed for regulatory purposes.

#### 12.3 *Hydrologic Properties*:

12.3.1 Aquifer tests are used to collect data for calculating hydraulic conductivity, transmissivity, and aquifer storage properties. Tests may include, but are not limited to packer tests for low-permeability rocks (see Test Method D 4630 and Test Method D 4631), slug tests (see Test Method D 4044, Test Method D 4104, and Test Method D 4050), and aquifer tests with control wells (see Test Methods D 4105, D 4106, D 5269, and D 5270). Guide D 4043 provides guidance on selection of aquifer field test methods and analysis procedures based on aquifer characteristics. In karst and fractured rock hydrogeologic settings refer to Guide D 5717 for special approaches required for characterization of hydrologic properties. In such settings conventional aquifer test methods may not be appropriate. Similar problems may also occur in heterogeneous porous media.

12.3.2 Test Method D 5084 provides a method for measuring point hydraulic conductivity of low-permeability materials using undisturbed core materials ( $<1 \times 10^{-3}$  cm/s); Test Method D 2434 provides a method for measuring hydraulic conductivity of granular materials ( $>1 \times 10^{-3}$  cm/s).

12.3.3 Field measurements of vadose zone hydrologic parameters include water content, matric potential, and infiltration rate and hydraulic conductivity. Guide D 5126 provides guidance on selection of methods for measuring saturated and unsaturated hydraulic conductivity in the vadose zone. Table X1.1 identifies ASTM methods for measuring infiltration rate, matric potential, and moisture content.

12.4 *Physical Properties*—In situ measurements of vertical and horizontal variations in soil density using a standard penetration test (see Test Method D 1586), cone penetrometry (see Test Method D 3441) or a gamma-gamma nuclear probe (see Test Methods D 2922 and D 5195), can provide useful information for stratigraphic interpretation within and between boreholes. Other physical properties that affect water movement can be measured with a variety of borehole geophysical logging tools, including induction, gamma, resistivity, neutron porosity, sonic, and caliper tools. In addition, downhole video and acoustic televiewer instruments may provide information on such properties as fractures, vugs, and bedding plane orientation.

12.5 Use of ion-selective electrodes to measure chemical parameters in place in the subsurface is an established technology (see Terminology D 4127). Fiber optic chemical sensors are a relatively new technology with good possibilities for making in-situ chemical measurements for environmental site characterization.<sup>43</sup>

12.6 *Engineering Properties*—Engineering properties are primarily of interest for environmental site characterization if design of pollution control measures, such as impoundment liners, or remediation activities are required. Numerous ASTM field methods are available for in situ measurement of soil and rock engineering properties. These are identified in Table X1.1.

<sup>43</sup> Both USCS and USDA classification systems can be used to estimate some hydrologic properties of soils impacting the fate and transport of contaminants. The plasticity index of the USCS

### 13. Analysis and Interpretation of Results

13.1 Evaluate data to determine whether data quality requirements were met (see 5.1.5). Data review and analysis should include all reliable field and laboratory data from previous investigations in the same area. Review field and laboratory QA/QC procedures and measurements to assess data validity, and determine whether data quality requirements (see 5.1.5) have been satisfied. Interpretation of field- and laboratory-measured environmental parameters should include an evaluation of possible limitations of the methods used. Basic assumptions for analytical techniques and methods should be evaluated to determine if site conditions meet assumptions. For example, the analysis of aquifer test results should identify the approximate volume of the aquifer measured by the test, and the underlying analytical or other equations used to compute aquifer parameters. If site conditions do not satisfy the assumptions of the solution method, the effect on accuracy and interpretation of results should be stated.

13.2 Develop graphical presentation of data to facilitate interpretation of spatial relationships and, when time series data are available, presence or absence of trends. Map views, cross sections, and data contouring methods are especially useful for presentation of spatial data.

13.2.1 A map of the area under investigations provides essential information about the land surface, including natural and anthropogenic features, and the locations of sampling, monitoring wells, and other observation points.

13.2.2 Cross sections should identify actual surface and subsurface observations according to elevation and location. Cross sections showing correlation of stratigraphic or lithologic units and interpretation of other conditions between direct subsurface observations should be indicated as interpretations (that is, dashed lines) and based on standard geologic procedures. When feasible, geophysical survey data, such as continuous geophysical profiles should be used to support correlations and other interpretations. The interpretive cross sections should be accompanied by notes describing anomalies or otherwise significant variations in the site conditions that might affect any interpretations.<sup>44</sup>

13.2.3 Contouring methods, such as structure contours of geologic strata or buried bedrock, potentiometric surfaces, and maps showing lines of equal concentration or value should be constructed using appropriate interpolation techniques.<sup>45</sup> The method of interpolation should be documented. When feasible, the same data should be contoured using different interpolation methods and compared.

13.3 Statistical methods used to analyze data should be appropriate for the type of data. Most conventional statistical methods assume a normal distribution around the mean. Typically, environmental data measurements do not exhibit normality because of spatial correlation, the presence of outliers, or other effects.<sup>46</sup> Geostatistical methods are best for analyzing spatially related data (see 11.1 and related references). When contaminants are present in low concentrations (at or below the detection limit), the report should indicate whether chemical data have been censored and if so, assess the possible effect of censoring (that is, values reported as not detected or below the detection limit). Practice D 4210 addresses data censoring and its possible significance.

13.4 Information on topography, geomorphology, soils, climate, vegetation, surface hydrology, and anthropogenic influences should be integrated with subsurface geologic, hydrogeologic, and geochemical/hydrochemical interpretations as required by the objectives of the investigation. At contaminated sites, identification of pathways for movement of contaminants and estimation of exposure concentrations, and determining the rate of movement may be an important result of the site characterization study.<sup>47</sup>

<sup>43</sup> The term in situ here is directly related confined to colloidal content methods that measure chemical parameters in place without bringing a sample to the soil and resulting sorptive capacity. surface. The USCS system is more applicable to very coarse-grained alluvial deposits containing appreciable gravels. Saturated hydraulic conductivity can often term may also be estimated within two or three orders applied to ground water sampling devices that do not require installation of magnitude-based on both USCS and USDA classification, and estimates a monitoring well. In situ chemical sensors can sometimes be narrowed within one order of magnitude for clean sands or placed in fine-grained soils where descriptions of morphology (structure, macroporosity, fissures, laminations, etc.) of undisturbed cores monitoring wells or exposures are possible. Numerous additional hydrologic parameters have been correlated to the USDA classification system for near-surface soils and could be useful for fine-grained unconsolidated material at greater depths. These parameters include: capillary fringe (39), specific yield (66), field moisture capacity (67), and available water capacity (68). Estimation of hydrologic parameters may be useful during the initial site characterization phases, but should not replace necessary definitive field and laboratory measurements which may be required for final site evaluations: by using CPT or other push technologies.

<sup>44</sup> Most soil physical and chemical properties are spatially correlated, and the location of contaminants in soil and ground water are also usually spatially correlated. Clark (73)

<sup>44</sup> Additional exploration should be considered if there is a good introductory text on geostatistics and Isaaks and Srivastava (74) provide advanced treatment not sufficient information to develop interpretative cross sections, with realistic descriptions of this subject. The ASCE Task Committee on Geostatistical Techniques anticipated variations in Geohydrology (75) contains a good review of basic concepts and applications. Several public domain geostatistical software packages are available from U.S. EPA (76,77,78). Geostatistical methods may not be appropriate where soil contamination exists as localized hotspots. Zirschky and Gilbert (79) provide guidance on statistical sampling designs for detecting hot spots at hazardous waste sites: subsurface conditions, to meet project requirements.

<sup>45</sup> The investigation may require the collection of sufficiently large soil, rock, waste;

<sup>45</sup> Most field geology texts identified in Footnote 16 discuss interpolation techniques. Davis (91), Hamilton and ground water samples of such quality as to allow adequate testing to determine the soil or rock classification or mineralogic type, or both; Jones (94) and chemical constituents of potential interest or concern; Jones et al. (95) are other good references.

<sup>46</sup> Driven wells are relatively easy and inexpensive to install in most unconsolidated materials where ground water is shallow. Deeper sampling and well installation methods using CPT and other push methods may be an alternative to conventional monitoring well installations. The decision to use these techniques

<sup>46</sup> The EPA's GRITS/STAT software for permanent analyzing ground-water monitoring well installations should be based on information indicating that sample representativeness and installation integrity (that is, avoidance data allows testing of cross-contamination the appropriateness of aquifers) are comparable to conventional monitoring well installations with screens, filter pack, and grouting. To ensure comparability statistical analysis of ground-water quality results, all monitoring well installations for time series data, and includes a particular phase number of investigations at a site should be of the same type (that is, either all alternative tests if conventional or all drive/push installations); tests are not appropriate (92).

<sup>47</sup> Good references for additional information on sampling

## 14. Report

14.1 Report the following information:

14.1.1 Pertinent ASTM Standards, (Terminology D 653, Practice D 3584, Practice E 177, and Practice E 380).

14.2 The report of an environmental site characterization study should include:

14.2.1 The location of the area investigated in terms pertinent to the project. This may include sketch maps or aerial photos on which the test pits, bore holes, and sample areas are located, as well as geomorphological data relevant to the determination of the various soil and rock types. Such data include elevation contours, stream beds, sinkholes, cliffs, and all other relevant physiographic features. All significant anthropogenic features should be located on the base map or a separate map. Where feasible, include in the report a geologic map or an agronomic soils map, or both, of the area investigated,

14.2.2 Additional basic information as required by the objectives of the investigation,

14.2.3 A description of the investigation procedures including all borings and test hole logs, graphic presentation of all lithologic and well construction logs, tabulation of all test results, and graphical interpretations of geophysical measurements, and

14.2.4 A summary of the findings obtained under Sections 6, 9, 10, 11, 12, and 13, using subhead titles for the respective sections, and appropriate recommendations and disclaimers for the use of the report.

## 15. Keywords

15.1 conceptual site model; environmental site characterization; exploration; feasibility studies; field investigations; geological investigations; geophysical investigations; ground water; hydrologic investigations; maps; preliminary investigations; reconnaissance surveys; sampling; site characterization; site investigations; soil surveys; subsurface investigations

---

<sup>47</sup> Estimation of submerged bottom sediments include: Barth exposure concentrations may require use of batch sorption/leaching tests and Starks vadose zone contaminant mobility studies. Roy et al (80) and Palmer (80). Guy and Norman (80) (93) provide additional information provides U.S. EPA guidance on sampling batch test for estimating soil sorption of fluvial sediment. chemicals, and Table X1.2 (Laboratory Fate Testing) provides an index of ASTM sorption and leachability test methods.

## APPENDIXES

### (Nonmandatory Information)

#### X1. ASTM STANDARDS PERTINENT TO ENVIRONMENTAL SITE CHARACTERIZATION

X1.1 This appendix lists more than ~~590~~ 600 standard test methods, practices, and guides for use in the field and laboratory that could be pertinent for site characterization for environmental purposes.

X1.1.1 Table X1.1 identifies about ~~500~~ 510 potential field and laboratory methods for sampling and characterization of soil, ground water, and waste materials. Other ASTM methods for measuring site parameters that may need to be monitored during environmental site investigations, such as humidity and wind, are also included in Table X1.1. All standards listed in this table follow in alphanumeric sequence.

X1.1.2 Table X1.1 identifies about 510 potential field and laboratory methods for sampling and characterization of soil, ground water, and waste materials. Other ASTM methods for measuring site parameters that may need to be monitored during environmental site investigations, such as humidity and wind, are also included in Table X1.1. All standards listed in this table follow in alphanumeric sequence.

X1.1.3 Table X1.1 identifies about 510 potential field and laboratory methods for sampling and characterization of soil, ground water, and waste materials. Other ASTM methods for measuring site parameters that may need to be monitored during environmental site investigations, such as humidity and wind, are also included in Table X1.1. All standards listed in this table follow in alphanumeric sequence.

X1.1.4 Table X1.2 identifies about 100 standard test methods, practices and guides that address field sampling for ecological characterization and laboratory methods, such as toxicity testing, relevant to human ecological risk assessment.

**TABLE X1.2 Index to ASTM Field and Laboratory Methods for Ecological Characterization**

Topic	ASTM Standard
<i>General:</i>	
Terminology	Biological effects and environmental fate ( E 943)
<i>Field Sampling:</i>	
Vegetation	<b>Terrestrial and wetland vegetation<sup>A</sup></b> ( E 1923)
Phytoplankton	Classification for sampling (Classification D 4149); <i>Sampling Methods</i> —Depth-integrating samplers (Practice D 4135); Clarke-Bumpus sampler (Practice D 4134); conical tow nets (Practice D 4132); pumps (Practice D 4133); water sampling bottles (Practice D 4136); <i>Sample Preservation</i> —Practice D 4137; <i>Other Methods</i> —Measurement of chlorophyll content of algae in surface water (Practice D 3731); Sedgwick-Rafter method (Test Method D 4148)
Zooplankton	<i>Sampling Methods</i> —Clarke-Bumpus sampler (Practice E 1199); conical tow nets (Practice E 1201); pumps (Practice E 1198); <i>Sample Preservation</i> —Practice E 1200.
Benthic Macroinvertebrates	<b>Selection of sampling devices (Guide D 4387)</b> ; <i>Grab Samplers</i> —Ekman (Practice D 4343); Holme scoop (Practice D 4348); Okean 50 (Practice D 4346); Orange Peel (Practice D 4407); Ponar (Practice D 4342); Peterson (Practice D 4401); Shipek scoop (Practice D 4347); Smith-McIntyre (Practice D 4344); Van Veen (Practice D 4345); <i>Other Samplers</i> : Basket (Practice E 1468); drift net (Practice D 4558); multiple plate (Practice E 1469); <b>selecting stream net devices (Guide D 4556)</b> ; Surber and related samplers (Practice D 4557)
Fishes	Classification for sampling (Practice D 4211); sampling with rotenone (Practice D 4131)
<i>Toxicity Testing:</i>	
Toxicity Test Data Analysis	Statistical analysis (E 1847)
Microbial Detoxification	Chemically contaminated water and soils (D 5660)
Water	Selection of resident species (E 1850); Behavioral testing in aquatic toxicology (E 1604); measurement of behavior during fish toxicity test; (E 1711); estimation of median lethal concentration for fish using octanol-water partition coefficient (Practice E 1242); ventilatory behavioral toxicology testing of freshwater fish (E 1768); <i>Acute Toxicity Tests</i> —Bivalve mollusks (Guide E 724); fishes, macroinvertebrates and amphibians (Practice E 729, Guide E 1192-aqueous effluents); mosquito <i>Wyoemyia smithii</i> (Guide E 1365); polychaeteous annelids (Guide E 1562); rotifer <i>Brachionus</i> (Guide E 1440), west coast Mysids (Guide E 1463); echinoid embryos (E 1563); <i>Life Cycle/Renewal Toxicity Tests</i> — <i>Daphnia magna</i> (Guide E 1193); <i>Ceriodaphnia dubia</i> (Guide E 1295); polychaeteous annelids (Guide E 1562); saltwater Mysids (Guide E 1191); <i>Static Toxicity Tests</i> —Bivalve mollusks (Guide E 724); <i>Lemna gibba</i> G3 (Guide E 1415); microalgae (Guide E 1218); mosquito <i>Wyoemyia smithii</i> (Guide E 1365); west coast Mysids (Guide E 1463); macrophyte <i>Myriophyllum Sibiricum</i> Komarov(1913); <i>Other Toxicity Tests</i> —Algal growth potential (Practice D 3978); chronic—polychaeteous annelids (Guide E 1562); early life-stage fishes (Guide E 1241); toxicity-induced enzymatic inhibition in <i>Daphnia magna</i> (Provisional Test Method PS 235); bioluminescent dinoflagellates (E 1924); renewal phytotoxicity with freshwater emergent macrophytes (E 1841)
Soil	Soil toxicity test with Lumbricid earthworm <i>Eisenia</i> (E 1676); terrestrial plant toxicity test (E 1963)
Soil	Soil toxicity test with Lumbricid earthworm <i>Eisenia</i> (E 1676); terrestrial plant toxicity test (E 1963); soil toxicity test with nematode <i>Caenorhabditis elegans</i> (E 2172)
Sediment	Selection of resident species (E 1850); collection, storage, characterization and manipulation (Guide E 1391); designing biological tests (E 1525); bioaccumulation by benthic invertebrates (E 1688); <i>Toxicity Tests</i> : marine and estuarine Amphipods (Guide E 1367); freshwater invertebrates (Guide E 1383, E 1706); polychaeteous annelids (E 1611)
Other Tests	Sexual reproduction test with seaweeds (E 1498); <i>Avian Species</i> : Substrate dietary toxicity tests (E 857); reproductive studies (E 1062); use of lighting in laboratory testing (E 1733)
<i>Fate-Related Procedures:</i>	
Hazard Assessment	Assessing the hazard of a material to aquatic organisms (Guide D 1023); radioactive pathway methodology for release of site following decommissioning (Guide E 1278); selecting and using ecological endpoints for contaminated site (E 1848); data information options for ecological risk assessment at contaminated sites (E 2020); fish and wildlife incident monitoring and reporting (E 1849)
Modeling	Evaluating mathematical models for the environmental fate of chemicals (Practice E 978)
Microcosm Tests	Freshwater aquatic microcosm (Practice E 1366); terrestrial soil-core microcosm (Guide E 1197); chemical fate in site specific sediment/water microcosms (E 1624)
Laboratory-Fate Testing	Substitute wastewater specification (D 5905) <i>Bioconcentration</i> —Fishes and bivalve mollusks (Practice E 1022); <i>Biodegradation</i> —anaerobic (Test Method E 1196); shake-flask die-away method (Test Method E 1279); organic chemicals in semi-continuous activated sludge (E 1625); sealed vessel CO <sub>2</sub> production test ( E 1720); in porous pots ( E 1798);in compost (D 5929); <i>Fate-Related Chemical Properties</i> —Aqueous solubility (Test Method E 1148); hydrolysis rate constants (Practice E 895); octanol/water partition coefficient (Test Method E 1147); vapor pressure (Test Method E 1194); <i>Sorption/Leachability</i> —Contaminant sorption (Test Method D 4646); 24-h batch sorption of volatile organics (Test Method D 5285); distribution ratios (Test Method D 4319); organic carbon sorption constant (Test Method E 1195); waste leaching column test (Test Method D 4874) <i>Environmental Analytical Laboratories</i> : training programs (D 5829); see also waste extraction procedures in Table X1.1.
Laboratory-Fate Testing	Substitute wastewater specification (D 5905) <i>Bioconcentration</i> —Fishes and bivalve mollusks (Practice E 1022); <i>Biodegradation</i> —anaerobic (Test Method E 1196); shake-flask die-away method (Test Method E 1279); organic chemicals in semi-continuous activated sludge (E 1625); sealed vessel CO <sub>2</sub> production test; E 1798 in porous pots, E 2170—anaerobic/methanogenic conditions); compost (D 5929); <i>Fate-Related Chemical Properties</i> —Aqueous solubility (Test Method E 1148); hydrolysis rate constants (Practice E 895); octanol/water partition coefficient (Test Method E 1147); vapor pressure (Test Method E 1194); <i>Sorption/Leachability</i> —Contaminant sorption (Test Method D 4646); 24-h batch sorption of volatile organics (Test Method D 5285); distribution ratios (Test Method D 4319); organic carbon sorption constant (Test Method E 1195); waste leaching column test (Test Method D 4874) <i>Environmental Analytical Laboratories</i> : training programs (D 5829); see also waste extraction procedures in Table X1.1.

<sup>A</sup>**Boldface**—Method selection guide.

**TABLE X1.1 Index to ASTM Field and Laboratory Methods Possibly Pertinent to Environmental Site Characterization<sup>A,B</sup>**

Topic	ASTM Standard
<i>General:</i>	
Reports	Indexing papers and reports (D 3584), use of modernized metric system (E 380)



**TABLE X1.1 Continued**

Topic	ASTM Standard
Terminology	Soil, rock and contained fluids (D 653); atmospheric sampling (D 1356); basic statistics (D 4375); waste and waste management (D 5681 ); water (D 1129)
Objective-Oriented Guides	<p>Acquisition of file aerial photography and imagery for establishing historic site use and surficial conditions (D 5518); <u>Contaminated Sites</u>: Expedited site characterization (PS 85, D 6235) developing conceptual site models for contaminated sites (E 1689); accelerated site characterization for petroleum releases (E 1912, PS 3); <u>Remediation/Corrective Action</u>; Risk-based corrective action (E 2081, PS 104) corrective action at petroleum release sites (E 1599, E 1739/ES38—risk based); short term measures or early actions for site remediation (D 5745); natural attenuation (E 1943); brownfields (E 1948); clean up levels (D 6597); activity and use limitations (E 2091); <u>Real Estate/Property Assessments</u>: Environmental condition of property area types for defense base closure (D 5746); environmental baseline surveys (D 6008); baseline property condition assessments (E 2018); real estate property transactions (E 1527, E 1528, E 1903—Phase II); <u>Site Characterization</u>: environmental (D 5730—this guide, D 5995 cold regions; D 6067—ECPT); engineering and construction purposes (D 420); <u>Septic System Characterization</u> (D 5879); Subsurface (D 5921): sizing (D 5925); <u>Environmental Management</u>: development and implementation of a pollution prevention program (E 1609); building lifecycle assessment (E 1991); lifecycle costing for pollution prevention (PS 14); UST Operational Conformance (E 1990); assessment of buried steel tanks (ES 40); environmental regulatory compliance audits (E 2107, PS 11); evaluation of an organizations environmental management system (PS 12); development and implementation of a source reduction program (PS 26)</p>
Objective-Oriented Guides	<p>Acquisition of file aerial photography and imagery for establishing historic site use and surficial conditions (D 5518); <u>Contaminated Sites</u>: Expedited site characterization (PS 85, D 6235) developing conceptual site models for contaminated sites (E 1689); accelerated site characterization for petroleum releases (E 1912, PS 3); <u>Remediation/Corrective Action</u>; Risk-based corrective action (E 2081, E 2247—protection of ecological resources PS 104) corrective action at petroleum release sites (E 1599, E 1739/ES38—risk based); short term measures or early actions for site remediation (D 5745); natural attenuation (E 1943); brownfields (E 1948); clean up levels (D 6597); activity and use limitations (E 2091); <u>Real Estate/Property Assessments</u>: Environmental condition of property area types for defense base closure (D 5746); environmental baseline surveys (D 6008); baseline property condition assessments (E 2018); real estate property transactions (Phase I: E 1527, E 1528, E 2247—forestland/rural; Phase II: E 1903); <u>Site Characterization</u>: environmental (D 5730 - this guide, D 5995 cold regions; D 6067 - ECPT); engineering and construction purposes (D 420); <u>Septic System Characterization</u> (D 5879); Subsurface (D 5921): sizing (D 5925); <u>Environmental Management</u>: development and implementation of a pollution prevention program (E 1609); building lifecycle assessment (E 1991); lifecycle costing for pollution prevention (PS 14); UST Operational Conformance (E 1990); assessment of buried steel tanks (ES 40); environmental liability disclosure (E 2173); environmental regulatory compliance audits (E 2107, PS 11); estimating environmental monetary costs and liabilities (E 2137); evaluation of an organizations environmental management system (PS 12); development and implementation of a source reduction program (PS 26)</p>
Certification/Accreditation:	Environmental professionals (E 1929); personnel engaged in testing soil and rock (D 5255)
Sampling:	
General	Collection and preservation of information and physical items by a technical investigator (E 1188); probability sampling of materials (E 105); <u>Sampling Design</u> : Waste management sampling design optimization (D 6311); ranked set sampling (D 6582)
Air	<p>Choosing locations and sampling methods for atmospheric deposition at nonurban locations (D 5111, D5012); guide for laboratories (D 3614); diffusive samplers (D 6246 ); flow rate calibration of personal sampling pumps (D 5337); planning ambient air sampling (D 1357); ambient air analyzer procedures (D 3249); sampling stationary source emissions (D 5835); <u>Airborne Microorganisms</u>: Sampling at municipal solid waste facilities (E 884); <u>Aerosols</u>: D 6552, D 6061, D 6062M; <u>Sampling Organic Vapors/Toxic Vapors</u>: <b>Method selection (D 6345)</b>; Charcoal tube absorption (D 3686), canister (D 5466); detector tubes (D 4490); length-of-stain dosimeter (D 4599); sorbent selection (D 6196); PAHs (D 6209); FTIR (D 6348) <u>Particulate Matter Determination</u>: Filter absorbance method (D 1704, D1704M); high-volume sampler (D 4096, D 4536); stationary source (D 6331); dustfall (D 1739—settleable particulates); <u>Worker Protection</u>: Air monitoring at waste management facilities for worker protection (D 4844); air sampling strategies for worker and workplace protection (E 1370); collection of airborne particulate lead during abatement and construction activities (E 1553); activated charcoal samplers (D 4597), liquid sorbent diffusional samplers (D 4598); pesticides and PCBs (D 4861) Sampling indoor air quality of building (D 5791)</p>
Biological Materials	Aseptic sampling (E 1287); see also Table X1.2
Soil/Rock/Sediments	<p>Minimum set of data elements for soil sampling (D 5911); locational data elements (D 6168); format for exchange of computerized rock and soil data (D 6453); <b>selection of soil and rock sampling devices used with drill rigs (D 6169); direct push soil sampling (D 6282); Drilling Methods: Selection of drilling methods (D 6286)</b>; cable tool (D 5875); casing advancement (D 5872); diamond core drilling (D 2113); direct air-rotary (D 5782); direct fluid rotary (D 5783); direct rotary wireline (D 5876); dual-wall reverse circulation (D 5781); hollow-stem auger (D 5784, D 6151); <u>Field Sampling and Handling Methods</u>: Auger sampling (D 1452); radionuclides (C 998); ring-lined barrel (D 3550); split barrel (D 1586); thin-wall tube (D 1587); piston sampler (D 6519); volatile organics (D 4547, D 6418—EnCore sampler); hollow stem auger (D 6151); coring/logging cement and lime stabilized soils (D 6236); <u>Sediments</u>: fluvial sediment in motion (D 4411, DD 4411, D 6236—transit ratios/sampling depth); submerged (D 4823); monitoring sediments in watershed (D 6145); handling, storing and preparing soft undisturbed marine soil (D 3213); collection for toxicological testing (E 1391)</p>
Soil/Rock/Sediments	<p>Minimum set of data elements for soil sampling (D 5911); locational data elements (D 6168); format for exchange of computerized rock and soil data (D 6453); <b>selection of soil and rock sampling devices used with drill rigs (D 6169); direct push soil sampling (D 6282); Drilling Methods: Selection of drilling methods (D 6286)</b>; cable tool (D 5875); casing advancement (D 5872); diamond core drilling (D 2113); direct air-rotary (D 5782); direct fluid rotary (D 5783); direct rotary wireline (D 5876); dual-wall reverse circulation (D 5781); hollow-stem auger (D 5784, D 6151); <u>Field Sampling and Handling Methods</u>: Auger sampling (D 1452); radionuclides (C 998); core barrel samplers (D 6640); ring-lined barrel (D 3550); split barrel (D 1586); thin-wall tube (D 1587); piston sampler (D 6519); volatile organics (D 4547, D 6418—EnCore sampler); hollow stem auger (D 6151); coring/logging cement and lime stabilized soils (D 6236); <u>Sediments</u>: fluvial sediment in motion (D 4411, DD 4411, D 6236—transit ratios/sampling depth); submerged (D 4823); monitoring sediments in watershed (D 6145); handling, storing and preparing soft undisturbed marine soil (D 3213); collection for toxicological testing (E 1391)</p>
Vadose Zone	<u>Field Methods</u> : <b>Pore liquids (D 4696); soil (D 4700)</b> ; soil gas (D 5314)

**TABLE X1.1** *Continued*

Topic	ASTM Standard
—Water	Reporting water chemical analyses (D 6568); Purgeable headspace sampling (D 3871); waterborne oils (D 4489); continual on-line monitoring (D 3864); on-line measurement of pH (D 6569); filterable and nonfilterable matter (D 5907); on-line sampling/analysis (D 5540—flow and temperature control), water-formed deposits (D 887); <i>Planning</i> : water quality measurement program (D 5612); water monitoring programs (D 5851); <i>Ground Water: Sampling methods (D 4448)</i> ; direct push sampling (D 6001); planning a ground-water sampling event (D 5903); documenting a ground-water sampling event (D 6089); purging methods (D 6452); filed filtration (D 6564); field sample preservation (D 6517) <i>Surface Water</i> : dipper or pond sampler (D 5358); monitoring aqueous nutrients in watersheds (D 6146); <i>Closed Conduits</i> : equipment (D 1192); sampling (D 3370); Laboratory Practices: D3856
Water	Reporting water analysis results (D 596), reporting water chemical analyses (D 6568); Purgeable headspace sampling (D 3871); waterborne oils (D 4489); continual on-line monitoring (D 3864); on-line measurement of pH (D 6569); on-line measurement of turbidity (D 6699); filterable and nonfilterable matter (D 5907); on-line sampling/analysis (D 5540—flow and temperature control), water-formed deposits (D 887); QC of screening methods in water (D 6950); <i>Planning</i> : water quality measurement program (D 5612); water monitoring programs (D 5851); <i>Ground Water: Sampling methods (D 4448)</i> ; <b>selection of sampling and purging devices (D 6634)</b> direct push sampling (D 6001); planning a ground-water sampling event (D 5903); documenting a ground-water sampling event (D 6089); bailers (D 6699); purging methods (D 6452, D 6771—low-flow purging and sampling); filed filtration (D 6564); field sample preservation (D 6517) <i>Surface Water</i> : dipper or pond sampler (D 5358); monitoring aqueous nutrients in watersheds (D 6146); <i>Closed Conduits</i> : equipment (D 1192); sampling (D 3370); Laboratory Practices: D3856
—Waste/Contaminants	<i>General Guidance: General planning (D 4687); sampling equipment selection (D 6232)</i> ; representative sampling (D 6044); composite sampling and field subsampling (D 6051); Heterogeneous wastes (D 5956); laboratory subsampling (D 6323) <i>Specific Sampling Procedures</i> : bituminous materials (D 140); COLIWASA (D 5495); drums general (D 6063 consolidated solids—D 5679, unconsolidated solids—D 5680); single or multilayered liquids (D 5743); pipes and other point discharges (D 5013); scoop (D 5633); trier sampler (D 5451); unconsolidated waste from truck (D 5013); grab and discrete release detection devices (E 1430, E1526); volatile organics (D 4547); waterborne oils (D 4489); oil/water mixtures for oil spill recovery equipment (F 1084) waste piles (D 6009); wastewater automatic samplers (D 538)
Waste/Contaminants	<i>General Guidance: General planning (D 4687); designing cost-effective sampling plans (D 6843); sampling equipment selection (D 6232)</i> ; representative sampling (D 6044); composite sampling and field subsampling (D 6051); Heterogeneous wastes (D 5956); laboratory subsampling (D 6323) <i>Specific Sampling Procedures</i> : bailers (D 6699); bituminous materials (D 140); COLIWASA (D 5495); drums general (D 6063 consolidated solids—D 5679, unconsolidated solids—D 5680); single or multilayered liquids (D 5743); pipes and other point discharges (D 5013); grab and discrete depth samplers (D 6759); scoop (D 5633); trier sampler (D 5451); unconsolidated waste from truck (D 5658); UST release detection devices (E 1430, E1526); volatile organics (D 4547); waterborne oils (D 4489); oil/water mixtures for oil spill recovery equipment (F 1084) waste piles (D 6009); wastewater automatic samplers (D 538); wipe sampling (D6601)
Preservation/Transport	Sample chain of custody (D 4840); estimation of holding time for water samples (D 4515, D4841); <i>Field Methods</i> —Rock core samples (D 5079); sample containers for organic constituents (D 3694); soil samples (D 4220); sediments for toxicological testing (E 1391); preservation/preparation of waterborne oil samples (D 3325, D 3326); handling, storing and preparing soft undisturbed marine soil (D 3213)
Decontamination of Field Equipment Data Management/Analysis	<i>Field Methods</i> : Nonradioactive waste sites (D 5088); low-level radioactive waste sites (D 5608) <i>QA/QC</i> : Waste management environmental data (D 5283); waste management DQOs (D 5792); precision and bias (E 177); QC specification for organic constituents (D 5789); <i>Data Analysis</i> : Evaluation of technical data (E 678); outlying observations (E 178); reporting results of examination and analysis of water-formed deposits (D 933); <i>Waste Management Data</i> : Data assessment (D 6333); decision point (D 6250); <i>Geostatistics</i> : reporting geostatistical site investigations (D 5549); analysis of spatial variation (D 5922); selection of curing methods (D 5923); selection of simulation approaches (D 5924); <i>Spatial Data</i> : digital geospatial metadata (D 5714); see also Ground Water (Data Analysis)
<i>Soil/Rock Hydrologic Properties:</i> Infiltration Rate Matric Potential	<i>Field Methods</i> : Double-ring infiltrometer (D 3385); sealed double-ring infiltrometer (D 5093) <i>Field Methods</i> : Tensiometers (D 3404); <i>Laboratory Method</i> : Filter paper method (D 5298)
—Water Content	<i>Field Methods</i> : Calcium carbide method (D 4944); neutron probe (D 3017—shallow depth, D 5220—depth probe; D 6031—horizontal, slanted and vertical access tubes); time domain reflectometry (D 6565) <i>Laboratory Methods</i> : Direct heating method (D 4959); microwave oven method (D 4643); standard oven drying method (D 2216); centrifuge moisture equivalent (D 425)
Water Content	<i>Field Methods</i> : Calcium carbide method (D 4944); neutron probe (D 3017—shallow depth, D 5220—depth probe; D 6031—horizontal, slanted and vertical access tubes); time domain reflectometry (D 6565, D 6780) <i>Laboratory Methods</i> : Direct heating method (D 4959); microwave oven method (D 4643); standard oven drying method (D 2216); centrifuge moisture equivalent (D 425)
Hydraulic Conductivity	<i>Field Methods: Vadose zone (D 5126)</i> ; <i>Laboratory Methods</i> : Granular soils (D 2434— $>1 \times 10^{-3}$ cm/sec); low permeability soils (D 5084— $<1 \times 10^{-3}$ cm/sec); rigid-wall compaction-mold permeameter (D 5856); effect of freeze/thaw (D 6035); peat (D 4511); unsaturated/saturated with centrifugation (D 6527); partially saturated (D 6539); see also Ground Water/Aquifer Hydraulic Properties
—Other Hydrologic Properties	<i>Laboratory Methods</i> : Air permeability (D 4525); Soil water retention (D 2325—medium/coarse textured, D3152—fine-textured)
Other Hydrologic Properties	Soil—water moisture flux (D 6642) <i>Laboratory Methods</i> : Air permeability (D 4525); Soil water retention (D 2325—medium/coarse textured, D3152—fine-textured)
<i>Soil/Rock Physical Properties:</i> Particle Size	<i>Soil Laboratory Methods</i> : Analysis (D 422); dry preparation (D 421); <200 sieve (D 1140); wet preparation (D 2217); <i>Sediment</i> : Selection of methods for fluvial sediment (D 4822)
—Soil Density	<i>Field Methods</i> : Drive cylinder (D 2937); gamma-gamma (D 2922—<12", D5195—>12"); (D 4531); penetration (D 1586); rubber balloon method (D 2167); sand-cone method (D 1556); sand replacement method (D 4914); sleeve method (D 4564) water replacement method (D 5030); nuclear method (D 6031)
Soil Density	<i>Field Methods</i> : Drive cylinder (D 2937); gamma-gamma (D 2922—<12", D5195—>12"); peat (D 4531); (D 4531); penetration (D 1586); rubber-balloon method (D 2167); sand-cone method (D 1556); sand replacement method (D 4914); sleeve method (D 4564); time domain reflectometry (D 6780); water replacement method (D 5030); nuclear method (D 6031)
Pore Volume/Specific Density	<i>Laboratory Methods</i> : pore volume (D 4404); specific gravity (D 854, D5550—gas pycnometer)

**TABLE X1.1** *Continued*

Topic	ASTM Standard
Cone Penetration	<i>Field Methods:</i> In-situ cone penetration testing (D 3441, D 5778); CPT stress wave energy measurements (D 4633); liquefaction potential evaluation (D 6066); ECPT for environmental site characterization (D 6067); LIF characterization of petroleum contamination (D 6187)
Classification	<i>Field Methods:</i> Field logging (D 5434); noncohesive sediments (D 5387); peat (D 4544—deposit thickness, degree of humification—D 5715); sediments (D 4410); visual-manual procedure (D 2488—unified, D4083—frozen soils); rock mass classification (D 5878); rock quality designation (D 6032); <i>Laboratory Methods:</i> frozen soils (D 4083); natural mineral aggregates (C 294); peat (D 2607); unified soil classification (D 2487)
—Geophysical Properties	<i>Surface Geophysical Methods:</i> <b>selecting surface geophysical methods (PS78, D6429)</b> ; seismic refraction (D-5777); soil resistivity (G 57— Wenner 4-electrode method); DC resistivity (D 6431); GPR (D 6432); gravity (D 6430); <i>Borehole Geophysical Methods:</i> Crosshole seismic testing (D 4428/D 4428M); <b>planning and conducting borehole geophysical logging (D 5753)</b> ; mechanical caliper (D 6167); gamma (D 6274)
Geophysical Properties	<i>Surface Geophysical Methods:</i> <b>selecting surface geophysical methods (PS78, D6429)</b> ; seismic refraction (D 5777); soil resistivity (G 57—Wenner 4-electrode method); DC resistivity (D 6431); GPR (D 6432); electromagnetic (D 6639—frequency domain, D 6820 — time domain) gravity (D 6430); <i>Borehole Geophysical Methods:</i> Crosshole seismic testing (D 4428/D 4428M); <b>planning and conducting borehole geophysical logging (D 5753)</b> ; mechanical caliper (D 6167); electromagnetic induction (D 6726), gamma (D 6274), neutron (D 6727)
—Engineering Properties	<i>In Situ Field Methods:</i> Bearing capacity/ratio (D 1194, D 4429); deformability and strength of weak rock (D 4555); direct shear strength (D 4554, D 5607); erodibility (D 5852); frost heave/thaw, susceptibility (D5918); extensometers (D 4403); in situ creep (D 4553); in situ modulus of deformation (D 4394—rigid plate, D 4395—flexible plate, D 4506—radial jacking test, D 4729—flatjack method, D 4791—borehole jack); in situ stress (D 4623—borehole deformation gage, D 4645—hydraulic fracturing; D 4729—flatjack method); pressure measurement (D 4719—pressuremeter, D 5720—transducer calibration); vane shear test (D 2573); <i>Laboratory Methods:</i> California bearing ratio (D 1883); classification (D 2487); compaction (D 698, D 1557, D 5080); compressive strength (D 2166, D 2930); consolidation (D 2435); core dimensional and shape tolerances (D 4543); dispersive characteristics (D 4221—double hydrometer; D 4647—pinhole test; D 6572—crumb test); elastic properties (D 2845, D 3148); impact valve (D 5874); linear displacement (D 6027—calibrating transducers); liquid limit (D 4318); moisture content penetration resistance (D 1558); one-dimensional swell (D 4546); plastic limit/plasticity index (D 4318); point load strength (D 5731); rock hardness (D 5873) shrinkage factors (D 427; D 4943); tensile strength (D 2936; D 3967); thermal properties (D 5334, D 5335); triaxial compression (D 2850, D 2664, D 4406, D 4767, D 5311, D 5407); uniaxial compression (D 4341, D 4405); use of significant digits (D 6026); shear tests (D 4648—vane; D 6467—drained; D 6528—undrained); <i>Evaluation of Laboratories:</i> D 3740
Engineering Properties	<i>In Situ Field Methods:</i> Bearing capacity/ratio (D 1194, D 4429); deformability and strength of weak rock (D 4555); direct shear strength (D 4554, D 5607); erodibility (D 5852); frost heave/thaw, susceptibility (D5918); extensometers (D 4403); in situ creep (D 4553); in situ modulus of deformation (D 4394—rigid plate, D 4395—flexible plate, D 4506—radial jacking test, D 4729—flatjack method, D 4791—borehole jack); in situ stress (D 4623—borehole deformation gage, D 4645—hydraulic fracturing; D 4729—flatjack method); pressure measurement (D 4719—pressuremeter, D 5720—transducer calibration); stiffness (D 6758); vane shear test (D 2573); <i>Laboratory Methods:</i> California bearing ratio (D 1883); classification (D 2487); compaction (D 698, D 1557, D 5080); compressive strength (D 2166, D 2938); consolidation (D 2435); core dimensional and shape tolerances (D 4543); dispersive characteristics (D 4221—double hydrometer; D 4647—pinhole test; D 6572—crumb test); elastic properties (D 2845, D 3148); impact valve (D 5874); linear displacement (D 6027 - calibrating transducers); liquid limit (D 4318); moisture content penetration resistance (D 1558); one-dimensional swell (D 4546); plastic limit/plasticity index (D 4318); point load strength (D 5731); rock hardness (D 5873) shrinkage factors (D 427; D 4943); tensile strength (D 2936; D 3967); thermal properties (D 5334, D 5335); triaxial compression (D 2850, D 2664, D 4406, D 4767, D 5311, D 5407); uniaxial compression (D 4341, D 4405); use of significant digits (D 6026); shear tests (D 4648—vane; D 6467—drained; D 6528—undrained); <i>Evaluation of Laboratories:</i> D 3740
Miscellaneous	<i>Field:</i> Geotechnical mapping of large underground openings in rock (D 4543); <i>Laboratory Methods:</i> X-ray radiography (D 4452)
—Peat/Organic Soils	<i>Laboratory Methods:</i> Bulk density (D 4531); classification (D 2607); hydraulic conductivity (D 4511); pH (D 2976); moisture/ash/organic matter (D 2974)
Peat/Organic Soils	<i>Laboratory Methods:</i> Bulk density (D 4531); classification (D 2607); hydraulic conductivity (D 4511); pH (D 2976); moisture/ash/organic matter (D 2974); moisture holding capacity and porosity (D 2980)
Frozen Soils	<i>Field:</i> Description (D 4083); <i>Laboratory:</i> Creep properties by uniaxial compression (D 5520)
Soil/Rock/Sediment Chemistry: Basic Chemistry	<i>Field Methods:</i> Soil pH for corrosion testing (G 51); <i>Laboratory Methods:</i> Calcium carbonate (D 4373); pH (D 4972); soluble salt content (D 4542); diagnostic soil test for plant growth and food chain protection (D 5435); minimum requirements for laboratories engaged in chemical analysis (D 5522)
Soil Contaminants	Nitroaromatic and nitramine explosives (D 5143); screening fuels (D 5831); PCBs using room temperature phosphorescence (PS 47); radionuclides (C 998, C 999); petroleum contamination with CPT/LIF (D 6187)
Sediments	Preparation for chemical analysis (D 3975, D3976)
Sorption/Leachability Ground Water:	See fate-related procedures in Table A.1
Characterization/Monitoring	Assessing aquifer sensitivity and vulnerability (D 6030); conceptualization and characterization (D 5979); wetland functions (EPS781938); wetland functions (E 1938); existing wells (D 5980); monitoring karst and fractured rock aquifers (D 5717); statistical approaches for ground-water detection monitoring programs (PS 64, D 6312); nomenclature for aquifers (D 6106)
Characterization/Monitoring	Assessing aquifer sensitivity and vulnerability (D 6030); conceptualization and characterization (D 5979); wetland functions (E1938); wetland functions (E 1938); existing wells (D 5980); locating abandoned wells (D 6285); monitoring karst and fractured rock aquifers (D 5717); statistical approaches for ground-water detection monitoring programs (PS 64, D 6312); nomenclature for aquifers (D 6106)
Data Elements	<i>Field Methods:</i> Minimum set (D 5254); additional identification descriptors (D 5408); additional physical descriptors (D 5409); additional usage description (D 5410); selection of data elements (D 5474)
Data Analysis/Presentation	Presentation of water level information (D 6000); <i>Chemical Analysis:</i> Diagrams for single analyses (D 5738); trilinear diagrams (D 5754); diagrams based on data analytical calculations (D 5877); use of maps (D 6036)
—Monitoring Wells	<i>Field Methods:</i> <b>Design/Installation</b> (D 5092); protection (D 5787); decommissioning (D 5299); casing (D 1785, F 480); grout (C 150—portland cement); water level measurement (D 4750); well development in granular aquifers (D 5521); well discharge (D 5716—circular orifice weir, D 5737—guide to methods); maintenance and rehabilitation (D 5978)



**TABLE X1.1** *Continued*

Topic	ASTM Standard
Monitoring Wells	<i>Field Methods: Design/installation</i> (D 5092); protection (D 5787); direct push D 6724, D 6725—prepacked screens; decommissioning (D 5299); casing (D 1785, F 480); grout (C 150—portland cement); water level measurement (D 4750); well development in granular aquifers (D 5521); well discharge (D 5716—circular orifice weir, D 5737—guide to methods); maintenance and rehabilitation (D 5978)
Aquifer Hydraulic Properties	<i>Field Methods: Packer tests</i> (D 4630, D 4631); aquifer tests with control wells (D 4105, D 4106, D 5269, D 5270, D 5472, D 5473); D 5920 - anisotropic unconfined; D 6028, D 6029—(leaky confining beds); slug tests (D 4044, D 4050, D 4104, D 5785, D 5881, D 5912); constant drawdown for flowing wells (D 5787, D 5855); constant rate pumping (D 6034); partially penetrating wells (D 5850); two-stage infiltration (D 6391); <b>test selection</b> (D 4043)
Modeling	Site specific application (D 5447); comparing simulation to site-specific information (D 5490); documenting model application (D 5718); defining boundary conditions (D 5609); defining initial conditions (D 5610); conducting sensitivity analysis (D 5611); simulation of subsurface air flow (D 5719); subsurface flow and transport modeling (D 5880) model calibration (D 5981); developing and evaluating codes (D 6025); describing functionality (D 6033); selecting a modeling code (D 6170); documenting a modeling code (D 6171)
Chemistry	<i>Field Methods: Acidity/Alkalinity</i> (D 1067); electrical conductivity/resistivity (D 1125); ion-selective electrodes (D 4127); low-level dissolved oxygen (D 5462); odor (D 1292); pH (D 1293, D 5464); redox potential (D 1498), test kits for inorganic constituents (D 5463); turbidity (D 1889); <i>Extraction Methods: purgeable organics using headspace sampling</i> (D 3871); micro-extraction for volatiles and semivolatiles (D 5241); <i>Laboratory Methods: Organic carbon</i> (D 2579); minimum requirements for laboratories engaged in chemical analysis (D 5522); see, generally, Vols 11.01 and 11.02
Microbiology	ATP content (D 4012); iron bacteria (D 932); sulfate-reducing bacteria (D 4412); microbial respiration (D 4478); microscopy (D 4454—total respiring bacteria, D4455—epifluorescence); plating methods (D 5465); on site screening heterotrophic bacteria (F 488)
Surface Water: Geometry/Flow Measurement	Depth measurement (D 5073 D 5909-horizontal positioning, fathometer calibration D 6318); measurement of morphologic characteristics of surface water bodies (D 4581); operating a gaging station (D 5674); <i>Discharge: Step backwater method</i> (D 5388); <i>Open Channel Flow: Selection of weirs and flumes</i> (D 5640); acoustic methods (D 4408); acoustic velocity method (D 5389); broad-crested weirs (D 5614); culverts (D 5243); developing a stage-discharge relation (D 5541); dye tracers (D 5613); electromagnetic current meters (D 5089); Palmer-Bowles Flume (D 5390); Parshall flume (D 1941); rotating element current meters (D 4409); slope-area method (D 5130); thin-plate weirs (D 5242); velocity-area method (D 3858); width contractions (D 5129); <i>Open Water Bodies: Water level measurement</i> (D 5413)
Other Characteristics	Suspended sediment concentration (D 3977); environmental conditions relevant to spill control systems (F 625); <i>Chemistry: See ground water above</i>
Waste/Contaminants: —Waste Properties	<i>Field/Screening Methods: Compatibility</i> (D 5059); cyanides (D 5049); flammability potential (D 4982); oxidizers (D 4981); pH (D 4980); physical description screening analysis (D 4979); radioactivity (D 5928); sulfides (D 4978); waste specific gravity/bulk density (D 5057); <i>Laboratory Methods: Waste bulk density</i> (E 1109); biological clogging of geotextiles (D 1987); coal fly ash (D 5759); solid waste freeze-thaw resistance (D 4842); stability and miscibility (D 5232); wetting and drying (D 4843); <i>Extraction Methods: Single batch extraction methods</i> (D 5233); sequential batch extraction with water (D 4793 - water, D 5284 - acidic extraction fluid); soxhlet extraction (D 5369); total solvent extractable content (D 5368); solvent extraction of total petroleum hydrocarbons (D 5765); shake extraction of solid waste and water (D 3987)
Waste Properties	<i>Field/Screening Methods: Compatibility</i> (D 5059); asbestos (D 2947); cyanides (D 5049); flammability potential (D 4982); oxidizers (D 4981); pH (D 4980); physical description screening analysis (D 4979); radioactivity (D 5928); sulfides (D 4978); waste specific gravity/bulk density (D 5057); <i>Laboratory Methods: Waste bulk density</i> (E 1109); biological clogging of geotextiles (D 1987); coal fly ash (D 5759); solid waste freeze-thaw resistance (D 4842); stability and miscibility (D 5232); wetting and drying (D 4843); <i>Extraction Methods: Single batch extraction methods</i> (D 5233); sequential batch extraction with water (D 4793 - water, D 5284 - acidic extraction fluid); soxhlet extraction (D 5369); total solvent extractable content (D 5368); solvent extraction of total petroleum hydrocarbons (D 5765); shake extraction of solid waste and water (D 3987)
Contaminant Fate	See fate-related procedures in Table A.2
Radioactive Materials	<i>Monitoring: Detector calibration</i> (E 181); radiation measurement/dosimetry (D 3648, E 170); radiation protection programs for decommissioning operations (E 1167); <i>Sampling/Preparation: sampling surface soil for radionuclides</i> (C 998); soil sample preparation for determination of radionuclides (C 999)
Asbestos	Screen analysis (D 2947)
Other Site Conditions: Field Atmospheric Conditions	Atmospheric pressure (D 3631); temperature (D 6167M); conversion unit and factors (D 1914); determining comparability of meteorological measurements (D 4430); <i>Humidity: Dew-point hygrometer</i> (D 4030); psychrometer (E 337); terminology (D 4023); <i>Wind: Anemometers</i> (D 4480, D 5096, D 5741, D 6011); surface wind by acoustic means (D 5527); wind vane (D 5741, performance - D 5366) see Volume 11.03 generally
Solar insolation	Pyranometers (E 824, E 913, E 941); pyrheliometers (E 816)

<sup>A</sup>**Boldface**—Method selection guide.

<sup>B</sup>*Italicized standard designation* = discontinued.

X1.1.2<sup>5</sup> Table X1.2 identifies more than 95 standard test method, practices and guides that address field sampling for ecological characterization and laboratory methods, such as toxicity testing, relevant to human and ecological risk assessment.

X1.2 This guide does not specifically address laboratory methods, but Table X1.1 provides a convenient index to laboratory methods that might be useful for testing and analysis of soil, water, and waste samples collected during an environmental site investigation. This appendix does not contain a detailed listing of laboratory methods for measurement of specific chemicals that might be of concern in an environmental investigation. However, methods for measurement of chemical parameters that are routinely used in field investigations and laboratory methods that provide information relevant to the transport and fate of contaminants and other chemical constituents in the subsurface are included.

X1.3 The following ASTM compilations may be useful for Environmental Site Characterization:

X1.3.1 *ASTM Standards on Ground Water and Vadose Zone Investigations: Drilling, Sampling, Geophysical Logging; Well*



*Installation and Decommissioning*, 2nd ed 1994. [56 Standards].

X1.3.2 *ASTM Standards Related to Phase II Environmental Site Assessments for Commercial Real Estate*, 1998, 333 pp. [22 Standards].

X1.3.3 *ASTM Standards on Environmental Site Assessments for Commercial Real Estate*, 2nd ed, 1994, 55 pp. [Includes E1527 and E1528].

X1.3.4 *ASTM Standards on Hazardous Substance and Oil Spill Response*, 2nd ed. 1994, 144 pp. [38 standards].

X1.3.5 *ASTM Standards on Lead-Based Paint Abatement in Buildings*. 1994, 174 pp. [28 standards].

X1.3.6 *ASTM Standards on Environmental Sampling*, 2nd ed., 1997, 1008 pp. [138 standards].

X1.3.7 *ASTM Standards on Determining Subsurface Hydraulic Properties and Ground Water Modeling*, 2nd ed., 1999, 350 pp. [45 standards].

X1.3.8 *ASTM Standards on Design and Planning and Reporting of Ground Water and Vadose Zone Investigations*, 2nd ed., 1999, 600 pp. [44 standards].

X1.3.9 *ASTM Standards Related to On-Site Septic Systems*, 1997, 176 pp. [18 standards].

X1.3.10 *ASTM Standards Related to Environmental Site Characterization*, 2nd edition, 2002, 2078 pp. [162 standards].

X1.4 *ASTM Standards*—Indexed in Table X1.1 (In Vols 04.08 or 04.09, unless otherwise specified).<sup>48, 49</sup>

C 150 – 99a	Specification for Portland Cement (Vol 04.01)
C 294 – 98	Descriptive Nomenclature for Constituents of Natural Mineral Aggregates (Vol 04.02)
C 998 – 90	Practice for Sampling Surface Soil for Radionuclides (Vol 12.01)
C 999 – 90	Practice for Soil Sample Preparation for Determination of Radionuclides (Vol 12.01)
D 140 – 98	Practice for Sampling Bituminous Materials
D 420 – 98	Guide to Site Characterization for Engineering, Design, and Construction Purposes
D 421 – 85	Practice for Dry Preparation of Soil Samples for Particle-Size Analysis and Determination of Soil Constants
D 422 – 63	Test Method for Particle-Size Analysis of Soils
D 425 – 88	Test Method for Centrifuge Moisture Equivalent of Soils
D 427 – 98	Test Method for Shrinkage Factors of Soils by the Mercury Method
D 596 – 01	Guide for Reporting Results of Analysis of Water
<del>D 653 – 97</del>	<del>Terminology Relating to Soil, Rock, and Contained Fluids</del>
D 653 – 02	Terminology Relating to Soil, Rock, and Contained Fluids
D 698 – 91	Test Method for Laboratory Compaction Characteristics of Soil Using Standard Effort (12 400 ft-lbf/ft <sup>3</sup> ) (600 kN-m/m <sup>3</sup> )
<del>D 854 – 98</del>	<del>Test Method for Specific Gravity of Soil</del>
D 854 – 02	Test Method for Specific Gravity of Soil
D 887 – 82	Practice for Sampling Water-Formed Deposits (Vol 11.02)
D 932 – 85	Test Method for Iron Bacteria in Water and Water-Formed Deposits (Vol 11.02)
D 933 – 84	Practice for Reporting Results of Examination and Analysis of Water-Formed Deposits (Vol 11.04)
D 1067 – 92	Test Methods for Acidity or Alkalinity of Water (Vol 11.01)
D 1125 – 82	Test Methods for Electrical Conductivity and Resistivity of Water (Vol 11.01)
<del>D 1129 – 99a</del>	<del>Terminology Relating to Water (Vol 11.01)</del>
D 1129 – 02a	Terminology Relating to Water (Vol 11.01)
D 1140 – 97	Test Method for Amount of Materials in Soils Finer than No. 200 (75- $\mu$ m) Sieve
D 1192 – 95	Specification for Equipment for Sampling Water and Steam in Closed Conduits (Vol 11.01)
D 1194 – 94	Test Method for Bearing Capacity of Soil for Static Load on Spread Footings
D 1292 – 86	Test Method for Odor in Water (Vol 11.01)
D 1293 – 99	Test Methods for pH in Water (Vol 11.01)
D 1356 – 00a	Terminology Relating to Atmospheric Sampling and Analysis (Vol 11.03)
D 1357 – 95	Practice for Planning the Sampling of the Ambient Atmosphere (Vol 11.03)
D 1452 – 80	Practice for Soil Investigation and Sampling by Auger Borings

<sup>48</sup> Chappelle (83) provides a useful reference for microbial sampling of ground water. Some major references

<sup>48</sup> Prior to 1994 Volume 04.08 contained all standards on soil microbiology and ecology, geomicrobiology rock. Beginning in 1994 this volume was broken into two volumes: Volume 04.08; Soil and microbial biogeochemistry include: Alexander (84), Ehrlich (85), Killham (86), Kuznetsov et al (87), Paul Rock (I): D420 to D4914, and Clark (88); Volume 04.09; Soil and Zajic (89); Rock (II): D4943 to latest; Geosynthetics.

<sup>49</sup> The last two digits indicate the year in situ here is confined to methods that measure chemical parameters which the standard was adopted or the most recent year in place without bringing a sample which substantive revisions to the surface. The term may also be applied to ground water sampling devices that do not require installation of a monitoring well. In situ chemical sensors can be placed in monitoring wells or by using CPT or other push technologies. standard were adopted.



D 1498 – 00a	Practice for Oxidation-Reduction Potential of Water (Vol 11.01)
D 1556 – 90	Test Method for Density and Unit Weight of Soil In Place by the Sand-Cone Method
<del>D 1557 – 94</del>	<del>Test Method for Laboratory Compaction Characteristics of Soil Using Modified Effort (56 000 ft-lbf/ft<sup>3</sup>) (2700 kN-m/m<sup>3</sup>)</del>
<u>D 1557 – 02</u>	<u>Test Method for Laboratory Compaction Characteristics of Soil Using Modified Effort (56 000 ft-lbf/ft<sup>3</sup>) (2700 kN-m/m<sup>3</sup>)</u>
D 1558 – 94	Test Method for Moisture Content Penetration Resistance Relationships of Fine Grained Soils
D 1586 – 99	Test Method for Penetration Test and Split-Barrel Sampling of Soils
D 1587 – 94	Practice for Thin-Walled Tube Geotechnical Sampling of Soils
<i>D 1704/</i> <i>D 1704M – 95</i>	<i>Test Method for Determining the Amount of Particulate Matter in the Atmosphere by Measurement of the Absorbance of a Filter Sample (Vol 11.03), Discontinued 2000.</i>
D 1739 – 98	Test Method for Collection and Analysis of Dustfall (Settleable Particulates) (Vol 11.03)
D 1785 – 99	Specifications for Polyvinyl Chloride (PVC) Plastic Pipe Schedules 40, 80, and 120 (Vol 08.04)
D 1883 – 99	Test Method for CBR (California Bearing Ratio) of Laboratory-Compacted Soils
D 1889 – 00	Test Methods for Turbidity in Water (Vol 11.01)
D 1914 – 95	Practice for Conversion Units and Factors Relating to Atmospheric Analysis (Vol 11.03)
D 1941 – 91	Test Method for Open Channel Flow Measurements of Water with the Parshall Flume (Vol 11.01)
D 1987 – 95	Test Method for Biological Clogging of Geotextiles of Soil/Geotextile Filters
D 2113 – 99	Test Method for Diamond Core Drilling for Site Investigation
D 2166 – 98a	Test Method for Unconfined Compressive Strength of Cohesive Soil
D 2167 – 94	Test Method for Density and Unit Weight of Soil in Place by the Rubber Balloon Method
D 2216 – 98	Test Method for Laboratory Determination of Water (Moisture) Content of Soil and Rock (Gravimetric Oven Drying)
D 2217 – 85	Practice for Wet Preparation of Soil Samples for Particle-Size Analysis and Determination Soil Constants
D 2325 – 68	Test Method for Capillary-Moisture Relationship for Coarse- and Medium-Textured Soils by Porous-Plate Apparatus (Soil Water Retention)
D 2434 – 68	Test Method for Permeability of Granular Soils (Constant Head) ( $>1 \times 10^{-3}$ cm/s)
<del>D 2435 – 96</del>	<del>Test Method for One-Dimensional Consolidation Properties of Soils</del>
<u>D 2435 – 02</u>	<u>Test Method for One-Dimensional Consolidation Properties of Soils</u>
D 2487 – 98	Classification of Soils for Engineering Purposes (Unified Soil Classification System)
D 2488 – 93	Practice for Description and Identification of Soils (Visual-Manual Procedures)
D 2573 – 94	Test Method for Field Vane Shear Test in Cohesive Soil
D 2579 – 93	Test Methods for Total and Organic Carbon in Water (Vol 11.02)
D 2607 – 69	Classification of Peats, Mosses, Humus, and Related Products (Discontinued in 1992)
D 2664 – 95a	Test Method for Triaxial Compressive Strength of Undrained Rock Core Specimen Without Pore Pressure Measurements
D 2845 – 90	Test Method for Laboratory Determination of Pulse Velocities and Ultrasonic Elastic Constants of Rock
<del>D 2850 – 95</del>	<del>Test Method for Unconsolidated, Undrained Compressive Strength of Cohesive Soils in Triaxial Compression</del>
<u>D 2850 – 03</u>	<u>Test Method for Unconsolidated, Undrained Compressive Strength of Cohesive Soils in Triaxial Compression</u>
D 2922 – 96	Test Methods for Density of Soil and Soil-Aggregate in Place by Nuclear Methods (Shallow Depth) (gamma-gamma, surface or <12 in. (305 mm))
D 2936 – 95	Test Method for Direct Tensile Strength of Intact Rock Core Specimens
D 2937 – 94	Test Method for Density of Soil in Place by the Drive-Cylinder Method
D 2938 – 95	Test Method for Unconfined Compressive Strength of Intact Rock Core Specimens

D 2947 – 88	Test Method for Screen Analysis of Asbestos Fibers (Vol 04.05 and Vol 08.02)
D 2974 – 87	Test Methods for Moisture, Ash, and Organic Matter of Peat and Other Organic Materials
D 2976 – 71	Test Method for pH of Peat Materials
<u>D 2980 – 02</u>	<u>Test Method for Volume, Mass, Moisture-Holding Capacity, and Porosity of Saturated Peat Materials</u>
D 3017 – 96	Test Method for Moisture Content of Soil and Rock in Place by Nuclear Methods (Shallow Depth), (neutron probe)
D 3080 – 98	Test Method for Direct Shear Test of Soils Under Consolidated Drained Conditions
D 3148 – 96	Test Methods for Elastic Moduli of Intact Rock Core Specimens in Uniaxial Compression
D 3152 – 72	Test Method for Capillary-Moisture Relationships for Fine-Textured Soils by Pressure-Membrane Apparatus
D 3213 – 91	Practice for Handling, Storing, and Preparing Soft Undisturbed Marine Soil
D 3249 – 95	Practice for General Ambient Air Analyzer Procedures (Vol 11.03)
D 3325 – 90	Practice for the Preservation of Waterborne Oil Samples (Vol 11.02)
D 3326 – 90	Practices for Preparation of Samples for Identification of Waterborne Oils (Vol 11.02)
D 3370 – 95a	Practices for Sample Water from Closed Conduits (Vol 11.01)
D 3385 – 94	Test Method for Infiltration Rate of Soils in Field Using Double-Ring Infiltrometers
D 3404 – 91	Guide for Measuring Matric Potential in the Vadose Zone Using Tensiometers
D 3441 – 98	Test Method for In-Situ Cone Penetration Tests of Soil
D 3550 – 84	Practice for Ring-Lined Barrel Sampling of Soils
<i>D 3584 – 83</i>	<i>Practice for Indexing Papers and Reports on Soil and Rock for Engineering Purposes, Discontinued 1996.</i>
D 3614 – 97	Guide for Laboratories Engaged in Sampling and Analysis of Atmospheres and Emissions (Vol 11.03)
D 3631 – 99	Method for Measuring Surface Atmospheric Pressure (Vol 11.03)
D 3648 – 95	Practices for Measurement of Radioactivity (Vol 11.02)
D 3686 – 95	Practice for Sampling Atmospheres to Collect Organic Compound Vapors (Activated Charcoal Tube Adsorption Method) (Vol 11.03)
D 3694 – 96	Practice for Preparation of Sample Containers and for Preservation of Organic Constituents (Vol 11.02)
D 3740 – 99c	Practice for Evaluation of Agencies Engaged in the Testing and/or Inspection of Soil and Rock Used In Engineering Design and Construction
D 3856 – 95	Guide for Good Laboratory Practices in Laboratories Engaged in Sampling and Analysis of Water (Vol 11.01)
D 3858 – 95	Practice for Open Channel Flow Measurement of Water by Velocity-Area Method (Vol 11.01)
D 3864 – 79	Guide for Continual On-Line Monitoring Systems for Water Analysis (Vol 11.01)
D 3871 – 84	Test Method for Purgeable Organic Compounds in Water Using Headspace Sampling (Vol 11.02)
D 3967 – 95a	Test Method for Splitting Tensile Strength of Intact Rock Core Specimens
D 3975 – 93	Practice for Development and Use (Preparation) of Samples for Collaborative Testings of Methods for Analysis of Sediments (Vol 11.02)
D 3976 – 92	Practice for Preparation of Sediments Samples for Chemical Analysis (Vol 11.02)
<i>D 3977 – 80</i>	<i>Practice for Determining Suspended Sediment Concentration in Water Sample (Vol 11.02), Discontinued 1995.</i>
D 3987 – 85	Test Method for Shake Extraction of Solid Waste and Water (Vol 11.04)
D 4012 – 81	Test Method for Adenosine Triphosphate (ATP) Content of Microorganisms in Water (Vol 11.02)
D 4023 – 82a	Definitions of Terms Relating to Humidity Measurements (Vol 11.03)
D 4043 – 96	Guide for Selection of Aquifer-Test Method in Determination of Hydraulic Properties by Well Techniques
D 4044 – 96	Test Method for (Field Procedures) for Instantaneous Change in Head (Slug Tests) for Determining Hydraulic Properties of Aquifers
D 4050 – 96	Test Method (Field Procedure) for Withdrawal and Injection Well Tests for Determining Hydraulic Properties of Aquifer Systems



D 4083 – 89	Practice for Description of Frozen Soils (Visual-Manual Procedure)
D 4096 – 91	Test Method for Determination of Total Suspended Particulate Matter in the Atmosphere (High-Volume Sampler Method), (Vol 11.03)
D 4104 – 96	Test Method (Analytical Procedure for) Determining Transmissivity of Confined Nonleaky Aquifers by Overdamped Well Response to Instantaneous Change in Head (Slug Test)
D 4105 – 96	Test Method for (Analytical Procedure for) Determining Transmissivity and Storage Coefficient of Nonleaky Confined Aquifers by the Modified Theis Nonequilibrium Method
D 4106 – 96	Test Method for (Analytical Procedure for) Determining Transmissivity and Storativity of Nonleaky Confined Aquifers by the Theis Nonequilibrium Method
D 4127 – 92	Terminology Used with Ion-Selective Electrodes (Vol 11.01)
D 4129 – 98	Test Method for Total and Organic Carbon in Water by High Temperature Oxidation and by Coulometric Detection (Vol 11.02)
D 4220 – 95	Practice for Preserving and Transporting Soil Samples
D 4221 – 99	Test Method for Dispersive Characteristics of Clay Soil by Double Hydrometer
<del>D 4230 – 83</del>	<del>Test Method of Measuring Humidity with Cooled-Surface Condensation (Dew Point) Hygrometer (Vol 11.03)</del>
<u>D 4230 – 02</u>	<u>Test Method of Measuring Humidity with Cooled-Surface Condensation (Dew Point) Hygrometer (Vol 11.03)</u>
D 4318 – 98	Test Method for Liquid Limit, Plastic Limit, and Plasticity Index of Soils
D 4341 – 93	Test Method for Creep of Cylindrical Hard Rock Core Specimens in Uniaxial Compression
<del>D 4373 – 96</del>	<del>Test Method for Calcium Carbonate Content of Soils</del>
<del>D 4373 – 02</del>	<del>Test Method for Calcium Carbonate Content of Soils</del>
<del>D 4375 – 96</del>	<del>Terminology for Basic Statistics in Committee D-19 on Water (Vol 11.01)</del>
D 4394 – 84	Test Method for Determining the In-Situ Modulus of Deformation of Rock Mass Using the Rigid Plate Loading Method
D 4395 – 84	Test Method for Determining the In-Situ Modulus of Deformation of Rock Mass Using the Flexible Plate Loading Method
D 4403 – 84	Practice for Extensometers Used in Rock
D 4404 – 84	Test Method for Determination of the Pore Volume and Pore Volume Distribution of Soil and Rock by Mercury Intrusion Porosimetry
D 4405 – 93	Test Method for Creep of Cylindrical Soft Rock Core Specimens in Uniaxial Compression
D 4406 – 93	Test Method for Creep of Cylindrical Soft Rock Core Specimens in Triaxial Compression
D 4409 – 91	Test Method for Velocity Measurement of Water in Open Channels with Rotating Element Current Meters (Vol 11.01)
D 4410 – 94	Terminology of Fluvial Sediment (Vol 11.01)
D 4411 – 93	Guide for Sampling Fluvial Sediment in Motion (Vol 11.02)
D 4412 – 84	Test Methods for Sulfate-Reducing Bacteria in Water and Water-Formed Deposits (Vol 11.02)
D 4428/ D 4428M – 91	Test Method for Crosshole Seismic Testing
D 4429 – 93	Test Method for Bearing Ratio of Soils in Place
D 4430 – 84	Practice for Determining the Operational Comparability of Meteorological Measurement (Vol 11.03)
D 4448 – 85a	Guide for Sampling Groundwater Monitoring Wells (Vol 11.04)
D 4452 – 85	Methods for X-Ray Radiography of Soil Samples
D 4454 – 85	Test Method for Simultaneous Enumeration of Total Respiring Bacteria in Aquatic Systems by Microscopy (Vol 11.02)
D 4455 – 85	Test Method for Enumeration of Aquatic Bacteria by Epifluorescence Microscopy Counting Procedure (Vol 11.02)
D 4478 – 85	Test Methods for Oxygen Uptake (Vol 11.02), (Microbial respiration)
<i>D 4480 – 85</i>	<i>Test Method for Measuring Surface Wind by Means of Wind Vanes and Rotating Anemometers (Vol 11.03), Discontinued 1999, Replaced by D5741.</i>
D 4489 – 95	Practices for Sampling Waterborne Oils (Vol 11.02)
D 4490 – 96	Practice for Measuring the Concentration of Toxic Gases or Vapors Using Detector Tubes (Vol 11.03)
<del>D 4506 – 90</del>	<del>Test Method for Determining the In-Situ Modulus of Deformation of Rock Mass Using a Radial Jacking Test</del>



<u>D 4506 – 02</u>	<u>Test Method for Determining the In-Situ Modulus of Deformation of Rock Mass Using a Radial Jacking Test</u>
D 4511 – 92	Test Method for Hydraulic Conductivity of Essentially Saturated Peat (Constant Head)
D 4515 – 85	Practice for Estimation of Holding Time for Water Samples Containing Organic Constituents (Vol 11.02)
D 4525 – 90	Test Method for Permeability of Rocks by Flowing Air
D 4531 – 86	Test Method for Bulk Density of Peat and Peat Products
D 4536 – 96	Test Method for High Volume Sampling for Solid Particulate Matter and Determination of Particulate Emissions (Vol 11.03)
D 4542 – 95	Test Method for Pore-Water Extraction and Determination of the Soluble Salt Content of Soils by Refractometer
D 4543 – 85	Practice for Determining Dimensional and Shape Tolerances of Rock Core Specimens
D 4544 – 86	Practice for Estimating Peat Deposit Thickness
<del>D 4546 – 96</del>	<del>Test Methods for One-Dimensional Swell/Settlement Potential of Cohesive Soils</del>
<u>D 4546 – 03</u>	<u>Test Methods for One-Dimensional Swell/Settlement Potential of Cohesive Soils</u>
D 4547 – 98	Practice for Sampling Waste and Soils for Volatile Organics (Vol 11.04)
<del>D 4553 – 90</del>	<del>Test Method for Determining the In-Situ Creep Characteristics of Rock</del>
<u>D 4553 – 02</u>	<u>Test Method for Determining the In-Situ Creep Characteristics of Rock</u>
<del>D 4554 – 90</del>	<del>Test Method for In-Situ Determination of Direct Shear Strength of Rock Discontinuities</del>
<u>D 4554 – 02</u>	<u>Test Method for In-Situ Determination of Direct Shear Strength of Rock Discontinuities</u>
D 4555 – 90	Test Method for Conducting an In-Situ Uniaxial Compressive Test for Determining Deformability and Strength of Weak Rock
<del>D 4564 – 93</del>	<del>Test Method for Density of Soil in Place by the Sleeve Method (cohesionless, gravelly soils)</del>
<u>D 4564 – 02</u>	<u>Test Method for Density of Soil in Place by the Sleeve Method (cohesionless, gravelly soils)</u>
D 4581 – 86	Guide for Measurement of Morphologic Characteristics of Surface Water Bodies (Vol 11.02)
D 4597 – 97	Practice for Sampling Workplace Atmospheres to Collect Organic Gases or Vapors with Activated Charcoal Diffusional Samplers (Vol 11.03)
<i>D 4598 – 87</i>	<i>Practice for Sampling Workplace Atmospheres to Collect Gases or Vapors with Liquid Sorbent Diffusional Samplers (Vol 11.03), Discontinued 1995</i>
D 4599 – 97	Practice for Measuring the Concentration of Toxic Gases or Vapors Using Length-of-Stain Dosimeter (Vol 11.03)
<del>D 4623 – 96</del>	<del>Test Method for Determination of In-Situ Stress in Rock Mass by Overcoring Method—USBM Borehole Deformation Gage</del>
<u>D 4623 – 02</u>	<u>Test Method for Determination of In-Situ Stress in Rock Mass by Overcoring Method—USBM Borehole Deformation Gage</u>
D 4630 – 96	Test Method for Determining Transmissivity and Storativity of Low Permeability Rocks by In-Situ Measurements Using the Constant Head Injection Test
D 4631 – 86	Test Method for Determining Transmissivity and Storativity of Low Permeability Rocks by In-Situ Measurements Using the Pressure Pulse Technique
<i>D 4633 – 86</i>	<i>Test Method for Stress Wave Energy Measurement for Dynamic Penetrometer Testing Systems, Discontinued 1998</i>
D 4638 – 86	Guide for Preparation of Biological Samples for Inorganic Chemical Analysis (Vol 11.01)
D 4643 – 93	Method for Determination of Water (Moisture) Content of Soil by the Microwave Oven Method
D 4645 – 87	Test Method for Determination of the In-Situ Stress in Rock Using the Hydraulic Fracturing Method
D 4647 – 94	Test Method for Identification and Classification of Dispersive Clay Soils by the Pinhole Test
D 4648 – 94	Test Method for Laboratory Miniature Vane Shear Test for Saturated Fine-Grained Clayey Soil
D 4687 – 87	Guide for General Planning of Waste Sampling (Vol 11.04)
D 4696 – 92	Guide for Pore-Liquid Sampling from the Vadose Zone
D 4700 – 91	Guide for Soil Sampling from the Vadose Zone
D 4719 – 87	Test Method for Pressuremeter Testing in Soils
D 4729 – 87	Test Method for In Situ Stress and Modulus of Deformation Using the Flatjack Method



D 4750 – 87	Test Method for Determining Subsurface Liquid Levels in a Borehole or Monitoring Well (Observation Well)
<del>D 4767 – 88</del>	<del>Test Method for Consolidated Undrained Triaxial Compression Test on Cohesive Soils</del>
<u>D 4767 – 02</u>	<u>Test Method for Consolidated Undrained Triaxial Compression Test on Cohesive Soils</u>
D 4793 – 93	Test Method for Sequential Batch Extraction of Waste with Water (Vol 11.04)
D 4822 – 88	Guide for Selection of Methods of Particle Size Analysis of Fluvial Sediments (Manual Methods) (Vol 11.02)
D 4823 – 95	Guide for Core-Sampling Submerged, Unconsolidated Sediments (Vol 11.02)
D 4840 – 99	Guide for Sample Chain of Custody Procedure (Vol 11.01)
D 4841 – 88	Practice to Estimation of Holding Time for Water Samples Containing Organic and Inorganic Constituents (Vol 11.01)
D 4842 – 90	Test Method for Determining the Resistance of Solid Wastes to Freezing and Thawing (Vol 11.04)
D 4843 – 88	Test Method for Wetting and Drying Test of Solid Waste (Vol 11.04)
D 4844 – 88	Guide for Air Monitoring at Waste Management Facilities for Worker Protection (Vol 11.04)
D 4861 – 00	Practice for Sampling and Selection of Analytical Techniques for Pesticides and Polychlorinated Biphenyls in Air (Vol 11.03)
<del>D 4879 – 89</del>	<del>Guide for Geotechnical Mapping of Large Underground Openings in Rock</del>
<u>D 4879 – 02</u>	<u>Guide for Geotechnical Mapping of Large Underground Openings in Rock</u>
D 4914 – 89	Test Method for Density of Soil and Rock in Place by the Sand Replacement Method in a Test Pit, (soils with particles larger than 3 in. (76 mm))
<del>D 4943 – 95</del>	<del>Test Method for Shrinkage Factors of Soils by the Wax Method</del>
<u>D 4943 – 02</u>	<u>Test Method for Shrinkage Factors of Soils by the Wax Method</u>
D 4944 – 98	Test Method for Field Determination of Water (Moisture) Content of Soil by the Calcium Carbide Gas Pressure Tester Method
D 4959 – 89	Test Method for Determination of Water (Moisture) Content of Soil by Direct Heating Method
<del>D 4971 – 89</del>	<del>Test Method for Determining the In-Situ Modulus of Deformation of Rock Using the Diametrically Loaded 76-mm (3-in.) Borehole Jack</del>
<u>D 4971 – 02</u>	<u>Test Method for Determining the In-Situ Modulus of Deformation of Rock Using the Diametrically Loaded 76-mm (3-in.) Borehole Jack</u>
D 4972 – 95a	Test Method for pH of Soils
D 4978 – 95	Test Method for Screening of Reactive Sulfide in Waste (Vol 11.04)
D 4979 – 95	Test Method for Physical Description Screening Analysis in Waste (Vol 11.04)
D 4980 – 89	Test Method for Screening of pH in Waste (Vol 11.04)
D 4981 – 89	Test Method for Screening of Oxidizers in Waste (Vol 11.04)
D 4982 – 89	Test Method for Flammability Potential Screening Analysis of Waste (Vol 11.04)
D 5012 – 89	Guide for Preparation of Materials Used for the Collection and Preservation of Atmospheric Wet Deposition (Vol 11.03)
D 5013 – 89	Practices for Sampling Wastes from Pipes and Other Point Discharges (Vol 11.04)
D 5030 – 89	Test Method for Density of Soil and Rock in Place by the Water Replacement Method in a Test Pit
<i>D 5049 – 90</i>	<i>Test Method for Screening of Cyanides in Waste (Vol 11.04), Discontinued 1999</i>
D 5057 – 90	Test Method for Screening of Apparent Specific Gravity and Bulk Density of Waste (Vol 11.04)
D 5059 – 98	Test Methods for Compatibility Screening Analysis of Waste (Vol 11.04)
<del>D 5073 – 90</del>	<del>Practice for Depth Measurement of Surface Water (Vol 11.02)</del>
<u>D 5073 – 02</u>	<u>Practice for Depth Measurement of Surface Water (Vol 11.02)</u>
<del>D 5089 – 90</del>	<del>Test Method for Velocity Measurements of Water in Open Channels with Electromagnetic Current Meters (Vol 11.04)</del>
<u>D 5079 – 02</u>	<u>Test Method for Velocity Measurements of Water in Open Channels with Electromagnetic Current Meters (Vol 11.04)</u>
<del>D 5079 – 90</del>	<del>Practices for Preserving and Transporting Rock Core Samples</del>

<u>D 5080 – 93</u>	<u>Test Method for Rapid Determination of Percent Compaction</u>
<u>D 5084 – 90</u>	<u>Test Method for Hydraulic Conductivity of Saturated Porous Materials Using a Flexible Wall Permeameter (low permeability materials <math>&lt;1 \times 10^{-3}</math> cm/s)</u>
<u>D 5088 – 02</u>	<u>Practice for Decontamination of Field Equipment Used at NonRadioactive Waste Sites</u>
<u>D 5088 – 90</u>	<u>Practice for Decontamination of Field Equipment Used at NonRadioactive Waste Sites</u>
<u>D 5089 – 90</u>	<u>Test Method for Velocity Measurements of Water in Open Channels with Electromagnetic Current Meters (Vol 11.01)</u>
<u>D 5092 – 90</u>	<u>Recommended Practice for Design and Installation of Ground Water Monitoring Wells in Aquifers</u>
<u>D 5092 – 02</u>	<u>Recommended Practice for Design and Installation of Ground Water Monitoring Wells in Aquifers</u>
<u>D 5093 – 90</u>	<u>Test Method for Field Measurement of Infiltration Rate Using a Double-Ring Infiltrometer with a Sealed-Inner Ring</u>
<u>D 5093 – 02</u>	<u>Test Method for Field Measurement of Infiltration Rate Using a Double-Ring Infiltrometer with a Sealed-Inner Ring</u>
<u>D 5096 – 96</u>	<u>Test Method for Determining the Performance of a Cup Anemometer or Propeller Anemometer (Vol 11.03)</u>
<u>D 5096 – 02</u>	<u>Test Method for Determining the Performance of a Cup Anemometer or Propeller Anemometer (Vol 11.03)</u>
<u>D 5111 – 99</u>	<u>Guide for Choosing Locations and Sampling Methods to Monitor Atmospheric Deposition at Non-Urban Locations (Vol 11.03)</u>
<u>D 5126 – 90</u>	<u>Guide for Comparison of Field Methods for Determining Hydraulic Conductivity in the Vadose Zone (saturated: single-/double-ring infiltrometer, double-tube, air-entry permeameter, borehole permeameter (constant head-borehole infiltration, Guelph permeameter), empirical; unsaturated: instantaneous profile, crust, empirical)</u>
<u>D 5129 – 95</u>	<u>Test Method for Open Channel Flow Measurement of Water Indirectly by Using Width Contractions (Vol 11.01)</u>
<u>D 5130 – 95</u>	<u>Test Method for Open Channel Flow Measurement of Water Indirectly by Slope-Area Method (Vol 11.01)</u>
<u>D 5143 – 91</u>	<u>Test Method for Analysis of Nitroaromatic and Nitramine Explosive in Soil by High Performance Liquid Chromatography</u>
<u>D 5195 – 94</u>	<u>Test Method for Determination of Density of Soil and Rock In-Place at Depths Below the Surface by Nuclear Methods (gamma-gamma, <math>&gt;12</math> in. (305 mm))</u>
<u>D 5195 – 02</u>	<u>Test Method for Determination of Density of Soil and Rock In-Place at Depths Below the Surface by Nuclear Methods (gamma-gamma, <math>&gt;12</math> in. (305 mm))</u>
<u>D 5220 – 92</u>	<u>Test Method for Water Content of Soil and Rock In-Place by the Neutron Depth Probe Method</u>
<u>D 5220 – 02</u>	<u>Test Method for Water Content of Soil and Rock In-Place by the Neutron Depth Probe Method</u>
<u>D 5232 – 92</u>	<u>Test Method for Determining the Stability and Miscibility of a Solid, Semi-Solid, or Liquid Waste Material (Vol 11.04)</u>
<u>D 5233 – 92</u>	<u>Test Method for Single Batch Extraction Methods for Wastes (Vol 11.04)</u>
<u>D 5239 – 98</u>	<u>Practice for Characterizing Fly Ash for Use in Soil Stabilization</u>
<u>D 5241 – 92</u>	<u>Practice for Micro-Extraction of Water for the Analysis of Volatile and Semi-Volatile Organic Compounds in Water (Vol 11.02)</u>
<u>D 5242 – 92</u>	<u>Test Method for Open Channel Flow Measurement of Water Indirectly at Culverts (Vol 11.01)</u>
<u>D 5243 – 92</u>	<u>Test Method for Open Channel Flow Measurements of Water Indirectly at Culverts (Vol 11.01)</u>
<u>D 5435 – 93</u>	<u>Test Method for Diagnostic Soil Test for Plant Growth and Food Chain Protection</u>
<u>D 5254 – 92</u>	<u>Practice for the Minimum Set of Data Elements to Identify a Ground Water Site</u>
<u>D 5255 – 01</u>	<u>Practice for Certification of Personnel Engaged in the Testing of Soil and Rock</u>
<u>D 5269 – 96</u>	<u>Test Method for Determining Transmissivity of Non-Leaky Confined Aquifers by the Theis Recovery Method</u>
<u>D 5270 – 96</u>	<u>Test Method for Determining Transmissivity and Storage Coefficient of Bounded, Nonleaky Confined Aquifers</u>
<u>D 5283 – 92</u>	<u>Practice for Generation of Environmental Data Related to Waste Management Activities: Quality Assurance and Quality Control Planning and Implementation (Vol 11.04)</u>
<u>D 5284 – 93</u>	<u>Test Method for Sequential Batch Extraction of Waste with Acidic Extraction Fluid (Vol 11.04)</u>
<u>D 5298 – 94</u>	<u>Test Method for Measurement of Soil Potential (Suction) Using Filter Paper</u>



D 5299 – 92	Guide for the Decommissioning of Ground Water Wells, Vadose Zone Monitoring Devices, Boreholes and Other Devices for Environmental Activities
D 5311 – 92	Test Method for Load Controlled Cyclic Triaxial Strength of Soil
D 5314 – 92	Guide for Soil Gas Monitoring in the Vadose Zone
D 5334 – 00	Test Method for Determination of Thermal Conductivity of Soil and Rock by Thermal Needle Probe Procedure
D 5335 – 99	Test Method for Linear Coefficient of Thermal Expansion of Rock Using Bonded Electric Resistance Strain Gages
D 5337 – 97	Practice for Flow Rate for Calibration of Personal Sampling Pumps (Vol 11.03)
D 5358 – 93	Practice for Sampling with a Dipper or Pond Sampler (Vol 11.04)
D 5366 – 96	Test Method for Determining the Dynamic Performance of a Wind Vane (Vol 11.03)
D 5368 – 93	Test Method for the Gravimetric Determination of Total Solvent Extractable Content (TSEC) of Solid Waste Samples (Vol 11.04)
D 5369 – 93	Test Method for the Extraction of Solid Waste Samples for Chemical Analysis Using Soxhlet Extraction (Vol 11.04)
D 5387 – 93	Guide for Elements of a Complete Data Set for Non-Cohesive Sediments (Vol 11.02)
D 5388 – 93	Test Method for Measurement of Discharge by Step-Backwater Method (Vol 11.01)
D 5389 – 93	Test Method for Open Channel Flow Measurement by Acoustic Velocity Meter Systems (Vol 11.02)
D 5390 – 93	Test Method for Open Channel Flow Measurement of Water with Palmer-Bowlus Flumes (Vol 11.02)
D 5407 – 93	Test Method for Elastic Moduli of Undrained Intact Rock Core Specimens in Triaxial Compression Without Pore Pressure Measurement
D 5408 – 93	Guide for the Set of Data Elements to Describe a Ground-Water Site, Part 1—Additional Identification Descriptors
D 5409 – 93	Guide for the Set of Data Elements to Describe a Ground-Water Site, Part 2—Physical Descriptors
D 5410 – 93	Guide for the Set of Data Elements to Describe a Ground-Water Site, Part 3—Usage Descriptors
D 5413 – 93	Test Methods for Measurement of Water Levels in Open-Water Bodies (Vol 11.01)
D 5434 – 93	Guide for Field Logging of Subsurface Explorations of Soil and Rock
D 5447 – 93	Guide for Application of a Ground-Water Flow Model to a Site Specific Problem
D 5451 – 93	Practice for Sampling Using a Trier Sampler (Vol 11.04)
<del>D 5462 – 93</del>	<del>Test Method for On-Line Measurement of Low Level Dissolved Oxygen in Water (Vol 11.01)</del>
<u>D 5462 – 02</u>	<u>Test Method for On-Line Measurement of Low Level Dissolved Oxygen in Water (Vol 11.01)</u>
D 5463 – 93	Guide for the Use of Test Kits to Measure Inorganic Constituents in Water (Vol 11.02)
D 5464 – 93	Test Methods for pH Measurement of Water of Low Conductivity (Vol 11.01)
D 5465 – 93	Practices for Counting, Calculating, and Reporting Microbial Colonies in Water (Vol 11.02)
D 5466 – 93	Test Methods for the Determination of Volatile Organic Chemicals in Atmospheres (Canister Sampling Methodology) (Vol 11.03)
D 5472 – 93	Test Method for Determining Specific Capacity and Estimating Transmissivity at the Control Well
D 5473 – 93	Test Method (Analytical Procedure) for Analyzing the Effects of Partial Penetration of Control Well and Determining the Horizontal and Vertical Hydraulic Conductivity in a Non-leaky Aquifer
D 5474 – 93	Guide for Selection of Data Elements for Ground-Water Investigations
D 5490 – 93	Guide for Comparing Ground-Water Flow Model Simulations to Site-Specific Information
D 5495 – 94	Practice for Sampling with a Composite Liquid Waste Sampler (COLIWASA) (Vol 11.04)
D 5518 – 94	Guide for Acquisition of File Aerial Photography and Imagery for Establishing Historic Site-Use and Surficial Conditions
D 5520 – 94	Test Method for Laboratory Determination of Creep Properties of Frozen Soil Samples by Uniaxial Compression
D 5521 – 94	Guide for Development of Ground-Water Monitoring Wells in Granular Aquifers



D 5522 – 99a	Specification for Minimum Requirements for Laboratories Engaged in Chemical Analysis of Soil, Rock and Contained Fluid
D 5527 – 94	Practice for Measuring Surface Wind and/or Temperature by Acoustic Means (Vol 11.03)
D 5540 – 94a	Practice for Flow Control and Temperature Control for On-Line Water Sampling and Analysis (Vol 11.01)
D 5541 – 94	Practice for Developing a Stage-Discharge Relation for Open Channel Flow (Vol 11.01)
D 5542 – 94	Test Methods for Low Level Dissolved Oxygen in Water (Vol 11.01)
D 5549 – 94	Guide for Reporting Geostatistical Site Investigations
D 5550 – 00	Test Method for Specific Gravity of Soils Solids by Gas Pycnometer
<del>D 5607 – 95</del>	<del>Test Method for Performing Laboratory Direct Shear Strength Tests of Rock Specimens under Constant Normal Force</del>
<u>D 5607 – 02</u>	<u>Test Method for Performing Laboratory Direct Shear Strength Tests of Rock Specimens under Constant Normal Force</u>
D 5608 – 94	Standard Practice for the Decontamination of Field Equipment Used at Low Level Radioactive Waste Sites
D 5609 – 94	Guide for Defining Boundary Conditions in Ground-Water Flow Modeling
D 5610 – 94	Guide for Defining Initial Conditions in Ground-Water Flow Modeling
D 5611 – 94	Guide for Conducting a Sensitivity Analysis for a Ground-Water Flow Model Application
D 5612 – 94	Guide for the Quality Planning and Field Implementation of a Water Quality Measurement Program (Vol 11.01)
D 5613 – 94	Test Method for Open Channel Measurements of Time of Travel Using Dye Tracers (Vol 11.02)
D 5614 – 94	Test Method for Open Channel Flow Measurement of Water with Broad-Crested Weirs (Vol 11.02)
D 5633 – 94	Practice for Sampling with a Scoop (Vol 11.04)
D 5640 – 95	Guide for Selection of Weirs and Flumes for Open Channel Flow Measurement of Water (Vol 11.02)
D 5658 – 95	Practice for Sampling Unconsolidated Waste from Trucks (Vol 11.04)
D 5674 – 95	Guide for Operations of a Gaging Station (Vol 11.02)
D 5679 – 95a	Practice for Sampling Consolidated Solids in Drums or Similar Containers (Vol 11.04)
D 5680 – 95a	Practice for Sampling Unconsolidated Solids in Drums or Similar Containers (Vol 11.04)
D 5681 – 98a	Terminology for Waste and Waste Management (Vol 11.04)
D 5714 – 95	Specification for Digital Geospatial Metadata
D 5715 – 95	Test Method for Estimating the Degree of Humification of Peat and Other Organic Soils (Visual/Manual Method)
D 5716 – 95	Test Method to Measure the Rate of Well Discharge by Circular Orifice Weir
D 5717 – 95	Guide for the Design of Ground-Water Monitoring Systems in Karst and Fractured-Rock Aquifers
D 5718 – 95	Guide for Documenting a Ground-Water Flow Model Application
D 5719 – 95	Guide to Simulation of Subsurface Air Flow Using Ground-Water Flow Modeling Codes
D 5720 – 95	Practice for Static Calibration of Electronic Transducer-Based Pressure Measurements Systems for Geotechnical Purposes
<del>D 5731 – 95</del>	<del>Test Method for Determination of the Point Load Strength Index of Rock</del>
<u>D 5731 – 02</u>	<u>Test Method for Determination of the Point Load Strength Index of Rock</u>
D 5737 – 95	Guide to Methods for Measuring Well Discharge
D 5738 – 95	Guide for Displaying the Results of Chemical Analyses of Ground Water for Major Ions and Trace Elements—Diagrams for Single Analyses
D 5741 – 96	Practice for Characterizing Surface Wind Using a Wind Vane and Rotating Anemometer (Vol 11.03)
D 5743 – 95	Practice for Sampling Single or Multilayered Liquids, With or Without Solids in Drums or Similar Containers (Vol 11.04)
D 5745 – 95	Guide for Developing and Implementing Short-Term Measures or Early Actions for Site Remediation (Vol 11.04)
D 5746 – 98	Classification of Environmental Condition of Property Area Types (Vol 11.04)
D 5753 – 95	Guide for Planning and Conducting Borehole Geophysical Logging



D 5754 – 95	Guide for Displaying the Results of Chemical Analyses of Ground Water for Major Ions and Trace Elements—Trilinear and Other Multi-Coordinate Diagrams
D 5759 – 95	Guide for Characterization of Coal Fly Ash and Clean Coal Combustion Fly Ash for Potential Use (Vol 11.04)
D 5765 – 95	Practice for Solvent Extraction of Total Petroleum Hydrocarbons from Soils and Sediments Using Closed Vessel Microwave Heating (Vol 11.01)
D 5777 – 95	Guide for Using the Seismic Refraction Method for Subsurface Investigations
D 5778 – 95	Test Method for Performing Electric Friction Cone and Piezocone Penetration Testing of Soils
D 5781 – 95	Guide for Use of Dual-Wall Reverse-Circulation Drilling for Geoenvironmental Exploration and Installation of Subsurface Water-Quality Monitoring Devices
D 5782 – 95	Guide for Use of Direct Air-Rotary Drilling for Geoenvironmental Exploration and Installation of Subsurface Water-Quality Monitoring Devices
D 5783 – 95	Guide for Use of Direct Rotary Drilling with Water-Based Drilling Fluid for Geoenvironmental Exploration and Installation of Subsurface Water-Quality Monitoring Devices
D 5784 – 95	Guide for Use of Hollow-Stem Augers for Geoenvironmental Exploration and Installation of Subsurface Water-Quality Monitoring Devices
D 5785 – 95	Test Method (Analytical Procedure) for Determining Transmissivity of Confined Nonleaky Aquifers by Under-Damped Well Response to Instantaneous Change in Head (Slug Test)
D 5786 – 95	Practice (Field Procedure) for Constant Drawdown Tests in Flowing Wells for Determining Hydraulic Properties of Aquifer Systems
D 5787 – 95	Practice for Monitoring Well Protection
D 5789 – 95	Practice for Writing Quality Control Specifications for Standard Test Methods for Organic Constituents (Vol 11.01)
D 5791 – 95	Guide for Using Probability Sampling Methods in Studies of Indoor Air Quality of Buildings (Vol 11.03)
<del>D 5792 – 95</del>	<del>Practice for Generation of Environmental Data Related to Waste Management Activities: Development of Data Quality Objectives (Vol 11.04)</del>
<u>D 5792 – 02</u>	<u>Practice for Generation of Environmental Data Related to Waste Management Activities: Development of Data Quality Objectives (Vol 11.04)</u>
D 5829 – 96	Guide for Preparing a Training Program for Environmental Analytical Laboratories (Vol 11.04)
D 5831 – 96	Test Method for Screening Fuels in Soils (Vol 11.04)
D 5835 – 95	Practice for Sampling Stationary Source Emissions for the Automated Determination of Gas Concentrations (Vol 11.03)
D 5850 – 95	Test Method for (Analytical Procedure) for Determining Transmissivity, Storage Coefficient, and Anisotropy Ratio from a Network of Partially Penetrating Wells
D 5851 – 95	Guide for Planning and Implementing a Water Monitoring Program (Vol 11.02)
D 5852 – 95	Test Method for Erodibility Determination of Soil in the Field or in the Laboratory by the Jet Index Method
D 5855 – 95	Test Method for (Analytical Procedure) for Determining Transmissivity and Storage Coefficient of a Confined Nonleaky or Leaky Aquifer by the Constant Drawdown Method in a Flowing Well
D 5856 – 95	Test Method for Measurement of Hydraulic Conductivity of Porous Material Using a Rigid-Wall, Compaction-Mold Permeameter
D 5872 – 95	Guide for Use of Casing Advancement Drilling Methods for Geoenvironmental Exploration and Installation of Subsurface Water-Quality Monitoring Devices
D 5873 – 00	Test Method for Determination of Rock Hardness by the Rebound Hammer Method
<del>D 5874 – 95</del>	<del>Test Method for Determination of the Impact Value (IV) of a Soil</del>
<u>D 5874 – 02</u>	<u>Test Method for Determination of the Impact Value (IV) of a Soil</u>
D 5875 – 95	Guide for Use of Cable-Tool Drilling and Sampling Methods for Geoenvironmental Exploration and Installation of Subsurface Water-Quality Monitoring Devices
D 5876 – 95	Guide for Use of Direct Rotary Wireline Casing Advancement Drilling Methods for Geoenvironmental Exploration and Installation of Subsurface Water-Quality Monitoring Devices

D 5877 – 95	Guide for Displaying the Results of Chemical Analyses of Ground Water for Major Ions and Trace Elements—Diagrams Based on Data Analytical Calculations
D 5878 – 00	Guide for Using Rock-Mass Classification Systems for Engineering Purposes
D 5879 – 95	Practice for Surface Site Characterization for On-Site Septic Systems
D 5880 – 95	Guide for Subsurface Flow and Transport Modeling
D 5881 – 95	Test Method (Analytical Procedure) for Determining Transmissivity of Confined Nonleaky Aquifers by Critically Damped Well Response to Instantaneous Change in Head (Slug Test)
D 5903 – 96	Guide for Planning and Preparing for a Ground-Water Sampling Event
D 5905 – 98	Specification for Substitute Wastewater (Vol 11.01)
<u>D 5906 – 02</u>	<u>Guide for Measuring Horizontal Positioning During Measurements of Surface Water Depths</u>
D 5907 – 96a	Test Method for Filterable and Non-Filterable Matter in Water (Vol 11.01)
D 5909 – 96a	Guide for Measuring Horizontal Positioning During Measurements of Surface Water Depths (Vol 11.01)
D 5911 – 96	Practice for a Minimum Set of Data Elements to Describe a Soil Sampling Site
D 5912 – 96	Test Method (Analytical Procedure) for Determining Hydraulic Conductivity of an Unconfined Aquifer by Overdamped Well Response to Instantaneous Change in Head (Slug Test)
D 5918 – 96	Test Methods for Frost Heave and Thaw Weakening Susceptibility of Soils
D 5920 – 96	Test Method (Analytical Procedure) for Tests of Anisotropic Unconfined Aquifers by the Neuman Method
D 5921 – 96	Practice for Subsurface Site Characterization of Test Pits for On-Site Septic Systems
D 5922 – 96	Guide for Analysis of Spatial Variation in Geostatistical Site Investigations
D 5923 – 96	Guide for the Selection of Kriging Methods in Geostatistical Site Investigations
D 5924 – 96	Guide for the Selection of Simulation Approaches in Geostatistical Site Investigations
D 5925 – 96	Practice for Preliminary Sizing and Delineation of Soil Absorption Field Areas for On-Site Septic Systems
D 5928 – 96	Test Method for the Screening of Waste for Radioactivity (Vol 11.04)
D 5956 – 96	Guide for Sampling Strategies for Heterogeneous Wastes (Vol 11.04)
D 5978 – 96	Guide for Maintenance and Rehabilitation of Ground Water Monitoring Wells
D 5979 – 96	Guide for Conceptualization and Characterization of Ground Water Flow Systems
D 5980 – 96	Guide for Selection and Documentation of Existing Wells for Use in Environmental Site Characterization and Monitoring
D 5981 – 96	Guide for Calibrating a Ground-Water Flow Model Application
D 5995 – 98	Guide for Environmental Site Characterization in Cold Regions
D 6000 – 96	Guide for the Presentation of Water-Level Information From Ground Water Sites
D 6001 – 96	Guide for Direct Push Water Sampling for Geoenvironmental Investigations
D 6008 – 96	Practice for Conducting Environmental Baseline Surveys (Vol 11.04)
D 6009 – 96	Guide for Sampling Waste Piles (Vol 11.04)
D 6011 – 96	Test Method for Determining the Performance of a Sonic Anemometer/Thermometer (Vol 11.03)
D 6025 – 96	Guide for Developing and Evaluating Ground-Water Modeling Codes
D 6026 – 99	Practice for Using Significant Digits in Calculating and Reporting Geotechnical Test Data
D 6027 – 96	Practice for Calibrating Linear Displacement Transducers for Geotechnical Purposes
D 6028 – 96	Test Method (Analytical Procedure) for Determining Hydraulic Properties of a Confined Aquifer Taking Into Consideration Storage of Water in Leaky Confining Beds by the Modified Hantush Method
D 6029 – 96	Test Method (Analytical Procedure) for Determining Hydraulic Properties of a Confined Aquifer and a Leaky Confining Bed With Negligible Storage by the Hantush-Jacob Method



D 6030 – 96	Guide to Selection of Methods for Assessing Ground Water or Aquifer Sensitivity and Vulnerability
D 6031 – 96	Test Method for Logging In Situ Moisture Content and Density of Soil and Rock by the Nuclear Method in Horizontal, Slanted and Vertical Tubes
<del>D 6032 – 96</del>	<del>Test Method for Determining Rock Quality Designation (RDQ) of Rock Core</del>
<u>D 6032 – 02</u>	<u>Test Method for Determining Rock Quality Designation (RDQ) of Rock Core</u>
D 6033 – 96	Guide for Describing the Functionality of a Ground-Water Modeling Code
D 6034 – 96	Test Method (Analytical Procedure) for Determining the Efficiency of a Production Well in A Confined Aquifer From a Constant Rate Pumping Test
<del>D 6035 – 96</del>	<del>Test Method for Determining the Effect of Freeze-Thaw on the Hydraulic Conductivity of Compacted or Undisturbed Soil Specimens Using a Flexible Wall Permeameter</del>
<u>D 6035 – 02</u>	<u>Test Method for Determining the Effect of Freeze-Thaw on the Hydraulic Conductivity of Compacted or Undisturbed Soil Specimens Using a Flexible Wall Permeameter</u>
D 6036 – 96	Guide for Displaying the Results of Chemical Analyses of Ground Water for Major Ions and Trace Elements—Use of Maps
D 6044 – 96	Guide for Representative Sampling and Management of Waste and Contaminated Media (Vol 11.04)
D 6051 – 96	Guide for Composite Sampling and Field Subsampling For Environmental Waste Management Activities (Vol 11.04)
D 6061 – 96	Practice for Evaluating the Performance of Respirable Aerosol Samplers (Vol 11.03)
D 6062M – 96	Guide for Personal Samplers of Health-Related Aerosol Fractions (Metric) (Vol 11.01)
D 6063 – 96	Guide for Sampling of Drums and Similar Containers By Field Personnel (Vol 11.04)
D 6066 – 96	Practice for Determining the Normalized Penetration Resistance of Sand for Liquefaction Potential Evaluation
D 6067 – 96	Guide for Using the Electronic Cone Penetrometer for Environmental Site Characterization
D 6089 – 97	Guide for Documenting a Ground-Water Sampling Event
D 6106 – 97	Guide for Establishing the Nomenclature of Ground-Water Aquifers
D 6145 – 97	Guide for Monitoring Sediment in Watersheds (Vol 11.02)
D 6146 – 97	Guide for Monitoring Aqueous Nutrients in Watersheds (Vol 11.02)
D 6151 – 97	Practice for Using Hollow-Stem Augers for Geotechnical Exploration and Soil Sampling
D 6167 – 97	Guide for Conducting Borehole Geophysical Logging-Mechanical Caliper
D 6168 – 97	Guide for Selection of the Minimum Set of Data Elements Required to Identify Locations Chosen for the Field Collection of Information to Describe Soil, Rock, and their Contained Fluids
D 6169 – 98	Guide for Selection of Soil and Rock Sampling Devices Used with Drill Rigs for Environmental Investigations
D 6170 – 97	Guide for Selecting a Ground-Water Modeling Code
D 6171 – 97	Guide for Documenting a Ground-Water Modeling Code
D 6176M – 97	Practice for Measuring Surface Atmospheric Temperature with Electrical Temperature Sensors (Metric) (Vol 11.03)
D 6187 – 97	Practice for Cone Penetrometer Technology Characterization of Petroleum Contaminated Site with Nitrogen Laser-Induced Fluorescence
D 6196 – 97	Practice for Selection of Sorbents and Pumped Sampling/Thermal Desorption Analysis Procedures for Volatile Organic Compounds In Air (Vol 11.03)
D 6209 – 98	Test Method for Determination of Gaseous and Particulate Polycyclic Aromatic Hydrocarbons in Ambient Air (Collection on sorbent-Backed Filters with Gas Chromatographic/Mass Spectrometric Analysis) (Vol 11.03)
D 6232 – 00	Guide for Selection of Sampling Equipment for Waste and Contaminated Media Data Collection Activities (Vol 11.04)
D 6233 – 98	Guide for Data Assessment for Environmental Waste Management Activities (Vol 11.04)
D 6235 – 98a	Practice for Expedited Site Characterization of Vadose Zone and Ground Water Contamination at Hazardous Waste Contaminated Sites
D 6236 – 98	Guide for Coring and Logging Cement-or Lime- Stabilized Soil
<del>D 6246 – 98</del>	<del>Practice for Evaluating the Performance of Diffusive Samplers (Vol 11.03)</del>



D 6246 – 02	<u>Practice for Evaluating the Performance of Diffusive Samplers (Vol 11.03)</u>
D 6250 – 98	Practice for Derivation of Decision Point and Confidence Limit for Statistical Testing of Mean Concentration in Waste Management Decisions (Vol 11.04)
D 6274 – 98	Guide for Conducting Borehole Geophysical Logging-Gamma
D 6282 – 98	Guide for Direct Push Soil Sampling for Environmental Site Characterizations
D 6285 – 99	Guide for SLocating Abandoned Wells
D 6286 – 98	Guide for Selection of Drilling Methods for Environmental Site Characterization
D 6311 – 98	Guide for Generation of Environmental Data Related to Waste Management Activities: Selection and Optimization of Sampling Design (Vol 11.04)
D 6312 – 98	Guide for Developing Appropriate Statistical Approaches for Ground-Water Detection Monitoring Programs
D 6318 – 98	Practice for Calibrating a Fathometer Using a Bar Check Method (Vol 11.01)
D 6323 – 98	Guide for Laboratory Subsampling of Media Related to Waste Management Activities (Vol 11.04)
D 6326 – 98	Practice for the Selection of Maximum Transit-Rate Ratios and Depths for the U.S. Series of Isokinetic Suspended-Sediment Samplers (Vol 11.01)
D 6331 – 98	Test Method for Determination of Mass Concentration of Particulate Matter from Stationary sources at Low Concentrations Manual Gravimetric Method (Vol 11.03)
D 6345 – 98	Guide for Selection of Method for Active, Integrative Sampling of Volatile Organic Compounds in Air (Vol 11.03)
D 6348 – 98	Test Method for Determination of Gaseous Compounds by Extractive Direct Interface Fourier Transform Infrared FTIR Spectroscopy (Vol 11.03)
D 6391 – 99	Test Method for Field Measurement of Hydraulic Conductivity Limits of Porous Materials Using Two Stages of Infiltration from a Borehole
D 6418 – 99	Practice for Using the Disposable En-Core Sampler for Sampling and Storing Soil For Volatile Organic Analysis (Vol 11.04)
D 6429 – 99	Guide for Selecting Surface Geophysical Methods
D 6430 – 99	Guide for Using the Gravity Method for Subsurface Investigation
D 6431 – 99	Guide for Using the Direct Current Resistivity Method for Subsurface Investigation
D 6432 – 99	Guide for Using the Surface Ground Penetrating Radar Method for Subsurface Investigation
D 6452 – 99	Guide for Purging Methods for Wells Used for Ground-Water Quality Investigations
D 6453 – 99	Guide for Format of Computerized Exchange of Soil and Rock Test Data
D 6467 – 99	Test Method for Torsional Ring Shear Test to Determine Drained Residual Shear Strength of Cohesive Soils
D 6517 – 00	Guide for Field Preservation of Ground-Water Samples
<del>D 6519 – 00</del>	<del>Practice for Sampling of Soils Using Hydraulically Operated Stationary Piston Sampler</del>
<u>D 6519 – 02</u>	<u>Practice for Sampling of Soils Using Hydraulically Operated Stationary Piston Sampler</u>
D 6527 – 00	Test Method for Determining Unsaturated and Saturated Hydraulic Conductivity in Porous Media by State-State Centrifugation
D 6528 – 00	Test Method for Consolidated Undrained Direct Simple Shear Testing of Cohesive Soils
D 6538 – 00	Guide for Sampling Wastewater with Automatic Samplers (Vol 11.04)
D 6539 – 00	Test Method for Measurement of Pneumatic Permeability of Partially Saturated Porous Materials by Flowing Air
D 6552 – 00	Practice for Controlling and Characterizing Errors in Weighing Collected Aerosols (Vol 11.03)
D 6564 – 00	Guide for Field Filtration of Ground-Water Samples
D 6565 – 00	Test Method for Determination of Water (Moisture) Content of Soil by the Time-Domain Reflectometry (TDR) Method
D 6568 – 006	Guide for Planning, Carrying Out, and Reporting Traceable Chemical Analyses of Water Samples (Vol 11.01)
D 6569 – 00	Test Method for On-Line Measurement of pH (Vol 11.01)
D 6572 – 00	Test Method for Determining Dispersive Characteristics of Clayey Soils by the Crumb Test
D 6582 – 00	Guide for Ranked Set Sampling: Efficient Estimation of a Mean Concentration in Environmental Sampling (Vol 11.04)



D 6597 – 00	Practice for Assessment of Attaining Clean Up Level for Site Closure (Vol 11.04)
D 6634 – 01	Guide for the Selection of Purging and Sampling Devices for Ground-Water Monitoring Wells
D 6639 – 01	Guide for Using the Frequency Domain Electromagnetic Method for Subsurface Investigations
D 6640 – 01	Practice for Collection and Handling of Soils Obtained in Core Barrel Samplers for Environmental Investigations
D 6642 – 01	Guide for Comparison of Techniques to Quantify the Soil-Water Moisture Flux
D 6661 – 01	Practice for Field Collection of Organic Compounds from Surfaces Using Wipe Sampling
D 6698 – 01	Test Method for On-Line Measurement of Turbidity Below 5 NTU in Water
D 6699 – 01	Practice for Sampling Liquids Using Bailers
D 6726 – 01	Guide for Conducting Borehole Geophysical Logging-Electromagnetic Induction
D 6727 – 01	Guide for Conducting Borehole Geophysical Logging-Neutron
D 6759 – 02	Practice for Sampling Liquids Using Grab and Discrete Depth Samplers
D 6764 – 02	Guide for Collection Water Temperature, Dissolved-Oxygen Concentrations, Specific Electrical Conductance, and pH Data from Open Channels
D 6820 – 02	Guide for Use of the Time Domain Electromagnetic Method for Subsurface Investigation
D 6836 – 02	Test Methods for Determination of the Soil Water Characteristic Curve for Desorption Using a Hanging Column, Pressure Extractor, Chilled Mirror Hygrometer, and/or Centrifuge
D 6724 – 01	Guide for Installation of Direct Push Ground Water Monitoring Wells
D 6725 – 01	Practice for Direct Push Installation of Prepacked Screen Monitoring Wells in Unconsolidated Aquifers
D 6758 – 02	Test Method for Measuring Stiffness and Apparent Modulus of Soil and Soil-Aggregate In-Place by an Electro-Mechanical Method
D 6771 – 02	Practice for Low-Flow Purging and Sampling for Wells and Devices Used for Ground-Water Quality Investigations
D 6780 – 02	Test Method for Water Content and Density of Soil by Time Domain Reflectometry (TDR)
D 6843 – 02	Guide for Designing Cost-Effective Sampling and Measurement Plans by Use of Estimated Uncertainty and Its Components in Waste Management Decision-Making (Vol 11.04)
D 6950 – 03	Guide for QC of Screening Methods in Water (Vol 11.02)
<del>E 105 – 58</del>	<del>Practice for Probability Sampling of Materials (Vold 14.02)</del>
E 105 – 58	Practice for Probability Sampling of Materials (Vol 14.02)
E 170 – 99	Terminology Relating to Radiation Measurements and Dosimetry (Vol 12.02)
E 177 – 90a	Practice for Use of the Terms Precision and Bias in ASTM Test Methods (Vol 14.02)
E 178 – 94	Practice for Dealing with Outlying Observations (Vol 14.02)
E 181 – 98	General Methods for Detector Calibration and Analysis of Radionuclides (Vol 12.02)
E 337 – 84	Test Method of Measuring Humidity with a Psychrometer (the Measurement of Wet- and Dry-Bulb Temperatures) (Vol 11.03)
E 380 – 92	Practice for Use of International System of Unit (SI) (Modernized Metric System) Replaced by IEEE/ASTM SI-10 (Vol 14.02)
E 678 – 98	Practice for Evaluation of Technical Data (Vol 14.02) [Focuses on product liability matters]
E 816 – 95	Test Method for Calibration of Secondary Reference Pyrheliometers and Pyrheliometers for Field Use (Vol 14.04)
E 824 – 94	Test Method for Transfer of Calibration from Reference to Field Pyranometers (Vol 14.04)
E 884 – 82	Practice for Sampling Airborne Microorganisms at Municipal Solid Waste Processing Facilities (Vol 11.04)
E 913 – 82	Method for Calibration of Reference Pyranometers with Axis Vertical by the Shading Method (Vol 12.02)
E 941 – 83	Test Method for Calibration of Reference Pyranometers with Axis Tilted by the Shading Method (Vol 12.02)
E 1109 – 86	Test Method for Determining the Bulk Density of Solid Waste Fractions (Vol 11.04)
E 1167 – 87	Guide for Radiation Protection Programs for Decommissioning Operations (Vol 12.02)
E 1188 – 95	Practice for Collection and Preservation of Information and Physical Items by a Technical Investigator (Vol 14.02)

E 1287 – 89	Guide for Aseptic Sampling of Biological Materials (Vol 11.04)
E 1370 – 96	Guide to Air Sampling Strategies for Worker and Workplace Protection (Vol 11.03)
E 1391 – 94	Guide for Collection, Storage, Characterization, and Manipulation of Sediments for Toxicological Testing (Vol 11.04)
<i>E 1430 – 91</i>	<i>Guide for Using Release Detection Devices with Underground Storage Tanks (Vol 11.04), Discontinued 2000</i>
<u>E 1526 – 93</u>	<u>Practice for Evaluating the Performance of Release Detection Systems for Underground Storage Tank Systems (Vol 11.04), Discontinued 2002</u>
<del>E 1526 – 93</del>	<del>Practice for Evaluating the Performance of Release Detection Systems for Underground Storage Tank Systems (Vol 11.04)</del>
E 1527 – 00	Practice for Environmental Site Assessments: Phase 1 Assessment Process (Vol 11.04)
E 1528 – 00	Practice for Environmental Site Assessment Transaction Screen Process (Vol 11.04)
E 1553 – 93	Practice for the Collection of Airborne Particulate Lead During Abatement and Construction Activities (Vol 04.07)
E 1599 – 94	Guide for Corrective Action for Petroleum Releases (Vol 11.04)
E 1609 – 94	Guide for Development and Implementation of a Pollution Prevention Program (Vol 11.04)
E 1689 – 95	Guide for Developing Conceptual Site Models for Contaminated Sites (Vol 11.05)
E 1739 – 95	Guide for Risk-Based Corrective Action Applied at Petroleum Release Sites (Vol 11.04)
E 1903 – 97	Guide for Environmental Site Assessments: Phase II Environmental Site Assessment Process (Vol 11.04)
E 1912 – 98	Guide for Accelerated Site Characterization for Confirmed or Suspected Petroleum Releases (Vol 11.04)
E 1929 – 98	Practice for Assessment of Certification Programs for Environmental Professional: Accreditation Criteria (Vol 11.04)
E 1943 – 98	Guide for Remediation of Ground Water by Natural Attenuation at Petroleum Release Sites (Vol 11.04)
E 1948 – 98	Guide for Process of Sustainable Brownfields Redevelopment (Vol 11.04)
E 1983 – 98	Guide for Assessment of Wetland Functions (Vol 11.04)
E 1990 – 98	Guide for Performing Evaluations of Underground Storage Tank Systems for Operational Conformance with 40 CFR, Part 280 Regulations (Vol 11.04)
E 1991 – 98	Guide for Environmental Life Cycle Assessment of Building Materials/Products (Vol 11.04)
E 2018 – 99	Guide for Property Assessments: Baseline Property Condition Assessment Process (Vol 11.04)
E 2081 – 00	Guide for Risk—Based Corrective Action (Vol 11.04)
E 2091 – 00	Guide for Use of Activity and Use Limitation, Including Institutional and Engineering Controls (Vol 11.04)
E 2107 – 00	Practice for Environmental Regulatory Compliance Audits (Vol 11.04)
<u>E 2137 – 01</u>	<u>Guide for Estimating Monetary Costs and Liabilities for Environmental Matters (Vol 11.04)</u>
<u>E 2173 – 01</u>	<u>Guide for Disclosure of Environmental Liabilities (Vol 11.04)</u>
<u>E 2205 – 02</u>	<u>Guide for Risk—Based Corrective Action for Protection of Ecological Resources (Vol 11.04)</u>
<u>E 2247 – 02</u>	<u>Practice for Environmental Site Assessments' Phase I Environmental Site Assessment Process for Forestland or Rural Property (Vol 11.04)</u>
<i>ES 38</i>	<i>Guide for Risk-Based Corrective Action Applied at Petroleum Release Sites, Discontinued 1995, Replaced by E 1739</i>
<i>ES 40</i>	<i>Practice for Procedures for the Assessment of Buried Steel Tanks Prior to the Additions of Cathodic Protection (Vol 11.04), Discontinued 1997</i>
F 480 – 99	Specifications for Thermoplastic Water Well Casing Pipe and Couplings Made in Standard Dimension Ratios (SDR) SCH 40 and SCH 80 (Vol 08.04)
F 488 – 95	Test Method for On-Site Screening Heterotrophic Bacteria in Water (Vol 11.02)
F 625 – 94	Practice for Classifying Water Bodies for Spill Control Systems (Vol 11.04)
F 1084 – 90	Guide for Sampling Oil/Water Mixtures for Oil Spill Recovery Equipment (Vol 11.04)
G 51 – 95	Test Method for pH of Soil for Use in Corrosion Testing
G 57 – 95a	Method for Field Measurement of Soil Resistivity Using the Wenner Four-Electrode Method
PS 3 – 95	Guide for Accelerated Site Characterization for Confirmed or Suspected Petroleum Releases (Vol 11.04)

PS 11 – 95	<i>Practice for Environmental Regulatory Compliance Audits (Vol 11.04), Discontinued 1998; see E2107</i>
PS 12 – 95	<i>Guide for the Study and Evaluation of an Organization's Environmental Management Systems (Vol 11.04) Discontinued 1998</i>
PS 14 – 95	<i>Practice for Lifecycle Costing for Pollution Prevention (Vol 11.04), Discontinued 1998</i>
PS 26 – 96	<i>Guide for Development and Implementation of a Source Reduction Program (Vol 11.04), Discontinued 1998</i>
PS 47 – 95	<i>Test Method for Screening, Qualification, and Characterization of Total Polychlorinated Biphenyls by Room Temperature Phosphorescence (Vol 11.02), Discontinued 1998</i>
PS 64 – 96	<i>Guide for Developing Appropriate Statistical Approaches for Ground-Water Detection Monitoring Programs, Discontinued 1998; Replaced by D6312</i>
PS 78 – 97	<i>Guide for Selecting Surface Geophysical Methods, Discontinued 2000; Replaced by D6429</i>
PS 85 – 96	<i>Guide for Expedited Site Characterization of Hazardous Waste Contaminated Sites, Discontinued 1998; Replaced by D6235</i>
PS 104 – 98	<i>Guide for Risk-Based Corrective Action (Vol 11.04), Discontinued 2000; Replaced by E2081.</i>

**X1.5 ASTM Standards—Indexed in Table X1.2 (In Vol 11.05, unless otherwise specified):<sup>-50</sup>**

D 3731 – 87	Practice for Measurement of Chlorophyll Content of Algae in Surface Waters
D 3978 – 80	Practice for Algal Growth Potential Testing with <i>Selenastrum Capricornutum</i>
D 4131 – 84	Practice for Sampling Fish with Rotenone
D 4132 – 82	Practice for Sampling Phytoplankton with Conical Tow Nets
D 4133 – 82	Practice for Sampling Phytoplankton with Pumps
D 4134 – 82	Practice for Sampling Phytoplankton with a Clark-Bumpus Plankton Sampler
D 4135 – 82	Practice for Sampling Phytoplankton with Depth-Integrating Samplers
D 4136 – 82	Practice for Sampling Phytoplankton with Water-Sampling Bottles
D 4137 – 82	Practice for Preserving Phytoplankton Samples
D 4148 – 82	Test Method for Analysis of Phytoplankton in Surface Water by the Sedgwick-Rafter Method
D 4149 – 82	Classification for Sampling Phytoplankton in Surface Waters
D 4211 – 82	Classification for Fish Sampling
D 4319 – 93	Test Method for Distribution Ratios by the Short-Term Batch Method (Vol 04.08)
D 4342 – 84	Practice for Collecting Benthic Macroinvertebrates with the Ponar Grab Sampler
D 4343 – 84	Practice for Collecting Benthic Macroinvertebrates with the Ekman Grab Sampler
D 4344 – 84	Practice for Collecting Benthic Macroinvertebrates with the Smith-McIntyre Grab Sampler
D 4345 – 84	Practice for Collecting Benthic Macroinvertebrates with the Van Veen Grab Sampler
D 4346 – 84	Practice for Collecting Benthic Macroinvertebrates with the Okean 50 Grab Sampler
D 4347 – 84	Practice for Collecting Benthic Macroinvertebrates with the Shipek (Scoop) Grab Sampler
D 4348 – 84	Practice for Collecting Benthic Macroinvertebrates with the Holme (Scoop) Grab Sampler
D 4387 – 87	Guide for Selecting Sampling Devices for Collection Benthic Macroinvertebrates
D 4401 – 84	Practice for Collecting Benthic Macroinvertebrates with the Peterson Grab Sampler
D 4407 – 84	Practice for Collecting Benthic Macroinvertebrates with the Orange Peel Grab Sampler
D 4556 – 85	Guide for Selecting Stream-Net Sampling Devices for Collecting Benthic Macroinvertebrates
D 4557 – 85	Practice for Collecting Benthic Macroinvertebrates with Surber and Related Type Samplers
D 4558 – 85	Practice for Collecting Benthic Macroinvertebrates with Drift Nets

<sup>50</sup> Additional exploration should be considered if there is not sufficient information

<sup>50</sup> Prior to develop interpretative cross sections, with realistic descriptions of anticipated variations 1995 ASTM standards on biological effects and environmental fate were published in subsurface conditions, to meet project requirements. Volume 11.04. Beginning in 1995 that volume was divided into two separate volumes: (1) Volume 11.04 (Environmental Assessment; Hazardous Substances and Oil Spill Response; Waste Management) and (2) Volume 11.05 (Biological Effects and Environmental Fate; Biotechnology; Pesticides).



D 4646 – 87	Test Method for 24-Hour Batch Type Measurement of Contaminant Sorption by Soils and Sediments
D 4874 – 95	Test Method for Leaching Solid Material Wastes in a Column Apparatus (Vol 11.04)
D 5285 – 92	Test Method for 24-Hour Batch-Type Measurements of Volatile Organic Sorption by Soils and Sediment
D 5660 – 95	Test Method for Assessing the Microbial Detoxification of Chemically Contaminated Water and Soils Using a Toxicity Test with a Luminescent Marine Bacterium (Vol 11.04)
D 5929 – 96	Test Method for Determining Biodegradability of Materials Exposed to Municipal Solid Waste Composting Conditions by Compost Respirometry (Vol 11.04)
E 724 – 94	Guide for Conducting Static Acute Toxicity Tests Starting with Embryos of Four Species of Saltwater Bivalve Mollusks
E 729 – 88a	Guide for Conducting Acute Toxicity Tests on Test Materials with Fishes, Macroinvertebrates, and Amphibians
E 857 – 87	Practice for Conducting Subacute Dietary Toxicity Tests with Avian Species
E 895 – 89	Practice for Determination of Hydrolysis Rate Constants of Organic Chemicals in Aqueous Solutions
E 896 – 92	Test Method for Conducting Aqueous Direct Photolysis Tests
E 943 – 00a	Terminology Relating to Biological Effects and Environmental Fate
E 978 – 92	Practice for Evaluating Environmental Fate Models of Chemicals
E 1022 – 94	Practice for Conducting Bioconcentration Tests with Fishes and Saltwater Bivalve Mollusks
E 1023 – 84	Guide for Assessing the Hazard of a Material to Aquatic Organisms and Their Uses
E 1062 – 86	Practice for Conducting Reproductive Studies with Avian Species
E 1147 – 92	Test Method for Partition Coefficient ( <i>N</i> -Octanol/Water) Estimation by Liquid Chromatography
E 1148 – 87	Test Method for Measurements of Aqueous Solubility
E 1191 – 90	Guide for Conducting Life-Cycle Toxicity Tests with Saltwater Mysids
E 1192 – 88	Guide for Conducting Acute Toxicity Tests on Aqueous Effluents with Fishes, Macroinvertebrates, and Amphibians
E 1193 – 94	Guide for Conducting Renewal Life-Cycle Toxicity Tests with <i>Daphnia magna</i>
E 1194 – 87	Test Method for Vapor Pressure
E 1195 – 87	Test Method for Sorption Constant (Koc) for Organic Chemicals in Soil and Sediments
E 1196 – 92	Test Method for Determining the Anaerobic Biodegradation Potential of Organic Chemicals
E 1197 – 87	Guide for Conducting a Terrestrial Soil-Core Microcosm Test
E 1198 – 87	Practice for Sampling Zooplankton with Pumps
E 1199 – 87	Practice for Sampling Zooplankton with Clarke-Pumpus Plankton Sampler
E 1200 – 87	Practice for Preserving Zooplankton Samples
E 1201 – 87	Practice for Sampling Zooplankton with Conical Tow Nets
E 1218 – 90	Guide for Conducting Static 96-h Toxicity Tests with Microalgae
E 1241 – 98	Guide to Conducting Early Life-Stage Toxicity Tests with Fishes
E 1242 – 88	Practice for Using Octanol-Water Partition Coefficient to Estimate Median Lethal Concentration for Fish Due to Narcosis
E 1278 – 88	Guide for Radioactive Pathway Methodology for Release of Site Following Decommissioning (Vol 12.02)
E 1279 – 89	Test Method for Biodegradation by a Shake-Flask Die-Away Method (Vol 11.02)
E 1295 – 89	Guide for Conducting Three-Brood Renewal Toxicity Tests with <i>Ceriodaphnia dubia</i>
E 1365 – 90	Guide for Conducting Static Acute Aquatic Toxicity Screening Tests with the Mosquito <i>Wyeomyia smithii</i> (Coquillett) (Discontinued; 1994)
E 1366 – 91	Practice for Standardized Aquatic Microcosm: Fresh Water
E 1366 – 02	Practice for Standardized Aquatic Microcosm: Fresh Water
E 1367 – 99	Guide for Conducting 10-Day Static Sediment Toxicity Tests with Marine and Estuarine Amphipods
E 1383 – 94a	Guide for Conducting Sediment Toxicity Tests with Freshwater Invertebrates, Discontinued 1995
E 1391 – 94	Guide for Collection, Storage, Characterization, and Manipulation of Sediments for Toxicological Testing
E 1415 – 91	Guide for Conducting Static Toxicity Tests with <i>Lemna Gibba</i>

E 1440 – 91	Guide for Acute Toxicity Test with the Rotifer <i>Brachionus</i>
E 1463 – 92	Guide for Conducting Static and Flow-Through Acute Toxicity Tests with Mysids from the West Coast of the United States
E 1468 – 92	Practice for Collecting Benthic Macroinvertebrates with the Basket Sampler
E 1469 – 92	Practice for Collecting Benthic Macroinvertebrates with Multiple-Plate Samplers
E 1498 – 92	Guide for Conducting Sexual Reproduction Test with Seaweeds
E 1525 – 94a	Guide for Designing Biological Tests With Sediments (Vol 11.05)
E 1562 – 94	Guide for Conducting Acute, Chronic and Lifecycle Aquatic Toxicity Tests with Polychaeteous Annelids (Vol 11.04)
E 1563 – 98	Guide for Conducting Static Acute Toxicity Tests with Echinoid Embryos
E 1604 – 94	Guide for Behavioral Testing in Aquatic Toxicology
E 1611 – 00	Guide for Conducting Sediment Toxicity Tests with Polychaeteous Annelids (Vol 11.05)
E 1624 – 94	Guide for Chemical Fate in Site-Specific Sediment/Water Microcosms
E 1625 – 94	Test Method for Determining Biodegradability of Organic Chemicals in Semi-Continuous Activated Sludge (SCAS)
E 1676 – 95	Guide for Conducting a Laboratory Soil Toxicity Test with Lumbricid Earthworm <i>Ei Senia Foetida</i>
E 1688 – 00	Guide for Determination of the Bioaccumulation of Sediment-Associated Contaminants by Benthic Invertebrates
E 1706 – 00	Test Methods for Measuring the Toxicity of Sediment-Associated Contaminates with Fresh Water Invertebrates
E 1711 – 95	Guide for the Measurement of Behavior During Fish Toxicity Tests
E 1720 – 95	Test Method for Determining Ready, Ultimate Biodegradability of Organic Chemicals in a Sealed Vessel CO <sub>2</sub> -Production Test
E 1733 – 95	Guide for the Use of Lighting in Laboratory Testing
E 1768 – 95	Guide for Ventilatory Behavioral Toxicology Testing of Freshwater Fish
E 1798 – 96	Test Method for Assessing Treatability or Biodegradability, or Both, of Organic Chemicals in Porous Pots (Vol 11.05)
E 1841 – 96	Guide for Conducting Renewal Phytotoxicity Test with Freshwater Emergent Macrophytes (Vol 11.05)
E 1963 – 98	Guide for Conducting Terrestrial Plant Toxicity Test
E 2020 – 99a	Guide for Data Information Options for Conducting and Ecological Risk Assessment at Contaminated Sites
E 2122 – 01	Guide for Conducting In-Situ Field Bioassays with Marine, Estuarine and Freshwater Bivalves (Vol 11.05)
<u>E 2172 – 01</u>	<u>Guide for Conducting Laboratory Soil Toxicity Test With the Nematode <i>Caenorhabditis elegans</i></u>
P 235 – 93	<i>Test Method for Fluorometric Determination of Toxicity-Induced Enzymatic Inhibition in <i>Daphnia magna</i>, Discontinued 1995</i>

X1.5.1 Table X1.2 identifies more than 95 standard test methods, practices and guides that address field sampling for ecological characterization and laboratory methods, such as toxicity testing, relevant to human and ecological assesment.

X1.5.2 This guide does not specifically address laboratory methods, but Table X1.1 provides a convenient index to laboratory methods that might be useful for testing and analysis of soil, water and waste samples collected during an environmental site investigation. This appendix does not contain a detailed listing of laboratory methods for measurement of specific chemicals that might be of concern in an environmental investigation. However, methods for measurement of chemical parameters that ar routinely used in field investigations, and laboratory methods that provide information relevant to the transport and fate of contaminants and other chemical constituents in the subsurface are included.

X1.5.3 The following ASTM compilations may be useful for Environmental site Characterization:

X1.5.3.1 *ASTM Standards on Ground Water and Vadose Zone Investigations: Drilling, Sampling, Geophysical Logging, Well Installation and Decommissioning, 2nd ed. 1999, 561 pp (56 standards).*

X1.5.3.2 *ASTM Standards Related to Phase II Environmental Site Assessment Process, 1998, 333pp (22 standards).*

X1.5.3.3 *ASTM Standards on Environmental Site Assesments for Commercial Real Estate, 2nd ed., 1994, 55 pp., (includes E1527 and E1528).*

X1.5.3.4 *ASTM SStandards on Hazardous Substance and Oil Spill Response, 2nd ed., 1994, 144 pp (38 standards).*

X1.5.3.5 *ASTM Standards on Lead-Based Paint Abatement in Buidlings, 1994, 174 pp, (28 standards).*

X1.5.3.6 *ASTM Standards on Environmental Sampling, 2nd ed., 1997, 1008 pp, (138 standards).*

X1.5.3.7 *ASTM Standards on Determining Subsurface Hydraulic Properties and Ground Water Modeling, 2nd ed., 1999, 350 pp, (45 standards).*

X1.5.3.8 *ASTM Standards on Design Planning and Reporting of Ground Water and Vadose Zone Investigations, 2nd ed., 1999, 600 pp, (44 standards).*

X1.5.3.9 *ASTM Standards Related to On-Site Septic Systems, 1997, 176 pp, (18 standards).*

X1.5.3.10 *ASTM Standards Related to Environmental Site Characterization, 1997, 1410 pp, (136 standards).*

## **X2. MAJOR NON-ASTM REFERENCES ON ENVIRONMENTAL SITE CHARACTERIZATION**

### **X2.1 General Applications:**

Boulding, J. R., *Subsurface Field Characterization and Monitoring Techniques: A Desk Reference Guide, Volume I: Solids and Ground Water, Volume II: The Vadose Zone, Field Screening and Analytical Methods*, EPA/625/R-93/003a and b, 1993.<sup>51</sup>

Boulding, J. R. and Ginn, J.S., *Practical Handbook of Soil, Vadose Zone, and Ground Water Contamination: Assessment, Prevention and Remediation*, Lewis Publishers, Boca Raton, FL, 1995-2003.

Brown, E. T. (ed), *Rock Characterization Testing and Monitoring: ISRM Suggested Methods*, Pergamon Press, Oxford, 1981.

Brown, R. H., Konoplyantsev, A. A., Ineson, J., and Kovalensky, V. S., "Ground Water Studies: An International Guide for Research and Practice," *Studies and Reports in Hydrology No. 7*, UNESCO, Paris. Originally published in 1972, with supplements added in 1973, 1975, 1977, and 1983.

CCME, *Guidance Manual on Sampling, Analysis, and Data Management for Contaminated Sites, Vol. I: Main Report, Vol. II: Analytical Method Summaries*, CCME EPC-NCS62E and CCME EPC-NCS66E, Canadian Council of Ministers of the Environment, 326 Broadway, Suite 400, Winnipeg, Manitoba R3C 0S5, 1993.

CCME, *Subsurface Assessment Handbook for Contaminated Sites*, CCME EPC-NCSRP-48E, Canadian Council of Ministers of the Environment, 326 Broadway, Suite 400, Winnipeg, Manitoba R3C 0S5, 1994.

Dowding, C. H. (ed), *Site Characterization Exploration*, Proceeding of Specialty Workshop, American Society of Civil Engineers, New York, 1978.

Flanagan, F., "Description of Eight New USGS Rock Standards," *U.S. Geological Survey Professional Paper 840*, 1976.

Harrelson, C. C., Rawlins, C. L., and Putyondy, J. P., *Stream Channel Reference Sites: An Illustrated Guide for Field Techniques. General Technical Report RM-245*, Rocky Mountain Forest and Range Experiment Station, Fort Collins, CO, pp. 61, 1994.

Hanna, T. H., *Field Instrumentation in Geotechnical Engineering*, Trans Tech Publications, Clausthal, Germany, 1985.

Hathaway, A. W., *Manual on Subsurface Investigations*, American Association of State Highway and Transportation Officials, Washington, DC, 1988.

Hvorslev, M. J., *Subsurface Exploration and Sampling of Soils*, Engineering Foundation, New York, 1948.

Krajca, J. M., *Water Sampling*, Halstead Press, John Wiley & Sons, New York, 1989.

Kolm, K. E., *Conceptualization and Characterization of Hydrologic Systems*, GWMI 93-01, International Ground Water Modeling Center, Golden, CO, 1993.

Koterba, M.T., Wilde, F.D., and Lapham, W.W., *Ground Water Data Collections Protocols and Procedures for the National Water-Quality Assessment Program: Selection and Documentation of Water-Quality Samples and Related Data*, U.S. Geological Survey Open-File Report 95-399, 1995.

Lambe, W. T., *Soil Testing for Engineers*, John Wiley & Sons, New York, 1951.

Lapham, W.W., Wilde, F.D., and Koterba, M.T., *Ground Water Data Collections Protocols and Procedures for the National Water-Quality Assessment Program: Selection, Installation, and Documentation of Wells, and Collection of Related Data*, U.S. Geological Survey Open-File Report 95-398, 1995.

Mudroch, A., and Azcue, J. M., *Manual of Aquatic Sediment Sampling*, Lewis Publishers, Boca Raton, FL, 1995.

Nielsen, D. M. (ed), *Practical Handbook of Ground Water Monitoring*, Lewis Publishers, Chelsea, MI, 1991.

Rehm, B. W., Stolzenburg, T. R., and Nichols, D. G., *Field Measurement Methods for Hydrogeologic Investigations: A Critical Review of the Literature*, EPRI EA-4301, Electric Power Research Institute, Palo Alto, CA, 1985.

Stednick, J. D., *Wildland Water Quality Sampling and Analysis*, Academic Press, HBJ, San Diego, CA, 1991.

Struckmeier, W. F., and Margat, J., *Hydrogeological Maps: A Guide and a Standard Legend*, IAH International Contributions to Hydrogeology Vol. 17, Verlag Heinz Heise, Hannover, Germany, 1995.

Thompson, C. M., et al, *Techniques to Develop Data for Hydrogeochemical Models*, EPRI EN-6637, Electric Power Research Institute, Palo Alto, CA, 1989.

Wilson, L. G., Everett, L. G., and Cullen, S. J., *Handbook of Vadose Zone Characterization and Monitoring*. Lewis Publications, Boca Raton, FL, pp. 896, 1994.

Wilson, N., *Soil Water and Ground Water Sampling*. Lewis Publishers, Boca Raton, FL, pp. 192, 1995.

<sup>54</sup> Most field geology texts identified in Footnote 16 discuss interpolation techniques. Davis (91), Hamilton and Jones (94) and Jones et al. (95) are other good references.

<sup>51</sup> Available from ORD Publications, U.S. EPA Center for Environmental Research Information, P.O. Box 19963, Cincinnati, OH 45268.

U.S. Army Corps of Engineers (USACE), “Engineering and Design—Geotechnical Investigation,” *Engineer Manual EM 1110-1-1804*, USACE, Washington, DC, 1984.

U.S. Geological Survey (USGS), *National Handbook of Recommended Methods for Water Data Acquisition*, USGS Office of Water Data Coordination, Reston, VA (Individual chapters have come out at different dates. Pertinent chapters include: (2) Ground Water (1980); (4) Biological and Microbiological Quality of Water (1983); (5) Chemical Quality (1982); and (6) Soil Water (1982)), 1977.

U.S. Environmental Protection Agency (EPA), *Test Methods for Evaluating Solid Waste*, 3rd ed, EPA/530/SW-846 (NTIS PB88-239223); First update, 3rd edition, EPA/530/SW-846.3-1 (NTIS PB89-148076). (Second edition was published in 1982 (NTIS PB87-1200291); current edition and updates available on a subscription basis from U.S. Government Printing Office, Stock #955-001-00000-1, 1986c, Revised final draft of Chapter 11 (Ground-Water Monitoring System Design, Installation, and Operating Practices contains extensive new guidance—see U.S. EPA, 1993b) (Volumes 1A ( *Metallic Analytes*), IB ( *Organic Analytes*), and IC ( *Miscellaneous Test Methods* ) cover laboratory methods; Volume II covers field methods (Part IV defines acceptable and unacceptable designs and practice for ground-water monitoring), 1986c.

U.S. Environmental Protection Agency (EPA), *Final RCRA Comprehensive Ground-Water Monitoring Evaluation (CME) Guidance Document*, Final OSWER Directive 9950.2 (NTIS PB91-140194), (Contains detailed checklist drawing heavily from U.S. EPA (1986b)), 1986d.

U.S. Environmental Protection Agency (EPA), *A Compendium of Superfund Field Operations Methods*, EPA/540/P-87/001 (NTIS PB88-181557), 1987a.

U.S. Environmental Protection Agency (EPA), *Data Quality Objectives for Remedial Response Activities*, Vol 1: Development Process; Vol 2: RI/FS Activities at a Site with Contaminated Soils and Ground Water, Vol 1 EPA/G-87/003 (NTIS PB88-131370), Vol 2 EPA/G-87/004 (NTIS PB88-131388), both Volumes: NTIS PB90-272634, 1987b.

U.S. Environmental Protection Agency (EPA), *Guidance for Conducting Remedial Investigations and Feasibility Studies Under CERCLA*, EPA/540/G-89/004, OSWER Directive 9355.3-01 (NTIS PB89184626), 1989a.

U.S. Environmental Protection Agency (EPA), *RCRA Facility Investigation (RFI) Guidance; Interim Final*, Vol I: *Development of an RFI Work Plan and General Considerations for RCRA Facility Investigations*; Vol II: *Soil, Groundwater, and Subsurface Gas Releases*; Vol III: *Air and Surface Water Releases*; Vol IV: *Case Study Examples*, EPA/530/SW-89/001, OSWER Directive 9502.00-6D (NTIS PB89-200299), 1989b.

U.S. Environmental Protection Agency (EPA), *Site Characterization for Subsurface Remediation*, EPA/625/4-91/026, 1991a.<sup>50</sup>

U.S. Environmental Protection Agency (EPA), *Emergency Response Team (ERT) Standard Operating Procedures (SOPs) Compendia: Compendium of ERT Soil Sampling and Surface Geophysics Procedures* (EPA/540/P-91/006); *Compendium of ERT Groundwater Sampling Procedures* (EPA/540/P-91/007); *Compendium of ERT Waste Sampling Procedures* (EPA/540/P-91/008); *Compendium of ERT Toxicity Testing Procedures* (EPA/540/P-91/009), 1991b.

U.S. Environmental Protection Agency (EPA), *Guidance for Performing Preliminary Assessments Under CERCLA*, OSWER 9345.0-01A (NTIS PB92-963303), 1991c.

U.S. Environmental Protection Agency (EPA), *Environmental Compliance Branch Standard Operating Procedures and Quality Assurance Manual*, U.S. EPA Region IV Environmental Services Division, College Station Road, Athens, GA 30613, (Available in Wordperfect 5.1 electronic format), 1991d.

U.S. Environmental Protection Agency (EPA), *Characterization Protocol for Radioactive Contaminated Soils*, OSWER Directive 9380.1-10FS, 1992.

U.S. Environmental Protection Agency (EPA), *Field Methods Compendium (FMC) Draft*, OERR #9285.2-11, Analytical Operation Branch, Hazardous Site Evaluation Division, Office of Emergency and Remedial Response, (Available in Wordperfect 5.1 electronic format from OERR, Washington, DC), 1993.

U.S. Environmental Protection Agency (EPA), *RCRA Ground Water Monitoring: Draft Technical Guidance*, EPA/530/R-93/001 (NTIS PB93-139350), (Provides supplemental guidance to Chapter 11 of U.S. EPA (1986a) and U.S. EPA 1986b), 1993b.

U.S. Geological Survey (USGS), Various authors and dates, *Techniques of Water-Resources Investigations*. (Series of more than 50 manuals and guides describing addressing field and laboratory methods for water resources investigations).

U.S. Naval Facilities Engineering Command, *Soil Mechanics Design Manual*, Volume 7.1. NAVFAC DM-7.1, (NITS ADA123-622) Department of the Navy (Includes section on site assessment techniques), 1982.

## X2.2 Controlled and Uncontrolled Waste Sites:

Breckenridge, R. P., Williams, J. R., and Keck, J. F., *Characterizing Soils for Hazardous Waste Site Assessments. Ground-Water Issue Paper EPA/600/8-91/008*, 1991, Available from CERL.<sup>50</sup>

Byrnes, M. E., *Field Sampling Methods for Remedial Investigations*, Lewis Publishers, Boca Raton, FL, 1994.

Cheremisinoff, P., *A Guide to Underground Storage Tanks: Evaluation, Site Assessment and Remediation*. Prentice-Hall, Englewood Cliffs, NJ, 1992.

Cohen, R. M., and Mercer, J. W., *DNAPL Site Evaluation*. EPA/600/R-93/002 (NTIS PB93-150217), (Also published by Lewis Publishers as C. K. Smoley edition, Boca Raton, FL), 1993.

Ford, P. J., and Turina, P. J., *Characterization of Hazardous Waste Sites—A Methods Manual: Vol I. Site Investigations*. EPA/600/4-84/075 (NTIS PB85-215960), 1985.



Ford, P. J., Turina, P. J., and Seely, D. E., *Characterization of Hazardous Waste Sites—A Methods Manual: Vol II. Available Sampling Methods*, 2nd ed. EPA 600/4-84/076 (NTIS PB85-521596), 1984.

Lipsky, D., Tusa, W., Dorrier, R., Johnson, B., and Gardner, M., *Methods for Evaluating the Attainment of Cleanup Standards, Volume 1: Soils and Solid Media*. EPA/230/2-89/042 (NTIS PB89-234959), 1989.

Oudjik, G., and Mujica, K., *Handbook for Identification, Location and Investigation of Pollution Sources Affecting Ground Water*. National Water Well Association, Dublin, OH, 1989.

Pankow, J.F. and Cherry, J.A., (eds.), *Dense Chlorinated Solvents and Other DNAPLs in Groundwater: History, Behavior, and Remediation*, Waterloo Press, Guelph, Ontario, 1996.

Sara, M. N., *Standard Handbook of Site Site Assessment for Solid and Hazardous Waste Facilities Remediation Handbook, 2nd Edition*. Lewis Publishers, Boca Raton, FL, ~~1994~~ 2003.

Sisk, S. W., *NEIC Manual for Groundwater/Subsurface Investigations at Hazardous Waste Sites*, EPA/330/9-81-002 (NTIS PB82-103755), 1981.

U.S. Department of Energy (DOE), Various Dates, *The Environmental Survey Manual*. DOE/EH-0053: Vol 1 (August 1987; Chapter 8, 2nd ed. January 1989—*Sampling and Analysis Phase*); Vol 2 (August 1987—Appendixes A, B, and C); Vol 3 (2nd ed. January 1989—Appendix D, Parts 1, 2, and 3; *Organic and Inorganic Analysis Methods and Non-Target List Parameters*); Vol 4 (2nd ed. January 1989—Appendix D, Part 4; *Radiochemical Analysis Procedures*); Vol 5 (2nd ed. January 1989—Appendixes: E, *Field Sampling*; F, *Quality Assurance*; G, *Decontamination*; H, *Sample Management*; I, *Sample Handling, Transport and Documentation*; J, *Health and Safety*; and K, *Sampling and Analysis Plan*).

U.S. Environmental Protection Agency (EPA), *RCRA Facility Assessment Guidance*. EPA/530-SW-86-053, (NTIS PB87-107769), 1986a.

U.S. Environmental Protection Agency (EPA), *RCRA Ground Water Monitoring Technical Enforcement Guidance Document*. EPA/530/SW-86/055 (OSWER-9950.1) (NTIS PB87-107751), 332 pp. (Also published in NWWA/EPA Series, National Water Well Association, Dublin, OH. Final OSWER Directive 9950.2 (NTIS PB91-140194). Executive Summary: OSWER 9950.1a (NTIS PB91-140186), 17 pp. See also, U.S. EPA (1986d and 1993b), 1986b.

U.S. Environmental Protection Agency (EPA), *U.S. EPA Region VIII Standard Operating Procedures for Field Sampling Activities*, Version 2, Denver, CO, 1994.

U.S. Environmental Protection Agency (EPA), *Using Dynamic Field Activities for On-Site Decision Making: A Guide for Project Managers*, EPA/530/R-03/002, OSWER Directive No. 9200.1-40 (<http://www.epa.gov/Sudefund/programs/DFA>), 2003.

Water Pollution Control Federation (WPCF/WEF), *Hazardous Waste Site Remediation: Assessment and Characterization*, Water Environment Federation, Alexandria, VA, 1988.

### X2.3 Environmental Audits and Site Assessments:

Association of Ground Water Scientists and Engineers, *Guidance to Environmental Site Assessments*. National Ground Water Association, Dublin, OH, 1992.

Colangelo, R. V., *Buyer Be(a)ware: The Fundamentals of Environmental Property Assessments*, National Water Well Association, Dublin, OH, 1991.

Environmental Resource Center, *Environmental Auditing and Compliance Manual*, Van Nostrand Reinhold, New York (1992 edition published by Environmental Resource Center), 1993.

Hess, K., *Environmental Site Assessment, Phase I: A Basic Guide*, Lewis Publishers, Boca Raton, FL, 1993.

Jain, R. K., Urban, L. V., Stacey, G. S., and Balbach, H. E., *Environmental Assessment*, McGraw-Hill, New York, 1993.

Vincoli, J., *Basic Guide to Environmental Compliance*, Van Nostrand Reinhold, New York, 1993.

### X2.4 Environmental Exposure and Risk Assessment:

Calabrese, E. J., and Kostecky, P. T., *Risk Assessment and Environmental Fate Methodologies*, Lewis Publishers, Boca Raton, FL (Description and critical review of existing software (AERIS, GEOTOX, LUFT, MYGRT, PCGEMS/SESOIL, POSSM, PPLV, PRZM, RAFT, Risk Assistant, SESOIL), and other methods developed at the state level (California, New Jersey, and Massachusetts)), 1992.

Hallenback, W. H., *Quantitative Risk Assessment for Environmental and Occupational Health*, 2nd Ed., Lewis Publishers, Chelsea, MI, 1993.

Hill, I. R., Heimbach, F., Leeuwangh, P., and Matthiessen, P. (eds.), *Freshwater Field Tests for Hazard Assessment of Chemicals*, Lewis Publishers, Boca Raton, FL, pp. 608, 1994.

Hoffman, D. J., Rattner, B. A., Burton, Jr., G. A., and Cairns, Jr., J., *Handbook of Ecotoxicology*, Lewis Publishers, Boca Raton, FL, 1995.

Newman, M. C., *Quantitative Methods in Aquatic Ecotoxicology*, Lewis Publishers, Boca Raton, FL, 1995.

Norton, S., McVey, M., Colt, J., Durda, J., and Hegner, R., *Review of Ecological Risk Assessment Methods*, EPA/230/10-88-041 (NTIS PB89-134357), (Review of sixteen methodologies), 1988.

Schaum, J., *Exposure Factors Handbook*, EPA/600/8-89/043 (NTIS PB90-106774), 1990.

Suter, II, G. W., *Ecological Risk Assessment*, Lewis Publishers, Chelsea, MI, 1993.

U.S. Environmental Protection Agency, *Ecological Risk Assessment Issue Papers*, EPA/630/R-94/009, 1994.

U.S. Environmental Protection Agency (EPA), *Superfund Exposure Assessment Manual*, EPA/540/1-88/001, OSWER Directive 9285.5-1 (NTIS PB90-135859), 1988.

U.S. Environmental Protection Agency (EPA), *Risk Assessment Guidance for Superfund, Volume 1: Human Health Evaluation Manual, Part A, Interim Final*, EPA/540/1-89/002 (NTIS PB90-155581), (1990 9-page Fact Sheet with same title: NTIS PB90-273830; 1991 *Human Health Evaluation Manual, Supplemental Guidance: Standard Default Exposure Factors*: NTIS PB91-921314), 1989a.

U.S. Environmental Protection Agency (EPA), *Risk Assessment Guidance for Superfund, Volume 2: Environmental Evaluation Manual, Interim Final*, EPA/540/1-89/001 (NTIS PB90-155599), 1989b.

U.S. Environmental Protection Agency (EPA), *Statistical Methods for Estimating Risk for Exposure Above the Reference Dose*, EPA/600/8-90/065 (NTIS PB90-261504), 1990.

U.S. Environmental Protection Agency (EPA), *Guidance for Data Useability in Risk Assessment (Parts A and B)*, Final, Part A: OSWER Directive 9285.7-09A (NTIS PB92-963356), Part B: OSWER Directive 9285.7-09B (NTIS PB92-963362), (Supersedes 1990 document by same title (EPA/540/G-90/008, OSWER Directive 9285.7-05; NTIS PB91-921208), 1992.

Wentsel, R., et al, *Procedural Guidelines for Ecological Risk Assessment at U.S. Army Sites*, Volume 1, 1994.

### X2.5 Atmospheric and Ecological Assessment:

Britton, L. J., and Greeson, P. E. (eds), *Methods for Collection and Analysis of Aquatic Biological and Microbiological Samples*, U.S. Geological Survey Techniques of Water-Resources Investigations TWRI 5-A4, 1989.

Electric Power Research Institute (EPRI), *Sampling Design for Aquatic Ecologic Monitoring*, Five Vols, EPRI EA-4302, EPRI, Palo Alto, CA, 1985.

Euphrat, F. D., and Warkentin, B. P., *A Watershed Assessment Primer*, U.S. EPA Region 10, EPA/B-94/005, 1994.

Kuechler, A. W., *Vegetation Mapping*, The Ronald Press Company, New York, 1967.

Lodge, J. (ed), *Methods of Air Sampling and Analysis*, 3rd ed. Lewis Publishers, Chelsea, MI, 1988.

Loeb, S. L., and Spacie, A., *Biological Monitoring of Aquatic Systems*, Lewis Publishers, Boca Raton, FL, 1994.

Maslansky, C. J., and Maslansky, S. P., *Air Monitoring Instrumentation: A Manual for Emergency, Investigatory and Remedial Responders*, Van Nostrand Reinhold, New York, NY, 1992.

Ohio Environmental Protection Agency, *Biological Criteria for the Protection of Aquatic Life, Vol II, User's Manual for Biological Assessment of Ohio Surface Waters*, Ohio EPA, Columbus, OH, 1987.

Ralph, C. J., Geupel, G. R., Pyle, P., Martin, T. E., and DeSante, D. F., *Handbook of Field Methods for Monitoring Landbirds. General Technical Report PSW-GTR-144*, U.S. Forest Service, Pacific Southwest Research Station, Albany, CA, pp. 41, 1993.

Taylor, S. A., and Ashcroft, G. L., *Physical Edaphology*, W. H. Freeman and Co., San Francisco, 1972.

Warren-Hicks, W., Parkhurst, B. R., and Baker, Jr., S. S., *Ecological Assessment of Hazardous Waste Sites: A Field and Laboratory Reference*. EPA/600/3-89/013 (NTIS PB89-205967), (Covers toxicity tests, biomarkers, and ecological field assessments), 1989.

Wight, G. D., *Fundamentals of Air Sampling*, Lewis Publishers, Boca Raton, FL, pp. 272, 1994.

## X3. MAJOR NON-ASTM REFERENCES ON TERMINOLOGY RELATED TO ENVIRONMENTAL SITE CHARACTERIZATION

Allaby, A. and Allaby, M., *The Concise Oxford Dictionary of Earth Sciences*. Oxford University Press, Oxford, UK, 1990.

American Society of Agricultural Engineers, *Glossary of Soil and Water Terms*. American Society of Agricultural Engineers, St. Joseph, MI, 1967.

Bates, R. and Jackson, J. (eds), *Dictionary of Geological Terms*, 3rd ed. AGI, Washington, DC, (Supersedes Weller (1960)), 1984.

Castany, G. and Margat, J., *Dictionnaire Français D'Hydrogéologie*, BRGM, Orléans, 1977.

Interagency Advisory Committee, *Subsurface-Water Flow and Solute Transport, Glossary of Selected Terms*. Draft report prepared by Subsurface-Water Glossary Working Group, Ground Water Subcommittee, 1988.

International Society for Rock Mechanics, *Final Document on Terminology, English Versions*, Committee on Terminology, Symbols and Graphic Representation, 1972.

Laney, R. L. and Davidson, C. B., *Aquifer Nomenclature Guidelines*, U.S. Geological Survey Open File Report 86-534, 1986.

Langbein, W. B. and Iseri, K. T., *General Introduction and Hydrologic Definitions*. U.S. Geological Survey Water Supply Paper 1541-A, 1960.

Lo, S. S., *Glossary of Hydrology*, Water Resources Publications, Highland Ranch, CO, 1992.

Lohman, S. W., et al, *Definitions of Selected Ground-Water Terms—Revisions and Conceptual Refinements*, U.S. Geological Survey Water-Supply Paper 1988, 1972.

Meinzer, O. E., *Outline of Ground Water Hydrology with Definitions*, U.S. Geological Survey Water Supply Paper 494, 1923.

Michel, J.-P. and Fairbridge, R. W., *Dictionary of Earth Sciences*, John Wiley & Sons, New York, 1992.

- Moore, W. G., *A Dictionary of Geography*, 4th edition, Penguin Books, Baltimore, MD, 1968.
- National Geodetic Survey, *Geodetic Glossary*, U.S. Department of Commerce, 1986.
- Parker, S. P. (ed), *Dictionary of Scientific and Technical Terms*, 4th ed., McGraw-Hill, New York, 1989.
- Pfannkuch, H. O., *Elsevier's Dictionary of Hydrogeology*, Elsevier, NY, 1969.
- Poland, J. F., et al, *Glossary of Selected Terms Useful in Studies of the Mechanics of Aquifer Systems and Land Subsidence Due to Fluid Withdrawal*, U.S. Geological Survey Water Supply Paper 2025, 1972.
- Porteous, A., *Dictionary of Environmental Science and Technology*, revised edition, John Wiley & Sons, New York, 1992.
- Soil Conservation Service (SCS), *Glossary of Selected Geologic and Geomorphic Terms*, U.S. Department of Agriculture, Soil Conservation Service Western Technical Service Center, Portland, OR, 1977.
- Soil Science Society of America, *Glossary of Soil Science Terms*, SSSA, Madison, WI, 1987.
- Stevenson, L. H., and Wynen, B., *The Facts on File Dictionary of Environmental Sciences*. Facts on File, New York, NY, 1991.
- Titelbaum, O. A., *Glossary of Water Resources Terms*, Federal Water Pollution Control Administration, 1970.
- UNESCO, *International Glossary of Hydrology*, WMO/OMM/BMO No. 385, 1974.
- U.S. Environmental Protection Agency (EPA), *Draft Glossary of Quality Assurance Related Terms*, Office of Research and Development, Sept. 29, 1988.
- U.S. Geological Survey, *Federal Glossary of Selected Terms: Subsurface-Water Flow and Solute Transport*, Office of Water Data Coordination, USGS, Reston, VA, 1989.
- Whitten, D. G. A. and Brooks, J. R. V., *The Penguin Dictionary of Geology*, Penguin Books, Baltimore, MD, 1972.
- Weller, J. M. (ed), *Glossary of Geology and Related Sciences with Supplement*, 2nd edition. American Geological Institute, Washington, DC, Supplement 72 pp. (Superseded by AGI (1984)), 1960.

## REFERENCES

- (1) Quinlan, J. F., Special Problems of Ground-Water Monitoring in Karst and Fracture Rock Terranes, In: *Ground-Water and Vadose Zone Monitoring, ASTM STP 1053*, D. M. Nielsen and A. I. Johnson (eds.), ASTM, Philadelphia, PA, pp. 275–304, 1990.
- (2) Avery, T. E., *Interpretation of Aerial Photographs*, Second ed, Burgess Publishing Company, Minneapolis, MN, 1968.
- (3) Ciciarelli, J., *A Practical Guide to Aerial Photography*, Van Nostrand Reinhold, New York, 1991.
- (4) Denny, C. S., Warren, C. R., Dow, D. H., and Dale, W. J., "A Descriptive Catalog of Selected Aerial Photographs of Geologic Features of the United States," *U.S. Geological Survey Professional Paper 590*, 1968.
- (5) Drury, S. A., *Image Interpretation in Geology*, Allen and Unwin, London, UK, 1987.
- (6) Dury, G. H., *Map Interpretation*, Pitman, London, 1960.
- (7) Johnson, A. I., and Gnaedinger, J. P., Bibliography, In: *Symposium on Soil Exploration, ASTM STP 351*, ASTM, Philadelphia, PA, pp. 137–155 (90 references on air photo interpretation), 1964.
- (8) Lattman, L. H. and Ray, R. G., *Aerial Photographs in Field Geology*, Holt Rinehart and Winston, New York, 1965.
- (9) Lueder, D. R., *Aerial Photographic Interpretation: Principles and Applications*, McGraw-Hill, New York, 1959.
- (10) Miller, V. C., and Miller, C. F., *Photogeology*, McGraw-Hill, New York, 1961.
- (11) Ray, R. G., "Aerial Photographs in Geologic Interpretation and Mapping," *U.S. Geological Survey Professional Paper 373*, 1960.
- (12) Soil Conservation Service (SCS), "Aerial-Photo Interpretation in Classifying and Mapping Soils," *U.S. Department of Agriculture Handbook 294*, 1973.
- (13) Strandberg, C. H., *Aerial Discovery Manual*, Wiley, New York, 1967.
- (14) Wright, J., *Ground and Air Survey for Field Scientists*, Oxford University Press, New York, 1982.
- (15) Sun, R. J. and Weeks, J. B., "Bibliography of Regional Aquifer-System Analysis Program of the U.S. Geological Survey, 1978–91" *U.S. Geological Survey Water-Resources Investigations Report 91-4122*, 1991.
- (16) U.S. Geological Survey. 1991–1994. Ground-Water Atlas of the United States [14 planned chapters; three currently published: 730-G (Alabama, Florida, Georgia, South Carolina), 730-H (Idaho, Oregon, Washington), and 730-J (Iowa, Michigan, Minnesota, Wisconsin)].
- (17) Boulding, J. R., *Description and Sampling of Contaminated Soils: A Field Pocket Guide*, EPA/625/12-91/002, 1991.<sup>52</sup>
- (18) Cameron, R. E., *Guide to Site and Soil Description for Hazardous Waste Sites, Volume 1: Metals*, EPA/600/4-91/029 (NTIS PB92-146158), 1991.
- (19) Bishop, M. S., *Subsurface Mapping*, Wiley, New York, 1960.
- (20) Brassington, R., *Field Hydrogeology*, Halsted Press, New York, 1988.
- (21) Bureau of Reclamation, *Engineering Geology Office Manual*, U.S. Department of the Interior, Bureau of Reclamation, Denver, CO, 1988.
- (22) Bureau of Reclamation, *Engineering Geology Field Manual*, U.S. Department of the Interior, Bureau of Reclamation, Denver, CO, 1988.
- (23) Compton, R. R., *Manual of Field Geology*, John Wiley & Sons, New York, 1962.
- (24) Compton, R. R., *Geology in the Field*, John Wiley & Sons, New York, 1985.
- (25) Dietrich, R. V., Dutro, Jr., J. V., and Foose, R. M. (Compilers), *AGI Data Sheets for Geology in Field, Laboratory, and Office*, 3rd Edition, American Geological Institute, Washington, DC, 1990.
- (26) Erdélyi, M. and Gálfi, J., *Surface and Subsurface Mapping in Hydrogeology*, Wiley-Interscience, New York, 1988.
- (27) Fetter, C. W., *Applied Hydrogeology*, 3rd ed. Macmillan, New York, 1994.

<sup>52</sup>The EPA's GRITS/STAT software

<sup>52</sup> Available from ORD Publications, U.S. EPA Center for analyzing ground-water monitoring data allows testing of the appropriateness of conventional statistical analysis of time-series data, and includes a number of alternative tests if conventional tests are not appropriate (92)-Environmental Research Information, P.O. Box 19963, Cincinnati, OH 45268-0963.



- (28) Lahee, F. H., *Field Geology (6th ed.)*, McGraw-Hill, New York, 1961.
- (29) LeRoy, L. W., LeRoy, D. O., Schwochow, S. D., and Raese, J. W. (eds), *Subsurface Geology*, 5th edition. Colorado School of Mines, Golden, CO, (1st edition: LeRoy and Cran [1947], 2nd edition: LeRoy [1951], 3rd edition: Huan and LeRoy [1958], and 4th edition [1977]), 1987.
- (30) Low, J. W., *Geologic Field Methods*, Harper, New York, 1957.
- (31) Rahn, P., *Engineering Geology*, Elsevier, New York, 1986.
- (32) Tearpock, D. and Bischke, R. E., *Applied Subsurface Geological Mapping*, Prentice Hall, Englewood Cliffs, NJ, 1991. (Focuses on construction of geological maps from various sources, including geophysical measurements).
- (33) Fry, N., *The Field Description of Metamorphic Rocks*, John Wiley & Sons, New York, 1984.
- (34) Thorpe, R. and Brown, G., *The Field Description of Igneous Rocks*, John Wiley & Sons, New York, 1985.
- (35) Tucker, M. E., *The Field Description of Sedimentary Rocks*, John Wiley & Sons, New York, 1982.
- (36) U.S. Environmental Protection Agency (EPA). 1992. *Locational Data Policy Implementation Guidance: Guide to the Policy*. EPA/220/B-92-008, Office of Administration and Resources Management (PMD-211D), Washington DC. [Note that U.S. EPA 1992a and 1992b are separate documents, but have the same document number]
- (37) U.S. Environmental Protection Agency (EPA). 1992. *Locational Data Policy Implementation Guidance: Guide to Selecting Latitude/Longitude Collection Methods*. EPA/220-B-92-008, Office of Administration and Resources Management (PMD-211D), Washington DC. [Note that U.S. EPA 1992a and 1992b are separate documents, but have the same document number]
- (38) U.S. Environmental Protection Agency (EPA). 1992. *Locational Data Policy Implementation Guidance—Global Positioning System Technology and Its Application In Environmental Programs—GPS Primer*. EPA/600/R-92/036. Available from CERL\*.
- (39) Boulding, J. R., *Description and Sampling of Contaminated Soils: A Field Guide, Revised and Expanded*, 2nd edition, Lewis Publishers, Chelsea, MI, 1994.
- (40) Vepraskas, M. J., *Redoximorphic Features for Identifying Aquatic Conditions*. North Carolina Agricultural Research Service Technical Bulletin 301, Department of Agricultural Communications, Box 7603, North Carolina State University, Raleigh, NC 27695-7603, 1992.
- (41) Soil Survey Staff, *Keys to Soil Taxonomy*, 5th ed, Soil Management Support Services (SMS) Technical Monograph No. 19, Pocahontas Press, P.O. Drawer F, Blacksburg, VA, 24063-1020, 1992.
- (42) Kirkaldie, L., "Potential Contaminant Movement Through Soil Joints," *Bull. Ass. Eng. Geologists* *IV*(4), 1988, pp. 520–524.
- (43) Boulding, J. R. 1993. *Subsurface Field Characterization and Monitoring Techniques: A Desk Reference Guide, Volume I: Solids and Ground Water, Volume II: The Vadose Zone, Field Screening and Analytical Methods*. EPA/625/R-93/003a&b. Available from CERL\*.
- (44) Benson, R. C., Glaccum, R. A., and Noel, M. R., *Geophysical Techniques for Sensing Buried Wastes and Waste Migration*, EPA/600/7-84/064 (NTIS PB84-198449). Also published in NWWA/EPA series by National Water Well Association, Dublin, OH, 1984.
- (45) Boulding, J. R., *Use of Airborne, Surface, and Borehole Geophysical Techniques at Contaminated Sites: A Reference Guide*, EPA/625/R-92/007, 1993.
- (46) Haeni, F. P., *Application of Seismic Refraction Techniques to Hydrogeologic Studies*, U.S. Geological Survey Techniques of Water-Resources Investigations TWRI 2-D2, 1988.
- (47) Ward, S. H. (ed), *Geotechnical and Environmental Geophysics, Vol I: Review and Tutorial*, Society of Exploration Geophysicists, Tulsa, OK, 1990a.
- (48) Ward, S. H. (ed), *Geotechnical and Environmental Geophysics, Vol II: Environmental and Groundwater*, Society of Exploration Geophysicists, Tulsa, OK, 1990b. (34 papers, including ER, EM multiple methods, thermal, others).
- (49) Zohdy, A. A., Eaton, G. P., and Mabey, D. R., *Application of Surface Geophysics to Ground-Water Investigations*, U.S. Geological Survey Techniques of Water-Resource Investigations, TWRI 2-D1, 1974, (ER, GR, MAG, SRR).
- (50) Keys, W. S., *Borehole Geophysics Applied to Ground-Water Investigations*, U.S. Geological Survey Techniques of Water-Resource Investigations TWRI 2-E2, 1990, (Supersedes report originally published in 1988 under the same title as U.S. Geological Survey Open-File Report 87-539, 303 pp., which was published in 1989 with the same title by the National Water Well Association, Dublin, OH, 313 pp.), Complements Keys and MacCary (1971).
- (51) Keys, W. S., and MacCary, L. M., *Application of Borehole Geophysics to Water Resource Investigations*, TWRI 2-E1, U.S. Geological Survey Techniques of Water-Resources Investigations, 1971. (Reprinted, 1990; see, also Keys, 1990).
- (52) Respol, H., *Well Logging in Groundwater Development. International Contributions to Hydrogeology*, Vol 9, International Association of Hydrogeologists, Verlag Heinz Heise, Hannover, West Germany, 1989.
- (53) Aller, L., et al, *Handbook of Suggested Practices for the Design and Installation of Ground-Water Monitoring Wells*, EPA/600/4-89/034, 1991.<sup>51</sup> (Also published in 1989 by National Water Well Association, Dublin, OH, in its NWWA/EPA series).
- (54) Eggington, J. F. et al., *Australian Drilling Manual*. Australian Drilling Industry Training Committee, North Ryde, NSW, Australia, 1992.
- (55) Clark, L. 1988. *The Field Guide to Water Wells and Boreholes*. Geological Society of London Professional Handbook. Halsted Press, New York, 155 pp.
- (56) Driscoll, F. G., *Groundwater and Wells*, 2nd ed, Johnson Filtration Systems, Inc., St. Paul, MN, 1986.
- (57) Harlan, R. L., Kolm, K. E., and Gutentag, E. D., *Water-Well Design and Construction*, Elsevier, New York, 1989.
- (58) Lehr, J., Hurlburt, S., Gallagher, B., and Voyteck, J., *Design and Construction of Water Wells: A Guide for Engineers*. Van Nostrand Reinhold, New York, NY, 1988.
- (59) Roscoe Moss Company, *Handbook of Ground Water Development*. John Wiley & Sons, New York, 1990.
- (60) Ruda, T. C. and Bosscher, P. J. (eds), *Drillers Handbook*, National Drilling Contractors Association, Columbia, SC, 1990.
- (61) Shuter, E., and Teasdale, W. E., *Application of Drilling, Coring, and Sampling Techniques to Test Holes and Wells*, U.S. Geological Survey Techniques of Water-Resource Investigations TWRI 2-F1, 1989.
- (62) Soil Conservation Service (SCS), *Photographic Documentation of Rock Core Samples*, Engineering Geology Investigation Geology Note 4, Note 1984.
- (63) Soil Survey Staff. 1975. *Soil Taxonomy: A Basic System of Soil Classification for Making and Interpreting Soil Surveys*. U.S. Department of Agriculture Agricultural Handbook No. 436, 754 pp.
- (64) Soil Survey Staff. 1993. *Soil Survey Manual (new edition)*. U.S. Dept. of Agric. Agricultural Handbook No. 18. U.S. Government Printing Office Stock No. 001-000-04611-0.
- (65) Dutro, Jr., J. T., Dietrich, R. M., and Foose, R. M. (Compilers), 1989. *AGI Data Sheets for Geology in Field Laboratory and Office*, 3rd Edition. American Geological Institute, Washington, DC, pp. 294.



- (66) Morris, D. A. and Johnson, A. I., *Summary of Hydraulic and Physical Properties of Rock and Soil Materials as Analyzed by the Hydraulic Laboratory of the U.S. Geological Survey*, U.S. Geological Survey Water Supply Paper 1839-D, 1967, pp. D1–D42.
- (67) Birkeland, P. W., *Soils and Geomorphology*, Oxford University Press, New York, NY, 1984, (Revision of Pedology, Weathering, and Geomorphological Research published in 1973).
- (68) Stefferud, A., *Water, the Yearbook of Agriculture*, U.S. Department of Agriculture, 1955.
- (69) Deere, D. U. and Deere, D. W., “A Rock Quality Designation (RQD) Index in Practice,” In: *Rock Classification Systems for Engineering Purposes*, L. Kirkdale (ed), *ASTM STP 984*, ASTM, Philadelphia, PA, 1988, pp. 91–101.
- (70) Barth, D. S., B. J. Mason, T. H. Starks, and K. W. Brown. 1989. *Soil Sampling Quality Assurance User’s Guide*, 2nd ed. EPA 600/8-89/046 (NTIS PB89-189864), 225 + pp.
- (71) Mason, B. J., *Preparation of Soil Sampling Protocols: Sampling Techniques and Strategies*, EPA/600/R-92/128 (NTIS PB92-220532), 1992, (Supersedes 1983 edition titled, Preparation of Soil Sampling Protocol: Techniques and Strategies, EPA-600/4-03-020 (NTIS PB83-206979).
- (72) Gilbert, R. O., *Statistical Methods for Environmental Pollution Monitoring*, Van Nostrand Reinhold, New York, 1987.
- (73) Clark, I., *Practical Geostatistics*, Applied Science Publishers, London, 1979.
- (74) Isaaks, E. H. and Srivastava, R. M., *Applied Geostatistics*, Oxford University Press, New York, 1989.
- (75) ASCE Task Committee on Geostatistical Techniques in Geohydrology, “Review of Geostatistics in Geohydrology, I. Basic Concepts, II. Applications,” *ASCE Journal of Hydraulic Engineering* 116(5), 1990, pp. 612–658.
- (76) Englund, E. J. and Sparks, A. R., *Geo-EAS (Geostatistical Environmental Assessment Software) User’s Guide*, EPA/600/4-88/033a, 1988, (Guide: NTIS PB89-151252, Software: PB89-151245).
- (77) Englund, E. and Sparks, A., *GEO-EAS 1.2.1 User’s Guide*, EPA/600/8-91/008, Available from U.S. EPA Environmental Monitoring Systems Laboratory, Las Vegas, NV, 1991.
- (78) Yates, S. R. and Yates, M. V., *Geostatistics for Waste Management: A User’s Manual for the GEOPACK (Version 1.0) Geostatistical Software System*, EPA/600/8-90/004 (NTIS PB90-186420/AS), 1990.
- (79) Zirschky, J. and Gilbert, R. O., “Detecting Hot Spots at Hazardous-Waste Sites,” *Chemical Engineering*, July 9, 1984, pp. 97–100.
- (80) Barth, D. S. and Starks, T. H., *Sediment Sampling Quality Assurance User’s Guide*, EPA/600/4-85/048 (NTIS PB85-233542), 1985.
- (81) Palmer, M., *Methods Manual for Bottom Sediment Sample Collection*, EPA/905/4-85/004 (NTIS PB86-107414), 1985.
- (82) Guy, H. P. and Norman, V. W., *Field Methods for Measurement of Fluvial Sediment*, U.S. Geological Survey Techniques of Water-Resources Investigations TWRI 3-C2, 1970, [Updated in U.S. Geological Survey Open-File Report 86-531].
- (83) Chappelle, F. H., *Ground-Water Microbiology and Geochemistry*, John Wiley & Sons, New York, NY, 1993.
- (84) Alexander, M., *Introduction to Soil Microbiology*, 2nd ed, John Wiley & Sons, New York, NY, 1977.
- (85) Ehrlich, H. L., *Geomicrobiology*, Marcel Dekker, New York, NY, 1981, (Focuses on microbiology of natural geological systems).
- (86) Killham, K., *Soil Ecology*, Cambridge University Press, New York, NY, 1994.
- (87) Kuznetsov, S. I., Ivanov, M. V., and Lyalikova, N. N., *Introduction to Geological Microbiology*, McGraw-Hill, New York, NY, 1963 (Text focusing on natural microbiological activity in subsurface geologic systems).
- (88) Paul, E. A. and Clark, F. E., *Soil Microbiology and Biochemistry*, Academic Press, 1989.
- (89) Zajic, J. E. 1969. *Microbial Biogeochemistry*. Academic Press, New York, NY. [Text focusing on the microbial biogeochemistry of natural geological systems]
- (90) Leach, L. E., Beck, F. P., Wilson, J. T., and Kampbell, D. H., “Aseptic Subsurface Sampling Techniques for Hollow-Stem Auger Drilling,” In: *Proc. Third National Outdoor Action Conference on Aquifer Restoration, Ground Water Monitoring and Geophysical Methods*, National Water Well Association, Dublin, OH, 1988, pp. 31–51.
- (91) Davis, J. C., *Statistics and Data Analysis in Geology*, John Wiley & Sons, New York, 1973.
- (92) U.S. Environmental Protection Agency (EPA), *User Documentation: A Ground Water Information Tracking System with Statistical Capability*, GRITS/STAT Version 4.2. EPA/625/11-91/002, 1992d.<sup>51</sup>
- (93) Roy, W. R., Krapac, I. G., Chou, S. F. J., and Griffin, R. A., *Batch-Type Procedures for Estimating Soil Adsorption of Chemicals*, EPA/530/SW-87/006F (NTIS PB92-146190), 1992.
- (94) Hamilton, D. G. and T. A. Jones (eds.), *Computer Modeling of Geologic Surfaces*, American Association of Petroleum Geologists, Tulsa, OK, 1992.
- (95) Jones, T. A., Hamilton, D. G., and Johnson, C. R., *Contouring Geologic Surfaces with the Computer*, Van Nostrand Reinhold, New York, NY, 1986.

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org).