



Standard Guide for In-Situ Burning of Spilled Oil: Fire-Resistant Boom¹

This standard is issued under the fixed designation F 2152; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This guide covers a set of criteria to evaluate the performance, material characteristics, and essential features of fire-resistant oil spill containment boom.

1.2 This guide covers two types of fire-resistant oil containment boom: those that are intrinsically fire-resistant through the use of fire-resistant materials, and those that provide fire-resistance through the use of coolants. This guide may not be fully applicable to other types of fire-resistant boom.

1.3 This guide is one of three related to in-situ burning of oil spills. Guide F 1788 addresses environmental and operational considerations, and Guide F 1990 addresses ignition devices.

1.4 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory requirements prior to use.*

2. Referenced Documents

2.1 ASTM Standards:

- F 625 Practice for Classifying Water Bodies for Spill Control Systems²
- F 715 Test Methods for Coated Fabrics Used for Oil Spill Control and Storage²
- F 818 Terminology Relating to Spill Response Barriers²
- F 962 Specification for Oil Spill Response Boom Connection²
- F 1093 Test Methods for Tensile Strength Characteristics of Oil Spill Response Boom²
- F 1523 Guide for Selection of Booms in Accordance With Water Body Classifications²
- F 1788 Guide for In-Situ Burning of Oil Spills on Water: Environmental and Operational Considerations²
- F 1990 Guide for In-Situ Burning of Spilled Oil: Ignition Devices²
- F 2084 Guide for Collecting Containment Boom Performance Data in Controlled Environments²

3. Terminology

3.1 Definitions of Terms Specific to This Standard:

3.1.1 *actively-cooled fire-resistant boom*—type of fire-resistant boom that uses ancillary equipment to supply coolant to the boom to increase its fire resistance.

3.1.2 *ancillary equipment*—mechanical devices essential to the operation of a given boom system; for example, water pumps, power supplies, control manifolds, and so forth.

3.1.3 *fire resistance*—the ability of a barrier to maintain structural integrity and oil containment ability while being subjected to the thermal stress of a petroleum fire.

3.1.4 *fire-resistant boom*—barrier intended for containment of burning oil floating on water.

3.1.5 *freeboard*—minimum vertical height of the boom above the water line.

3.1.6 *heat flux*—the thermal intensity indicated by the amount of energy per unit area. (kW/m^2).

3.1.7 *in-situ burning*—burning of oil directly on the water surface.

3.1.8 *residue*—the material, excluding airborne emissions, remaining after the oil stops burning.

3.1.8.1 *Discussion*—Residue includes only material derived from the oil that is burned, and it shall not include material related to the boom or its components.

3.1.9 *salvageable components*—components of the boom that may be reused in a repair or reconstruction of the boom to its original state.

3.2 For other definitions relating to boom properties and dimensions, refer to Terminology F 818.

4. Equipment Description

4.1 To be effective, the fire-resistant boom shall contain oil floating on water before, during, and after exposure to in-situ burning of oil.

4.2 Some fire-resistant booms use coolant to increase their fire resistance. With some booms, this is actively supplied by ancillary equipment; others rely on wicking of the water in which the boom is floating. Additional requirements and testing stipulations for such booms are noted in 5.5 and 6.5.

4.3 If a boom is defined as reusable, a procedure for cleaning, decontaminating, salvage, and restoration shall be provided to the user by the manufacturer.

4.4 Fire-resistant booms may be used in conjunction with

¹ This guide is under the jurisdiction of ASTM Committee F20 on Hazardous Substances and Oil Spill Response and is the direct responsibility of Subcommittee F20.15 on In-Situ Burning.

Current edition approved Oct. 10, 2001. Published December 2001.

² *Annual Book of ASTM Standards*, Vol 11.04.

conventional booms or “transition” booms. If a boom is to be used in this fashion, a suitable means of connection between the fire boom and transition boom must be made, such as a connector in accordance with Specification F 962.

5. Minimum Equipment Performance Characteristics

5.1 Overview:

5.1.1 Minimum performance characteristics are grouped under three headings: Operability, Oil Containment; and Fire-Resistance. All minimum performance characteristics listed here shall be achieved before a boom is considered to meet the requirements of this guide.

5.1.2 The fire-resistant boom shall withstand oil fires and contain oil in various conditions that include both calm water and waves with a significant wave height of up to 1 m and a period of 3 to 4 s.

5.1.3 For booms intended for use in salt water or brackish water, the boom shall be tested in water that has a salinity of 15 o/oo (parts per thousand) or greater. For booms that rely on wicking, the salinity shall be 33 o/oo or greater. For actively-cooled booms, the water in which the boom is tested may be 15 o/oo if the water supplied to the boom (from a separate supply) has a salinity of 33 o/oo or greater.

5.2 Operability Characteristics:

5.2.1 The fire-resistant boom shall meet the minimum physical dimensions and strength parameters as for conventional oil containment booms, except for the buoyancy-to-weight ratio. These parameters are listed in Guide F 1523 and summarized in Table 1.

5.2.2 *Total Tensile Strength*—Prior to exposure to an in-situ burn, the fire-resistant boom shall meet the minimum total strength for the various water body classifications listed in Table 1.

5.2.3 Total tensile strength for fire-resistant booms may decrease after each burn exposure. In any case, the boom shall retain sufficient strength following a burn to retain burn residue and any unburned oil and to allow the salvage and disposal of the boom.

5.2.4 *Corrosion Resistance*—Fire-resistant oil spill containment booms (and ancillary systems, if applicable) shall be manufactured of components that do not degrade significantly and that maintain fire resistance characteristics while exposed to typical marine environmental conditions.

5.2.5 *Extreme Temperature Properties*—The fire-resistant

boom and any ancillary equipment shall not be adversely affected by use or storage at temperatures within the range of -40 to 40°C.

5.2.6 *Fabric Tests*—Fabrics and components shall meet the applicable test methods for fabrics used in spill control barriers and temporary storage devices in accordance with Test Methods F 715.

5.2.7 *Hazardous Waste*—If the boom’s materials of manufacture include any hazardous materials, the appropriate Material Safety Data Sheet and exposure limits shall be provided by the manufacturer. The fire-resistant boom system shall not create or add to the hazardous waste pollution, nor shall it have any special disposal requirements beyond that typically required of oil spill booms.

5.2.8 *End Connectors*—The fire-resistant boom section interconnections shall meet boom fire tolerance requirements.

5.2.9 *Documentation*—Documentation shall be provided by the manufacturer addressing storage, handling, maintenance, health and safety, test results, and recommended repair procedures.

5.3 Oil Containment Characteristics:

5.3.1 Prior to exposure to an oil fire, the fire-resistant boom shall display similar oil containment characteristics expected of conventional oil spill containment booms.

5.4 Fire-Resistance Characteristics:

5.4.1 The fire-resistant boom shall contain oil and survive in heat fluxes equivalent to an in-situ burn of diesel with a minimum diameter of 4.5 m, for a total of three 1 h burn cycles, with a minimum 1 h cool down between cycles.

5.5 Additional Requirements for Actively-Cooled Booms:

5.5.1 Additional fire-resistance testing for actively-cooled booms is specified in 6.5.2 to confirm the adequacy of backup systems for coolant supply. To fulfill the additional test requirement, it is recommended that actively-cooled booms have the following features:

5.5.1.1 Backup coolant supply system,

5.5.1.2 Flowmeter or indicator on each coolant supply to monitor the flow, and

5.5.1.3 Capability to switch to the backup coolant supply in the event of failure of the primary supply.

5.5.2 The manufacturer shall specify the required minimum flowrate and corresponding pressure drop per unit length (of hose and boom) required to adequately cool the boom.

5.5.3 Previous testing has identified the clogging of nozzles and small orifices as a potential problem with actively-cooled booms. To negate this as a potential problem, it is recommended that the coolant supply be filtered or that adequate redundancy in coolant supply be provided, or both.

TABLE 1 Minimum Design Values for Fire-Resistant Boom

Boom Property	Calm Water ^A	Calm Water – Current ^A	Protected Water ^A	Open Water ^A
Freeboard prior to burn, mm	120	130	260	530
Freeboard following burn, mm	60	70	130	270
Draft, mm	150	160	330	660
Gross buoyancy-to-weight ratio prior to burn			3:1	
Gross buoyancy-to-weight ratio following burn			1.5:1	
Tensile strength, N per mm of boom draft ^B	57	140	64	72
Tear strength, N	450	450	450	450

^A Water body types defined in Practice F 625.

^B Tensile strength measured by Test Methods F 1093.

6. Outline of Equipment Testing

6.1 The following test outline includes three components that apply to all fire-resistant booms (testing for operability, oil containment, and fire resistance) and two additional stipulations for actively-cooled booms.

6.2 Operability Testing:

6.2.1 The fire-resistant boom shall be towed in a U-configuration and in a straight line to confirm its towing characteristics and its short-term durability. A minimum 150-m length of boom shall be used for the tests.

6.2.2 The boom system shall be towed, without significant damage, for 2 h at 1.0 knots in a U-configuration with a gap ratio of 1:3 (± 0.5), and in a straight line at 5 knots for 2 h. The presence of waves is not required for this test.

6.3 Oil Containment Testing:

6.3.1 The fire-resistant boom shall be subjected to the standard oil containment test protocol in accordance with Guide F 2084. This component of the test protocol will establish the containment limits (that is, waves and current) of the boom, and will identify any potential problems in boom towability and stability under tow and in waves.

6.3.2 Prior to and during a burn exposure, the boom shall be capable of containing a layer of low viscosity oil of 200 mm in thickness without significant losses.

6.3.3 After the second or third of the three 1 h burns, the boom shall contain a layer of diesel of 200 mm in calm water. The losses from the boom due to leakage shall be no greater than 10 %, measured by volume, over a period of 10 min from the start of the test.

6.3.4 In 6.3.2 and 6.3.3, the layer of oil shall be the lesser of 200 mm or 50 % of the boom's draft.

6.3.5 At the conclusion of the third burn, the boom shall have sufficient strength and integrity such that it can contain any floating residue and can be retrieved.

6.4 Fire Resistance Testing:

6.4.1 The fire-resistant boom shall survive direct fire exposure with an average heat flux of 100 kW/m² or greater (heat flux measurements averaged over the 1 h burn period), with peaks of 100 to 150 kW/m², while exposed to wave action. The boom shall be exposed to a series of three 1 h burns with a minimum 1 h cool-down period between burns.

6.4.2 Heat flux is very difficult to measure accurately. Heat flux gages respond quickly to changes in the fire, and substantial fluctuation is normal for these measurements. Readings will vary significantly with attitude and direction of a sensor,

and also with the wind speed and direction.³

6.4.3 Given the difficulties in accurately measuring heat flux, the recommended test is an in-situ burn of diesel with a minimum burn diameter of 4.5 m (15 ft). This test meets the requirements for this guide without the need for doing heat flux measurements.

6.4.4 During the heat exposure and intervening cool-down periods (with the exception of the leak test in 6.3.2), the boom shall be exposed to wave action. A wave height of at least 15 cm with a period of 3 s or less is recommended. The wave height shall be the minimum of 15 cm or the minimum freeboard following the burn for the appropriate boom category as shown in Table 1.

6.5 Additional Stipulations for Actively-Cooled Booms:

6.5.1 *Operability Testing*—For all fire-resistant booms, a tow test is specified in 6.2. For actively-cooled booms, the straight-line tow tests shall be carried out with the boom and all ancillary equipment in their operating configuration, and the U-shape tow tests shall be carried out with the ancillary equipment rigged and operating at design conditions.

6.5.2 *Fire Resistance Testing*—A fire-resistance test is specified in 6.4 for all fire-resistant booms. For actively-cooled booms, all backup systems necessary to ensure an uninterrupted flow of cooling water shall be tested during each of the three specified burn periods. At the midpoint of each of the burn periods, the backup systems shall be tested by intentionally switching to the backup water supply or power system to simulate failure of the primary systems during the burn. If an actively-cooled boom is not equipped with a backup cooling water system, the absence shall be noted in the test report.

7. Keywords

7.1 fire containment booms; fire-resistant booms; in-situ burning; oil spill burning; oil spill containment; oil spill disposal

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org).