

Standard Specification for Nuclear-Grade Gadolinium Oxide (Gd₂O₃) Powder¹

This standard is issued under the fixed designation C 888; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This specification provides the chemical and physical requirements for nuclear-grade gadolinium oxide powder intended for subsequent processing and use in nuclear fuel applications, for example, as an addition to uranium dioxide.

1.2 This specification does not include requirements for health and safety. Observance of this specification does not relieve the user of the obligation to be aware of and conform to all federal, state, and local regulations pertaining to possessing, shipping, processing, or using this material.

2. Referenced Documents

2.1 ASTM Standards:

- B 329 Test Method for Apparent Density of Powders of Refractory Metals and Compounds by the Scott Volume-ter²
- C 493 Test Method for Bulk Density and Porosity of Granular Refractory Materials by Mercury Displacement³
- C 859 Terminology Relating to Nuclear Materials⁴
- C 889 Test Methods for Chemical and Mass Spectrographic Analysis of Nuclear-Grade Gadolinium Oxide (Gd_2O_3) Powder⁴
- E 11 Specification for Wire-Cloth Sieves for Testing Purposes⁵
- E 105 Practice for Probability Sampling of Materials⁵
- 2.2 ANSI Standard:
- ANSI/ASME NQA-1 Quality Assurance Program Requirements for Nuclear Facility Applications⁶
- 2.3 U.S. Government Document:
- Code of Federal Regulations, Title 10, Part 50-Energy (10

CFR 50), Domestic Licensing of Production and Utilization Facilities⁷

3. Terminology

3.1 Definitions of Terms Specific to This Standard:

3.1.1 Terms shall be defined in accordance with Terminology C 859 except as defined herein.

3.1.1.1 *buyer*—the organization issuing the purchase order.

3.1.1.2 *powder lot*—a quantity of gadolinium oxide powder that has been processed in a manner such that samples taken in accordance with the procedures of 8.1 can be considered as representative of the entire powder lot.

3.1.1.3 seller-the gadolinium oxide powder supplier.

4. Ordering Information

4.1 The buyer shall specify the following information for all orders where this specification applies:

4.1.1 Powder lot size (allowable range),

4.1.2 Quantity (weight of delivered product),

4.1.3 Nominal particle size range and applicable tolerances in accordance with U.S. Standard Sieve Series (Specification E 11),

4.1.4 Density (optional), Scott Volumeter (Test Method B 329) and Mercury Displacement (Test Method C 493) are referenced as guides to density measurement techniques,

4.1.5 Shape factor and method of determination (optional),

- 4.1.6 Sampling requirements,
- 4.1.7 Crystal structure (optional), and

4.1.8 Quality requirements.

5. Chemical Composition

5.1 Loss-on-Ignition— The loss-on-ignition as determined after ignition for 2 h at a minimum temperature of 900°C shall not exceed 1.5 weight %.

5.2 Gadolinium Oxide Concentration—The minimum Gd_2O_3 concentration shall be 99.8 weight % exclusive of the constituents lost on ignition as determined by Test Methods C 889.

5.2.1 Gadolinium Oxide Isotope Concentration—The isotopic concentration of the gadolinium shall be that which is

¹ This specification is under the jurisdiction of ASTM Committee C-26 on Nuclear Fuel Cycle and is the direct responsibility of Subcommittee C26.03 on Neutron Absorber Materials Specifications.

Current edition approved May 10, 1997. Published May 1998. Originally published as C 888 – 78. Last previous edition C 888 – 89.

² Annual Book of ASTM Standards, Vol 02.05.

³ Annual Book of ASTM Standards, Vol 15.01.

⁴ Annual Book of ASTM Standards, Vol 12.01.

⁵ Annual Book of ASTM Standards, Vol 14.02.

⁶ Available from the American National Standards Institute, 11 W. 42nd St., 13th Floor, New York, NY 10036.

⁷ Available from Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

NOTICE: This standard has either been superceded and replaced by a new version or discontinued. Contact ASTM International (www.astm.org) for the latest information.

🚻 C 888

found in naturally occurring gadolinium for the following isotopes:

Isotope	Atomic %
¹⁵⁵ Gd	14.9 ± 1.0
¹⁵⁷ Gd	15.7 ± 1.0

5.3 Impurity Content:

5.3.1 *Individual Impurity Limits*—Individual impurities exclusive of constituents lost on ignition shall not exceed the following limits.

	Maximum
Element	Concentration
	(µg/g Gd ₂ O ₃)
Boron	5
Cadmium	25
Thorium	30
(Chlorine + fluorine)	100
(Europium + samarium + terbium + ytterbium + dysprosium)	1000
Carbon	600

5.3.2 Any identified impurity exceeding 1000 μ g/g Gd₂O₃ shall be reported. The total of all measured impurities shall not exceed 2000 μ g/g Gd₂O₃.

The buyer may specify individual impurity limits for any elements not listed in 5.3.1.

6. Physical Properties

6.1 Physical properties listed in 4.1.3, 4.1.4, 4.1.5, and 4.1.7 shall be in compliance with the buyer's requirements.

7. Cleanliness

7.1 The lot shall be processed and packaged in a manner that precludes contamination by dust, organics, plastics, or other foreign materials.

8. Sampling

8.1 Sampling plans to meet acceptance criteria and inspection and measurement procedures that describe the method of compliance with this specification shall be approved by the buyer. The degree of sampling where not specified in this document varies with the application and therefore should be specified on the purchase order. Recommended Practice E 105 is referenced as a guide.

8.2 Each sample taken shall be sufficient to perform the following in the event they are necessary or desired by the buyer:

8.2.1 Quality verification tests by the seller,

8.2.2 Acceptance tests by the buyer,

8.2.3 Referee tests, in the event these become necessary, and

8.2.4 Retention of archive samples by the seller.

8.3 Archive samples shall be retained for a period of time

specified by the buyer and delivered to the buyer upon request.

9. Inspection and Certification

9.1 The seller shall inspect the material covered by this specification and shall provide the buyer with certificates of tests showing the results of all testing and inspection performed on each lot.

9.2 The seller shall deliver all test certificates to the buyer prior to or concurrent with the shipment of the powder lot.

10. Rejection and Rehearing

10.1 Unless the buyer and seller agree otherwise, rejection and acceptance shall be on a lot basis.

10.2 Powder lots that fail to conform to the requirements of this specification may be rejected by the buyer. The seller may petition the buyer to waive selected requirements for identified out-of-specification lots. The decision to grant such waiver belongs to the buyer. The seller may also apply any remedy to bring rejected lots into specification providing he can demonstrate to the buyer that such remedy does not impair the function or preclude the certification of the rejected material.

10.3 In the event of disagreement over the results of chemical analyses, samples shall be submitted to a mutually selected referee for resolution.

11. Packaging and Package Marking

11.1 Gadolinium oxide powder shall be packaged in sealed containers to prevent loss or damage, or both, of material and contamination from airborne or container materials. The exact size and type of packing shall be as mutually agreed upon by the buyer and the seller.

11.2 Each container shall bear, as a minimum, a label on the lid and side with the following information:

11.2.1 Material in container (gadolinium oxide powder),

11.2.2 Specification number,

11.2.3 Purchase order number,

- 11.2.4 Powder lot number,
- 11.2.5 Gross, net, and tare weights,

11.2.6 Name of seller, and

11.2.7 Container, numbered to identify individual container and total quantity of containers in shipment.

12. Quality Assurance

12.1 Quality assurance requirements shall be agreed upon between the buyer and seller when specified in the purchase order. CFR Title 10, Part 50, Appendix B, and ANSI/ASME NQA-1 are referenced as guides.

The American Society for Testing and Materials takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org).