



Standard Terminology Relating to Geothermal Energy¹

This standard is issued under the fixed designation E 957; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

aquifer, *n*—a water-bearing, permeable body of rock or granular material below the surface of the earth.

binary cycle plant, *n*—a facility that generates electric power by transferring heat from produced geothermal fluids to a non-aqueous working fluid that vaporizes and causes a turbine to rotate the shaft of a generator.

brine, *n*—in geothermal, fluids in a liquid phase that have been produced from geothermal wells or from hot springs and that contain appreciable amounts of sodium chloride and other salts.

capacity, *n*—the power which a component of a geothermal facility (e.g., a well, a reservoir, a power plant, or a direct-use facility) is capable of supplying at a point in time, assuming that other required components of the geothermal facility are available. Capacity is expressed in units of power (e.g., Megawatts, kilowatts).

direct-use facility, *n*—a facility which uses geothermal energy for purposes other than the generation of electricity (e.g., space heating, greenhouses, bathing, and industrial processes).

fumarole, *n*—a vent at the earth's surface that emits steam or gaseous vapor.

DISCUSSION—Such vents are usually found in volcanic areas.

geochemistry, *n*—the study of the chemistry of the rocks and fluids of the earth for the purpose of understanding their composition, their temperature, and their origin.

geothermal, *adj*—relating to or derived from the natural heat of the earth.

geothermal anomaly, *n*—a conspicuous deviation of the earth's temperature, geothermal gradient, or heat flow from average values; an area where such a deviation exists.

geothermal energy, *n*—the thermal energy contained in the rocks and fluids of the earth.

geothermal facility, *n*—the physical components necessary for the utilization of geothermal energy, including the reservoir, production and injection wells, pipelines, and the power plant or direct-use facility.

geothermal fluid, *n*—water in a vapor or liquid phase or in a

mixture of these phases that exists within or has been emitted from a geothermal reservoir, together with any entrained or dissolved substances.

geothermal gradient, *n*—the change in temperature of the earth with depth, expressed either in degrees of temperature per unit depth, or units of depth per degree.

geothermal power plant, *n*—a facility for the production of electricity using geothermal energy, typically including a turbine, a generator, and associated surface equipment.

geothermal heat pump, *n*—a heat pump that transfers energy to or from the earth.

geothermal reserves, *n*—the amount of energy anticipated to be economically recoverable from a geothermal facility over a specified time period (e.g., the project life) using existing technology. Geothermal reserves are expressed in units of energy (e.g., terajoules in SI units), which are dimensionally equivalent to units of power multiplied by units of time (e.g., Megawatt-years or kilowatt-hours). Geothermal reserves may also be expressed as an equivalent amount of another energy source (e.g., barrels of oil equivalent).

DISCUSSION—Geothermal reserves can also be characterized as to the degree of certainty of recovery. By analogy to usage in the mining and petroleum industries, reserves may be qualified as proved, probable, or possible.

Example of Usage:

This facility has geothermal reserves of 4,000 Megawatt-years, recoverable over a project life of 30 years.

geothermal reservoir, *n*—an aquifer of sufficient temperature and permeability to support the economic use of geothermal energy.

DISCUSSION—The extent of a geothermal reservoir is determined by the degree of hydrologic interconnection. When an aquifer contains both hot portions and portions that are too cool for economic use, those portions that are sufficiently interconnected to have a significant hydrologic or thermal impact on each other are considered part of the same geothermal reservoir.

geothermal steam, *n*—a geothermal fluid in the vapor phase.

geothermometer, *n*—a method of estimating the temperature of a geothermal reservoir based on the minerals in the reservoir rock or the concentration of chemical species in geothermal fluids that have come from the reservoir.

geyser, *n*—a spring that intermittently blows forth hot water and steam.

¹ This terminology is under the jurisdiction of ASTM Committee E44 on Solar, Geothermal, and Other Alternative Energy Sources and is the direct responsibility of Subcommittee E44.01 on Terminology.

Current edition approved May 10, 2002. Published August 2002. Originally published as E 957 – 83. Last previous edition E 957 – 98.

heat flow, *n*—dissipation or transfer of heat coming from within the earth by conduction, convection or radiation at the surface; usually reported in units of energy per unit time per unit area, for example, joules per second per square metre or watts per square metre.

hot spring, *n*—a thermal spring whose temperature is above that of the human body. *Meinzer (1923)*

magma, *n*—molten rock within the earth or within other planets.

moisture content, *n*—the percentage by mass of liquid-phase water in a two-phase mixture of vapor-and liquid-phase water.

DISCUSSION—The moisture content of a two-phase mixture is equivalent to 100 minus the steam quality

noncondensable gas content, *n*—the concentration of noncondensable gas in a geothermal fluid.

DISCUSSION—The principal geothermal noncondensable (NC) gases include carbon dioxide, hydrogen sulfide, ammonia, nitrogen, methane, hydrogen, and argon. Standard usage is to express NC gas content as a percentage by mass in the reference fluid; that is,

$(\text{NC gas content} = [\text{mass NC gas} / (\text{mass fluid} + \text{mass NC gas})] \times 100, \text{ where fluid} = \text{water vapor, or water vapor} + \text{liquid (total fluid)})$

Other units for NC gas content (such as percentage by volume or mole ration) may also be used. The units and the reference fluid for NC gas content should always be explicitly stated.

noncondensable gases, *n*—in geothermal, chemical species (such as carbon dioxide or hydrogen sulfide) that are constituents of geothermal fluids, that partition primarily into the vapor phase when geothermal fluids boil, and that do not condense along with geothermal steam when put through a condenser in a geothermal power plant.

permeability, *n*—the ability of a rock to transmit fluid.

DISCUSSION—The amount of permeability of a rock depends on the size, shape, and degree of interconnection of the rock's pores and fractures. Permeability is expressed as the ability to transmit fluid of a specified viscosity at a specified flow rate through a specified area under the influence of a specified pressure gradient. The traditional unit of permeability is the darcy or the millidarcy. The SI unit is the square micrometer. These units have the dimension of length squared.

phreatic eruption, *n*—an explosion of the surface of the earth that results from a sudden increase in the volume of groundwater when it flashes to steam due to contact with hot rocks.

DISCUSSION—Typically in an area of hot springs or fumaroles, and no lava or other materials derived from magma are erupted.

porosity, *n*—the ratio of the aggregate volume of interstices in a rock or soil to its total volume, usually stated as a percent.

project life, *n*—the time period over which the economic

viability of a geothermal facility is evaluated.

reinjection/injection, *n*—the process of conveying geothermal fluids to sub-surface formations through wells.

DISCUSSION—After such fluids have been processed by a geothermal power plant or its associated facilities, or both, this process is sometimes referred to as “reinjection” when injected water circulates back through the geothermal reservoir to the production wells.

steam quality, *n*—the percentage by mass of vapor-phase water in a two phase mixture of vapor- and liquid-phase water.

DISCUSSION—Geothermal steam may contain a small amount of liquid-phase water, as well as non-aqueous constituents, such as noncondensable gas and silica. Steam quality expresses the proportion of vapor-phase water relative to the mixture of vapor-and liquid-phase water only. The term “steam quality” is synonymous with the term “steam dryness”.

Example — A two-phase geothermal fluid consists of the following mass percentages: 90% vapor-phase water, 6% liquid-phase water, 3% noncondensable gas, 1% total dissolved solids.

The steam quality of this mixture is $[90/(90+6)] \times 100 = 93.75\%$.

sustainable capacity, *n*—the power which a component of a geothermal facility (such as a reservoir or a power plant) is capable of sustaining for a specified period of time.

DISCUSSION—The period of time over which a certain capacity can be sustained may be different than the project life.

Examples of Usage:

This reservoir has a sustainable capacity of 100 MW for at least 30 years.

This reservoir has a capacity of 50 MW, sustainable for at least the first 20 years of a 30-year project life.

With proper maintenance, this power plant has a sustainable capacity of 30 MW for 30 years.

total dissolved solids content of steam, *n*—the concentration by mass of non-volatile, dissolved impurities in geothermal steam.

DISCUSSION—Geothermal steam may contain non-volatile impurities, such as silica, sodium, chloride and iron, that may be considered dissolved in droplets of liquid water. The total dissolved solids content (TDS) of steam expresses the sum of these impurities as a concentration by mass in the water vapor and liquid mixture. Semi-volatile constituents such as boron (boric acid, H3BO3) are not usually considered part of the total dissolved solids in steam.

warm spring, *n*—thermal spring whose temperature is appreciably above the local mean annual temperature but below that of the human body. *Meinzer (1923)*

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

**NOTICE: This standard has either been superseded and replaced by a new version or discontinued.
Contact ASTM International (www.astm.org) for the latest information.**



This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org).