



## Standard Practice for Single Person Cold Water Survival/Rescue Technique: Help Position<sup>1</sup>

This standard is issued under the fixed designation F 1729; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

### 1. Scope

1.1 This practice covers the recommended water rescue procedure for performing the heat escape lessening posture (HELP) position.

1.2 This practice is one in a set of self rescue techniques for the water rescuer.

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

### 2. Terminology

2.1 *HELP position, n*—heat escape lessening posture (HELP) is a single person water rescue technique for heat conservation when immersed in cold water. This technique conserves heat by using personal flotation devices, clothing, and body posture to limit exposure of the body's major heat loss areas to the cold water.

2.2 *personal flotation device (PFD), n*—a buoyant device suitable for use by one person in water emergencies. These devices may be vests, ring buoys, life preservers, cushions, and other special purpose buoyant devices.

### 3. Significance and Use

3.1 This practice establishes a single person cold water survival/rescue procedure.

3.2 All persons who are identified as water rescuers shall meet the requirements of this practice.

3.3 This practice is intended to assist government agencies, state, local, or regional organizations; fire departments; rescue teams and others who are responsible for establishing a minimum performance for personnel who respond to water emergencies.

3.4 A rescuer needs to be wearing a personal flotation device to perform this technique. These devices should conform to standards set by the appropriate national regulatory authority, that is, the U.S. Coast Guard in the United States, and be in good and serviceable condition.

3.5 A water rescuer sometimes may be immersed in cold water for prolonged periods of time. They are unable to get to shore or shore is too far away, rescue is not imminent, no boat is available to get into or on top of, and no flotsam is available. The water rescuer needs to assume a defensive posture to conserve heat and increase survival time.

### 4. Procedure

4.1 Upon initial immersion in cold water, the rescuer should cover the mouth and nose to prevent the aspiration of water.

4.2 Float in a sitting position with the legs drawn up, knees together, and with the ankles crossed.

4.3 Place arms against the sides of the torso, bent at the elbows, and across the chest.

4.4 Remain calm and think clearly.

4.5 Leave all clothing on.

4.6 Wait for rescue.

### 5. Keywords


5.1 cold water survival; Heat Escape Lessening Posture (HELP) position; self rescue technique; water rescue; water rescuers

<sup>1</sup> This practice is under the jurisdiction of ASTM Committee F-32 on Search and Rescue and is the direct responsibility of Subcommittee F32.05 on Rescue Operations and Technology.

Current edition approved Sept. 10, 1996. Published November 1996.

*The American Society for Testing and Materials takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.*

*This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, 100 Barr Harbor Drive, West Conshohocken, PA 19428.*

 **F 1729**

*This standard is copyrighted by ASTM, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or [service@astm.org](mailto:service@astm.org) (e-mail); or through the ASTM website (<http://www.astm.org>).*