



## Standard Guide for Using Whistle Signals During Rope Rescue Operations<sup>1</sup>

This standard is issued under the fixed designation F 1768; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

### 1. Scope

1.1 This guide covers the methodology for the use of whistles as a means of communication during rope rescue operations.

1.2 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

### 2. Terminology

2.1 There are no terms in this guide that require new or other than dictionary definitions.

### 3. Significance and Use

3.1 Whistle signals are a simple and effective means of communication between rescuers and those operating a roping or rope-lowering system. They may be used as a primary means of communication or as a backup when radios fail or when ambient noise makes them unintelligible.

3.2 These same signals can be used in non-rescue situations, for example, by persons rappelling in caves.

### 4. Procedure

4.1 Using a whistle device, or method, with enough volume to be audible over ambient noise and for the distances involved, use the following pattern of whistle blasts to signal the required action:

4.1.1 **Stop**, 1 Long Whistle Blast—Used to stop all move-

ment until further instructions.

4.1.2 **Up**, 2 Short Whistle Blasts—Means something or somebody is moving up or requires to be moved up. On horizontal systems it would indicate movement of the load towards the anchor or hauling system.

4.1.3 **Down**, 3 Short Whistle Blasts—Means something or somebody is moving down or requires to be moved down. On horizontal systems it would indicate movement of the load away from the anchor or hauling system. It has an opposite field of use to **Up**.

4.1.4 **Rope Free**, 4 Short Whistle Blasts—Used at the end of a climb, rappel, raise, or lower to communicate that one is off the rope, has found a safe position, and that the rope can be used by the next person or for the next operation.

4.1.5 **Help**, Continuous Blast—A general emergency call. Its use may indicate different actions depending upon the system in use at the time. For example, during a rappel, it would include the need for a bottom belay. The signal alerts others to come to the aid and, if necessary, work quickly and safely to effect a rescue.

4.2 A “Short Whistle Blast” is defined as 1 s in duration. Where the signal calls for multiple blasts there shall be a 1-s interval between each blast. A “Long Whistle Blast” is 3 s in duration. A “Continuous Blast” indicating the need for help should be long enough to attract attention and be differentiated from any other signal, at least 10 s if possible.

4.3 These same patterns could be used with any audible signaling device such as a compressed gas horn, vehicle horn, and so forth.

### 5. Keywords

5.1 signals; whistles

<sup>1</sup> This guide is under the jurisdiction of ASTM Committee F32 on Search and Rescue and is the direct responsibility of Subcommittee F32.02 on Search and Rescue Management.

Current edition approved Feb. 10, 1997. Published May 1997.

*The American Society for Testing and Materials takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.*

*This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.*

*This standard is copyrighted by ASTM, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org).*