



Standard Specification for Electronic and Degreasing Grades of 1,1,2-Trichloro 1,2,2,-Trifluoroethane Solvent¹

This standard is issued under the fixed designation D 4995; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This specification establishes the requirements for three grades of trichlorotrifluoroethane solvent:

- 1.1.1 Type I electronic or ultra-clean grade,
- 1.1.2 Type II standard or vapor-degreasing grade, and
- 1.1.3 Type IIA general purpose, packaged in a pressurized container grade.

2. Referenced Documents

2.1 ASTM Standards:²

- D 1078 Test Method for Distillation Range of Volatile Organic Liquids
- D 2109 Test Methods for Nonvolatile Matter in Halogenated Organic Solvents and Their Admixtures
- D 3401 Test Methods for Water in Halogenated Organic Solvents and Their Admixtures
- D 3443 Test Method for Chloride in Trichlorotrifluoroethane
- D 3444 Test Method for Total Acid Number of Trichlorotrifluoroethane
- D 3448 Test Method for Specific Aqueous Conductance of Trichlorotrifluoroethane
- D 3844 Practice for Labeling Halogenated Hydrocarbon Solvent Containers
- D 6806 Practice for Analysis of Halogenated Organic Solvents and Their Admixtures by Gas Chromatography

2.2 Other Documents:³

- 29 CFR 1919.1200 Department of Labor, OSHA Regulations on Hazard Communications
- 49 CFR 100 to 199 Department of Transportation Hazard-

ous Materials Regulations

PPP-C-2020 Federal Specification, Chemicals, Liquid, Dry and Paste: Packaging of⁴

STP 310A Handbook of Vapor-Degreasing⁵

STP 403A Cold Cleaning with Halogenated Solvents⁵

3. Classification

3.1 *Type I*—Type I solvent is intended for use in the cleaning of space vehicle components, precision assemblies, oxygen systems and electronic equipment by the processes of spraying, flushing, vapor degreasing, or ultrasonics. The solvent is especially applicable for cleaning precision parts and assemblies in clean rooms and for use as a medium in testing the cleanliness of components that are assumed to be clean.

3.2 *Types II and IIA*—Types II and IIA are typically used in vapor degreasing applications or in other processes where the requirements for purity and cleanliness are less stringent than those of a cleaning process using Type I solvent.

4. Properties

4.1 Electronic or ultra-clean and degreasing grades of trichlorotrifluoroethane shall conform to the requirements prescribed in Table 1.

5. Packaging

5.1 Package and label industrial or commercial quantities in accordance with DOT regulations in 49 CFR 100 to 199, in accordance with state and local regulations, in accordance with OSHA regulations found in 29 CFR 1910.1200, and in accordance with EPA regulations found in 40 CFR 82 Subpart E.

6. Keywords

6.1 CFC-113; trichlorotrifluoroethane

¹ This specification is under the jurisdiction of ASTM Committee D26 on Halogenated Organic Solvents and Fire Extinguishing Agents and is the direct responsibility of Subcommittee D26.03 on Cold Cleaning.

Current edition approved Jan. 1, 2004. Published March 2004. Originally approved in 1994. Last previous edition approved in 2000 as D 4995 – 00.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ The Code of Federal Regulations may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

⁴ Copies of Federal Specifications are available from General Services Administration, Specification Unit WFSIS, 7th and D Street SW, Washington, DC 20406, or from General Services Administration Business Service Centers in Boston, New York, Philadelphia, Atlanta, Chicago, Kansas City, MO, Ft. Worth, Houston, Denver, San Francisco, Los Angeles, and Seattle, WA.

⁵ Available from ASTM Headquarters, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959.

TABLE 1 Chemical and Physical Properties^A

Property	Solvent Type			Test Method
	Type I	Type II	Type IIa	
Boiling point (at standard barometric pressure)	47.6 ± 0.2°C (117.6 ± 0.4°F)	47.6 ± 0.2°C (117.6 ± 0.4°F)	47.6 ± 0.2°C (117.6 ± 0.4°F)	D 1078
Chemical purity trichlorotrifluoroethane; percent, minimum (by weight)	99.9	99.8	99.8	D 6806
Balance of product	Other halogenated solvents	Other halogenated solvents	Other halogenated solvents	D 6806
Moisture Content, ppm, maximum (by weight)	10	10	50	D 3401
Chloride Ion, ppm, max (by weight)	0.1	0.1	0.1	D 3443
Specific Aqueous Conductance ^B (µs/cm; max)	1.9	1.9		D 3448
Acid Number, mg KOH/g of sample, max	0.003	0.003		D 3444
Residue, ppm, max (by weight)	1	2	25	D 2109

^A Properties apply to total trifluorotrchloroethane and do not specify distribution between isomers.

^B Specific aqueous conductance test may be used as an alternate to chloride ion test for types I and II.

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org).